```python
def linearSearchProduct(productList, targetProduct):
  indices = []

  for index, product in enumerate(productList):
    if product == targetProduct:
      indices.append(index)

  return indices


# Example usage:
products = ["shoes", "boot", "loafer", "shoes", "sandal", "shoes"]
target = "shoes"
target2 = 'apple'
result = linearSearchProduct(products, target)
print(result)
```

```
$ python3 $file
[0, 3, 5]
$
```

```
13
reverse=True)
14    # Syntax - lambda arg:exp
15    return sorted_students
16
17
18  # Example usage:
19  students = [
20      Student("Hari", "A123", 7.8),
21      Student("Srikanth", "A124", 8.9),
22      Student("Saumya", "A125", 9.1),
23      Student("Mahidhar", "A126", 9.9),
24  ]
25
26  sorted_students =
    sort_students(students)
27
28  # Print the sorted list of students
29  for student in sorted_students:
30    print("Name: {}, Roll Number: {},
    CGPA: {}".format(student.name,
31
                     student.roll_number,
32
```

```
$ python3 $file
Name: Mahidhar, Roll Number: A126, CGPA: 9
.9
Name: Saumya, Roll Number: A125, CGPA: 9.1
Name: Srikanth, Roll Number: A124, CGPA: 8
.9
Name: Hari, Roll Number: A123, CGPA: 7.8
$
```