Project NUDTEE – Team Dek70

Member 1.6931503050 Ninmanee Nualsee
2.6931503065 Rawisara Palang
3.6931503119 Suratsawadee Areerob
4.6931503074 Sirawit Kansuwan
5.6931503107 Thanyarat Ainpasat

Problem

General activity scheduling often suffers from unclear timing and participant requirements. Critical details like location and schedules get buried in group chats, leading to confusion and forgotten appointments.

Who has this problem?

Groups wanting to organize activities and the organizers who need to track participant numbers.

Why it matters / what it costs them

Time wasted scrolling through chat histories, missed opportunities due to delayed coordination, and the hassle of following up with people who forget the schedule.

Gate 1 — Real users

1. Ms. Rawipriya Udomplaa (student) tel-0887741637 2 November 2569
2. Ms. Jeeranan Yepiang (student) tel-0946208353 2 November 2569
3. Mr. Apiwat Chaiswat (student) tel-0955687886 2 November 2569

Gate 2 — MVP scope

FR-1 Create / edit a session A user creates or modifies a session with a title, pinned location, date/time, minimum/maximum players, and a closing time Must

FR-2 Join / leave a session A user joins or leaves a session; the system counts joined players and computes remaining spots Must

FR-3 Real-time session status The session details and participant count update instantly when someone joins or leaves, with no refresh Must

FR-4 Display location on map A user views the session's location(map pin) on an interactive map Must

FR-5 In-room chat A user sends and receives messages in real time within the specific session's chat room Should

FR-6 Auto-close session The system automatically blocks new users from joining once the specified closing time is reached Must

FR-7 Add to Google Calendar A user exports or adds a joined session directly to their Google Calendar Should

Which FRs contain real logic or decisions

FR-2 (Join / leave a session): remaining spots = max_players - current_joined; a join must be rejected when the session is full. Includes race condition handling (e.g., if two users tap join at the exact same time with only one spot left, only one may succeed).

FR-3 (Real-time session status): State must be synchronized in real time across many users within 2 seconds, and clients must resynchronize after a connection loss.

FR-6 (Auto-close session): The system must continuously or conditionally check the current time against the session's closing time; it must contain logic to automatically reject any join attempts once the deadline has passed.

Out of scope this term

Venue booking and payments: Integrating with cafes, sports clubs, or shops for direct reservations, or handling in-app bill splitting.

Friend systems: Creating friend lists, user following, or direct 1-on-1 messaging outside of the specific session's chat room.

Data that must persist

User profile: Display name and account/authentication details.

Session details: Title, pinned location (map coordinates), date/time, minimum/maximum players, closing time, and current joined count.

Participation records: Data mapping which user has joined which session (used to calculate remaining spots and reject joins when the session is full).

Chat data: Messages sent within each session's in-room chat, including sender ID and timestamps.

Success metrics

ID	Metric	Target
SM-1	Time for an organizer to create a session	60 seconds or less
SM-2	Taps for a player to join an open session from the list	2 taps or fewer
SM-3	Time for another device to show a join/leave change	2 seconds or less
SM-4	Taps to add a joined session to Google Calendar (after first-time consent):	2 taps or fewer
SM-5	Rejection rate for join attempts after the session closing time	100%
SM-6	Delivery time for in-room chat messages across devices	2 seconds or less

Gate 3 — Access and dependencies

Dependency	How we confirm it is really accessible
Auth provider (Google OAuth)	Create an OAuth client in Google Cloud Console before coding; check that it is free and what the rate limits are
Realtime database (Supabase)	Check that the free tier supports enough concurrent connections; set up a test project, send a realtime event, and confirm latency is about 2 seconds or better
Map tile provider (OpenStreetMap / Leaflet)	Confirm that tile server endpoints are open, free of charge, and do not require a paid API key or restrictive paywall for rendering location maps.
Google Calendar API	Enable the API in Google Cloud Console, test creating/exporting events using an OAuth token, and confirm it stays within the free usage quota.
Hosting (Vercel / Netlify)	Deploy a test environment from a free account and confirm no paywall or timeout issues block the real-time websocket connections and external API requests.

Role

Role	Responsibility	Owner
Product/project lead	Scope,planning	-Sirawit Kansuwan
Documetation	SRS,diagrams	-Sirawit Kansuwan -Suratsawadee Areerob -Thanyarat Ainpasat
Design/Frond/UI	Screens and clickable prototype,design doc	-Ninmanee Nualsee -Rawisara Palang
Backend/data	Supabase,join logic,realtime	-Thanyarat Ainpasat -Ninmanee Nualsee
QA/AI log	Test results,AI usage log	-Suratsawadee Areerob -Rawisara Palang