

RHCE Preparation (RHEL6)

# **OpenRHCE**

**A Creative Commons Courseware for RHCE Preparation**

## RHCE Preparation (RHEL6)

# Course Outline

## Contents

<b>Course Outline</b>	<b>3</b>
<b>Session One: Introduction</b>	<b>8</b>
Introductions: Your Instructor	9
Introductions: Your Instructor	10
Qualifications:	10
Personal:	10
Introductions: Fellow Students	11
Please Introduce Yourself	11
Introductions: The Course	12
Expectations	12
Preparation Recommendations	12
Red Hat Enterprise Linux	13
The Red Hat Certification Landscape	14
RHCSA Objectives	15
RHCSA Objectives: Understand & Use Essential Tools	15
RHCSA: ...Essential Tools... (cont)	15
RHCSA: Operate Running Systems	15
RHCSA: Configure Local Storage	15
RHCSA: Create and Configure File Systems	16
RHCSA: Deploy, Configure & Maintain	16
RHCSA: Manage Users and Groups	16
RHCSA: Manage Security	16
RHCE Objectives	18
RHCE: System Configuration and Management	18
RHCE: Network Services	18
RHCE: HTTP/HTTPS	18
RHCE: DNS	18
RHCE: FTP	19
RHCE: NFS	19
RHCE: SMB	19
RHCE: SMTP	19
RHCE: SSH	20
RHCE: NTP	20

## RHCE Preparation (RHEL6)

Boot, Reboot, Shutdown	21
Runlevels	22
Single User Mode	23
Log Files	24
Start/Stop Virtual Machines	25
Virtual Machine Consoles	26
Virtual Machine Text Console	27
Virtual Machine Text Console Caveat	28
Start, stop, and check the status of network services	29
Modify the system bootloader	30
<b>Session 2 Storage and filesystems</b>	<b>31</b>
"Filesystem" - Disambiguation	32
Linux Filesystem Hierarchy	33
Disk and Filesystem tools	34
Working with Partitions	35
Working with Logical Volume Management	36
Removing Logical Volume structures	37
Commands to Know	38
Working with LUKS encrypted storage	39
Persistent mounting of LUKS devices	40
Working with SWAP	41
Using a file for SWAP	42
Mounting Using UUIDs and Filesystem Labels	43
Local Storage: Adding New Storage	44
File systems: Working with Common Linux Filesystems	45
Filesystem Permissions: Basic Permissions	46
Three Sets of Permissions:	47
Three Types of Permissions:	48
Three Extended Attributes:	49
Viewing Permissions	50
Setting Permissions	51
Setting Permissions with Numeric Options	52
Setting Extended Attributes with Numeric Options	53
Setting Extended Attributes with Symbolic Values:	54
Extended Attributes in Directory Listings	55
Umask	56

## RHCE Preparation (RHEL6)

Umask Examples	57
SGID and Stickybit Use Case -- Collaborative Directories	58
File Access Control Lists	59
getfacl	60
Working with CIFS network file systems	61
Working with NFS file systems	62
iSCSI Devices	63
Accessing iSCSI Devices	64
Disconnecting from iSCSI Devices	65
Additional References	66
<b>Session 3 Managing software, processes, kernel attributes, and users and groups</b>	<b>67</b>
The Red Hat Network (RHN)	68
RHN Subscription Activation	69
3rd Party Yum Repositories	70
Yum Repository Mandatory Configuration Items	71
Yum Repository Common Optional Configuration Items	72
Managing Software: Using yum	73
Yum-related man pages	74
RPM Architecture	75
RPM Package Naming	76
Package Naming Example	77
Installing and Upgrading Packages	78
Upgrading a Kernel	79
RPM and Modified Config Files	80
Uninstalling	81
RPM over a Network	82
Common RPM Queries	83
RPM Verification	84
Validate Package Signatures	85
RPM Checksig Sample Output	86
Verify Installed Files	87
Change Codes from rpm --verify	88
RPM Verify Sample Output	89
Identifying Installed Packages	90
Managing Software: Building RPMs	91
Inside an RPM package	92

## RHCE Preparation (RHEL6)

Main contents of a .spec file	93
Preamble directives	94
Required Spec file sections	95
Package Building Tools	96
Setting up a Build Environment	97
Viewing the Build Environment	98
Building the RPM	99
RPM Building Exercise	100
Signing Your RPMs	102
Create a Repo with your files	104
RPM Packaging, Other Documentation:	105
Manage Processes and Services	106
Persistent Configuration of Services	107
Manage Processes and Services: Configure systems to boot into a specific runlevel automatically	108
Monitoring Processes	109
Killing Processes	110
Prioritizing Processes	111
<code>nice</code> and <code>renice</code> commands	112
Manage system performance	113
Manage Users and Groups	114
<b>Session 4 Networking and Routing</b>	<b>115</b>
Network Configuration and Troubleshooting	116
IP Address and Subnet Mask	117
Routing and Default Gateway	118
Hostname	119
Name Resolution	120
Two Controlling Services	121
Switching between Controlling Services	122
Network Configuration Files	123
Reference	124
Future (Near!) Network Device Naming Scheme	125
Troubleshooting Toolkit	126
<b>Session 5 Firewalls and SELinux</b>	<b>127</b>
Firewalling in RHEL6	128
iptables Built-in Chains	129
iptables Targets	130

## RHCE Preparation (RHEL6)

Connection Tracking States	131
SELinux	132
<b>Session 6 Virtualization</b>	<b>133</b>
<b>Session 7 Logging and remote access</b>	<b>134</b>
<b>Session 8 Network Time Protocol</b>	<b>135</b>
<b>Session 9 HTTP and FTP</b>	<b>136</b>
<b>Session 10 NFS and Samba</b>	<b>137</b>
<b>Session 11 DNS and SMTP</b>	<b>138</b>
<b>Session 12 Finish uncompleted topics, Review, or Practice Exam</b>	<b>139</b>
<b>Supplemental Topics</b>	<b>140</b>
Manage Processes and Services: Schedule tasks using cron	141

## **Session One: Introduction**



## **Introductions: Your Instructor**

Scott Purcell

[scott@texastwister.info](mailto:scott@texastwister.info)

<http://www.linkedin.com/in/scottpurcell>

<http://twitter.com/texastwister>

<http://www.facebook.com/Scott.L.Purcell>

## **Introductions: Your Instructor**

### ***Qualifications:***

- RHCSA, RHCE #110-008-877 (RHEL6)
- Also: CTT+, CLA, CLP, CNI, LPIC1, Linux+
- Curriculum Developer and Trainer for a major computer manufacturer for going on 11 years
- Linux Enthusiast since 2000

### ***Personal:***

- Husband, father, disciple and
- Fun: Part-time Balloon Entertainer

## **Introductions: Fellow Students**

### ***Please Introduce Yourself***

- Name
- Where you work or what you do.
- What Linux experience do you already have?
- What goals do you have for this class?
- Something fun about yourself.

## Introductions: The Course

### ***Expectations***

- Should I be able to pass the RHCE on this class alone?

A stunning number of seasoned professionals taking Red Hat's own prep courses fail to pass on first attempt.

- Planning for more than one attempt is prudent.
- Maximizing your out-of-class preparation time is prudent.

### ***Preparation Recommendations***

- Practice/Study Environment
  - 2 or 3 systems or VMs, networked together. Virtualized hosting providers may be an alternative.
  - RHEL 6 (eval), CENTOS 6 (when available), or Fedora (Fedora 13 will be closest to RHEL 6)
  - Red Hat docs at:  
[http://docs.redhat.com/docs/en-US/Red\\_Hat\\_Enterprise\\_Linux/index.html](http://docs.redhat.com/docs/en-US/Red_Hat_Enterprise_Linux/index.html)
  - RHCE Objectives and other information at:  
<http://www.redhat.com/certification/>
  - Take initiative -- form a study group.
  - Practice, practice, practice!

## **Red Hat Enterprise Linux**

- Overview
- Server and Desktop variants
- Add-on Functionality
- LifeCycle

## The Red Hat Certification Landscape

- RHCSA

RHCSA is new, replacing the RHCT. It is the "core" sysadmin certification from Red Hat. To earn RHCE and other system administration certs will require first earning the RHCSA.

- RHCE

RHCE is a senior system administration certification. It is an eligibility requirement for taking any COE exams and is thus a requirement for the upper-level credentials as well.

- Certificates of Expertise

COEs are incremental credentials demonstrating skills and knowledge in specialized areas. They are worthy credentials in their own right, but also the building blocks of the upper level credentials.

- RHCSS, RHCDS, RHCA

These upper level credentials recognize those who have achieved expertise in several related specialized areas. Each one requires multiple COEs.

## **RHCSA Objectives**

### ***RHCSA Objectives: Understand & Use Essential Tools***

- Access a shell prompt and issue commands with correct syntax
- Use input-output redirection (>, >>, |, 2>, etc.)
- Use grep and regular expressions to analyze text
- Access remote systems using ssh and VNC
- Log in and switch users in multi-user runlevels
- Archive, compress, unpack and uncompress files using tar, star, gzip, and bzip2

### ***RHCSA: ...Essential Tools... (cont)***

- Create and edit text files
- Create, delete, copy and move files and directories
- Create hard and soft links
- List, set and change standard ugo/rwx permissions
- Locate, read and use system documentation including man, info, and files in /usr/share/doc .

[Note: Red Hat may use applications during the exam that are not included in Red Hat Enterprise Linux for the purpose of evaluating candidate's abilities to meet this objective.]

### ***RHCSA: Operate Running Systems***

- Boot, reboot, and shut down a system normally
- Boot systems into different runlevels manually
- Use single-user mode to gain access to a system
- Identify CPU/memory intensive processes, adjust process priority with renice, and kill processes
- Locate and interpret system log files
- Access a virtual machine's console
- Start and stop virtual machines
- Start, stop and check the status of network services

### ***RHCSA: Configure Local Storage***

- List, create, delete and set partition type for primary, extended, and logical partitions
- Create and remove physical volumes, assign physical volumes to volume groups, create and delete logical volumes
- Create and configure LUKS-encrypted partitions and logical volumes to prompt for password and mount a decrypted file system at boot
- Configure systems to mount file systems at boot by Universally Unique ID (UUID) or label
- Add new partitions, logical volumes and swap to a system non-destructively

## ***RHCSA: Create and Configure File Systems***

- Create, mount, unmount and use ext2, ext3 and ext4 file systems
- Mount, unmount and use LUKS-encrypted file systems
- Mount and unmount CIFS and NFS network file systems
- Configure systems to mount ext4, LUKS-encrypted and network file systems automatically
- Extend existing unencrypted ext4-formatted logical volumes
- Create and configure set-GID directories for collaboration
- Create and manage Access Control Lists (ACLs)
- Diagnose and correct file permission problems

## ***RHCSA: Deploy, Configure & Maintain***

- Configure networking and hostname resolution statically or dynamically
- Schedule tasks using cron
- Configure systems to boot into a specific runlevel automatically
- Install Red Hat Enterprise Linux automatically using Kickstart
- Configure a physical machine to host virtual guests
- Install Red Hat Enterprise Linux systems as virtual guests
- Configure systems to launch virtual machines at boot
- Configure network services to start automatically at boot
- Configure a system to run a default configuration HTTP server
- Configure a system to run a default configuration FTP server
- Install and update software packages from Red Hat Network, a remote repository, or from the local filesystem
- Update the kernel package appropriately to ensure a bootable system
- Modify the system bootloader

## ***RHCSA: Manage Users and Groups***

- Create, delete, and modify local user accounts
- Change passwords and adjust password aging for local user accounts
- Create, delete and modify local groups and group memberships
- Configure a system to use an existing LDAP directory service for user and group information

## ***RHCSA: Manage Security***

- Configure firewall settings using system-config-firewall or iptables
- Set enforcing and permissive modes for SELinux
- List and identify SELinux file and process context



## RHCE Preparation (RHEL6)

- Restore default file contexts
- Use boolean settings to modify system SELinux settings
- Diagnose and address routine SELinux policy violations

## **RHCE Objectives**

### ***RHCE: System Configuration and Management***

- Route IP traffic and create static routes
- Use iptables to implement packet filtering and configure network address translation (NAT)
- Use /proc/sys and sysctl to modify and set kernel run-time parameters
- Configure system to authenticate using Kerberos
- Build a simple RPM that packages a single file
- Configure a system as an iSCSI initiator that persistently mounts an iSCSI target
- Produce and deliver reports on system utilization (processor, memory, disk, and network)
- Use shell scripting to automate system maintenance tasks
- Configure a system to log to a remote system
- Configure a system to accept logging from a remote system

### ***RHCE: Network Services***

Network services are an important subset of the exam objectives. RHCE candidates should be capable of meeting the following objectives for each of the network services listed below:

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service

RHCE candidates should also be capable of meeting the following objectives associated with specific services:

### ***RHCE: HTTP/HTTPS***

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Configure a virtual host
- Configure private directories
- Deploy a basic CGI application
- Configure group-managed content

### ***RHCE: DNS***

## RHCE Preparation (RHEL6)

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Configure a caching-only name server
- Configure a caching-only name server to forward DNS queries
- Note: Candidates are not expected to configure master or slave name servers

### ***RHCE: FTP***

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Configure anonymous-only download

### ***RHCE: NFS***

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Provide network shares to specific clients
- Provide network shares suitable for group collaboration

### ***RHCE: SMB***

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Provide network shares to specific clients
- Provide network shares suitable for group collaboration

### ***RHCE: SMTP***

## RHCE Preparation (RHEL6)

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Configure a mail transfer agent (MTA) to accept inbound email from other systems
- Configure an MTA to forward (relay) email through a smart host

### ***RHCE: SSH***

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Configure key-based authentication
- Configure additional options described in documentation

### ***RHCE: NTP***

- Install the packages needed to provide the service
- Configure SELinux to support the service
- Configure the service to start when the system is booted
- Configure the service for basic operation
- Configure host-based and user-based security for the service
- Synchronize time using other NTP peers

## **Boot, Reboot, Shutdown**

- GRUB Menu
- Display Manager Screen
- Gnome or KDE
- Terminal commands: shutdown, halt, poweroff, reboot, init

## Runlevels

- Default
- From GRUB Menu

## Single User Mode

- Password Recovery

Note: SELinux bug prevents password changes while set to "Enforcing".

## Log Files

`/var/log/*`

View with `cat`, `less` or other tools

Search with `grep`



## **Start/Stop Virtual Machines**

- Using virt-manager
- Using virsh commands

## Virtual Machine Consoles

- virt-manager
- virt-viewer

## Virtual Machine Text Console

With libguestfs-tools installed and the VM in question shut-down, from the host:

```
# virt-edit {VMname} /boot/grub/menu.lst
```

There, append to the kernel line:

```
console=tty0 console=ttyS0.
```

After saving, the following commands should allow a console based view of the boot process and a console login:

```
# virsh start {VMname} ; virsh console {VMname}
```

## Virtual Machine Text Console Caveat

After this change, some messages that appear only on the default console will be visible only here. For example, the passphrase prompt to decrypt LUKS-encrypted partitions mounted in `/etc/fstab` will not be visible when using `virt-viewer` and the vm will appear to be hung. Only by using `virsh` console can the passphrase be entered to allow the boot process to continue.

## **Start, stop, and check the status of network services**

## **Modify the system bootloader**

## **Session 2 Storage and filesystems**

## **"Filesystem" - Disambiguation**

Several meanings for the term:

- The way files are physically written to storage devices, as in the ext3, Fat-32, NTFS filesystems, or etc.
- The unified directory structure which logically organizes files
- The standard which defines how directories should be structured and utilized in Linux



## Linux Filesystem Hierarchy

The directory structure of a Linux system is standardized through the Filesystem Hierarchy Standard (explained at <http://www.pathname.com/fhs>)

The Linux Manual system has an abbreviated reference:

```
$ man 7 hier
```

Red Hat has a more complete description, along with RedHat-specific implementation decisions in their **Deployment Guide** at [http://www.redhat.com/docs/en-US/Red\\_Hat\\_Enterprise\\_Linux/5/html/Deployment\\_Guide/ch-filesystem.html](http://www.redhat.com/docs/en-US/Red_Hat_Enterprise_Linux/5/html/Deployment_Guide/ch-filesystem.html)

## Disk and Filesystem tools

- `fdisk` or `parted` -- Used to partition hard disks or other block devices
- `mkfs` and variants -- Used to create filesystems on block devices (actually a front-end for a variety of FS-specific tools)
- `fsck` and variants -- Used to run filesystem checks (a front-end to FS specific tools)
- `mount` -- Used to mount a filesystem to a specific location in the directory structure
- `/etc/fstab` -- Configuration file used to describe the filesystems that should be persistently mounted
- `blkid` -- used to identify filesystems or other in-use devices by UUID or filesystem labels.
- `df` -- used to display the capacity and utilization % of mounted filesystems.
- `partx` -- used to force implementation of a new partition table on an in-use device w/o the need to reboot.

## Working with Partitions

Overview of process for using Basic Storage Devices:

- Install the device or otherwise make it available to the system.
- Partition it with `fdisk` or `parted`.
- Create a filesystem on the partition with `mkfs` or other tools.
- Choose or create a directory to serve as a mount point.
- Mount the partition.
- Add an entry to `/etc/fstab` to make it persistent.

## Working with Logical Volume Management

Overview of process for using Logical Volume Management:

- Install the device or otherwise make it available to the system.
- Create a type 8e partition with `fdisk` or `parted`.
- Initialize the partition as a physical volume with `pvcreate`.
- Add the storage of the PV to a volume group with `vgcreate`.
- Allocate storage from the volume group to a logical volume with `lvcreate`.
- Create a filesystem on the logical volume with `mkfs` or other tools.
- Choose or create a directory to serve as a mount point.
- Mount the partition.
- Add an entry to `/etc/fstab` to make it persistent.

## Removing Logical Volume structures

- Unmount the lv you want to remove
- Edit `/etc/fstab` to remove its entry
- Remove the logical volume: `lvremove /dev/<vg>/<lv>`
- Before removing a VG, ensure there are no more LVs within it.
- Remove the volume group: `vgremove /dev/<vg>`
- Remove the LVM signature from the partitions: `pvremove /dev/<part>`

## Commands to Know

### fdisk

- Always use -u and -c for best compatibility with newer storage devices
- Can't create partitions  $\geq$  2TB, use parted with GPT instead

### mkfs

- Used to create filesystems on devices
- Front-end for other filesystem-specific tools (usually named mkfs.<fstype>)

### blkid

- Shows device name, Filesystem Labels, and UUID of detected block devices.
- May not show block devices until a filesystem is created on them.
- May not show block devices used in non-standard ways (for example, a filesystem on a whole disk instead of on a partition)

### mount

- used to make a new filesystem available

## Working with LUKS encrypted storage

cryptsetup-luks-1.1.2-2.el6.x86\_64

Overview of process for using LUKS encryption:

- Create a new partition
- Encrypt it with `cryptsetup luksFormat /dev/<partition>`
- Open the encrypted device and assign it a name with `cryptsetup luksOpen /dev/<partition> <name>`
- Create a filesystem on the named device (`/dev/mapper/<name>`)
- Create a mountpoint for the device
- Mount the device

To lock the volume:

- unmount it
- Use `cryptsetup luksClose <name>` to remove the decryption mapping

## Persistent mounting of LUKS devices

To persistently mount it

- Create an entry in /etc/crypttab:

```
<name> /dev/<partition> <password> (none|<blank>|<path/to/file/with/password>)>
```

- If the password field is "none" or left blank, the system will prompt for a password.
- Create an entry in /etc/fstab

### **Note**

At reboot, the password prompt goes only to the default console. If console redirection is enabled, as it might be in the case of enabling a virtual machine to accessible through `virsh console <name>`, then the only place where the prompt is seen and the passphrase can be entered is at that redirected console.



## Working with SWAP

Overview of process for adding SWAP space using a partition:

- Create a type 82 partition
- Initialize as swap with `mkswap /dev/<partition>`
- Identify the UUID with `blkid`
- Add an `/etc/fstab` line:

```
UUID=<UUID> swap swap defaults 0 0
```

- Activate the new swap space with: `swapon -a`

## Using a file for SWAP

Overview of process for adding SWAP space using a file:

- create a pre-allocated file of the desired size:

```
dd if=/dev/zero of=/path/to/<swapfile> bs=1M count=<size in MB>
```

- Initialize as swap with `mkswap /path/to/<swapfile>`
- Add an `/etc/fstab` line:

```
/path/to/<swapfile> swap swap defaults 0 0
```

- Activate the new swap space with: `swapon -a`

## **Mounting Using UUIDs and Filesystem Labels**

Configure systems to mount file systems at boot by Universally Unique ID (UUID) or label

## **Local Storage: Adding New Storage**

Add new partitions, logical volumes, and swap to a system non-destructively

## **File systems: Working with Common Linux Filesystems**

Create, mount, unmount and use ext2, ext3 and ext4 file systems

Extend existing unencrypted ext4-formatted logical volumes

## **Filesystem Permissions: Basic Permissions**

Linux permissions are organized around:

- Three sets of permissions -- User, Group, and Other
- Three types of permissions -- Read, Write, and Execute
- Three extended attributes -- SUID, SGID, and Stickybit

## Three Sets of Permissions:

Any given file or directory can be owned by one (and only one) user and one (and only one) group. Three different sets of permissions can be assigned.

- User -- User permissions apply to the individual user who owns the file or directory.
- Group -- Group permissions apply to any user who is a member of the group that owns the file or directory.
- Other -- Other permissions apply to any user account with access to the system that does not fall into the previous categories.

## Three Types of Permissions:

- Read ("r")
  - On a file, allows reading
  - On a directory, allows listing
- Write ("w")
  - On a file, allows editing
  - On a directory, allows creation and deletion of files
- Execute ("x")
  - On a file, allows execution if the file is otherwise executable (script or binary)
  - On a directory, allows entry or traversal (`# cd {dirname}`)



## Three Extended Attributes:

- **SUID (Set User ID)**

On an executable, runs a process under the UID of the file owner rather than that of the user executing it.

- **SGID (Set Group ID)**

On a directory, causes any files created in the directory to belong to the group owning the directory.

- **"Stickybit"**

On a directory, ensures that only the owner of a file or the owner of the directory can delete it, even if all users or other members of a group have write access to the directory.

## Viewing Permissions

Permissions are displayed with positions 2-10 of a "long" filelisting:

```
drwxr-xr-x
-rw-r--r--
drwxr-xr-x
  user group other
```

## Setting Permissions

The `chmod` command is used to set permissions on both files and directories. It has two modes -- one using symbolic options and one using octal numbers.

**`chmod [option] [ugoa...][+ -=][rwxst] filename`**

where ugo are user, group, other, or all and rwxst are read, write, execute, s{u/g}id, stickybit.

**`chmod [option] XXXX filename`**

where XXXX is a number representing the complete permissions on the file.

## Setting Permissions with Numeric Options

	User			Group			Other		
Permissions	r	w	x	r	w	x	r	w	x
Numeric Value	4	2	1	4	2	1	4	2	1
Sum	0-7			0-7	0-7				

example.txt	User			Group			Other		
Permissions	r	w	x	r	-	x	-	-	x
Numeric Value	4	2	1	4	0	1	0	0	1
Sum	7			5	1				

```
# chmod 751 myfile.txt
```

## Setting Extended Attributes with Numeric Options

chmod numeric options are actually 4 digits (not three). Missing digits are assumed to be leading zeroes.

The leftmost place is for extended attributes:

Attribute	SUID	SGID	Stickybit
Value	4	2	1

**Example:** `$ chmod 3775 MySharedDir`

## Setting Extended Attributes with Symbolic Values:

```
chmod +t {filename}
```

Sets the sticky bit

```
chmod u+s {filename}
```

Sets suid

```
chmod g+s {filename}
```

Sets sgid

## Extended Attributes in Directory Listings

-rwxrwxrwx	Normal Permissions, All permissions granted
-rwSrwxrwx	Indicates SUID set
-rwsrwxrwx	Indicates SUID and execute permission set
-rwxrwSrwx	Indicates SGID set
-rwxrwsrwx	Indicates SGID and execute permission set
-rwxrwxrWT	Indicates Stickybit set
-rwxrwxrwt	Indicates Stickybit and execute permission set

## Umask

- The `umask` value determines the permissions that will be applied to newly created files and directories.
- As a "mask" it is subtractive -- representing the value of the permissions you DO NOT want to grant.
- Execute rights are automatically withheld (w/o regard for the `umask`) for *files* but not for *directories*.
- Extended attributes are not addressed -- even though a `umask` is four characters.
- The default `umask` value is set in `/etc/bashrc` and can be modified (non-persistently!) with the bash built-in command `umask`.



## Umask Examples

- Umask of 0002 yields permissions of 0775 on new directories and 0664 on new files
- Umask of 0022 yields permissions of 0755 on new directories and 0644 on new files

## **SGID and Stickybit Use Case -- Collaborative Directories**

- Create a Group for Collaboration
- Add users to the group
- Create a directory for collaboration
- Set its group ownership to the intended group
- Set its group permissions appropriately
- Recursively set the SGID and sticky bits on the directory

This ensures that:

1. All files created in this directory will be owned by the intended group (SGID effect)
2. All files created in this directory can only be deleted by the user who owns the file or the user who owns the directory (stickybit effect)

## File Access Control Lists

- Provide more granular control of permissions.
- Filesystem must be mounted with the 'acl' option or be compiled with that option by default

getfacl

setfacl

## getfacl

Example of "getfacl acldir"

```
# file: acldir
# owner: frank
# group: frank
user::rwx
user:bob:-wx
user:mary:rw-
group::rwx
mask::rwx
other::r-x
```

Example of `ls -l acldir:`

```
drwxrwxr-x+ 2 frank frank 4096 2009-05-27 14:15 acldir
```

## **Working with CIFS network file systems**

Will be covered in more detail later.

Mount and unmount CIFS network file systems

## **Working with NFS file systems**

Mount and unmount NFS file systems

## iSCSI Devices

Package: iscsi-initiator-utils

Allows a system to access remote storage devices with SCSI commands as though it were a local hard disk.

Terms:

- iSCSI initiator: A client requesting access to storage
- iSCSI target: Remote storage device presented from an iSCSI server or "target portal"
- iSCSI target portal: A server providing targets to the initiator
- IQN: "iSCSI Qualified Name" -- a unique name. Both the initiator and target need such a name to be assigned

## Accessing iSCSI Devices

- Install the `iscsi-initiator-utils` package
- Start the `iscsi` and `iscsid` services (and configure them persistently on)
- Set the initiator IQN in `/etc/iscsi/initiatorname.iscsi`
- Discover targets with:

```
iscsiadm -m discovery -t st -p <portal IP address>
```

- Log in to the target using the name displayed in discovery:

```
iscsiadm -m node -T <IQN> -p <portal IP address> -l
```

- Identify the SCSI device name with `dmesg`, `tail /var/log/messages` or `ls -l /dev/disk/by-path/*iscsi*`
- Use the disk as though it were a local hard disk

### ***Important***

Be certain to use UUIDs or labels for persistent mounts in `/etc/fstab`. Also, provide `_netdev` as a mount option so that this device will not be mounted until the network is already up.



## Disconnecting from iSCSI Devices

- Ensure the device is not in use
- Unmount the device
- Remove its `/etc/fstab` entry
- Logout from the target:

```
iscsiadm -m node -T <IQN> -p <portal IP> -u
```

- Delete the local record:

```
iscsiadm -m node -T <IQN> -p <portal IP> -o delete
```

## Additional References

- Chapter 4 of the Storage Administration Guide for RHEL6 ([http://docs.redhat.com/docs/en-US/Red\\_Hat\\_Enterprise\\_Linux/6/html/Storage\\_Administration\\_Guide/index.html](http://docs.redhat.com/docs/en-US/Red_Hat_Enterprise_Linux/6/html/Storage_Administration_Guide/index.html)) covers the usage of parted.
  - Man pages for fdisk(8), fstab(5), mkfs(8), blkid(8), partprobe(8), mount(8), parted(8), cryptsetup(8), and crypttab(5)

## **Session 3 Managing software, processes, kernel attributes, and users and groups**

## The Red Hat Network (RHN)

The primary delivery mechanism for installable software, updates, errata and bug fixes and systems management functions for an installation of RHEL 6 is the Red Hat Network or RHN.

The "cost" of RHEL 6 is really a subscription to this support network.

These commands are using in managing an RHN subscription:

```
# man -k rhn
rhn-profile-sync      (8) - Update system information on Red Hat Network
rhn_check             (8) - Check for and execute queued actions on RHN
rhn_register          (8) - Connect to Red Hat Network
rhnplugin             (8) - Red Hat Network support for yum(8)
rhnplugin.conf [rhnplugin] (5) - Configuration file for the rhnplugin(8) yum(8) plugin
rhnreg_ks             (8) - A program for non interactively registering systems to Red Hat Network
rhnsd                 (8) - A program for querying the Red Hat Network for updates and information
```

## RHN Subscription Activation

A new user of RHEL6 should receive information similar to this:

```
Red Hat subscription login:
Account Number      : *****
Contract Number     : *****
Item Description     : Red Hat Enterprise Linux <Edition>
RHEL Subscription Number : *****
Quantity            : #
Service Dates       : 12-JUN-10 through 11-JUN-11
Customer Name       : *****
Account Number      : *****
Log into the new portal here: access.redhat.com
Login: *****
Password: *****
Email address: *****
```

That information can then be used with `rhnm_register` to activate a new subscription

## 3rd Party Yum Repositories

These are other repositories of installable software, updates, or bugfixes. The `yum` command can be configured to use them in addition to or instead of the RHN.

- Configuration of repositories other than the RHN is accomplished through text configuration files located in the directory: `/etc/yum.repos.d/`
- A configuration file for each repository (or group of related repos) should be created in `/etc/yum.repos.d/`
- The name of each repo config file should end in ".repo".
- This allows repos to be easily temporarily disabled simply by renaming the file to something like: `myrepo.repo.disabled`

## Yum Repository Mandatory Configuration Items

### Repository ID

Short name for identifying this repository in reports

```
[MyRepo]
```

### Name

Longer description of this repository

```
name=My Custom Repository
```

### Baseurl

Description of protocol and location needed to locate the repo files.

```
baseurl=ftp://192.168.5.200/pub/rhel6
```

## Yum Repository Common Optional Configuration Items

### gpgcheck

Defines whether yum should attempt to validate package signatures. "0" = "off", "1" = "on".

```
gpgcheck=1
```

### gpgkey

Defines (via URL) where the keys for signature validation are located (typically `file:///etc/pki/rpm-gpg/<key name>`)

```
gpgkey=file:///etc/pki/rpm-gpg/RPM-GPG-KEY-redhat-release
```

### enabled

(Optional) Defines whether this repository should be currently active. "0" = "off", "1" = "on".

```
enabled=1
```



## Managing Software: Using yum

Common commands:

**yum help**

Displays usage information.

**yum list**

Lists all available packages and indicates which are installed.

**yum search KEYWORD**

Searches for packages with a keyword in the package metadata.

**yum info PACKAGENAME**

Displays information about a package taken from the package metadata.

**yum install PACKAGENAME**

Installs a package (obtained from the repository) and any required dependencies.

**yum localinstall RPMFILENAME**

Installs a local .rpm file, but uses the repository to satisfy dependencies.

**yum remove PACKAGENAME**

Uninstalls a package and any other packages dependent upon it.

**yum update PACKAGENAME**

Installs a newer version of the package, if available.

**yum update**

Updates an installed package for which a newer version is available.

## Yum-related man pages

```
# man -k yum
greposync          (1) - synchronize yum repositories to a local directory
rhnplugin          (8) - Red Hat Network support for yum(8)
rhnplugin.conf [rhnplugin] (5) - Configuration file for the rhnplugin(8) yum(8) plugin
yum                (8) - Yellowdog Updater Modified
yum [yum-shell]    (8) - Yellowdog Updater Modified shell
yum-groups-manager (1) - create and edit yum's group metadata
yum-utils          (1) - tools for manipulating repositories and extended package management
yum.conf [yum]     (5) - Configuration file for yum(8)
```

## **RPM Architecture**

`rpm` executable

RPM packages -- Files to install + SPEC file (metadata)

Local RPM database -- retains metadata from all installed packages

Database is kept in `/var/lib/rpm`

## RPM Package Naming

- name-version-release.architecture\*.rpm
- Version is the version of the "upstream" open source code
- Release refers to Red Hat internal patches to the source code
- Architecture is one of:
  - i386,i686 -- 32 bit x86 compatible
  - x86\_64 -- Intel/AMD 64 bit
  - ppc64 -- Power PC 64 bit
  - ia64 -- Intel Itanium 64 bit
  - noarch -- Arch-independent code (scripts, docs, images, etc)
  - src -- Source code

## Package Naming Example

bash-3.2-24.el5.x86\_64.rpm

Name	Project Version	RH Release	Arch
bash	3.2	24.el5	x86_64

This package starts with version 3.2 of bash (from <ftp.gnu.org/gnu/bash>), applies a RH patch identified as 24.el5 to it, and is then built to run on an Intel/AMD 64 bit processor.

## Installing and Upgrading Packages

```
# rpm -i[v,h] name-ver-rel.arch.rpm
```

Installs a package

```
# rpm -U[v,h] name-ver-rel.arch.rpm
```

Upgrades a package if an older version was previously installed. Otherwise, simply installs the new version.

```
# rpm -F[v,h] name-ver-rel.arch.rpm
```

Upgrades a package if an older version is installed. Otherwise, does nothing -- **does not install new packages if no older version was installed.**

## Upgrading a Kernel

- Always use `#rpm -i ...`
- This leaves the previously installed kernel on the system and in the GRUB menu as a fall-back in case the new version has problems.

## RPM and Modified Config Files

Scenario: `niftyapp-1.0-1.el5.rpm` uses a config file, `/etc/nifty.conf`. You tweaked `/etc/nifty.conf` to fit your system. Now `niftyapp-2.0-1.el5.rpm` is available with new features that require changes in the `.conf` file and provides a new default config file. What to do?

- If the previous version provided a default config file, the changes are detected. Your modified version of the `.conf` file is saved as `/etc/nifty.conf.rpmsave` and the new default config is installed. You can compare the files and modify as needed.
- If the previous version did NOT provide a default config file, your version of the `.conf` file is saved as `/etc/nifty.conf.rpmorig` and the new default config is installed. You can compare the files and modify as needed.



## Uninstalling

```
# rpm -e name[-ver][-rel]
```

- Package removal is never verbose, never shows progress ( -v, -h have not effect)
- Package removal only needs the name (or when multiple versions of the same package are installed, sometimes the version or release) but not the architecture or the .rpm extension.

## RPM over a Network

```
# rpm -ivh ftp://{Host}/path/to/package-name-ver-rel.arch.rpm
```

```
# rpm -ivh http://{Host}/path/to/package-name-ver-rel.arch.rpm
```

And wildcard "globbing" is allowed:

```
# rpm -ivh http://{Host}/path/to/package-name*
```

## Common RPM Queries

Query	Result
<code>rpm -qa</code>	lists all installed packages.
<code>rpm -q pkg</code>	Reports the version of the package.
<code>rpm -qf /path/file</code>	Reports which package provided the file.
<code>rpm -qc pkg</code>	Lists all configuration files of the package.
<code>rpm -qd pkg</code>	Lists all documentation of the package.
<code>rpm -qi pkg</code>	Reports a description of the package.
<code>rpm -ql pkg</code>	Lists all files contained in the package.
<code>rpm -qR pkg</code>	Lists all dependencies.
<code>rpm -q --scripts</code>	Lists the scripts that run when installing/removing.

**`rpm -q{c|d|i|l|R}p /path/to/package-name-ver-rel-arch.rpm`**

Reports the same info as above, but pulls info from the .rpm file instead of the rpm database.

## RPM Verification

The RPM system satisfies two types of security concerns:

1. Is this package *authentic*? How do I know it came from Red Hat?
2. Has this package retained *integrity*? How do I know they haven't been modified?

Authenticity and integrity of packages can be confirmed prior to installation with GPG signing and MD5 checksums of the RPM packages.

Integrity of files can be confirmed after installation with verification of installed files against the recorded metadata in the package.

## Validate Package Signatures

1. Import the Red Hat GPG public key (It can be found on the installation CD or in the /etc/pki/rpm-gpg/ directory):

```
# rpm --import /media/disk/RPM-GPG-KEY-redhat-release
```

or:

```
# rpm --import /etc/pki/rpm-gpg/RPM-GPG-KEY-redhat-release
```

2. Check the signature of the package in question:

```
# rpm --checksig /path/to/package-ver-rel.arch.rpm
```

## RPM Checksig Sample Output

```
$ rpm --checksig ftp://linuxlib.us.dell.com/  
pub/Distros/RedHat/RHEL5/5.3/Server/x86_64/  
install-x86_64/Server/ImageMagick-6.2.8.0-4.el5_1.1.i386.rpm  
  
ftp://linuxlib.us.dell.com/pub/Distros/RedHat  
/RHEL5/5.3/Server/x86_64/install-x86_64/Server  
/ImageMagick-6.2.8.0-4.el5_1.1.i386.rpm: (sha1) dsa sha1 md5 gpg OK
```

## Verify Installed Files

`rpm -V` (or `--verify`) will compare existing files on the system to their pristine state in the packages they came from.

There are 8 points of comparison as shown in the following table, in the Michael Jang book and in the rpm man page:

## Change Codes from rpm --verify

Change Code	Meaning
5	MD5 checksum
S	File size
L	Symbolic Link
T	Modification time
D	Device
U	User
G	Group
M	Mode



## RPM Verify Sample Output

```
#rpm -Va
...

S.5....T  c /etc/ntp.conf
..?..... c /etc/ntp/keys
S.5....T  /usr/bin/aspell
.....T   /usr/share/ImageMagick-6.2.8/config/magic.xml
.....T  d /usr/share/doc/ImageMagick-6.2.8/images/arc.png
.....T  d /usr/share/doc/ImageMagick-6.2.8/images/background.jpg
...

```

## Identifying Installed Packages

View a list of the packages originally installed on the system:

```
# less /root/install.log
```

View a list of the packages installed through yum:

```
# less /var/log/yum.log
```

Query the RPM database for the packages installed right now:

```
# rpm -qa
```

## **Managing Software: Building RPMs**

As of this writing, Red Hat is pointing users to the following RPM Guide from the Fedora project for more information on RPM creation:

[http://docs.fedoraproject.org/en-US/Fedora\\_Draft\\_Documentation/0.1/html/RPM\\_Guide/](http://docs.fedoraproject.org/en-US/Fedora_Draft_Documentation/0.1/html/RPM_Guide/)

## Inside an RPM package

- files
- scripts
- metadata

The package is defined by a "build specification file" or *spec file*.

A good example of a spec file can be obtained from the source rpm for redhat-release.

<ftp://ftp.redhat.com/pub/redhat/linux/enterprise/6Server/en/os/SRPMS/redhat-release-server-6Server-6.0.0.37.el6.src.rpm>

### ***Tip***

Open .spec files in vim for color highlighting

## **Main contents of a .spec file**

- Introduction or preamble: Contains metadata about the package
- Build instructions on how to compile the source code or otherwise prepare the package payload.
- Scriptlets that perform the installation, uninstallation, or upgrade.
- Manifest of files to be installed, along with their permissions.
- Changelog recording the changes made to the package with each revision.

## Preamble directives

### **Name**

Name of the package

### **Version**

Version identifier

### **Release**

Indicates incremental changes within a version.

### **Group**

The package group that should include this package. This can come from the list at `/usr/share/doc/rpm-*/GROUPS` or can be unique to you. Not related to yum package groups.

### **License**

Short License Identifier as described at <http://fedoraproject.org/wiki/Packaging/LicensingGuidelines>

### **Summary**

Short (<=50 chars) one-line description.

### **Source**

The file to be used as the source code. Add'l sources can be specified as Source0, Source1, etc.

### **BuildArch**

Arch to use when building. Defaults to the existing system arch. May also be "noarch" for arch-independent packages.

### **Requires**

Requirements that this package needs to run. Can be in the form of files or other packages

### **BuildRequires**

Requirements needed to build this package.

## Required Spec file sections

%description

%prep

%build

%install

%clean

%files

%changelog

## Package Building Tools

These packages will provide tools for setting up a build environment and the ability to create your own packages.

- rpm-build
- rpmdevtools
- rpmlint



## Setting up a Build Environment

As a non-privileged user, run:

```
$ rpmdev-setuptree
```

This should create the following directory structure in your home directory:

```
~/rpmbuild
|-- BUILD
|-- RPMS
|-- SOURCES
|-- SPECS
\-- SRPMS
```

In that structure, your source files (in a tarball) should be placed `~/rpmbuild/SOURCES/` and your `.spec` file in `~/rpmbuild/SPECS/`. The `~/rpmbuild/BUILD/` directory will be a temporary working directory for the build process. And, after the `rpmbuild` process is complete, the finished binary and source RPMs will be placed in `~/rpmbuild/RPMS/` and `~/rpmbuild/SRPMS/`, respectively.

## Viewing the Build Environment

When diagnosing build problems, it is sometimes useful to see what files are actually being created in the build environment in order to identify deviations of actual behavior from expected behavior. The tree utility is useful for that.

Install tree with `# yum install tree`.

Invoke tree with `$ tree ~/rpmbuild` to show the contents of the build environment.

## Building the RPM

With the source files in place and a properly configured `.spec` file written, the `rpmbuild` command can be used to build the rpm either at once, or (for troubleshooting) in stages

```
$ rpmbuild -bp <spec file>
```

Builds through the `%prep` section -- unpacks sources and applies patches.

```
$ rpmbuild -bc <spec file>
```

Builds through compile -- processes the `%prep` and `%build` sections.

```
$ rpmbuild -bi <spec file>
```

Builds through `%install` -- processes `%prep`, `%build`, and `%install`.

```
$ rpmbuild -bb <spec file>
```

Builds only the binary rpm file.

```
$ rpmbuild -bs <spec file>
```

Builds only the source rpm file.

```
$ rpmbuild -ba <spec file>
```

Builds both the binary and source rpm files.

Use `rpmbuild --help` or `man rpmbuild` for other options.

## RPM Building Exercise

As root, install rpm-build, rpmlint, rpmdevtools:

```
# yum -y install rpmbuild rpmdevtools rpmlint
```

As a non-privileged user, create a project directory:

```
$ mkdir ~/hello-1.0
```

Name this according to the convention: <projname>-<majorver>.<minorver>

Create bash script: ~/hello-1.0/hello.sh

```
#!/bin/bash
# hello.sh
echo 'hello'
exit 0
```

Create a tarball of the project directory:

```
$ tar cvzf hello-1.0.tar.gz ~/hello-1.0/
```

Create an rpm development environment:

```
$ rpmdev-setuptree
```

Move the tarball to the SOURCES directory

Create a .spec file in the SPECS directory:

```
$ vim pkgname.spec
```

or:

```
$ rpmdev-newspec -o pkgname.spec
```

Insert a name (Match the pkgname on the tarball and directory)

Insert a version (Match the version)

Leave the release alone

Insert a summary (one line)

Insert a group (package group)

Insert a license

Insert a URL or delete the line

Insert on the Source0 line, the name of your tarball

Leave the BuildRoot line alone

Unless your package has prerequisites needed before it can be compiled, delete the BuildRequires line

## RHCE Preparation (RHEL6)

Unless your package has prerequisites needed before it can work, delete the Requires line

On a blank line below %description, insert a brief description of your package

Leave the %prep and %setup lines alone

If your package does not need to be "built" (compiled), delete the %build, %configure, and make lines.

Leave the %install section header alone.

Under the %install section, leave the rm line alone.

If your package does not need to be built, modify the make install line to something like this:

```
install -D myfile $RPM_BUILD_ROOT/path/to/install/dest/myfile
```

Leave the %clean and the rm -rf lines alone.

Under %files, use the following syntax to list each of the files your package will place on the target system:

```
%attr(770,owner,group)/path/to/file
```

Use the following syntax to list each of the directories your package will place on the target system:

```
%dir /root/bin
```

The changelog section can be deleted or left alone.

## Signing Your RPMs

Your RPMs can be digitally signed to protect users from the possibility of forged packages (any RPM package can execute scripts w/ root privileges when installed!). To implement this, first generate and identify a gpg key:

```
$ gpg --gen-key
gpg (GnuPG) 2.0.14; Copyright (C) 2009 Free Software Foundation, Inc.
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.

Please select what kind of key you want:
  (1) RSA and RSA (default)
  (2) DSA and Elgamal
  (3) DSA (sign only)
  (4) RSA (sign only)
Your selection?
RSA keys may be between 1024 and 4096 bits long.
What keysize do you want? (2048)
Requested keysize is 2048 bits
Please specify how long the key should be valid.
    0 = key does not expire
    <n>  = key expires in n days
    <n>w  = key expires in n weeks
    <n>m  = key expires in n months
    <n>y  = key expires in n years
Key is valid for? (0)
Key does not expire at all
Is this correct? (y/N) y

GnuPG needs to construct a user ID to identify your key.

Real name: Scott Purcell
Email address: scott@texastwister.info
Comment:
You selected this USER-ID:
    "Scott Purcell <scott@texastwister.info>"

Change (N)ame, (C)omment, (E)mail or (O)kay/(Q)uit? O
You need a Passphrase to protect your secret key.

We need to generate a lot of random bytes. It is a good idea to perform
some other action (type on the keyboard, move the mouse, utilize the
disks) during the prime generation; this gives the random number
generator a better chance to gain enough entropy.
gpg: key B9AED1DE marked as ultimately trusted
public and secret key created and signed.

gpg: checking the trustdb
gpg: 3 marginal(s) needed, 1 complete(s) needed, PGP trust model
gpg: depth: 0  valid:   1  signed:   0  trust: 0-, 0q, 0n, 0m, 0f, 1u
pub   2048R/B9AED1DE 2011-02-22
      Key fingerprint = 9987 B276 A24A 1210 13A7  4D05 9F3F 8934 B9AE D1DE
uid                               Scott Purcell <scott@texastwister.info>
```

## RHCE Preparation (RHEL6)

```
sub    2048R/0DA4CCE9 2011-02-22

[scott@Client1 rhel6]$
```

The key ID can be seen in the output above, or can be found with `gpg --fingerprint`

Export the key to a file:

```
$ gpg --armor --output ~/RPM-GPG-KEY-ScottPurcell --export B9AED1DE
```

```
[scott@Client1 ~]$ cat RPM-GPG-KEY-ScottPurcell -----BEGIN PGP PUBLIC KEY BLOCK-----
Version: GnuPG v2.0.14 (GNU/Linux)

mQENBE1jVagBCADVDT0vRI3Z5xPZb6AAI2D3bM/H4kEhyJ+yk1pbVPmu8yu0Cbsl
R+J9rjvN8rNpQwm40Gx6RpM7qtP/LodzD46dNfbr87IJ4F+4A3U= =f4Gq -----END PGP PUBLIC KEY
BLOCK-----
```

Configure rpm-related tools to use your signature:

```
$ echo '%_gpg_name Scott Purcell'>> ~/.rpmmacros
```

or:

```
$ echo '%_gpg_name B9AED1DE'>> ~/.rpmmacros
```

Now packages can be created and signed at the same time with `rpmbuild` using the `--sign` option. Or existing packages can be retroactively signed with `rpm` using the `--addsign` or `--resign` options.

With a signed package in place, the user intending to install it now needs to import the key:

```
# rpm --import /home/scott/RPM-GPG-KEY-ScottPurcell
```

And with the key imported, the package can be verified:

```
$ rpm -K rpmbuild/RPMS/x86_64/rhel6rhce-0.5-1.el6.x86_64.rpm
rpmbuild/RPMS/x86_64/rhel6rhce-0.5-1.el6.x86_64.rpm: rsa sha1 (md5) pgp md5 OK
```

## Create a Repo with your files

(Assumes httpd already installed)

```
# yum -y install createrepo
# mkdir -p /var/www/html/repo/Packages
# cp MyPackage.rpm /var/www/html/repo/Packages
# createrepo -v /var/www/html/repo
# cp /home/me/RPM-GPG-KEY-me /var/www/html/repo
```



## **RPM Packaging, Other Documentation:**

Red Hat Enterprise Linux Deployment Guide, section on "Querying RPM"

Man Pages:

- rpm (8)
- rpm2cpio (8)
- cpio (1)

## Manage Processes and Services

### Start a service:

- `service <servicename> start`
- `/etc/init.d/<servicescript> start`

### Stop a service:

- `service <servicename> stop`
- `/etc/init.d/<servicescript> stop`

### Check status of a service:

- `service <servicename> status`
- `/etc/init.d/<servicescript> status`

### Reload a service's config:

- `service <servicename> reload`
- `/etc/init.d/<servicescript> reload`

## Persistent Configuration of Services

Configure a service to start at boot:

- `chkconfig <servicename> on`
- `system-config-services`
- `ntsysv`

## **Manage Processes and Services: Configure systems to boot into a specific runlevel automatically**

`/etc/inittab`

## Monitoring Processes

**ps**

Highly configurable command to list running processes

**top**

Command to provide realtime reports of the most active running processes

## Killing Processes

### **kill**

kills a process by PID. Optionally sends "signals" other than "kill".

### **kill-all**

Kills a process by name. Use care not to match names you don't intend to kill.

### **pkill**

Also kills processes by name. Use care not to match names you don't intend to kill.

### **pgrep**

Searches processes by name. Useful for verifying which processes would be killed by pkill.

## Prioritizing Processes

The kernel calculates the priority of each process through a variety of factors. One input into that calculation is a user-modifiable value called "niceness".

- A process with higher niceness has lower priority and is thus more willing to share resources with other processes.
- niceness can range from -20 (highest priority) to 19 (lowest priority).

## **nice and renice commands**

### **nice**

Launches commands with a specified "niceness" value affecting process priority.

- Default niceness is "0".
- Root can set any value.
- Non-privileged users can only use positive values.

### **renice**

Modifies the niceness of an already-running process.

- Root can modify the niceness of any process in either direction.
- Non-privileged users can only modify their own processes and by increasing niceness (lowering priority)



## **Manage system performance**

- Use `/proc/sys` and `sysctl` to modify and set kernel run-time parameters
- Produce and deliver reports on system utilization (processor, memory, disk, and network)
- Use shell scripting to automate system maintenance tasks

## **Manage Users and Groups**

- Create, delete, and modify local user accounts
- Change passwords and adjust password aging for local user accounts
- Create, delete and modify local groups and group memberships
- Configure a system to use an existing LDAP directory service for user and group information
- Configure system to authenticate using Kerberos

## **Session 4 Networking and Routing**

## Network Configuration and Troubleshooting

Class discussion -- Populate a table explaining for each of the following aspects of network configuration:  
1) How to view or verify the existing configuration, and 2) How to change the configuration.

- IP Address and Subnet Mask
- Routing and Default Gateway
- Hostname
- Name Resolution

## IP Address and Subnet Mask

- Verifying configuration

`ip a, ifconfig`

- Changing configuration

`nm_applet, system-config-network, manual editing of interface config files`

## Routing and Default Gateway

- Verifying configuration

`route, ip r`

- Changing configuration

`route, ip r`, manual editing of route config files,

## Hostname

- Verifying configuration
- Changing configuration

## **Name Resolution**

- Verifying configuration
- Changing configuration



## Two Controlling Services

### **NetworkManager**

- RHEL6 default
- Ideal for client systems and systems with dynamic network conditions
- No support for bonding/bridging/aliases, etc.

### **network**

- RHEL5 and earlier default
- Ideal for systems with static network conditions
- Bonding/bridging/aliases supported.

## Switching between Controlling Services

To disable NetworkManager and enable network:

```
# service NetworkManager stop; chkconfig NetworkManager off
# service network start; chkconfig network start
```

To disable network and enable NetworkManager:

```
# service network stop; chkconfig network off
# service NetworkManager start; chkconfig NetworkManager on
```

To exempt a particular interface from control by NetworkManager, but leave it in control of other interfaces:

- In the interface configuration file of the interface to be exempted, insert the line:

```
NM_CONTROLLED=no
```

- Ensure both services are configured on and running.
- Configured interfaces can be brought up with `ifup eth<x>` or down with `ifdown eth<x>` regardless of whether they are managed by NetworkManager or not.

## Network Configuration Files

### **/etc/hosts**

Static hostname-to-IP resolution.

### **/etc/resolv.conf**

Client configuration for DNS.

### **/etc/sysconfig/network**

Main system networking config file. Enables/disables networking in general, sets the hostname, and configures routing.

### **/etc/sysconfig/network-scripts/ifcfg-*<ifname>***

Config file for each configured interface.

### **/etc/sysconfig/network-scripts/route-*<name>***

Config file for static routes (where needed)

### **Note**

/etc/sysconfig/networking/ is used by system-config-network and should not be manually edited.

## Reference

`/usr/share/doc/initscripts-9.03.17/sysconfig.txt`

## **Future (Near!) Network Device Naming Scheme**

[http://linux.dell.com/files/whitepapers/consistent\\_network\\_device\\_naming\\_in\\_linux.pdf](http://linux.dell.com/files/whitepapers/consistent_network_device_naming_in_linux.pdf)

## **Troubleshooting Toolkit**

## **Session 5 Firewalls and SELinux**

## Firewalling in RHEL6

RHEL6 implements a packet filtering firewall called iptables. You should know several key terms:

**rule**

A one-line rule defining a packet type and how it should be handled.

**chain**

A list of rules.

**table**

A list of rules aggregating all of the chains and rules taking a particular path through the network stack.

**policy**

A default rule that applies in the absence of other rules.



## **iptables Built-in Chains**

### **INPUT**

Applies to traffic with your server as the destination.

### **OUTPUT**

Applies to traffic origination on your server as the source.

### **FORWARD**

Applies to traffic being routed by your system from one network to another

## **iptables Targets**

### **ACCEPT**

Allows the packet to proceed to its destination.

### **DROP**

Silently drop the packet.

### **REJECT**

Drop the packet with a rejection message

### **LOG**

Combined with other targets, also log the action

## Connection Tracking States

Iptables can filter packets based on their relationship with previous traffic.

### **NEW**

The packet has started a new connection.

### **ESTABLISHED**

Applies to packets that are part of an established TCP connection (packets have already been delivered in both directions).

### **RELATED**

The packet is starting a new connection, but associated with an existing connection.

### **INVALID**

The packet is associated with no known connection.

## **SELinux**

## Session 6 Virtualization

o KVM Virtualization + \* Configure a physical machine to host virtual guests + \* Install Red Hat Enterprise Linux systems as virtual guests + \* Configure systems to launch virtual machines at boot + \* Install Red Hat Enterprise Linux automatically using Kickstart

## Session 7 Logging and remote access

o + - Remote Logging + \* Configure a system to log to a remote system + \* Configure a system to accept logging from a remote system o + - Remote Access + SSH # \* Install the packages needed to provide the service # \* Configure SELinux to support the service # \* Configure the service to start when the system is booted # \* Configure the service for basic operation # \* Configure host-based and user-based security for the service # \* Configure key-based authentication # \* Configure additional SSH options described in documentation + VNC # \* Install the packages needed to provide the service # \* Configure SELinux to support the service # \* Configure the service to start when the system is booted # \* Configure the service for basic operation # \* Configure host-based and user-based security for the service

## Session 8 Network Time Protocol

- o NTP + \* Install the packages needed to provide the service + \* Configure SELinux to support the service
- + \* Configure the service to start when the system is booted + \* Configure the service for basic operation
- + \* Configure host-based and user-based security for the service

## **Session 9 HTTP and FTP**



## **Session 10 NFS and Samba**

## **Session 11 DNS and SMTP**

## **Session 12 Finish uncompleted topics, Review, or Practice Exam**

## **Supplemental Topics**

## **Manage Processes and Services: Schedule tasks using cron**