

4CCS1DBS – Database Systems

The Relational Data Model and Relational Database Constraints

Introductions – Vasa Curcin

- Senior Lecturer in Health Informatics
- Based in School of Population Health Sciences, Faculty of Medicine
- Working on software to support clinical research
- Interest in data provenance and reproducibility of research
- Office hours on Mondays 1pm-3pm, BH(N) 7.05












Recap: ER Model Concepts

- ER model has three main concepts:
 - **Entities** (and their entity types and entity sets)
 - **Attributes** (simple, composite, multivalued)
 - **Relationships** (and their relationship types and relationship sets)
- Entities and Attributes
 - **Entities** are specific objects or things in the mini-world that are represented in the database.
 - **Attributes** are properties used to describe an entity.
- Entities with the same basic attributes are grouped or typed into an entity type.
- Each entity type will have a collection of entities stored in the database: the entity set

Recap: ER Model Concepts

- A **relationship** relates two or more distinct entities with a specific meaning.
- Relationships of the same type are grouped or typed into a ***relationship type***.
- Each relationship type will have a set of associations: the ***relationship set***.

Recap: Summary of notation for ER diagrams

Symbol	Meaning
	Entity
	Weak Entity
	Relationship
	Identifying Relationship
	Attribute
	Key Attribute
	Multivalued Attribute
	Composite Attribute
	Derived Attribute
	Total Participation of E_2 in R
	Cardinality Ratio 1 : N for $E_1:E_2$ in R

Recap: Relationship type vs. relationship set

■ Relationship Type:

- A set of associations among entities
- Is the schema description of a relationship
- Identifies the relationship name and the participating entity types
- Also identifies certain relationship constraints


■ Relationship Set:

- The current set of relationship instances represented in the database
- The current state of a relationship type


Constraints on Relationships

- Structural Constraints on Relationship Types
 - Also known as *ratio constraints*.
 - Cardinality Ratio: specifies **maximum** number of relationship instances that an entity can participate in.
 - One-to-one (1:1)
 - One-to-many (1:N) or Many-to-one (N:1)
 - Many-to-many (M:N)
 - Existence Dependency Constraint: specifies **minimum participation**, i.e. if existence of an entity depends on its being related to another entity via relationship type (also called *participation constraint*)
 - zero (optional participation, not existence-dependent)
 - one or more (mandatory participation, existence-dependent)

The Schema for COMPANY Database



The Schema for COMPANY Database (2)



Outline for Today

- Relational Model Concepts
- Relational Model Constraints and Relational Database Schemas
- Update Operations and Dealing with Constraint Violations

Relational Model Concepts

- The relational Model of Data is based on the concept of a *Relation*
 - The strength of the relational approach to data management comes from the formal foundation provided by the theory of relations
- We review the essentials of the *formal relational model*
- In *practice*, there is a *standard model* based on SQL – this will be described in later lectures
- Note: There are several important differences between the *formal* model and the *practical* model, as we shall see

Relational Model Concepts

- A Relation is a mathematical concept based on the ideas of sets
- The model was first proposed by Dr. E.F. Codd of IBM Research in 1970 in the following paper:
 - "A Relational Model for Large Shared Data Banks," Communications of the ACM, June 1970
- The above paper caused a major revolution in the field of database management and earned Dr. Codd the coveted ACM Turing Award

Informal Definitions

- Informally, a **relation** looks like a **table** of values.
- A relation typically contains a **set of rows**.
- The data elements in each **row** represent certain facts that correspond to a real-world **entity** or **relationship**
 - In the formal model, rows are called **tuples**
- Each **column** has a column header that gives an indication of the meaning of the data items in that column
 - In the formal model, the column header is called an **attribute name** (or just **attribute**)

Example of a Relation

Relation Name

STUDENT

Attributes

Tuples

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25

Informal Definitions

- Key of a Relation:

- Each row has a value of a data item (or set of items) that uniquely identifies that row in the table

- Called the *key*

- In the STUDENT table, SSN is the key

- Sometimes row-ids or sequential numbers are assigned as keys to identify the rows in a table

- Called **artificial key** or **surrogate key**

- one that was created specifically to be the unique identifier of a row
(NOT already exists in the table and chosen as key)

Formal Definitions - Schema

- The **Schema** (or description) of a Relation:
 - Denoted by $R(A_1, A_2, \dots, A_n)$
 - R is the **name** of the relation
 - The **attributes** of the relation are A_1, A_2, \dots, A_n
- Example:
CUSTOMER (Cust-id, Cust-name, Address, Phone#)
 - CUSTOMER is the relation name
 - Defined over the four attributes: Cust-id, Cust-name, Address, Phone#
- Each **attribute** has a **domain** or a set of valid values.
 - For example, the domain of Cust-id is 6 digit numbers.

Formal Definitions - Tuple

- A **tuple** is an **ordered set of values** (enclosed in angled brackets ' $\langle \dots \rangle$ ')
 - Each value is derived from an appropriate *domain*.
 - A row in the CUSTOMER relation is a **4-tuple** and would consist of four values, for example:
 - $\langle 632895, \text{"John Smith"}, \text{"101 Main St. Atlanta, GA 30332"}, \text{"(404) 894-2000"} \rangle$
 - This is called a 4-tuple as it has 4 values
 - A tuple (row) in the CUSTOMER relation.
- A relation is a **set of such tuples (rows)**

Formal Definitions - Domain

- A **domain** (a set of atomic values) has a logical definition:
 - Example: “USA_phone_numbers” are the set of 10 digit phone numbers valid in the U.S.
- A domain also has a **data-type** or a format defined for it.
 - The USA_phone_numbers may have a format: (ddd)ddd-dddd where each d is a decimal digit.
 - Dates have various formats such as year, month, date formatted as yyyy-mm-dd, or as dd mm,yyyy etc.
- 지정하다
The attribute name designates the role played by a domain in a relation:
 - Used to interpret the meaning of the data elements corresponding to that attribute
 - Example: The domain Date may be used to define two attributes named “Invoice-date” and “Payment-date” with different meanings

Formal Definitions - State

- The **relation state** is a subset of the Cartesian product of the domains of its attributes
 - each domain contains the set of all possible values the attribute can take.
- Example: attribute Cust-name is defined over the domain of character strings of maximum length 25
 - **dom(Cust-name) is varchar(25)**
- The role these strings play in the CUSTOMER relation is that of the *name of a customer*.

Formal Definitions - Summary

- Formally,
 - Given $R(A_1, A_2, \dots, A_n)$ a subset of the Cartesian product of the domains of its attributes
 - $r(R) \subset \text{dom}(A_1) \times \text{dom}(A_2) \times \dots \times \text{dom}(A_n)$
 - Cartesian product specifies all possible combinations of values from the underlying domains
- $R(A_1, A_2, \dots, A_n)$ is the **schema** of the relation
- R is the **name** of the relation
- A_1, A_2, \dots, A_n are the **attributes** of the relation
- $r(R)$: a specific **state** (or "value" or "population") of relation R – this is a set of tuples (rows)
 - $r(R) = \{t_1, t_2, \dots, t_n\}$ where each t_i is an n-tuple
 - $t_i = \langle v_1, v_2, \dots, v_n \rangle$ where each v_j element-of $\text{dom}(A_j)$

relation state


Formal Definitions - Example

- Let $R(A1, A2)$ be a relation schema:
 - Let $\text{dom}(A1) = \{0,1\}$
 - Let $\text{dom}(A2) = \{a,b,c\}$
- Then: $\text{dom}(A1) \times \text{dom}(A2)$ is all possible combinations:
 $\{ \langle 0,a \rangle, \langle 0,b \rangle, \langle 0,c \rangle, \langle 1,a \rangle, \langle 1,b \rangle, \langle 1,c \rangle \}$
- The relation state $r(R) \subset \text{dom}(A1) \times \text{dom}(A2)$
- For example: $r(R)$ could be $\{ \langle 0,a \rangle, \langle 0,b \rangle, \langle 1,c \rangle \}$
 - this is one possible state (or “population” or “extension”) r of the relation R , defined over $A1$ and $A2$.
 - It has three 2-tuples: $\langle 0,a \rangle, \langle 0,b \rangle, \langle 1,c \rangle$

Definition Summary

<u>Informal Terms</u>		<u>Formal Terms</u>
Table		Relation
Column Header		Attribute
All possible Column Values		Domain
Row		Tuple
Table Definition		Schema of a Relation
Populated Table		State of the Relation

Example – A relation STUDENT



Characteristics of Relations

- Relation is a set of tuples
- Ordering of *tuples* in a relation $r(R)$:
 - The tuples are *not considered to be ordered*, even though they appear to be in the tabular form.
- Ordering of *attributes* in a relation schema R (and of values within each tuple):
 - We will consider the attributes in $R(A_1, A_2, \dots, A_n)$ and the values in $t = \langle v_1, v_2, \dots, v_n \rangle$ to be *ordered*.
 - (However, a more general alternative definition of relation does not require this ordering)

Same state as previous Figure (but with different order of tuples)

STUDENT



Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21

Characteristics of Relations

- Values in a tuple:

not multivalued, single valued

- All values are considered **atomic** (indivisible).
- Each value in a tuple must be from the domain of the attribute for that column
 - If tuple $t = \langle v_1, v_2, \dots, v_n \rangle$ is a tuple (row) in the relation state r of $R(A_1, A_2, \dots, A_n)$
 - Then each v_i must be a value from $dom(A_i)$
- A special **null** value is used to represent values that are unknown or inapplicable to certain tuples.

Characteristics of Relations

■ Notation:

- We refer to **component values** of a tuple t by:

- $t[A_i]$ or $t.A_i$ $v_i = t[A_i]$ or $t.A_i$

- This is the value v_i of attribute A_i for tuple t

- Similarly, $t[A_u, A_v, \dots, A_w]$ refers to the subtuple of t containing the values of attributes A_u, A_v, \dots, A_w , respectively in t

given $t[A_a, A_b, A_c \dots A_z]$ then subtuple is $t[A_u, A_v]$

Relational Integrity Constraints

- Constraints are **conditions** that must hold on **all** valid relation states.
- There are three main types of constraints in the relational model:
 - **Key constraints**
 - **Entity integrity constraints**
 - **Referential integrity constraints**
- Another implicit constraint is the **domain constraint**
 - Every value in a tuple must be from the domain of its attribute (or it could be **null**, if allowed for that attribute)

Key Constraints

- **Superkey of R:** A superkey is a group of single or multiple keys which identifies rows in a table. A Super key may have additional attributes that are not needed for unique identification
 - Is a set of attributes SK of R with the following condition:
 - No two tuples in any valid relation state $r(R)$ will have the same value for SK
 - That is, for any distinct tuples t_1 and t_2 in $r(R)$, $t_1[SK] \neq t_2[SK]$
 - This condition must hold in *any valid state* $r(R)$
- **Key of R:**
 - we can't take out an attribute ■ A "minimal" superkey commonly refer as key
 - That is, a key is a superkey K such that removal of any attribute from K results in a set of attributes that is not a superkey (does not possess the superkey uniqueness property)

Key Constraints (continued)

- Example: Consider the CAR relation schema:
 - CAR(State, Reg#, SerialNo, Make, Model, Year)
 - Define superkeys of relation CAR
 - Define keys of relation CAR

Key Constraints (continued)

- Example: Consider the CAR relation schema:
 - CAR(State, Reg#, SerialNo, Make, Model, Year)
 - CAR has two keys:
 - Key1 = {State, Reg#}
 - Key2 = {SerialNo}
 - Both are also superkeys of CAR
 - {SerialNo, Make} is a superkey but *not* a key.
- In general:
 - Any key is a superkey (but not vice versa)
 - Any set of attributes that *includes a key* is a superkey
 - A *minimal* superkey is also a key

includes a key SerialNo so superkey

Not all superkeys are key

A super key with no repeated attribute is called candidate key.
The Primary key should be selected from the candidate keys.
Every table must have at least a single candidate key.

Key Constraints (continued)

- If a relation has several **candidate keys**, one is chosen arbitrarily to be the **primary key**.
 - The primary key attributes are underlined.
- Example: Consider the CAR relation schema:
 - CAR(State, Reg#, SerialNo, Make, Model, Year)
 - We chose SerialNo as the primary key
- The primary key value is used to *uniquely identify* each tuple in a relation
 - Provides the tuple identity
- Also used to *reference* the tuple from another tuple
 - General rule: Choose as primary key the **smallest of the candidate keys (in terms of size)**
 - Not always applicable – choice is sometimes subjective

The primary key field cannot be null.

CAR table with two candidate keys – LicenseNumber chosen as Primary Key

CAR

<u>License_number</u>	Engine_serial_number	Make	Model	Year
Texas ABC-739	A69352	Ford	Mustang	02
Florida TVP-347	B43696	Oldsmobile	Cutlass	05
New York MPO-22	X83554	Oldsmobile	Delta	01
California 432-TFY	C43742	Mercedes	190-D	99
California RSK-629	Y82935	Toyota	Camry	04
Texas RSK-629	U028365	Jaguar	XJS	04

Relational Database Schema

- **Relational Database Schema:**

- A set S of relation schemas that belong to the same database.
- S is the name of the whole **database schema**
- $S = \{R_1, R_2, \dots, R_n\}$
- R_1, R_2, \dots, R_n are the names of the individual **relation schemas** within the database S
- Following slide shows a COMPANY database schema with 6 relation schemata

COMPANY Database Schema

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

$S = \{R1, R2, \dots, Rn\}$

S = Company

R1 = Employee

R2 = Department

R3 = Dept_Locations

R4 = Project

R5 = Works_On

R6 = Dependent

Entity Integrity

- **Entity Integrity:**

- The *primary key attributes* **PK** of each relation schema **R** in **S** **cannot have null values in any tuple of $r(R)$.**
 - This is because primary key values are used to *identify* the individual tuples.
 - $t[PK] \neq \text{null}$ for any tuple t in $r(R)$
 - If PK has several attributes, null is not allowed in any of these attributes
- Note: Other attributes of **R** may be constrained to disallow null values, even though they may not be members of the primary key.


Referential Integrity

- A constraint involving **two** relations
 - The previous constraints involve a single relation.
- Used to specify a **relationship** among tuples in two relations:
 - The **referencing relation** and the **referenced relation**.

Foreign Key

- A set of attributes FK in relation schema R_1 is a **foreign key** of R_1 that references relation R_2 if it satisfies the following two rules:
 - The attributes in FK have the same domain(s) as the primary key attributes PK of R_2
 - the attributes FK are said to *reference* or *refer* to the relation R_2
 - A value of FK in tuple t_1 of $r_1(R_1)$ either occurs as a value of PK for some tuple t_2 in the relation state $r_2(R_2)$ or it is null.
 - $t_1[FK]=t_2[PK]$, i.e tuple t_1 *references* or *refers* to tuple t_2

Foreign Key - example



Referential Integrity

- Tuples in the **referencing relation R1** have attributes FK (called **foreign key** attributes) that reference the primary key attributes PK of the **referenced relation R2**.
 - A tuple t_1 in R1 is said to **reference** a tuple t_2 in R2 if $t_1[FK] = t_2[PK]$.
- A referential integrity constraint can be displayed in a relational database schema as a directed arc from **R1.FK** to **R2.PK**

Referential Integrity (or Foreign Key) Constraint

- Statement of the constraint
 - The value in the foreign key column (or columns) FK of the the **referencing relation** R1 can be **either**:
 - (1) a value of an existing primary key value of a corresponding primary key PK in the **referenced relation** R2, or
 - (2) a **null**.
- In case (2), the FK in R1 should **not** be a part of its own primary key.

Displaying a Relational Database Schema and its Constraints

- Each relation schema can be displayed as a row of attribute names
- The name of the relation is written above the attribute names
- The primary key attribute (or attributes) will be underlined
- A foreign key (referential integrity) constraints is displayed as a directed arc (arrow) from the foreign key attributes to the referenced table
 - Can also point to the primary key of the referenced relation for clarity
- COMPANY relational schema diagram next

Referential Integrity Constraints for COMPANY database

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT


Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------



Other Types of Constraints

- **Semantic Integrity Constraints:**
 - based on application semantics and cannot be expressed by the model per se
 - Example: “the max. no. of hours per employee for all projects he/she works on is 56 hrs per week”
 - A **constraint specification** language may have to be used to express these
 - SQL-99 allows triggers and **ASSERTIONS** to express some of these constraints

Populated Database State

- Each *relation* will have many tuples in its current relation state
- The *relational database state* is a union of all the individual relation states
- Whenever the database is changed, a new state arises
- Basic operations for changing the database:
 - INSERT a new tuple in a relation
 - DELETE an existing tuple from a relation
 - MODIFY an attribute of an existing tuple
- Next slide shows an example state for the COMPANY database

Populated Database State for COMPANY

EMPLOYEE

Fname	Minit	Lname	Ssn	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	Dnumber	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT_LOCATIONS

Dnumber	Dlocation
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS_ON

Essn	Pno	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0

PROJECT

Pname	Pnumber	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

DEPENDENT

Essn	Dependent_name	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
987654321	Elizabeth	F	1967-05-05	Spouse

Update Operations on Relations

- **INSERT** a tuple.
- **DELETE** a tuple.
- **MODIFY** a tuple.
- Integrity constraints should not be violated by the update operations.
- Several update operations may have to be grouped together.
- Updates may **propagate** to cause other updates automatically. This may be necessary to maintain integrity constraints.

Update Operations on Relations

- In case of integrity violation, several actions can be taken:
 - Cancel the operation that causes the violation (RESTRICT or REJECT option)
 - Perform the operation but inform the user of the violation
 - Trigger additional updates so the violation is corrected (CASCADE option, SET NULL option)
 - Execute a user-specified error-correction routine

Possible Violations for Each Operation

- INSERT may violate any of the constraints:
 - Domain constraint:
 - if one of the attribute values provided for the new tuple is not of the specified attribute domain
 - Key constraint:
 - if the value of a key attribute in the new tuple already exists in another tuple in the relation
 - Referential integrity:
 - if a foreign key value in the new tuple references a primary key value that does not exist in the referenced relation
 - Entity integrity:
 - if the primary key value is null in the new tuple

Possible Violations for Each Operation

- DELETE may violate only referential integrity:
 - If the primary key value of the tuple being deleted is referenced from other tuples in the database
 - Can be remedied by several actions: RESTRICT, CASCADE, SET NULL (will be discussed in one of following lectures)
 - **RESTRICT** option: reject the deletion if a record in the parent table is deleted, then the corresponding records in the child table will automatically be deleted
 - **CASCADE** option: delete referencing tuples
 - **SET NULL** option: set the foreign keys of the referencing tuples to NULL
 - One of the above options must be specified during database design for each foreign key constraint

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS ON

PROJECT

Possible Violations for Each Operation

- UPDATE may violate domain constraint and NOT NULL constraint on an attribute being modified
- Any of the other constraints may also be violated, depending on the attribute being updated:
 - Updating the primary key (PK):
 - Similar to a DELETE followed by an INSERT
 - Need to specify similar options to DELETE
 - Updating a foreign key (FK):
 - May violate referential integrity
 - Updating an ordinary attribute (neither PK nor FK):
 - Can only violate domain constraints

Summary

- Presented Relational Model Concepts
 - Definitions
 - Characteristics of relations
- Discussed Relational Model Constraints and Relational Database Schemas
 - Domain constraints
 - Key constraints
 - Entity integrity
 - Referential integrity
- Described the Relational Update Operations and Dealing with Constraint Violations