

# HOT FORMED HOLLOW SECTIONS

## Rectangular Hollow Sections - Length Ranges & Tolerances

| Size               |                   | Welded                  |                        |              | Seamless                  |                          |
|--------------------|-------------------|-------------------------|------------------------|--------------|---------------------------|--------------------------|
| Squares mm         | Rectangles mm     | Standard Mill Lengths m | Special Mill Lengths m | Tolerance mm | Standard Random Lengths m | Special Random Lengths m |
| 20 x 20            | --                | 6.4                     | 5.4 - 7.5              | + 150 - 0    |                           |                          |
| 25 x 25 & 30 x 30  | --                | 6.4 & 7.5               | 5.4 - 7.5              | + 150 - 0    |                           |                          |
| --                 | 50 x 25           | 7.5                     | 5.4 - 7.5              | + 150 - 0    |                           |                          |
| 40 x 40 uti        | 50 x 30 uti       | 7.5, 10 & 12            | 5.4 - 13.7             | + 150 - 0    |                           |                          |
| 100 x 100 x 8      | 120 x 80 x 8      |                         |                        |              |                           |                          |
| 100 x 100 x 10 uti | 120 x 80 x 10 uti | 7.5, 10 & 12            | 6.1 - 14.6             | + 150 - 0    |                           |                          |
| 150 x 150 x 12.5   | 200 x 100 x 12.5  |                         |                        |              |                           |                          |
| 150 x 150 x 16     | 200 x 100 x 16    |                         |                        |              | 10 - 11.2                 | 5.6 - 11.2               |
| 180 x 180 to       | 250 x 150 to      | 10 & 12                 | 9 - 14.8               | + 300 - 0    |                           |                          |
| 400 x 400          | 500 x 300         |                         |                        |              |                           |                          |
| 400 x 400 x 20     | --                | 6 - 9 randoms           | --                     | --           |                           |                          |

Minimum quantities supplied from our works in one size, thickness, length and quality.

Welded - Standard Mill lengths uti 150 x 150 x 12.5 and 200 x 100 x 12.5, 2 bundles, above these sizes 10 tonnes or less at works discretion.

Special Mill lengths - 10 tonnes.

Seamless - Standard Random lengths, 2.5 tonnes.

Special Random lengths, 10 tonnes.

## Circular Hollow Sections - Length Ranges & Tolerances

| Outside Diameter mm | Welded       |                         |                        |              | Seamless     |                         |               |
|---------------------|--------------|-------------------------|------------------------|--------------|--------------|-------------------------|---------------|
|                     | Thickness mm | Standard Mill Lengths m | Special Mill Lengths m | Tolerance mm | Thickness mm | Standard Mill Lengths m | Tolerances mm |
| 21.3 & 26.9         | all          | 6.0 & 6.4               | 5.4 - 7.5              | + 150 - 0    | --           |                         |               |
| 33.7 - 48.3         | all          | 6.0, 6.4 & 7.5          | 5.4 - 7.5              | + 150 - 0    | --           |                         |               |
| 60.3 - 114.3        | all          | 6.0, 6.4, 7.5 & 10      | 5.4 - 12               | + 150 - 0    | --           |                         |               |
| 139.7 - 168.3       | all          | 7.5, 10 & 12            | 6.1 - 14.6             | + 150 - 0    | --           |                         |               |
| 193.7               | uti 12.5     | 7.5, 10 & 12            | 6.1 - 14.6             | + 150 - 0    | 16           | 8, 10 & 12              | + 300 - 0     |
| 219.1               | uti 12.5     | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 16           | 8, 10 & 12              | + 300 - 0     |
|                     |              |                         |                        |              | 20           | 6, 8 & 10               | + 300 - 0     |
| 244.5               | 6.3 - 16     | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 6, 8 & 10               | + 300 - 0     |
| 273.0               | 6.3 - 16     | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 6, 8 & 10               | + 300 - 0     |
|                     |              |                         |                        |              | 25           | 4, 6 & 8                | + 300 - 0     |
| 323.9               | 6.3 - 16     | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 6, 8 & 10               | + 300 - 0     |
|                     |              |                         |                        |              | 25           | 4, 6 & 8                | + 300 - 0     |
| 355.6               | 8.0 - 16     | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 6, 8 & 10               | + 300 - 0     |
|                     |              |                         |                        |              | 25           | 4, 6 & 8                | + 300 - 0     |
| 406.4               | 10 - 16      | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 8, 10 & 12              | + 300 - 0     |
|                     |              |                         |                        |              | 25           | 4, 6 & 8                | + 300 - 0     |
|                     |              |                         |                        |              | 32           | 2, 4 & 6                | + 300 - 0     |
| 457.0               | 10 - 16      | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 8, 10 & 12              | + 300 - 0     |
|                     |              |                         |                        |              | 25           | 6, 8 & 10               | + 300 - 0     |
|                     |              |                         |                        |              | 32           | 4, 6 & 8                | + 300 - 0     |
|                     |              |                         |                        |              | 40           | 2, 4 & 6                | + 300 - 0     |
| 508.0               | 10 - 16      | 10 & 12                 | 9 - 14.8               | + 300 - 0    | 20           | 6, 8 & 10               | + 300 - 0     |
|                     |              |                         |                        |              | 25           | 6, 8 & 10               | + 300 - 0     |
|                     |              |                         |                        |              | 32           | 4, 6 & 8                | + 300 - 0     |
|                     |              |                         |                        |              | 40           | 2, 4 & 6                | + 300 - 0     |
|                     |              |                         |                        |              | 50           | 3, 4 & 5                | + 300 - 0     |

Minimum quantities supplied from our works in one size, thickness, length and quality.

Welded - Standard Mill lengths uti 193.7 - 4/5 tonnes. Over 193.7 - 10 tonnes or less at works discretion.

Special Mill lengths - 10 tonnes.

Seamless - Standard Mill lengths - 10 tonnes, or less at works discretion.