


HOT FORMED HOLLOW SECTIONS



RECTANGULAR

Section size D x B	Thickness t	Unit weight M	Section area A	Moment of inertia		Radius of gyration r		Elastic modulus Z		Plastic modulus S		Torsional constants J C		Superficial area per m	Approx. length per tonne
				x-x	y-y	x-x	y-y	x-x	y-y	x-x	y-y	x-x	y-y		
mm	mm	kg/m	cm ²	cm ⁴	cm ⁴	cm	cm	cm ³	cm ³	cm ³	cm ³	cm ⁴	cm ³	m ²	m
50 x 25	2.5*	2.72	3.47	10.5	3.44	1.75	1.00	4.25	2.75	5.41	3.25	8.41	4.62	0.145	368
	3.0*	3.22	4.10	12.2	3.89	1.73	0.98	4.88	3.11	6.30	3.77	9.64	5.21	0.144	311
	3.2*	3.41	4.34	12.8	4.05	1.72	0.97	5.11	3.24	6.64	3.96	10.1	5.42	0.143	294
50 x 30	2.5*	2.92	3.72	12.0	5.30	1.80	1.19	4.81	3.53	6.01	4.16	11.7	5.74	0.155	343
	3.0*	3.45	4.40	13.9	6.04	1.78	1.17	5.54	4.03	7.01	4.83	13.5	6.52	0.154	290
	3.2	3.66	4.66	14.5	6.31	1.77	1.16	5.82	4.21	7.39	5.08	14.2	6.81	0.153	274
	4.0*	4.46	5.68	17.0	7.25	1.73	1.13	6.80	4.83	8.81	6.01	16.6	7.79	0.151	224
	5.0*	5.40	6.88	19.5	8.13	1.68	1.09	7.79	5.42	10.4	6.98	19.0	8.71	0.149	185
60 x 40	2.5*	3.71	4.72	23.1	12.2	2.21	1.61	7.71	6.10	9.43	7.09	25.0	9.74	0.195	270
	3.0*	4.39	5.60	26.9	14.1	2.19	1.59	8.96	7.04	11.1	8.29	29.2	11.2	0.194	228
	3.2	4.66	5.94	28.3	14.8	2.18	1.58	9.44	7.39	11.7	8.75	30.8	11.8	0.193	215
	4.0	5.72	7.28	33.6	17.3	2.15	1.54	11.2	8.67	14.1	10.5	36.6	13.7	0.191	175
	5.0*	6.97	8.88	39.2	20.0	2.10	1.50	13.1	10.0	16.8	12.4	43.0	15.8	0.189	143
	6.0*	8.15	10.4	43.9	22.1	2.06	1.46	14.6	11.0	19.2	14.1	48.3	17.3	0.187	129
	6.3*	8.49	10.8	45.1	22.6	2.04	1.45	15.0	11.3	19.9	14.6	49.7	17.7	0.186	118
80 x 40	3.0*	5.34	6.80	55.0	18.2	2.85	1.64	13.8	9.10	17.3	10.5	43.7	15.3	0.234	188
	3.2	5.67	7.22	58.1	19.1	2.84	1.63	14.5	9.56	18.3	11.1	46.1	16.1	0.233	177
	4.0	6.97	8.88	69.6	22.6	2.80	1.59	17.4	11.3	22.2	13.4	55.1	18.9	0.231	144
	5.0*	8.54	10.9	82.4	26.2	2.75	1.55	20.6	13.1	26.7	15.9	65.0	21.9	0.229	117
	6.0	10.0	12.8	93.5	29.1	2.70	1.51	23.4	14.5	30.8	18.2	73.5	24.3	0.227	100
	6.3*	10.5	13.3	96.5	29.8	2.69	1.50	24.1	14.9	31.9	18.8	75.8	24.9	0.226	95.2
	8.0*	12.8	16.3	111	33.1	2.61	1.42	27.7	16.6	37.8	21.8	86.3	27.6	0.223	78.1
90 x 50	3.0*	6.28	8.0	85.4	33.8	3.27	2.05	19.0	13.5	23.4	15.5	76.4	22.4	0.274	160
	3.6	7.46	9.5	99.8	39.1	3.24	2.03	22.2	15.6	27.6	18.1	89.3	25.9	0.272	135
	5.0	10.1	12.9	130	50.0	3.18	1.97	28.9	20.0	36.6	23.9	116	32.9	0.269	99.1
	6.0	11.9	15.2	149	56.4	3.13	1.93	33.1	22.6	42.5	27.5	133	37.0	0.267	84
	6.3*	12.5	15.9	154	58.1	3.12	1.91	34.2	23.3	44.2	28.5	138	38.2	0.266	80
	8.0*	15.3	19.5	180	66.3	3.04	1.84	40.0	26.5	53.0	33.7	161	43.4	0.263	65.4
100 x 50	3.0*	6.75	8.60	111	37.1	3.59	2.08	22.2	14.8	27.6	16.9	88.3	25.0	0.294	149
	3.2	7.18	9.14	117	39.1	3.58	2.07	23.5	15.6	29.2	17.9	93.3	26.4	0.293	140
	4.0	8.86	11.3	142	46.7	3.55	2.03	28.4	18.7	35.7	21.7	113	31.4	0.291	113
	5.0	10.9	13.9	170	55.1	3.50	1.99	34.0	22.0	43.3	26.1	135	37.0	0.289	91.8
	6.0	12.9	16.4	195	62.3	3.45	1.95	39.0	24.9	50.4	30.2	154	41.7	0.287	77.5
	6.3*	13.4	17.1	202	64.2	3.44	1.94	40.5	25.7	52.5	31.3	160	43.0	0.286	74.7
	8.0*	16.6	21.1	238	73.5	3.36	1.86	47.6	29.4	63.1	37.1	187	49.1	0.283	60.2
	8.0*	16.6	21.1	238	73.5	3.36	1.86	47.6	29.4	63.1	37.1	187	49.1	0.283	60.2
100 x 60	3.0*	7.22	9.2	125	56.2	3.69	2.47	25.0	18.7	30.5	21.3	121	30.7	0.314	139
	3.6*	8.59	10.9	147	65.4	3.66	2.45	29.3	21.8	36.0	25.1	142	35.6	0.312	117
	5.0	11.7	14.9	192	84.7	3.60	2.39	38.5	28.2	48.1	33.3	187	45.9	0.309	85.5
	6.0	13.8	17.6	222	96.6	3.55	2.34	44.4	32.2	56.1	38.6	216	52.2	0.307	72.5
	6.3	14.4	18.4	230	99.9	3.54	2.33	46.0	33.3	58.4	40.2	224	53.9	0.306	69.5
	8.0*	17.8	22.7	272	116	3.46	2.26	54.4	38.7	70.5	48.1	266	62.4	0.303	56.2
120 x 60	3.6	9.72	12.4	230	76.9	4.31	2.49	38.3	25.6	47.6	29.2	183	43.3	0.352	103
	5.0	13.3	16.9	304	99.9	4.24	2.43	50.7	33.3	63.9	38.8	242	56.0	0.349	75.2
	6.0	15.7	20.0	352	114	4.20	2.39	58.7	38.1	74.8	45.1	279	63.9	0.347	63.7
	6.3	16.4	20.9	366	118	4.18	2.38	61.0	39.4	78.0	46.9	290	66.0	0.346	61
	8.0*	20.4	25.9	437	138	4.10	2.31	72.8	45.9	94.8	56.4	344	76.8	0.343	49

Notes:

Sizes printed black on grey background are by the Continuous Weld Process. Sizes printed in bold type are by the Hot Finished Seamless Process.

* Size not included in BS 4848 Part 2

† 43C only

Length per tonne rounded up