


HOT FORMED HOLLOW SECTIONS



CIRCULAR

Outside diameter	Thickness	Unit weight	Section area	Moment of inertia	Radius of gyration	Elastic modulus	Plastic modulus	Torsional	Constants	Superficial area per m	Approx. length per tonne
mm	t	kg/m	cm ²	cm ⁴	cm	cm ³	cm ³	cm ⁴	cm ³	m ²	m
21.3	3.2	1.43	1.82	0.77	0.65	0.72	1.06	1.54	1.44	0.067	700
26.9	3.2	1.87	2.38	1.70	0.846	1.27	1.81	3.41	2.53	0.085	535
33.7	2.6	1.99	2.54	3.09	1.10	1.84	2.52	6.19	3.67	0.106	503
	3.2	2.41	3.07	3.60	1.08	2.14	2.99	7.21	4.28	0.106	415
	4.0	2.93	3.73	4.19	1.06	2.49	3.55	8.38	4.97	0.106	342
42.4	2.6	2.55	3.25	6.46	1.41	3.05	4.12	12.9	6.10	0.133	393
	3.2	3.09	3.94	7.62	1.39	3.59	4.93	15.2	7.19	0.133	324
	4.0	3.79	4.83	8.99	1.36	4.24	5.92	18.0	8.48	0.133	264
48.3	3.2	3.56	4.53	11.6	1.60	4.80	6.52	23.2	9.59	0.152	281
	4.0	4.37	5.57	13.8	1.57	5.70	7.87	27.5	11.4	0.152	229
	5.0	5.34	6.80	16.2	1.54	6.69	9.42	32.3	13.4	0.152	188
60.3	3.2	4.51	5.74	23.5	2.02	7.78	10.4	46.9	15.6	0.189	222
	4.0	5.55	7.07	28.2	2.00	9.34	12.7	56.3	18.7	0.189	181
	5.0	6.82	8.69	33.5	1.96	11.1	15.3	67.0	22.2	0.189	147
76.1	3.2	5.75	7.33	48.8	2.58	12.8	17.0	97.6	25.6	0.239	174
	4.0	7.11	9.06	59.1	2.55	15.5	20.8	118	31.0	0.239	141
	5.0	8.77	11.2	70.9	2.52	18.6	25.3	142	37.3	0.239	115
88.9	3.2	6.76	8.62	79.2	3.03	17.8	23.5	158	35.6	0.279	148
	4.0	8.38	10.7	96.3	3.00	21.7	28.9	193	43.3	0.279	120
	5.0	10.3	13.2	116	2.97	26.2	35.2	233	52.4	0.279	97.1
114.3	3.6	9.83	12.5	192	3.92	33.6	44.1	384	67.2	0.359	102
	5.0	13.5	17.2	257	3.87	45.0	59.8	514	89.9	0.359	74.1
	6.3	16.8	21.4	313	3.82	54.7	73.6	625	109	0.359	59.6
139.7	5.0	16.6	21.2	481	4.77	68.8	90.8	961	138	0.439	60.3
	6.3	20.7	26.4	589	4.72	84.3	112	1,177	169	0.439	48.4
	8.0	26.0	33.1	720	4.66	103	139	1,441	206	0.439	38.5
	10.0	32.0	40.7	862	4.60	123	169	1,724	247	0.439	31.3
168.3	5.0	20.1	25.7	856	5.78	102	133	1,712	203	0.529	49.8
	6.3	25.2	32.1	1,053	5.73	125	165	2,107	250	0.529	39.7
	8.0	31.6	40.3	1,297	5.67	154	206	2,595	308	0.529	31.7
	10.0	39.0	49.7	1,564	5.61	186	251	3,128	372	0.529	25.7
193.7	5.0 *	23.3	29.6	1,320	6.67	136	178	2,640	273	0.609	43.0
	6.3	29.1	37.1	1,630	6.63	168	221	3,260	337	0.609	34.4
	8.0	36.6	46.7	2,016	6.57	208	276	4,031	416	0.609	27.4
	10.0	45.3	57.7	2,442	6.50	252	338	4,883	504	0.609	22.1
	12.5	55.9	71.2	2,934	6.42	303	411	5,869	606	0.609	17.9
	16.0 †	70.1	89.3	3,554	6.31	367	507	7,109	734	0.609	14.3
219.1	5.0 *	26.4	33.6	1,928	7.57	176	229	3,856	352	0.688	37.9
	6.3	33.1	42.1	2,386	7.53	218	285	4,772	436	0.688	30.3
	8.0	41.6	53.1	2,960	7.47	270	357	5,919	540	0.688	24.1
	10.0	51.6	65.7	3,598	7.40	328	438	7,197	657	0.688	19.4
	12.5	63.7	81.1	4,345	7.32	397	534	8,689	793	0.688	15.7
	16.0 †	80.1	102	5,297	7.20	483	661	10,590	967	0.688	12.5
	20.0 †	98.2	125	6,261	7.07	572	795	12,520	1143	0.688	10.2

Notes:

Sizes printed black on grey background are by the Continuous Weld Process. Sizes printed in bold type are by the Hot Finished Seamless Process.

Sizes printed in italics may be supplied Hot Finished, Seamless at our option.

* Size not included in BS 4848 Part 2

† Grade 50C only

Details of larger sizes of CHS available on application. Length per tonne rounded up