

PIPES

BRITISH STANDARD WELDED STEEL PIPES

BRITISH STANDARD STEEL TUBES FOR SCAFFOLDING (BS 1139: SECTION 1.1:1990)

Outside Diameter	Wall Thickness	Calculated Weight	Cross -Sectional Area	Second Moment of Inertia	Section Modulus	Radius of Gyration of Area	Plastic Modulus
mm	mm	kg/m	cm ²	cm ⁴	cm ³	cm	cm ³
48.30	4.00	4.37	5.57	13.80	5.70	1.57	7.87

Applicable Tolerances : Thickness $\pm 10\%$
Outside Diameter ± 0.50 mm

BRITISH STANDARD GALVANIZED STEEL CONDUIT (BS 31-1940 CLASS B SCREWED)

Nominal Size		Outside Diameter				Thickness				Calculated Weight with Coupler			No. of Threads	Length of Threads			
		Nominal		Minimum		Nominal		Minimum						Maximum		Minimum	
in	mm	in	mm	in	mm	in	mm	in	mm	kg/m	kg/ft	lb/ft	per inch	in	mm	in	mm
¾	19	0.75	19.05	0.7387	18.76	0.064	1.63	1.52	0.060	0.713	0.217	0.479	16	0.5625	14.3	0.500	12.7
1	25	1.00	25.40	0.9887	25.11	0.064	1.63	1.52	0.060	0.972	0.296	0.653	16	0.6875	17.5	0.625	15.9
1¼	32	1.25	31.75	1.2387	31.46	0.064	1.63	1.52	0.060	1.240	0.376	0.830	16	0.7500	19.1	0.6875	17.5
1½	38	1.50	38.10	1.4880	37.80	0.072	1.83	1.73	0.068	1.680	0.511	1.130	14	0.8125	20.6	0.750	19.1
2	50	2.00	50.80	1.9880	50.50	0.080	2.03	1.93	0.076	2.510	0.765	1.690	14	0.9375	23.8	0.875	22.2

Standard Length 3.81 m (12 ft. 6 in) without coupler

Features:

- * Made of hot-dip galvanized steel strip with extra-smooth surface and highly-adherent zinc coating by the unique tube-making process. The weld zone coating restored in-line
- * Inside weld bead controlled to a minimum for easier wire pulling
- * Screwed on both ends to BS 31 and fitted with a zinc-coated coupler on one end
- * Packed in bare bundles, but the unsocketed ends protected with plastic caps
- * Easier to cut, thread, bend and pull. Dimensionally accurate. Uniform quality in every respect.

EARTH PIPE - MANUFACTURER STANDARD

Nominal Size		Outside Diameter	Wall Thickness	Weight		
in	mm	mm	mm	kg/m	kg/ft	lb/ft
2	50	60.33	1.60	2.318	0.707	1.559

Standard Length: 4.78 m (16 ft.)

WINDOW PIPE - MANUFACTURER STANDARD

Nominal Size		Outside Diameter	Wall Thickness	Weight		
in	mm	mm	mm	kg/m	kg/ft	lb/ft
0.625	16	15.90	1.20	0.435	0.133	0.293