

EXPLANATORY NOTES

HIGH STRENGTH STEEL

OFFSHORE PLATFORM, F.P.S.O., BRIDGE GIRDERS, STRUCTURAL TUBULARS & FABRICATIONS. LOW TEMP CHARPY TESTED, + M = T.M.C.P QUALITY

National Standard		Grade	Min Yield N/mm²	UTS N/mm²	Charpy °C	Impacts (L) Joules	Former National Specifications					
							EU		GB		DE	
Year-ASTM + Shipbuilding = Latest							EN 10025: 1993		BS 43601: 1986		DIN 17100: 1983	
JP	JIS G3106 :2004	SM490B	325	490/610	0	27						
ANS	AS/NZS 3678:1996	350	340	480 min	N/R	N/R						
		350 L0	340	480 min	0	27						
USASTM	A572M Gr 50	345	450 min	N/R	N/R							
		A633M Gr C	345	450 min	0	26	Equivalent to					
		A588 Gr B	345	485 min	N/R	N/R						
							COR-TEN A	355	470-630	-20	27	
							COR-TEN B	355	470-630	-20	27	
CN	GB/T 1591:1994	Q345 A	345	470/630	N/R	N/R						
		Q345 B	345	470/630	+20	27						
		Q345 C	345	470/630	0	27						
		Q345 D	345	470/630	-20	27						
IN	IS 2062:2006	E350 A	350	490 min	N/R	N/R	IS 8500: 1991					
		E350 BR	350	490 min	+20	27						
		E350 B0	350	490 min	0	27						
		E350 C	350	490 min	-20	27						
EUEN 10025-2:2004		S355 JR	355	470/630	+20	27	S355 JR	50B	St.52-3			
		S355 JO	355	470/630	0	27	S355 JO	50C	St.52-3			
		S355 J2+N	355	470/630	-20	27	S355 J2G3	50D	St.52-3 N			
		S355 J2	355	470/630	-20	27	S355 J2G4	50EE				
		S355 K2/ K2+N	355	470/630	-20	40	S355 K2G3	50DD				
EUEN 10025-3:2004		S355N	355	470/630	-20	40	EN 10113: 1993 S355 N	50				
		S355NL	355	470/630	-50	27	EN 10113: 1993 S355 NL	50EE				
EUEN 10025-4:2004		S355M	355	520/680	-20	40	EN 10113: 1993 S355 M					
		S355ML	355	520/680	-50	27	EN 10113: 1993 S355 ML					
EUEN 10225:2004		S355 G2/G3+N	355	470/630	-20/-40	50	API: 1993	BS 7191: 1989				
		S355 G5/G6+M	355	470/630	-20/-40	50		355D/E				
		S355 G7+M/N	355	470/630	-40	50		355D/E				
		S355 G8+M/N	355	470/630	-40	50	API - 2H Gr50	355EM				
		S355 G9+M/N	355	470/630	-40	50	API - 2W Gr50	355MZ				
		S355 G10+M/N	355	470/630	-40	50	API - 2W Gr50T					
JP	JIS G3106:2004	SM490YB	365	490/610	0	27						
		SM520B	365	520/640	0	27						
JP	JIS G3101:2004	SS540	390	540 min	N/R	N/R						

ROLLED TUBULARS

Availability: 20" O/dia + over

API-2B/ 2H: 1 or more "Cans" can be fabricated from above S355 plates to suit req'd OD x WT x Length

PRODUCTS STOCK SIZES

AVAILABLE		S355JR - S355G10+N/M	ASTM A572-50-A588 GrB
Plates		Wide: 1.25m - 2.0m, 2.5m, 3.05m & 3.5m	Wide: 48" - 120" (1219 - 3048mm)
		Long: 3.0m - 6.0m, 8.0m, 10.0m, 12.0m & 15.0m	Long: 3' - 40' > 60' (915mm - 12.2m > 18.3m)
		THK: 5mm - 350mm	THK: 3/16" - 12" (4.75mm - 305mm)
		S355G7 - G10+M = 100mm MAX S355G7 - G10+N = 150mm MAX	
Coils	S355JR S355J2	Wide: 1.0m, 1.25m, 1.5m - 2.0m THK: 1mm - 12mm	