


CHANNELS



U-CHANNELS (Inside slope 5°)

Section size A x B	Unit weight M		Section depth A		Flange width B		Flange thickness t1		Web thickness t2		Corner radius			
											r1		r2	
mm (in)	kg/m	lb/ft	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in
127 x 64 (5 x 2 1/2)	14.90	10.0	127.0	5.0	63.5	2.5	9.2	0.362	6.4	0.252	10.7	0.421	2.4	0.094
152 x 76 (6 x 3)	17.88	12.0	152.4	6.0	76.2	3.0	9.0	0.354	6.4	0.252	12.2	0.480	2.4	0.094
152 x 89 (6 x 3 1/2)	23.84	16.0	152.4	6.0	88.9	3.5	11.6	0.457	7.1	0.280	13.7	0.539	3.2	0.126
178 x 76 (7 x 3)	20.84	14.0	177.8	7.0	76.2	3.0	10.3	0.405	6.6	0.260	12.2	0.480	3.2	0.126
178 x 89 (7 x 3 1/2)	26.81	18.0	177.8	7.0	88.9	3.5	12.3	0.484	7.6	0.299	13.7	0.539	3.2	0.126
203 x 76 (8 x 3)	23.82	16.0	203.2	8.0	76.2	3.0	11.2	0.441	7.1	0.280	12.2	0.480	3.2	0.126
203 x 89 (8 x 3 1/2)	29.78	20.0	203.2	8.0	88.9	3.5	12.9	0.508	8.1	0.319	13.7	0.539	3.2	0.126
229 x 76 (9 x 3)	26.06	17.5	228.6	9.0	76.2	3.0	11.2	0.441	7.6	0.299	12.2	0.480	3.2	0.126
229 x 89 (9 x 3 1/2)	32.76	22.0	228.6	9.0	88.9	3.5	13.3	0.524	8.6	0.339	13.7	0.539	3.2	0.126
254 x 76 (10 x 3)	28.29	19.0	254.0	10.0	76.2	3.0	10.9	0.429	8.1	0.319	12.2	0.480	3.2	0.126
254 x 89 (10 x 3 1/2)	35.74	24.0	254.0	10.0	88.9	3.5	13.6	0.535	9.1	0.358	13.7	0.539	3.2	0.126
305 x 89 (12 x 3 1/2)	41.69	28.0	304.8	12.0	88.9	3.5	13.7	0.539	10.2	0.402	13.7	0.539	3.2	0.126
305 x 102 (12 x 4)	46.18	31.0	304.8	12.0	101.6	4.0	14.8	0.583	10.2	0.402	15.2	0.598	4.8	0.189
381 x 102 (15 x 4)	55.10	37.0	381.0	15.0	101.6	4.0	16.3	0.642	10.4	0.409	15.2	0.598	4.8	0.189
432 x 102 (17 x 4)	65.54	44.0	431.8	17.0	101.6	4.0	16.8	0.661	12.2	0.480	15.2	0.598	4.8	0.189