

## HIGH-TENSILE GALVANISED C-PURLINS

### PURLIN SELECTION TABLES FOR ROOFING APPLICATION

The following purlin selection tables provide an easy reference for selection of appropriate purlin size in accordance with the bay width or column spacing of the building.

These tables can be generally used in Singapore and Malaysia. However, for optimum designs where specific roofing and insulation loads are to be used or for any other structure or for application outside Singapore and Malaysia, contact CHYE HIN HARDWARE PTE LTD for free technical advice.

TABLE NO. 2 - PURLIN SELECTION TABLE

Roof decking (0.61 mm TCT at 6.55kg/m<sup>2</sup> distributed load) on C-Purlin

| Span mm | Purlin spacing 1200 mm c/c | Purlin spacing 1500 mm c/c | Purlin spacing 1800 mm c/c | Purlin spacing 2100 mm c/c |
|---------|----------------------------|----------------------------|----------------------------|----------------------------|
| 5000    | SC100-16                   | SC100-20                   | SC150-16                   | SC150-16                   |
| 6000    | SC150-16                   | SC150-16                   | SC150-16                   | SC150-20                   |
| 7000    | SC150-20                   | SC200-16                   | SC200-16                   | SC200-16                   |
| 7500    | SC200-16                   | SC200-16                   | SC200-20                   | SC200-16                   |
| 8000    | SC200-16                   | SC200-16                   | SC200-16                   | SC200-16                   |
| 9000    | SC200-16                   | SC200-16                   | SC200-20                   | SC200-25                   |
| 10000   | SC200-20                   | SC200-25                   | --                         | --                         |
| 11000   | SC200-25                   | --                         | --                         | --                         |

TABLE NO. 3 - PURLIN SELECTION TABLE

Roof decking (0.61 mm TCT at 6.55kg/m<sup>2</sup> distributed load) on  
50mm thk insulation wool (32 kg/m<sup>3</sup>) on  
1 layer Aluminium Foil on  
1 layer Chicken mesh on C- Purlin

| Span mm | Purlin spacing 1200 mm c/c | Purlin spacing 1500 mm c/c | Purlin spacing 1800 mm c/c | Purlin spacing 2100 mm c/c |
|---------|----------------------------|----------------------------|----------------------------|----------------------------|
| 5000    | SC100-20                   | SC100-20                   | SC150-16                   | SC150-16                   |
| 6000    | SC150-16                   | SC150-16                   | SC150-16                   | SC150-20                   |
| 7000    | SC150-20                   | SC200-16                   | SC200-16                   | SC200-16                   |
| 7500    | SC200-16                   | SC200-16                   | SC200-20                   | SC200-16                   |
| 8000    | SC200-16                   | SC200-16                   | SC200-16                   | SC200-20                   |
| 9000    | SC200-16                   | SC200-20                   | SC200-25                   | SC200-25                   |
| 10000   | SC200-20                   | SC200-25                   | --                         | --                         |

Note: All purlins shall have one bridging at midspan except for purlins in shaded area where 2 bridging are provided at L/3 and 2L/3 between supports.