

EXPANDED METAL

SPECIFICATIONS

B.S No.	Code No.	Material	Nominal Size of Mesh		Thickness	Strand Width	Approx. Nominal Wt. kg/m ² ± 10%
			SWM	LWM			
			mm	mm		mm	mm
XM 21	3001	STEEL	76	200	6.0	12.5	16.5
XM 22	3002	STEEL			6.0	11.0	14.5
XM 23	3003	STEEL			4.5	12.0	12.4
XM 24	3004	STEEL			6.0	7.5	10.4
XM 25	3005	STEEL			4.5	9.0	9.3
XM 26	3006	STEEL			6.0	6.0	8.3
XM 27	3007	STEEL			4.5	7.0	7.0
XM 28	3008	STEEL			4.5	6.0	6.2
XM 29	3009	STEEL			3.0	7.5	5.1
XM 30	3010	STEEL			4.5	4.5	4.6
XM 31	3011	STEEL			3.0	6.0	4.1
XM 33	3013	STEEL			3.0	3.0	2.0
XM 41	1501	STEEL	38	114	4.5	9.5	18.0
XM 42	1502	STEEL			4.5	7.5	15.5
XM 43	1503	STEEL			4.5	6.0	12.4
XM 44	1504	STEEL			3.0	6.0	8.3
XM 45	1505	STEEL			3.0	4.5	6.2
XM 46	1506	STEEL			3.0	3.0	4.1
XM 47	1507	STEEL			1.5	6.0	4.1
XM 48	1508	STEEL			1.5	4.5	3.1
XM 49	1509	STEEL			1.5	3.0	2.0
XM 61	1001	STEEL	25	76	3.0	4.5	8.1
XM 63	1003	STEEL			3.0	3.0	5.4
XM 65	1005	STEEL			1.5	4.5	4.0
XM 66	1006	STEEL			1.5	3.0	2.7
XM 71	7502	STEEL	19	50	3.0	4.5	10.4
XM 72	7503	STEEL			3.0	3.0	7.1
XM 73	7504	STEEL			1.5	6.0	6.1
XM 75	7506	STEEL			1.5	3.0	3.5
XM 76	7507	STEEL			1.5	2.3	2.7

Code	Nominal size of mesh (mm)		Dimensions of strands (mm)		Approx. nominal weight kg/m ² ± 1 0%
	S.W.M.	L.W.M.	Thickness	Width	
G 1020	16	38	1.2	2.0	1.9
G 1032	25	40	3.0	3.0	5.4
G 1201	32	114	4.5	7.5	13.1
G 1232	33	102	3.0	3.0	4.5
G 2263	65	185	3.0	6.0	3.2
G 3092	38	76	3.0	4.5	4.5
G 5011	45	135	4.5	11.0	15.0
1000	30	76	4.5	6.0	15.7
1000 (3.8)	30	76	4.5	10.0	22.1
½ X18G	13	28	1.2	1.5	2.3

Tolerances :

Reference to sheet size, strand width, thickness and weights are approximate only. Whilst every effort is made for these figures to be accurate, it must be understood that the specification of goods manufactured and supplied by the company is subject to normal trade tolerances.

The company policy is one of continuous development : we therefore reserve the right to alter specifications, etc without notice.