


WROUGHT STEEL BUTT-WELDING FITTINGS

Standard Sizes of Butt-Welding Fittings (Metric Unit: mm)

DIMENSIONS OF FITTING ENDS

Nominal Pipe Size	Outside Diameter OD	Inside Diameter ID				Wall Thickness T			
		STD	S-40	XS	S-80	STD	S-40	XS	S-80
½	21.3	15.7	15.7	13.9	13.9	2.8	2.8	3.7	3.7
¾	26.7	20.9	20.9	18.9	18.9	2.9	2.9	3.9	3.9
1	33.4	26.6	26.6	24.4	24.4	3.4	3.4	4.5	4.5
1¼	42.2	35.0	35.0	32.4	32.4	3.6	3.6	4.9	4.9
1½	48.3	40.9	40.9	38.1	38.1	3.7	3.7	5.1	5.1
2	60.3	52.5	52.5	49.3	49.3	3.9	3.9	5.5	5.5
2½	73.0	62.6	62.6	59.0	59.0	5.2	5.2	7.0	7.0
3	88.9	77.9	77.9	73.7	73.7	5.5	5.5	7.6	7.6
3½	101.6	90.2	90.2	85.4	85.4	5.7	5.7	8.1	8.1
4	114.3	102.3	102.3	97.1	97.1	6.0	6.0	8.6	8.6
5	141.3	128.1	128.1	122.3	122.3	6.6	6.6	9.5	9.5
6	168.3	154.1	154.1	146.3	146.3	7.1	7.1	11.0	11.0
8	219.1	202.7	202.7	193.7	193.7	8.2	8.2	12.7	12.7
10	273.1	254.5	254.5	247.7	242.9	9.3	9.3	12.7	15.1
12	323.9	304.9	303.3	298.5	289.1	9.5	10.3	12.7	17.4
14	355.6	336.6	333.4	330.2	317.6	9.5	11.1	12.7	19.0
16	406.4	387.4	381.0	381.0	363.6	9.5	12.7	12.7	21.4
18	457.2	438.2	428.6	431.8	409.6	9.5	14.3	12.7	23.8

Note: Dimensions of outside diameter and wall thickness conform to ANSI B 36.10



45° ELBOWS

ANSI B 16.9

Nominal Pipe Size	Outside Diameter OD	STD		XS		Centre to Face B	Approx. Weight kg	
		ID	T	ID	T		STD	XS
½	21.3	15.7	2.8	13.9	3.7	15.9	0.0379	0.0485
¾	26.7	20.9	2.9	18.9	3.9	11.1	0.0378	0.0494
1	33.4	26.6	3.4	24.4	4.5	22.2	0.0748	0.0968
1¼	42.2	35.0	3.6	32.4	4.9	25.4	0.127	0.167
1½	48.3	40.9	3.7	38.1	5.1	28.6	0.182	0.243
2	60.3	52.5	3.9	49.3	5.5	34.9	0.326	0.448
2½	73.0	62.6	5.2	59.0	7.0	44.5	0.646	0.854
3	88.9	77.9	5.5	73.7	7.6	50.8	1.01	1.37
3½	101.6	90.2	5.7	85.4	8.1	57.2	1.42	1.95
4	114.3	102.3	6.0	97.1	8.6	63.5	1.92	2.67
5	141.3	128.1	6.6	122.3	9.5	79.4	3.26	4.63
6	168.3	154.1	7.1	146.3	11.0	95.3	5.08	7.64
8	219.1	202.7	8.2	193.7	12.7	127.0	10.2	15.5
10	273.1	254.5	9.3	247.7	12.7	158.8	18.1	24.4
12	323.9	304.9	9.5	298.5	12.7	190.5	26.5	35.0
14	355.6	336.6	9.5	330.2	12.7	222.3	34.1	45.0
16	406.4	387.4	9.5	381.0	12.7	254.0	44.6	59.0
18	457.2	438.2	9.5	431.8	12.7	285.8	56.6	74.9