


WROUGHT STEEL BUTT-WELDING FITTINGS


Standard Sizes of Butt-Welding Fittings (Metric Unit: mm)



90° ELBOWS Long Radius

ANSI B 16.9

Nominal Pipe Size	Outside Diameter OD	STD		XS		Centre to Face A	Approx. Weight kg	
		ID	T	ID	T		STD	XS
1/2	21.3	15.7	2.8	13.9	3.7	38.1	0.0759	0.0971
3/4	26.7	20.9	2.9	18.9	3.9	28.6	0.0756	0.0987
1	33.4	26.6	3.4	24.4	4.5	38.1	0.15	0.194
1 1/4	42.2	35.0	3.6	32.4	4.9	47.6	0.253	0.334
1 1/2	48.3	40.9	3.7	38.1	5.1	57.2	0.364	0.486
2	60.3	52.5	3.9	49.3	5.5	76.2	0.652	0.895
2 1/2	73.0	62.6	5.2	59.0	7.0	95.3	1.29	1.71
3	88.9	77.9	5.5	73.7	7.6	114.3	2.03	2.74
3 1/2	101.6	90.2	5.7	85.4	8.1	133.4	2.84	3.90
4	114.3	102.3	6.0	97.1	8.6	152.4	3.85	5.34
5	141.3	128.1	6.6	122.3	9.5	190.5	6.52	9.26
6	168.3	154.1	7.1	146.3	11.0	228.6	10.2	15.3
8	219.1	202.7	8.2	193.7	12.7	304.8	20.4	30.9
10	273.1	254.5	9.3	247.7	12.7	381.0	36.1	48.8
12	323.9	304.9	9.5	298.5	12.7	457.2	53.0	69.9
14	355.6	336.6	9.5	330.2	12.7	533.4	68.1	89.9
16	406.4	387.4	9.5	381.0	12.7	609.6	89.3	118.0
18	457.2	438.2	9.5	431.8	12.7	685.8	113.0	150.0



90° ELBOWS Short Radius

ANSI B 16.9

Nominal Pipe Size	Outside Diameter OD	STD		XS		Centre to Face A	Approx. Weight	
		ID	T	ID	T		STD	XS
1	33.4	26.6	3.4	24.4	4.5	25.4	0.0998	0.129
1 1/4	42.2	35.0	3.6	32.4	4.9	31.8	0.169	0.223
1 1/2	48.3	40.9	3.7	38.1	5.1	38.1	0.243	0.324
2	60.3	52.5	3.9	49.3	5.5	50.8	0.435	0.597
2 1/2	73.0	62.6	5.2	59.0	7.0	63.5	0.861	1.14
3	88.9	77.9	5.5	73.7	7.6	76.2	1.35	1.83
3 1/2	101.6	90.2	5.7	85.4	8.1	88.9	1.89	2.60
4	114.3	102.3	6.0	97.1	8.6	101.6	2.56	3.56
5	141.3	128.1	6.6	122.3	9.5	127.0	4.35	6.17
6	168.3	154.1	7.1	146.3	11.0	152.4	6.77	10.2
8	219.1	202.7	8.2	193.7	12.7	203.2	13.6	20.6
10	273.1	254.5	9.3	247.7	12.7	254.0	24.1	32.5
12	323.9	304.9	9.5	298.5	12.7	304.8	35.3	46.6
14	355.6	336.6	9.5	330.2	12.7	355.6	45.4	60.0
16	406.4	387.4	9.5	381.0	12.7	406.4	59.5	78.7
18	457.2	438.2	9.5	431.8	12.7	457.2	75.5	99.9