


WROUGHT STEEL BUTT-WELDING FITTINGS

Standard Sizes of Butt-Welding Fittings (Metric Unit: mm)




180° RETURNS Long Radius

ANSI B 16.9

Nominal Pipe Size	Outside Diameter OD	STD		XS		Centre to centre P	Centre to Face K	Approx. Weight kg	
		ID	T	ID	T			STD	XS
½	21.3	15.7	2.8	--	--	76.2	47.6	0.152	--
¾	26.7	20.9	2.9	18.9	3.9	57.2	42.9	0.151	0.197
1	33.4	26.6	3.4	24.4	4.5	76.2	55.6	0.299	0.387
1¼	42.2	35.0	3.6	32.4	4.9	95.3	69.9	0.506	0.668
1½	48.3	40.9	3.7	38.1	5.1	114.3	82.6	0.728	0.972
2	60.3	52.5	3.9	49.3	5.5	152.4	106.4	1.30	1.79
2½	73.0	62.6	5.2	59.0	7.0	190.5	131.8	2.58	3.42
3	88.9	77.9	5.5	73.7	7.6	228.6	158.8	4.05	5.48
3½	101.6	90.2	5.7	85.4	8.1	266.7	184.2	5.68	7.81
4	114.3	102.3	6.0	97.1	8.6	304.8	209.6	7.69	10.7
5	141.3	128.1	6.6	122.3	9.5	381.0	261.9	13.0	18.5
6	168.3	154.1	7.1	146.3	11.0	457.2	312.7	20.3	30.6
8	219.1	202.7	8.2	193.7	12.7	609.6	414.3	40.7	61.9
10	273.1	254.5	9.3	247.7	12.7	762.0	517.5	72.2	97.5
12	323.9	304.9	9.5	298.5	12.7	914.4	619.1	106.0	140.0

YICK HOE



180° RETURNS Short Radius

ANSI B 16.9

Nominal Pipe Size	Outside Diameter OD	STD		XS		Centre to centre P	Centre to Face K	Approx. Weight kg	
		ID	T	ID	T			STD	XS
1	33.4	26.6	3.4	24.4	4.5	50.8	41.3	0.200	0.258
1¼	42.2	35.0	3.6	32.4	4.9	63.5	52.4	0.338	0.446
1½	48.3	40.9	3.7	38.1	5.1	76.2	61.9	0.485	0.647
2	60.3	52.5	3.9	49.3	5.5	101.6	81.0	0.87	1.19
2½	73.0	62.6	5.2	59.0	7.0	127.0	100.0	1.72	2.28
3	88.9	77.9	5.5	73.7	7.6	152.4	120.7	2.70	3.65
3½	101.6	90.2	5.7	85.4	8.1	177.8	139.7	3.79	5.20
4	114.3	102.3	6.0	97.1	8.6	203.2	158.8	5.13	7.12
5	141.3	128.1	6.6	122.3	9.5	254.0	196.9	8.69	12.3
6	168.3	154.1	7.1	146.3	11.0	304.8	236.5	13.5	20.4
8	219.1	202.7	8.2	193.7	12.7	406.4	312.7	27.1	41.2
10	273.1	254.5	9.3	247.7	12.7	508.0	390.5	48.1	65.0
12	323.9	304.9	9.5	298.5	12.7	609.6	466.7	70.7	93.3