

CLASS 600

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	3 ³ / ₄ (95)	2 ⁵ / ₈ (67)	4	1/2 (13)	5/8 (16)	1 ³ / ₈ (35)	1/4 (6)	-	-	9/16 (14)
3/4	4 ⁵ / ₈ (117)	3 ¹ / ₄ (83)	4	5/8 (16)	3/4 (19)	1 ¹¹ / ₁₆ (43)	1/4 (6)	-	-	5/8 (16)
1	4 ⁷ / ₈ (124)	3 ¹ / ₂ (89)	4	5/8 (16)	3/4 (19)	2 (51)	1/4 (6)	-	-	1 ¹¹ / ₁₆ (17)
1 1/4	5 ¹ / ₄ (133)	3 ⁷ / ₈ (98)	4	5/8 (16)	3/4 (19)	2 1/2 (64)	1/4 (6)	-	-	1 ³ / ₁₆ (21)
1 1/2	6 ¹ / ₈ (156)	4 ¹ / ₂ (114)	4	3/4 (19)	7/8 (22)	2 ⁷ / ₈ (73)	1/4 (6)	-	-	7/8 (22)
2	6 ¹ / ₂ (165)	5 (127)	8	5/8 (16)	3/4 (19)	3 ⁵ / ₈ (92)	1/4 (6)	-	-	1 (25)
2 1/2	7 ¹ / ₂ (191)	5 ⁷ / ₈ (149)	8	3/4 (19)	7/8 (22)	4 ¹ / ₈ (105)	1/4 (6)	-	-	1 ¹ / ₈ (29)
3	8 ¹ / ₄ (210)	6 ⁵ / ₈ (168)	8	3/4 (19)	7/8 (22)	5 (127)	1/4 (6)	-	-	1 ¹ / ₄ (32)
4	10 ³ / ₄ (273)	8 ¹ / ₂ (216)	8	7/8 (22)	1 (25)	6 ³ / ₁₆ (157)	1/4 (6)	-	-	1 ¹ / ₂ (38)
5	13 (330)	10 ¹ / ₂ (267)	8	1 (25)	1 ¹ / ₈ (29)	7 ⁵ / ₁₆ (186)	1/4 (6)	-	-	1 ³ / ₄ (44)
6	14 (356)	11 ¹ / ₂ (292)	12	1 (25)	1 ¹ / ₈ (29)	8 ¹ / ₂ (216)	1/4 (6)	-	-	1 ⁷ / ₈ (48)
8	16 ¹ / ₂ (419)	13 ³ / ₄ (349)	12	1 ¹ / ₈ (29)	1 ¹ / ₄ (32)	10 ⁵ / ₈ (270)	1/4 (6)	-	-	2 ³ / ₁₆ (56)
10	20 (508)	17 (432)	16	1 ¹ / ₄ (32)	1 ³ / ₈ (35)	12 ³ / ₄ (324)	1/4 (6)	-	-	2 ¹ / ₂ (64)
12	22 (559)	19 ¹ / ₄ (489)	20	1 ¹ / ₄ (32)	1 ³ / ₈ (35)	15 (381)	1/4 (6)	-	-	2 ⁵ / ₈ (67)
14	23 ³ / ₄ (603)	20 ³ / ₄ (527)	20	1 ³ / ₈ (35)	1 ¹ / ₂ (38)	16 ¹ / ₄ (413)	1/4 (6)	-	-	2 ³ / ₄ (70)
16	27 (686)	23 ³ / ₄ (603)	20	1 ¹ / ₂ (38)	1 ⁵ / ₈ (41)	18 ¹ / ₂ (470)	1/4 (6)	-	-	3 (76)
18	29 ¹ / ₄ (743)	25 ³ / ₄ (654)	20	1 ⁵ / ₈ (41)	1 ³ / ₄ (44)	21 (533)	1/4 (6)	-	-	3 ¹ / ₄ (83)
20	32 (813)	28 ¹ / ₂ (724)	24	1 ⁵ / ₈ (41)	1 ³ / ₄ (44)	23 (584)	1/4 (6)	-	-	3 ¹ / ₂ (89)
24	37 (940)	33 (838)	24	1 ⁷ / ₈ (48)	2 (51)	27 ¹ / ₄ (692)	1/4 (6)	-	-	4 (102)

CLASS 900

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	4 ³ / ₄ (121)	3 ¹ / ₄ (83)	4	3/4 (19)	7/8 (22)	1 ³ / ₈ (35)	1/4 (6)	-	-	7/8 (22)
3/4	5 ¹ / ₈ (130)	3 ¹ / ₂ (89)	4	3/4 (19)	7/8 (22)	1 ¹¹ / ₁₆ (43)	1/4 (6)	-	-	1 (25)
1	5 ⁷ / ₈ (149)	4 (102)	4	7/8 (22)	1 (25)	2 (51)	1/4 (6)	-	-	1 ¹ / ₈ (29)
1 1/4	6 ¹ / ₄ (159)	4 ³ / ₈ (111)	4	7/8 (22)	1 (25)	2 1/2 (64)	1/4 (6)	-	-	1 ¹ / ₈ (29)
1 1/2	7 (178)	4 ⁷ / ₈ (124)	4	1 (25)	1 ¹ / ₈ (29)	2 ⁷ / ₈ (73)	1/4 (6)	-	-	1 ¹ / ₄ (32)
2	8 ¹ / ₂ (216)	6 ¹ / ₂ (165)	8	7/8 (22)	1 (25)	3 ⁵ / ₈ (92)	1/4 (6)	-	-	1 ¹ / ₂ (38)
2 1/2	9 ⁵ / ₈ (244)	7 ¹ / ₂ (191)	8	1 (25)	1 ¹ / ₈ (29)	4 ¹ / ₈ (105)	1/4 (6)	-	-	1 ⁵ / ₈ (41)
3	9 ¹ / ₂ (241)	7 ¹ / ₂ (192)	8	7/8 (22)	1 (25)	5 (127)	1/4 (6)	-	-	1 ¹ / ₂ (38)
4	11 ¹ / ₂ (292)	9 ¹ / ₄ (235)	8	1 ¹ / ₈ (29)	1 ¹ / ₄ (32)	6 ³ / ₁₆ (157)	1/4 (6)	-	-	1 ³ / ₄ (44)
5	13 ³ / ₄ (349)	11 (279)	8	1 ¹ / ₄ (32)	1 ³ / ₈ (35)	7 ⁵ / ₁₆ (186)	1/4 (6)	-	-	2 (51)
6	15 (381)	12 ¹ / ₂ (318)	12	1 ¹ / ₈ (29)	1 ¹ / ₄ (32)	8 ¹ / ₂ (216)	1/4 (6)	-	-	2 ³ / ₁₆ (56)
8	18 ¹ / ₂ (470)	15 ¹ / ₂ (394)	12	1 ³ / ₈ (35)	1 ¹ / ₂ (38)	10 ⁵ / ₈ (270)	1/4 (6)	-	-	2 ¹ / ₂ (64)
10	21 ¹ / ₂ (546)	18 ¹ / ₂ (470)	16	1 ³ / ₈ (35)	1 ¹ / ₂ (38)	12 ³ / ₄ (324)	1/4 (6)	-	-	2 ³ / ₄ (70)
12	24 (610)	21 (533)	20	1 ³ / ₈ (35)	1 ¹ / ₂ (38)	15 (381)	1/4 (6)	-	-	3 ¹ / ₈ (80)
14	25 ¹ / ₄ (641)	22 (559)	20	1 ¹ / ₂ (38)	1 ⁵ / ₈ (41)	16 ¹ / ₄ (413)	1/4 (6)	-	-	3 ³ / ₈ (86)
16	27 ³ / ₄ (705)	24 ¹ / ₄ (616)	20	1 ⁵ / ₈ (41)	1 ³ / ₄ (44)	18 ¹ / ₂ (470)	1/4 (6)	-	-	3 ¹ / ₂ (89)
18	31 (787)	27 (686)	20	1 ⁷ / ₈ (48)	2 (51)	21 (533)	1/4 (6)	-	-	4 (102)
20	33 ³ / ₄ (857)	29 ¹ / ₂ (749)	20	2 (51)	2 ¹ / ₈ (54)	23 (584)	1/4 (6)	-	-	4 ¹ / ₄ (108)
24	41 (1041)	35 ¹ / ₂ (902)	20	2 ¹ / ₂ (64)	2 ⁵ / ₈ (67)	27 ¹ / ₄ (692)	1/4 (6)	-	-	5 ¹ / ₂ (140)