

SLIP-ON FLANGES(BS 4504)

PN 6

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	80	55	4	M10	11	40	2	12	-	-
3/4	90	65	4	M10	11	50	2	14	-	-
1	100	75	4	M10	11	60	2	14	-	-
1 1/4	120	90	4	M12	14	70	2	16	-	-
1 1/2	130	100	4	M12	14	80	3	16	-	-
2	140	110	4	M12	14	90	3	16	-	-
2 1/2	160	130	4	M12	14	110	3	16	-	-
3	190	150	4	M16	18	128	3	18	-	-
4	210	170	4	M16	18	148	3	18	-	-
5	240	200	8	M16	18	178	3	20	-	-
6	265	225	8	M16	18	202	3	20	-	-
8	320	280	8	M16	18	258	3	22	-	-
10	375	335	12	M16	18	312	3	24	-	-
12	440	395	12	M20	22	365	4	24	-	-
14	490	445	12	M20	22	415	4	26	-	-
16	540	495	16	M20	22	465	4	28	-	-
18	595	550	16	M20	22	520	4	30	-	-
20	645	600	20	M20	22	570	4	30	-	-
24	755	705	20	M24	26	670	5	30	-	-

PN 10

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	95	65	4	M12	14	45	2	14	-	-
3/4	105	75	4	M12	14	58	2	16	-	-
1	115	85	4	M12	14	68	2	16	-	-
1 1/4	140	100	4	M16	18	78	2	18	-	-
1 1/2	150	110	4	M16	18	88	3	18	-	-
2	165	125	4	M16	18	102	3	20	-	-
2 1/2	185	145	4	M16	18	122	3	20	-	-
3	200	160	8	M16	18	138	3	22	-	-
4	220	180	8	M16	18	158	3	24	-	-
5	250	210	8	M16	18	188	3	26	-	-
6	285	240	8	M20	22	212	3	26	-	-
8	340	295	8	M20	22	268	3	26	-	-
10	395	350	12	M20	22	320	3	28	-	-
12	445	400	12	M20	22	370	4	28	-	-
14	505	460	16	M20	22	430	4	30	-	-
16	565	515	16	M24	23	482	4	32	-	-
18	615	565	20	M24	26	532	4	32	-	-
20	670	620	20	M24	26	585	4	34	-	-
24	780	725	20	M27	30	685	5	36	-	-