

FLANGES

PN 16

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	95	65	4	M12	14	45	2	14	6	16
3/4	105	75	4	M12	14	58	2	16	6	18
1	115	85	4	M12	14	68	2	16	8	18
1 1/4	140	100	4	M16	18	78	2	18	8	18
1 1/2	150	110	4	M16	18	88	3	18	9	18
2	165	125	4	M16	18	102	3	20	11	20
2 1/2	185	145	4	M16	18	122	3	20	13	18
3	200	160	8	M16	18	138	3	22	13	20
4	220	180	8	M16	18	158	3	24	16	20
5	250	210	8	M16	18	188	3	26	-	22
6	285	240	8	M20	22	212	3	26	-	22
8	340	295	12	M20	22	268	3	30	-	24
10	405	355	12	M24	26	320	3	32	-	26
12	460	410	12	M24	26	378	4	32	-	28
14	520	470	16	M24	26	438	4	36	-	30
16	580	525	16	M27	30	490	4	38	-	32
18	640	585	20	M27	30	550	4	40	-	-
20	715	650	20	M30	33	610	4	42	-	36
24	840	770	20	M33	36	725	5	48	-	40

PN 25

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	95	65	4	M12	14	45	2	16	8	16
3/4	105	75	4	M12	14	58	2	18	8	18
1	115	85	4	M12	14	68	2	18	9	18
1 1/4	140	100	4	M16	18	78	2	20	9	18
1 1/2	150	110	4	M16	18	88	3	20	11	18
2	165	125	4	M16	18	102	3	22	11	20
2 1/2	185	145	8	M16	18	122	3	24	13	22
3	200	160	8	M16	18	138	3	26	14	24
4	235	190	8	M20	22	162	3	28	17	24
5	270	220	8	M24	26	188	3	30	-	26
6	300	250	8	M24	26	218	3	34	-	28
8	360	310	12	M24	26	278	3	34	-	30
10	425	370	12	M27	30	335	3	36	-	32
12	485	430	16	M27	30	395	4	40	-	34
14	555	490	16	M30	33	450	4	44	-	38
16	620	550	16	M33	36	505	4	48	-	40
20	730	660	20	M33	36	615	4	52	-	44
24	845	770	20	M36	39	720	5	-	-	46