

PN 40

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	95	65	4	M12	14	45	2	-	9	16
3/4	105	75	4	M12	14	58	2	-	9	18
1	115	85	4	M12	14	68	2	-	11	18
1 1/4	140	100	4	M16	18	78	2	-	11	18
1 1/2	150	110	4	M16	18	88	3	-	13	18
2	165	125	4	M16	18	102	3	-	13	20
2 1/2	185	145	8	M16	18	122	3	-	14	22
3	200	160	8	M16	18	138	3	-	16	24
4	235	190	8	M20	22	162	3	-	19	24
5	270	220	8	M24	26	188	3	-	-	26
6	300	250	8	M24	26	218	3	-	-	28
8	375	320	12	M27	30	285	3	-	-	34
10	450	385	12	M30	33	345	3	-	-	38
12	515	450	16	M30	33	410	4	-	-	42
14	580	510	16	M33	36	465	4	-	-	46
16	660	585	16	M36	39	535	4	-	-	50
20	755	670	20	M39	42	615	4	-	-	52
24	890	795	20	M45	48	735	5	-	-	60

PN 64

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	105	75	4	M12	14	45	2	-	-	20
3/4	130	90	4	M16	18	58	2	-	-	22
1	140	100	4	M16	18	68	2	-	-	24
1 1/4	155	110	4	M20	22	78	2	-	-	26
1 1/2	170	125	4	M20	22	88	3	-	-	28
2	180	135	4	M20	22	102	3	-	-	26
2 1/2	205	160	8	M20	22	122	3	-	-	26
3	215	170	8	M20	22	138	3	-	-	28
4	250	200	8	M24	26	162	3	-	-	30
5	295	240	8	M27	30	188	3	-	-	34
6	345	280	8	M30	33	218	3	-	-	36
8	415	345	12	M33	36	285	3	-	-	42
10	470	400	12	M33	36	345	3	-	-	46
12	530	460	16	M33	36	410	4	-	-	52
14	600	525	16	M36	39	465	4	-	-	56
16	670	585	16	M39	42	535	4	-	-	60
20	800	705	20	M45	48	615	4	-	-	68
24	930	820	20	M52	56	735	4	-	-	76