

FLANGES

PN 100

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	105	75	4	M12	14	45	2	-	-	20
3/4	130	90	4	M16	18	58	2	-	-	22
1	140	100	4	M16	18	68	2	-	-	24
1 1/4	155	110	4	M20	22	78	2	-	-	26
1 1/2	170	125	4	M20	22	88	3	-	-	28
2	195	145	4	M24	26	102	3	-	-	30
2 1/2	220	170	8	M24	26	122	3	-	-	34
3	230	180	8	M24	26	138	3	-	-	36
4	265	210	8	M27	30	162	3	-	-	40
5	315	250	8	M30	33	188	3	-	-	40
6	355	290	12	M30	33	218	3	-	-	44
8	430	360	12	M33	36	285	3	-	-	52
10	505	430	12	M36	39	345	3	-	-	60
12	585	500	16	M39	42	410	4	-	-	68
14	655	560	16	M45	48	465	4	-	-	74
16	715	620	16	M45	48	535	4	-	-	78
20	870	760	20	M52	56	615	4	-	-	94
24	990	875	20	M56	62	735	4	-	-	104

PN 160

Nominal Size in	Dia. of Flange	Bolt Circle Dia.	No. of Bolts	Dia. of Bolts	Dia. of Holes	Dia. of Raised Face	Height of Raised Face	Thickness of Flange		
								Grey Cast Iron	Copper Alloy	Cast and Forged Steel
1/2	105	75	4	M12	14	45	2	-	-	20
3/4	130	90	4	M16	18	58	2	-	-	22
1	140	100	4	M16	18	68	2	-	-	24
1 1/4	155	110	4	M20	22	78	2	-	-	26
1 1/2	170	125	4	M20	22	88	3	-	-	28
2	195	145	4	M24	26	102	3	-	-	30
2 1/2	220	170	8	M24	26	122	3	-	-	34
3	230	180	8	M24	26	138	3	-	-	36
4	265	210	8	M27	30	162	3	-	-	40
5	315	250	8	M30	33	188	3	-	-	44
6	355	290	12	M30	33	218	3	-	-	50
8	430	360	12	M33	36	285	3	-	-	60
10	515	430	12	M39	42	345	3	-	-	68
12	585	500	16	M39	42	410	4	-	-	78