



DIN 2635 PN 40 Raised face to DIN 2526, form C

| Tube<br>DN | Flange               |         |         |         | Hub                  |                      |         |         |                      | Raised face               |         | Drilling Template |        |                      |              |
|------------|----------------------|---------|---------|---------|----------------------|----------------------|---------|---------|----------------------|---------------------------|---------|-------------------|--------|----------------------|--------------|
|            | d <sub>1</sub><br>mm | D<br>mm | b<br>mm | k<br>mm | h <sub>1</sub><br>mm | d <sub>3</sub><br>mm | s<br>mm | r<br>mm | h <sub>2</sub><br>mm | d <sub>4</sub><br>mm<br>≈ | f<br>mm | Number            | Thread | d <sub>2</sub><br>mm | Weight<br>kg |
| 10         | 14<br>17.2           | 90      | 16      | 60      | 35                   | 25<br>28             | 1.8     | 4       | 6                    | 40                        | 2       | 4                 | M 12   | 14                   | 0.661        |
| 15         | 20<br>21.3           | 95      | 16      | 65      | 38                   | 30<br>32             | 2       | 4       | 6                    | 45                        | 2       | 4                 | M 12   | 14                   | 0.746        |
| 20         | 25<br>26.9           | 105     | 18      | 75      | 40                   | 38<br>40             | 2.3     | 4       | 6                    | 58                        | 2       | 4                 | M 12   | 14                   | 1.060        |
| 25         | 30<br>33.7           | 115     | 18      | 85      | 40                   | 42<br>46             | 2.6     | 4       | 6                    | 68                        | 2       | 4                 | M 12   | 14                   | 1.290        |
| 32         | 38<br>42.4           | 140     | 18      | 100     | 42                   | 52<br>56             | 2.6     | 6       | 6                    | 78                        | 2       | 4                 | M 16   | 18                   | 1.880        |
| 40         | 44.5<br>48.3         | 150     | 18      | 110     | 45                   | 60<br>64             | 2.6     | 6       | 7                    | 88                        | 3       | 4                 | M 16   | 18                   | 2.330        |
| 50         | 57<br>60.3           | 165     | 20      | 125     | 48                   | 72<br>75             | 2.9     | 6       | 8                    | 102                       | 3       | 4                 | M 16   | 18                   | 2.820        |
| 65         | 76.1                 | 185     | 22      | 145     | 52                   | 90                   | 2.9     | 6       | 10                   | 122                       | 3       | 8                 | M 16   | 18                   | 3.740        |
| 80         | 88.9                 | 200     | 24      | 160     | 58                   | 105                  | 3.2     | 8       | 12                   | 138                       | 3       | 8                 | M 16   | 18                   | 4.750        |
| 100        | 108<br>114.3         | 235     | 24      | 190     | 65                   | 128<br>134           | 3.6     | 8       | 12                   | 162                       | 3       | 8                 | M 20   | 22                   | 6.520        |
| 125        | 133<br>139.7         | 270     | 26      | 220     | 68                   | 155<br>162           | 4       | 8       | 12                   | 188                       | 3       | 8                 | M 24   | 26                   | 9.070        |
| 150        | 159<br>168.3         | 300     | 28      | 250     | 75                   | 182<br>192           | 4.5     | 10      | 12                   | 218                       | 3       | 8                 | M 24   | 26                   | 11.800       |
| 200        | 219.1                | 375     | 34      | 320     | 88                   | 244                  | 6.3     | 10      | 16                   | 285                       | 3       | 12                | M 27   | 30                   | 21.500       |