

STAINLESS STEEL WELDED TUBINGS

*SWG = Standard Wire Gauge
BWG = Birmingham Wire Gauge
SWG can almost invariably be
replaced by BWG as the wall of
BWG is slightly thicker.

INSTRUMENTATION TUBE

Outside Diameter	Wall Thickness	Nominal* Size	Weight	3R12 SS 2352 AISI 304L	3R60 2353 316L	8R30 2337 321	8R70 2350 (316Ti)
mm	mm		kg/m				
6	1.0 1.5		0.125 0.169	•	• •	• •	• •
6.35	0.89 0.91 1.22 1.24	1/4" X 20 BWG 20 SWG 18 SWG 18 BWG	0.122 0.124 0.157 0.159		• • • •		
8	1.0 1.5 2.0		0.175 0.244 0.300	• • •	• • •	• • •	• • •
9.53	0.89 0.91 1.22 1.24 1.63 1.65	3/8" x 20 BWG 20 SWG 18 SWG 18 BWG 16 SWG 16 BWG	0.193 0.196 0.254 0.257 0.322 0.326		• • • • • •		
10	1.0 1.5 2.0		0.225 0.319 0.400	• • •	• • •	• • •	• • •
10.2	2.0		0.411	•	•		
12	1.0 1.5 2.0		0.275 0.394 0.500	• • •	• • •	• • •	• • •
12.7	1.22 1.24 1.63 1.65	1/2" X 18 SWG 18 BWG 16 SWG 16 BWG	0.350 0.356 0.452 0.456		• • • •		
14	1.0 1.5 2.0		0.325 0.469 0.600	• • •	• • •	• • •	• • •
15	1.0 1.5 2.0		0.350 0.507 0.651	• • •	• • •	• • •	• • •
15.88	1.22 1.24	5/8" X 18 SWG 18 BWG	0.448 0.454		• •		
16	1.0 1.5 2.0 2.5 3.0		0.375 0.544 0.701 0.845 0.976	• • • • •	• • • • •	• • • • •	• • • • •
17.2	1.6 2.9		0.625 1.038	• •	• •	• •	• •
18	1.0 1.5 2.0 2.5 3.0		0.425 0.619 0.801 0.970 1.126	• • • • •	• • • • •	• • • • •	• • • • •
19.05	1.22 1.24	3/4" X 18 SWG 18 BWG	0.544 0.553		• •		
20	1.5 2.0 2.5 3.0 4.0		0.694 0.901 1.095 1.28 1.60	• • • • •	• • • • •	• • • • •	• • • • •

TOLERANCES

Metric sizes acc. to ISO 1127

Outside Diameter	Wall Thickness
±0.75%, but min. ±0.30 mm (D3)	±10%, but min. ±0.2 mm (T3)

Tube in imperial sizes acc. to ASTM A213/A450

Size	Outside Diameter	Wall Thickness average wall*	min wall
mm	mm	%	%
<25.4	+0.10/-0.10	+ 10/-10	+ 20/0

* Valid for stocked sizes.

SPECIFICATIONS

3R12 (AISI 304L) and 3R60 (AISI 316L)
SS 219711 (condition 22, i.e. 3R12=SS 2352-22)
DIN 17458, testing level 1
NFA 49-117
8R30 (AISI 321) and 8R70 (AISI 316Ti)
DIN 17458, testing level 1
Imperial size
3R60 (AISI 316L) ASTM A213, A269