


UNIVERSAL BEAMS AND COLUMNS



Section size	Unit weight M	Section depth D	Flange width B	Thickness		Corner radius r	Section area A	Moment of inertia		Radius of gyration		Modulus of section	
				t (web)	T (flange)			I _x	I _y	i _x	i _y	Z _x	Z _y
mm	kg/m	mm	mm	mm	mm	mm	cm ²	cm ⁴	cm ⁴	cm	cm	cm ³	cm ³
100 x 50	9.3	100	50	5	7	8	11.85	187	14.8	3.98	1.12	37.5	5.91
100 x 100	17.2	100	100	6	8	10	21.90	333	134	4.18	2.47	76.5	26.7
125 x 60	13.2	125	60	6	8	9	16.84	413	29.2	4.95	1.32	66.1	9.73
125 x 125	23.8	125	125	6.5	9	10	30.31	847	293	5.29	3.11	136	47.0
150 x 75	14.0	150	75	5	7	8	17.85	666	49.5	6.11	1.66	88.8	13.2
150 x 100	21.1	148	100	6	9	11	26.84	1,020	151	6.17	2.37	138	30.1
150 x 150	31.5	150	150	7	10	11	40.14	1,640	563	6.39	3.75	219	75.1
175 x 90	18.1	175	90	5	8	9	23.04	1,210	97.5	7.26	2.06	139	21.7
175 x 125	23.3	169	125	5.5	8	12	29.65	1,530	261	7.18	2.97	181	41.8
175 x 175	40.2	175	175	7.5	11	12	51.21	2,880	984	7.50	4.38	330	112
200 x 100	18.2	198	99	4.5	7	11	23.18	1,580	114	8.26	2.21	160	23.0
	21.3	200	100	5.5	8	11	27.16	1,840	134	8.24	2.22	184	26.8
200 x 150	30.6	194	150	6	9	13	39.01	2,690	507	8.30	3.61	277	67.6
200 x 200	49.9	200	200	8	12	13	63.53	4,720	1,600	8.62	5.02	472	160
	56.2	200	204	12	12	13	71.53	4,980	1,700	8.35	4.88	498	167
	65.7	208	202	10	16	13	83.69	6,530	2,200	8.83	5.13	628	218
250 x 125	25.7	248	124	5	8	12	32.68	3,540	255	10.4	2.79	285	41.1
	29.6	250	125	6	9	12	37.66	4,050	294	10.4	2.79	324	47.0
250 x 175	44.1	244	175	7	11	16	56.24	6,120	984	10.4	4.18	502	113
250 x 250	64.4	244	252	11	11	16	82.06	8,780	2,940	10.3	5.98	720	233
	66.5	248	249	8	13	16	84.70	9,930	3,350	10.8	6.29	801	269
	72.4	250	250	9	14	16	92.18	10,800	3,650	10.8	6.29	867	292
	82.2	250	255	14	14	16	104.7	11,500	3,880	10.5	6.09	919	304
300 x 150	32.0	298	149	5.5	8	13	40.80	6,320	442	12.4	3.29	424	59.3
	36.7	300	150	6.5	9	13	46.78	7,210	508	12.4	3.29	481	67.7
300 x 200	56.8	294	200	8	12	18	72.38	11,300	1,600	12.5	4.71	771	160
	65.4	298	201	9	14	18	83.36	13,300	1,900	12.6	4.77	893	189
300 x 300	84.5	294	302	12	12	18	107.7	16,900	5,520	12.5	7.16	1,150	365
	87	298	299	9	14	18	110.8	18,800	6,240	13.0	7.51	1,270	417
	94	300	300	10	15	18	119.8	20,400	6,750	13.1	7.51	1,360	450
	106	300	305	15	15	18	134.8	21,500	7,100	12.6	7.26	1,440	466
	106	304	301	11	17	18	134.8	23,400	7,730	13.2	7.57	1,540	514
350 x 175	41.4	346	174	6	9	14	52.68	11,100	798	14.5	3.88	641	91
	49.6	350	175	7	11	14	63.14	13,600	984	14.7	3.95	775	112
350 x 250	69.2	336	249	8	12	20	88.15	18,500	3,090	14.5	5.92	1,100	248
	79.7	340	250	9	14	20	101.5	21,700	3,650	14.6	6.00	1,280	292