


LIGHT BEAMS AND JOISTS



Section size	Unit weight M		Section depth D		Flange width B		Web thickness t		Flange thickness T		Corner radius r		Section area A	
	lb/ft	kg/m	in	mm	in	mm	in	mm	in	mm	in	mm	in ²	cm ²
6 x 4 (J)	8.5	12.65	5.83	148	3.94	100	0.17	4.32	0.194	4.93	0.25	6.35	2.50	16.1
6 x 4 (L)	12	17.86	6.00	152	4.00	102	0.23	5.84	0.279	7.09	0.25	6.35	3.53	22.8
	16	23.81	6.25	159	4.03	102	0.26	6.60	0.404	10.26	0.25	6.35	4.72	30.5
8 x 4 (J)	10	14.88	7.90	201	3.94	100	0.17	4.32	0.204	5.18	0.30	7.62	2.95	19.0
8 x 4 (L)	13	19.35	8.00	203	4.00	102	0.23	5.84	0.254	6.45	0.30	7.62	3.83	24.7
	15	22.32	8.12	206	4.015	102	0.245	6.22	0.314	7.98	0.30	7.62	4.43	28.6
10 x 4 (J)	11.5	17.11	9.87	251	3.95	100	0.18	4.57	0.204	5.18	0.30	7.62	3.39	21.9
10 x 4 (L)	15	22.32	10.00	254	4.00	102	0.23	5.84	0.269	6.83	0.30	7.62	4.40	28.4
	17	25.30	10.12	257	4.01	102	0.24	6.10	0.329	8.36	0.30	7.62	4.98	32.1
	19	28.28	10.25	260	4.02	102	0.25	6.35	0.394	10.01	0.30	7.62	5.61	36.2
12 x 4 (J)	14	20.83	11.91	303	3.97	101	0.20	5.08	0.224	5.69	0.30	7.62	4.14	26.7
12 x 4 (L)	16.5	24.55	12.00	305	4.00	102	0.23	5.84	0.269	6.83	0.30	7.62	4.86	31.4
	19	28.28	12.16	309	4.01	102	0.24	6.10	0.349	8.86	0.30	7.62	5.62	36.3
	22	32.74	12.31	313	4.03	102	0.26	6.60	0.424	10.77	0.30	7.62	6.47	41.7
14 x 4 (L)	17.2*	25.60*	14.00*	356*	4.00*	102*	0.21*	5.33*	0.272	6.91*	0.43*	10.9*	5.05*	32.6*
14 x 5 (L)	22	32.74	13.72	348	5.00	127	0.23	5.84	0.335	8.51	0.43	10.9	6.47	41.7
	26	38.69	13.89	353	5.025	128	0.255	6.48	0.418	10.62	0.43	10.9	7.65	49.4
16 x 5 1/2 (L)	26	38.69	15.65	398	5.50	140	0.25	6.35	0.345	8.76	0.43	10.9	7.65	49.4
	31	46.13	15.84	402	5.525	140	0.275	6.99	0.442	11.23	0.43	10.9	9.12	58.8

L = Light beams, J = Joists

Note:

Sizes indicated by an asterisk (*) are not included in regular rolling schedules.