


LIGHT BEAMS AND JOISTS



Section size	Unit weight M		Web thickness t		Flange thickness T		Radius Root r ₁		Toe r ₂		Section Area A	
	kg/m	lb/ft	mm	in	mm	in	mm	in	mm	in	cm ²	in ²
76 x 51 (3 x 2)	6.71	4.5	3.81	0.15	5.69	0.224	6.90	0.27	2.4	0.094	8.5	1.32
102 x 64 (4 x 2 1/2)	9.65	6.5	4.09	0.161	6.63	0.261	6.90	0.27	2.4	0.094	12.3	1.91
102 x 76 (4 x 3)	14.90	10	6.10	0.24	8.81	0.347	9.40	0.37	4.6	0.18	18.9	2.94
127 x 76 (5 x 3)	13.36	9	4.52	0.178	7.62	0.30	7.90	0.31	2.4	0.094	17.0	2.64
152 x 76 (6 x 3)	17.88	12	5.84	0.23	9.57	0.377	9.40	0.37	4.6	0.18	22.8	3.53
152 x 89 (6 x 3 1/2)	17.09	11.5	4.93	0.194	8.28	0.326	7.90	0.31	2.4	0.094	21.8	3.38
152 x 127 (6 x 5)	37.25	25	10.41	0.41	13.21	0.520	13.50	0.53	6.6	0.26	47.5	7.37
178 x 102 (7 x 4)	21.54	14.5	5.33	0.21	9.07	0.357	9.40	0.37	3.2	0.13	27.4	4.26
178 x 102 (7 x 4)	23.84	16	6.35	0.25	9.83	0.387	11.40	0.45	5.6	0.22	30.6	4.75
203 x 102 (8 x 4)	25.33	17	5.84	0.23	10.36	0.408	9.40	0.37	3.2	0.13	32.3	5.00
203 x 102 (8 x 4)	26.82	18	7.11	0.28	10.11	0.398	11.40	0.45	5.6	0.22	34.2	5.30
203 x 152 (8 x 6)	52.16	35	8.89	0.35	16.46	0.648	15.50	0.61	7.6	0.30	66.5	10.30
228 x 102 (9 x 4)	31.29	21	7.62	0.30	11.61	0.457	11.40	0.45	5.6	0.22	39.9	6.18
254 x 127 (10 x 5)44.71	30	9.14	0.36	14.02	0.552	13.50	0.53	6.6	0.26	57.1	8.85	
254 x 152 (10 x 6)59.61	40	9.14	0.36	18.01	0.709	15.50	0.61	7.6	0.30	75.9	11.77	
254 x 203 (10 x 8)81.97	55	10.16	0.40	19.89	0.783	19.60	0.77	9.7	0.38	104.4	16.18	
305 x 127 (12 x 5)47.69	32	8.89	0.35	11.61	0.550	13.50	0.53	6.6	0.26	60.9	9.45	
305 x 152 (12 x 6)65.57	44	10.16	0.40	18.21	0.717	15.50	0.61	7.6	0.30	83.9	13.00	