


BEARING PILES



Section size	Unit weight M		Section depth D		Flange width B		Web & Flange thickness t T		Corner radius r		Section area A	
	lb/ft	kg/m	in	mm	in	mm	in	mm	in	mm	in ²	cm ²
8 x 8	30	45.0	7.88	200.2	8.085	205.4	0.373	9.5	0.4	10.2	8.83	57.0
	36	54.0	8.026	203.9	8.158	207.2	0.446	11.3	0.4	10.2	10.6	68.4
10 x 10	42	63.0	9.72	246.9	10.078	256.0	0.418	10.6	0.5	12.7	12.4	79.7
	48	71.0	9.838	249.9	10.137	257.5	0.477	12.1	0.5	12.7	14.1	91.0
	57	85.0	10.012	254.3	10.224	259.7	0.564	14.3	0.5	12.7	16.8	108.1
12 x 12	53	79.0	11.78	299.2	12.046	306.0	0.436	11.1	0.6	15.2	15.5	100.4
	59	88.0	11.878	301.7	12.095	307.2	0.485	12.3	0.6	15.2	17.36	112.0
	64	95.0	11.96	303.8	12.136	308.3	0.526	13.4	0.6	15.2	18.4	121.0
	74	110.0	12.122	307.9	12.217	310.3	0.607	15.4	0.6	15.2	21.8	140.4
	85	126.0	12.308	312.6	12.31	312.7	0.70	17.8	0.6	15.2	24.6	161.0
	100	149.0	12.528	318.2	12.42	315.5	0.81	20.6	0.6	15.2	29.4	190.0
	125	186.0	12.928	328.4	12.62	320.5	1.01	25.7	0.6	15.2	36.73	237.0
	150	223.0	13.308	338.0	12.81	325.4	1.20	30.5	0.6	15.2	44.17	285.0
14 x 14 1/2	73	109.0	13.636	346.4	14.586	370.5	0.506	12.9	0.6	15.2	21.4	138.4
	89	133.0	13.856	351.9	14.696	373.3	0.616	15.6	0.6	15.2	26.1	169.0
	102	152.0	14.032	356.4	14.784	375.5	0.704	17.9	0.6	15.2	30.0	193.6
	117	174.1	14.234	361.5	14.885	378.1	0.805	20.4	0.6	15.2	34.4	222.2