



BEARING PILES

Section Size		Moment of inertia				Radius of gyration				Modulus of section			
		Ix		Iy		ix		iy		Zx		Zy	
in (mm)		in ⁴	cm ⁴	in ⁴	cm ⁴	in	cm	in	cm	in ³	cm ³	in ³	cm ³
8 x 8		98.0	4,079	37.0	1,539	3.33	8.46	1.93	4.90	24.9	408	8.1	133
		119.8	4,987	40.4	1,683	3.36	8.54	1.95	4.95	29.8	489	9.9	162
10 x 10	210.8	8,775	71.4	2,971	4.13	10.5	2.41	6.11	43.4	711	14.2	232	
		243.9	10,153	82.9	3,451	4.17	10.6	2.40	6.10	49.6	813	16.4	268
		294.6	12,264	100.6	4,188	4.21	10.7	2.45	6.22	58.9	965	19.7	323
12 x 12	394.0	16,400	127.1	5,292	5.04	12.8	2.86	7.26	66.9	1,096	21.1	346	
		442.1	18,402	143.2	5,959	5.04	12.8	2.87	7.30	74.4	1,220	23.7	388
		483.2	20,111	156.9	6,529	5.08	12.9	2.87	7.30	80.8	1,324	25.9	424
		566.5	23,580	184.7	7,689	5.12	13.0	2.91	7.40	93.5	1,532	30.3	496
		661.3	27,526	216.5	9,013	5.16	13.1	2.95	7.50	107.6	1,763	35.2	577
		793.8	33,040	261.1	10,869	5.20	13.2	2.99	7.60	126.6	2,075	42.0	689
		1,024.1	42,625	338.9	14,108	5.28	13.4	3.03	7.70	158.5	2,597	53.8	881
		1,268.9	52,817	422.1	17,570	5.35	13.6	3.07	7.80	190.8	3,126	65.9	1,080
14 x 14 ^{1/2}		733.1	30,515	261.9	10,901	5.83	14.8	3.49	8.87	107.5	1,762	35.9	588
		909.1	37,840	326.2	13,576	5.91	15.0	3.53	8.96	131.2	2,150	44.4	727
		1,055.1	43,916	379.6	15,799	5.94	15.1	3.56	9.03	150.4	2,464	51.3	841
		1,228.5	51,134	443.1	18,444	5.98	15.2	3.59	9.11	172.6	2,829	59.6	976