
GENERAL INFORMATION

Steel sheet piling is used in all types of temporary works and permanent structures including cofferdams, retaining walls, river frontages, quays, wharves, dock and harbour works, permanent foundations, land reclamation and sea defence works.

The sections are designed to provide the maximum strength and durability at the lowest possible weight consistent with good driving qualities. The design of the section interlocks facilitates pitching and driving and results in a series of closely fitting joints, forming a continuous wall.

A comprehensive range of sections in widely differing sizes and weights is obtainable in various grades of steel which enables the most economical choice to be made to suit the nature and requirements of any given contract. This range can be extended if the tonnage required is economic.

Certain sections intended for use in permanent structures where stresses are not severe, such as cut-off-walls, are of uniform thickness throughout in order to provide the maximum effective useful life.

Where piles form temporary works, they can be extracted easily and without distortion for re-use.

Corner, junction and closure piles are available to cover all requirements.

Should any doubts or problems arise advice is available on application to the publisher of this handbook - CHYE HIN HARDWARE PTE LTD.

SPLICES

Steel sheet piling is generally available in lengths up to 30m. Where it is necessary to increase the pile length during driving, fishplated or site-welded joints can be used. Particulars of standard fish-plated joints or weld preparations are available on application.

Because of normal rolling tolerances there may be variations in the pile profile. Every effort should be made to match pile ends before welding.

CIRCULAR CONSTRUCTION

Steel sheet piling can be driven to form a complete circle without the water tightness of the locks being impaired.

The maximum angle of deviation in the locks is 9° for Larssen piles, and 3° for Frodingham piles. Deviation in the locks of Larssen Box Piles is limited to 3°.

The following table gives the approximate minimum diameters of circles which can be constructed using various sheet pile sections.

The diameters are only intended for guidance, as the possible deviation will vary according to length of piles, penetration required and section used.

Smaller diameters can be obtained if individual bent corners are introduced.