


STEEL PILES

Z-TYPE

Section	Dimensions				Section area Per pile	Unit weight		Moment of inertia		Modulus of section	
	w	h	t1	t2		Per pile	Per wall width	Per pile	Per wall width	Per pile	Per wall width
	mm in	mm in	mm in	mm in	cm ² in ²	kg/m lb/ft	kg/m ² lb/ft ²	cm ⁴ in ⁴	cm ⁴ /m in ⁴ /ft	cm ³ in ³	cm ³ /m in ³ /ft
FSP Z-25	400	305	13.0	9.6	94.32	74.0	185	15,300	38,300	1,000	2,510
	15.7	12.0	0.512	0.378	14.62	49.7	37.9	368	280	61.0	46.7
FSP Z-32	400	344	14.2	10.4	107.7	84.5	211	22,000	55,000	1,280	3,200
	15.7	13.5	0.559	0.409	16.69	56.8	43.2	529	403	78.1	59.5
FSP Z-38	400	364	17.2	11.4	122.3	96.0	240	27,700	69,200	1,520	3,800
	15.7	14.3	0.677	0.449	18.96	64.5	49.2	665	507	92.8	70.7
FSP Z-45	400	367	21.9	13.2	148.2	116	290	33,400	83,500	1,820	4,550
	15.7	14.4	0.862	0.52	22.97	77.9	59.4	802	611	111	84.6

STRAIGHT WEB-TYPE



Section	Dimensions			Section area Per pile	Unit weight		Moment of inertia Per pile	Modulus of section Per pile	Interlock strength min.	
	w	h	t		Per pile	Per wall width				
	mm in	mm in	mm in	cm ² in ²	kg/m lb/ft	kg/m ² lb/ft ²	cm ⁴ in ⁴	cm ³ in ³	t/m lb/ft	
YSP F	400	44.5	9.5	69.07	54.2	136	190	47.8	400	
	15.7	1.75	0.374	10.71	36.4	27.9	4.56	2.92	268	780
YSP FA	400	44.5	12.7	77.50	60.8	152	196	48.3	400	
	15.7	1.75	0.5	12.01	40.9	31.1	4.71	2.95	268	780
YSP FX	400	47.0	12.7	85.66	67.2	168	224	56.1	600	
	15.7	1.85	0.5	13.28	45.2	34.4	5.38	3.42	403	170

Note:

1. YSP FA with minimum interlock strength of 500 t/m is subject to negotiation.
2. Normal interlock swing of YSP and YSP FA is at least 10° and that of YSP FX at least 8°.