

API PIPES ERW & SEAMLESS PIPES

TOLERANCES (EXCERPTS FROM API SPECIFICATIONS)

Pipe Specification		API 5L				API 5LU			
Outside Diameter	Pipe Body	1.90 in. & smaller	+0.016 in. -0.031 in.				Less than 20 in.	+0.75% -0.75%	
		2-3/8 in. through 18 in.	+0.75% -0.75%						
		20 in. through 36 in.							
		Non-expanded	+ 1.00% -1.00%						
	Cold-expanded	+0.75% -0.25%							
	Larger than 36 in.								
Non-expanded	+1.00% -1.00%								
Cold -expanded*2	+1/4 in. -1/8 in.								
Pipe Ends *1	10-3/4 in. & smaller	+1/16 in. -1/64in. (measured with ring gage)				10-3/4 in & smaller	+1/16 in. -1/64 in. (measured with ring gage)		
	12-3/4 in. through 20 in.	+3/32 in. -1/32 in. (measured with ring gage)				12-3/4 in. through 20in.	+3/32 in. -1/32 in. (measured with ring gage)		
	Larger than 20 in. (22 in. & larger)	+3/32 in. -1/32 in. (measured with diameter tape)				Larger than 20 in.	+3/32 in. -1/32 in. (measured with diameter tape)		
Wall Thickness		Welded Pipe:	Grade A, B X42 through X70				Welded Pipe:		
		2.875 in. OD & smaller	+20.0% -12.5% +15.0% -12.5%						
		3-1/2 in. OD	+18.0% -12.5% +15.0% -12.5%						
		4 in. through 18 in. OD	+15.0% -12.5% +15.0% -12.5%						
		20 in. OD & larger	+17.5% -10.0% +19.5% -8.0%						
		Seamless Pipe:	Grade A,B X42 through X70				Seamless Pipe:		
		2.875 in. OD & smaller	+20.0% -12.5% +15.0% -12.5%						
		3-1/2 in. OD	+18.0% -12.5% +15.0% -12.5%						
4 in. through 18 in. OD	+15.0% -12.5% +15.0% -12.5%								
20 in. OD & larger	+15.0% -12.5% +17.5% -10.0%								
Weight	Single Length	Standard weight					Regular weight	+10.0% -3.5%	
		Regular weight	+10.0% -3.5%						
		Extra strong weight							
		Double extra strong weight							
		Special plain end weight	+10.0% -5.0%				Special light weight	+10.0% -5.0%	
	Carload Lots	-1.75%				-1.75%			
Straightness		For pipe 4-1/2 in OD & larger max. 0.2%				max. 0.2%			
Out of Roundness -pipe larger than 20in. OD		Max. OD - specified OD ≤ 1% x specified OD Specified OD - min. OD ≤ 1% x specified OD				Max. OD - specified OD ≤ 1% x specified_OD Specified OD - min. OD ≤ 1% x specified_OD			
Pipe End Preparation		For pipe 2-3/8 in. OD & larger Bevel angle 30°, +5° - 0° Root face 1/16 in. ± 1/32 in. Squareness for 10-3/4 in. OD & larger max. 1/16 in.				Bevel angle 30°, +5° - 0° 1/16 in. ± 1/32 in. Squareness 10-3/4 in. OD & larger max. 1/16 in.			