

API PIPES ERW & SEAMLESS PIPES

Size						Weight			Hydrostatic Test Pressure												
Outside Diameter			Wall Thickness						API 5L				API 5LX								
									A		B										
Nominal Size	in	mm	Sch No	in	mm	lb/ft	kg/m	kg/ft	Std.	Alt.	Std.	Alt.	X42	X46	X52	X56	X60	X65	X70		
3	3-1/2	88.9	40 (std)	0.083	2.11	3.03	4.51	1.38	850	--	1000	--	1200	1310	1480	1590	1710	1850	1990		
				0.109	2.77	3.95	5.88	1.79	--	--	--	--	1570	1720	1940	2090	2240	2430	2620		
				0.125	3.18	4.51	6.72	2.05	1290	--	1500	--	1800	1970	2230	2400	2570	2790	3000		
				0.141	3.58	5.06	7.54	2.30	--	--	--	--	2030	2220	2510	2710	2900	3000	3000		
				0.156	3.96	5.57	8.30	2.53	1600	--	1870	--	2250	2460	2780	3000	3000	3000	3000		
				0.172	4.37	6.11	9.10	2.77	1770	--	2060	--	2480	2710	3000	3000	3000	3000	3000		
				0.188	4.78	6.65	9.91	3.02	1930	--	2260	--	2710	2970	3000	3000	3000	3000	3000		
				0.216	5.49	7.58	11.29	3.44	2220	--	2500	--	3000	3000	3000	3000	3000	3000	3000		
				0.250	6.35	8.68	12.93	3.94	2500	--	2500	--	3000	3000	3000	3000	3000	3000	3000		
				0.281	7.14	9.66	14.39	4.39	2500	--	2500	--	3000	3000	3000	3000	3000	3000	3000		
			80 (XS) 160 (XXS)	0.300	7.62	10.25	15.27	4.65	2500	--	2500	--	3000	3000	3000	3000	3000	3000	3000	3000	
				0.438	11.13	14.32	21.33	6.50	--	--	--	--	--	--	--	--	--	--	--	--	
				0.600	15.24	18.58	27.67	8.44	2500	--	2500	--	3000	3000	3000	3000	3000	3000	3000	3000	
3-1/2	4	101.6	40 (std)	0.083	2.11	3.47	5.17	1.58	750	--	870	--	1050	1150	1290	1390	1490	1620	1740		
				0.109	2.77	4.53	6.75	2.06	980	--	1140	--	1370	1500	1700	1830	1960	2130	2290		
				0.125	3.18	5.17	7.70	2.35	1120	--	1310	--	1580	1720	1950	2100	2250	2440	2630		
				0.141	3.58	5.81	8.65	2.64	1270	--	1480	--	1780	1950	2200	2370	2540	2750	2960		
				0.156	3.96	6.40	9.53	2.91	1400	--	1640	--	1970	2150	2430	2620	2810	3000	3000		
				0.172	4.37	7.03	10.47	3.19	1550	--	1810	--	2170	2370	2680	2890	3000	3000	3000		
				0.188	4.78	7.65	11.39	3.47	1690	--	1970	--	2370	2590	2930	3000	3000	3000	3000		
				0.226	5.74	9.11	13.57	4.14	2030	--	2370	--	2850	3000	3000	3000	3000	3000	3300		
				0.250	6.35	10.01	14.91	4.54	2250	--	2620	--	3000	3000	3000	3000	3000	3000	3000		
				0.281	7.14	11.16	16.62	5.07	2530	--	2800	--	3000	3000	3000	3000	3000	3000	3000		
			80 (XS)	0.318	8.08	12.50	18.62	5.68	2800	--	2800	--	3000	3000	3000	3000	3000	3000	3000		
4	4-1/2	114.3	40 (std)	0.083	2.11	3.92	5.84	1.78	660	--	770	--	930	1020	1150	1240					
				0.109	2.77	5.11	7.61	2.32	870	--	1020	--	--	--	--	--					
				0.125	3.18	5.84	8.70	2.65	1000	--	1170	--	1400	1530	1730	1870					
				0.141	3.58	6.56	9.77	2.98	1130	--	1320	--	1580	1730	1960	2110					
				0.156	3.96	7.24	10.78	3.29	1250	--	1460	--	1750	1910	2160	2330					
				0.172	4.37	7.95	11.84	3.61	1380	--	1610	--	1930	2110	2390	2570					
				0.188	4.78	8.66	12.90	3.93	1500	--	1750	--	2110	2310	2610	2810					
				0.203	5.16	9.32	13.88	4.23	1620	--	1890	--	2270	2490	2810	3000					
				0.219	5.56	10.01	14.91	4.54	1750	--	2040	--	2450	2690	3000	3000					
				0.237	6.02	10.79	16.07	4.90	1900	--	2210	--	2650	2910	3000	3000					
				0.25	6.35	11.35	16.91	5.15	2000	--	2330	--	2800	3000	3000	3000					
				60	0.281	7.14	12.66	18.86	5.75	2250	--	2620	--	3000	3000	3000	3000				
					0.312	7.92	13.96	20.79	6.34	2500	--	2800	--	3000	3000	3000	3000				
					80 (XS)	0.337	8.56	14.98	22.31	6.80	2700	--	2800	--	3000	3000	3000	3000			
			0.438			11.13	19.00	28.30	8.63	2800	--	2800	--	3000	3000	3000	3000				
			120	0.531	13.49	22.51	33.53	10.22	2800	--	2800	--	3000	3000	3000	3000					
				160 (XXS)	0.674	17.12	27.54	41.02	12.50	2800	--	2800	--	3000	3000	3000	3000				
5	5-9/16	141.3		40 (std)	0.083	2.11	4.86	7.24	2.21	540	--	630	--	--	--	--	--				
			0.125		3.18	7.26	10.81	3.30	810	--	940	--	--	--	--	--					
			0.156		3.96	9.01	13.42	4.09	1010	--	1180	--	--	--	--	--					
			0.188		4.78	10.79	16.07	4.90	1220	--	1420	--	--	--	--	--					
			0.219		5.56	12.50	18.62	5.68	1420	--	1650	--	--	--	--	--					
			0.258		6.55	14.62	21.76	6.63	1670	--	1950	--	--	--	--	--					
			0.281		7.14	15.85	23.61	7.20	1820	--	2120	--	--	--	--	--					
			0.312		7.92	17.50	26.05	7.94	2020	--	2360	--	--	--	--	--					
			0.344		8.74	19.17	28.55	8.70	2230	--	2600	--	--	--	--	--					
			80 (XS)		0.375	9.52	20.78	30.94	9.43	2430	--	2800	--	--	--	--	--				
					0.50	12.70	27.03	40.26	12.27	2800	--	2800	--	--	--	--	--				
					160	0.625	15.88	32.96	49.08	14.96	2800	--	2800	--	--	--	--	--			
						0.75	19.05	38.55	57.41	17.50	2800	--	2800	--	--	--	--	--			