

API PIPES ERW & SEAMLESS PIPES

Size						Weight			Hydrostatic Test Pressure								
Outside Diameter			Wall Thickness						API 5L				API 5LX				
									A		B						
Nominal Size	in	mm	Sch No	in	mm	lb/ft	kg/m	kg/ft	Std.	Alt.	Std.	Alt.	X42	X46	X52	X56	
6	6-5/8	168.3	30	0.083	2.11	5.80	8.64	2.63	450	560	530	660	790	860	980	1050	
				0.109	2.77	7.59	11.31	3.45	590	740	690	860	1040	1140	1280	1380	
				0.125	3.18	8.68	12.93	3.94	680	850	790	990	1190	1300	1470	1580	
				0.141	3.58	9.76	14.54	4.43	770	960	890	1120	1340	1470	1660	1790	
				0.156	3.96	10.78	16.06	4.89	850	1060	990	1240	1480	1620	1840	1980	
				0.172	4.37	11.85	17.65	5.38	930	1170	1090	1360	1640	1790	2030	2180	
				0.188	4.78	12.92	19.24	5.87	1020	1280	1190	1490	1790	1960	2210	2380	
				0.203	5.16	13.92	20.73	6.32	1100	1380	1290	1610	1930	2110	2390	2570	
				0.219	5.56	14.98	22.31	6.80	1190	1490	1390	1740	2080	2280	2580	2780	
				0.250	6.35	17.02	25.35	7.73	1360	1700	1580	1980	2380	2600	2940	3000	
				40 (std)	0.280	7.11	18.97	28.26	8.61	1520	1900	1780	2220	2660	2920	3000	3000
				0.312	7.92	21.04	31.34	9.55	1700	2120	1980	2470	2970	3000	3000	3000	
			80 (XS)	0.344	8.74	23.08	34.38	10.48	1870	2340	2180	2730	3000	3000	3000	3000	
				0.375	9.52	25.03	37.28	11.36	2040	2550	2380	2800	3000	3000	3000	3000	
				0.432	10.97	28.57	42.56	12.97	2350	2800	2740	2800	3000	3000	3000	3000	
				0.500	12.70	32.71	48.72	14.85	2720	2800	2800	2800	3000	3000	3000	3000	
				120	0.562	14.27	36.39	54.20	16.52	2800	2800	2800	2800	3000	3000	3000	3000
				0.625	15.88	40.05	59.65	18.18	2800	2800	2800	2800	3000	3000	3000	3000	
				160	0.719	18.26	45.35	67.55	20.59	2800	2800	2800	2800	3000	3000	3000	3000
				(XXS)	0.864	21.95	53.16	79.18	24.13	2800	2800	2800	2800	--	--	--	--
8	8-5/8	219.1	20	0.125	3.18	11.35	16.91	5.15	520	650	610	760	910	1000	1130	1220	
				0.156	3.96	14.11	21.02	6.41	650	810	760	950	1140	1250	1410	1520	
				0.188	4.78	16.94	25.23	7.69	780	980	920	1140	1370	1500	1700	1830	
				0.203	5.16	18.26	27.20	8.29	--	--	--	--	1480	1620	1840	2000	
				0.219	5.56	19.66	29.28	8.93	910	1140	1070	1330	1600	1750	1980	2130	
				0.250	6.35	22.36	33.31	10.15	1040	1300	1220	1520	1830	2000	2260	2430	
				30	0.277	7.04	24.70	36.79	11.21	1160	1450	1350	1690	2020	2220	2510	2700
				0.312	7.92	27.70	41.26	12.58	1300	1630	1520	1900	2280	2500	2820	3000	
				40 (std)	0.322	8.18	28.55	42.53	12.96	1340	1680	1570	1960	2350	2580	2910	3000
				0.344	8.74	30.42	45.31	13.81	1440	1790	1680	2090	2510	2750	3000	3000	
				0.375	9.52	33.04	49.21	15.00	1570	1960	1830	2280	2740	3000	3000	3000	
				60	0.406	10.31	35.64	53.09	16.18	--	--	--	--	--	--	--	--
			0.438	11.13	38.30	57.05	17.39	1830	2290	2130	2670	3000	3000	3000	3000		
			80 (XS)	0.500	12.70	43.39	64.63	19.70	2090	2610	2430	2800	3000	3000	3000	3000	
			0.562	14.27	48.40	72.09	21.97	2350	2800	2740	2800	3000	3000	3000	3000		
			100	0.594	15.09	50.95	75.89	23.13	--	--	--	--	--	--	--	--	
			0.625	15.88	53.40	79.54	24.24	2610	2800	2800	2800	3000	3000	3000	3000		
			120	0.719	18.26	60.71	90.43	27.56	2800	2800	2800	2800	3000	3000	3000	3000	
			140	0.812	20.62	67.76	100.93	30.76	--	--	--	--	--	--	--	--	
			(XXS)	0.875	22.22	72.42	107.87	32.88	2800	2800	2800	2800	--	--	--	--	
160	0.906	23.01	74.69	111.25	33.91	--	--	--	--	--	--	--	--				
10	10-3/4	273.0	20	0.156	3.96	17.65	26.29	8.01	520	650	610	760	1040	1130	1280	1380	
				0.188	4.78	21.21	31.59	9.63	630	790	730	920	1250	1370	1550	1660	
				0.203	5.16	22.87	34.06	10.38	--	--	--	--	1350	1480	1670	1800	
				0.219	5.56	24.63	36.69	11.18	730	920	860	1070	1450	1590	1800	1940	
				0.250	6.35	28.04	41.77	12.73	840	1050	980	1220	1660	1820	2060	2210	
				0.279	7.09	31.20	46.47	14.16	930	1170	1090	1360	1850	2030	2290	2470	
				30	0.307	7.80	34.24	51.00	15.54	1030	1290	1200	1500	2040	2230	2520	2720
				0.344	8.74	38.23	56.94	17.36	1150	1440	1340	1680	2280	2500	2830	3000	