

API PIPES ERW & SEAMLESS PIPES

Size						Weight			Hydrostatic Test Pressure							
Outside Diameter			Wall Thickness						API 5L				API 5LX			
Nominal Size	in	mm	Sch No	in	mm	lb/ft	kg/m	kg/ft	A		B		X42	X46	X52	X56
									Std.	Alt.	Std.	Alt.				
10	10-3/4	273.0	40 (std)	0.365	9.27	40.48	60.29	18.38	1220	1530	1430	1780	2420	2660	3000	3000
				0.438	11.13	48.24	71.85	21.90	1470	1830	1710	2140	2910	3000	3000	3000
			60 (XS)	0.500	12.70	54.74	81.54	24.85	1670	2090	1950	2440	3000	3000	3000	3000
				0.562	14.27	61.15	91.08	27.76	1880	2350	2200	2740	3000	3000	3000	3000
			80	0.594	15.09	64.43	95.97	29.25	--	--	--	--	--	--	--	--
				0.625	15.88	67.58	100.66	30.68	2090	2620	2440	2800	3000	3000	3000	3000
			100	0.719	18.26	77.03	114.74	34.97	2410	2800	2800	2800	3000	3000	3000	3000
				0.812	20.62	86.18	128.37	39.13	2720	2800	2800	2800	--	--	--	--
			120	0.844	21.44	89.29	133.00	40.54	--	--	--	--	--	--	--	--
				1.000	25.40	104.13	155.10	47.28	--	--	--	--	--	--	--	--
12	12-3/4	323.8	20	0.172	4.37	23.11	34.42	10.49	490	610	570	710	960	1050	1190	1280
				0.188	4.78	25.22	37.57	11.45	530	660	620	770	1050	1150	1300	1400
				0.203	5.16	27.20	40.51	12.35	--	--	--	--	1140	1250	1410	1520
				0.219	5.56	29.31	43.66	13.31	620	770	720	900	1230	1340	1520	1640
				0.250	6.35	33.38	49.72	15.15	710	880	820	1030	1400	1530	1730	1870
				0.281	7.14	37.42	55.74	16.99	790	990	930	1160	1570	1720	1950	2100
			30	0.312	7.92	41.45	61.74	18.82	880	1100	1030	1280	1750	1910	2160	2330
				0.330	8.38	43.77	65.20	19.87	930	1160	1090	1360	1850	2020	2290	2460
				0.344	8.74	45.58	67.89	20.69	970	1210	1130	1420	1930	2110	2390	2570
				(std) 0.375	9.52	49.56	73.82	22.50	1060	1320	1240	1540	2100	2300	2600	2800
			40	0.406	10.31	53.52	79.72	24.30	--	--	--	--	2270	2490	2810	3000
				0.438	11.13	57.59	85.78	26.15	1240	1550	1440	1800	2450	2690	3000	3000
				(XS) 0.500	12.70	65.42	97.44	29.70	1410	1760	1650	2060	2800	3000	3000	3000
				0.562	14.27	73.15	108.96	33.21	1590	1980	1850	2310	3000	3000	3000	3000
			60	0.625	15.88	80.93	120.55	36.74	1760	2210	2060	2570	3000	3000	3000	3000
				0.688	17.48	88.63	132.01	40.24	1940	2430	2270	2800	3000	3000	3000	3000
				0.750	19.05	96.12	143.17	43.64	2120	2650	2470	2800	3000	3000	3000	3000
				0.812	20.62	103.53	154.21	47.00	2290	2800	2670	2800	3000	3000	3000	3000
			80	0.844	21.44	107.32	159.85	48.72	--	--	--	--	--	--	--	--
				0.875	22.22	110.97	165.29	50.38	2470	2800	2800	2800	3000	3000	3000	3000
				1.000	25.40	125.49	186.92	56.97	--	--	--	--	--	--	--	--
			100	0.188	4.78	27.73	41.30	12.59	480	600	560	700	960	1050	1190	1280
				0.203	5.16	29.91	44.55	13.58	520	650	610	760	--	--	--	--
				0.210	5.33	30.93	46.07	14.04	--	--	--	--	1070	1170	1330	1430
				0.219	5.56	32.23	48.01	14.63	--	--	--	--	1120	1220	1380	1490
14	14	355.6	10	0.250	6.35	36.71	54.68	16.67	640	800	750	940	1280	1400	1580	1700
				0.281	7.14	41.17	61.32	18.69	720	900	840	1050	1430	1570	1770	1910
				0.312	7.92	45.61	67.94	20.71	800	1000	940	1170	1590	1740	1970	2120
				0.344	8.74	50.17	74.73	22.78	880	1110	1030	1290	1750	1920	2170	2340
				(std) 0.375	9.52	54.57	81.28	24.77	960	1210	1120	1410	1910	2090	2370	2550
				0.406	10.31	58.94	87.79	26.76	--	--	--	--	2070	2270	2560	2760
			20	0.438	11.13	63.44	94.49	28.80	1130	1410	1310	1640	2230	2450	2770	2980
				0.469	11.91	67.78	100.96	30.77	--	--	--	--	2390	2620	2960	3000
				(XS) 0.500	12.70	72.09	107.38	32.73	1290	1610	1500	1880	2550	2790	3000	3000
				0.562	14.27	80.66	120.14	36.62	1450	1810	1690	2110	2870	3000	3000	3000
			30	0.594	15.09	85.05	126.68	38.61	--	--	--	--	--	--	--	--
				0.625	15.88	89.28	132.98	40.53	1610	2010	1880	2340	3000	3000	3000	3000
				0.688	17.48	97.81	145.69	44.41	1770	2210	2060	2580	3000	3000	3000	3000
				0.750	19.05	106.13	158.08	48.18	1930	2410	2250	2800	3000	3000	3000	3000
			40	0.812	20.62	114.37	170.35	51.92	2090	2610	2440	2800	3000	3000	3000	3000
				0.875	22.22	122.65	182.69	55.68	2250	2800	2620	2800	3000	3000	3000	3000
				0.938	23.83	130.85	194.90	59.41	2410	2800	2800	2800	3000	3000	3000	3000
				1.000	25.40	138.84	206.80	63.03	--	--	--	--	--	--	--	--