



COLD FORMED HOLLOW SECTIONS

SQUARE

Section size		Wall thickness t		Unit weight M		Section area A	Moment of inertia I	Radius of gyration i	Modulus of section Z
in	mm	in	mm	lb/ft	kg/m	in ²	in ⁴	in	in ³
3 x 3	76.2 x 76.2	0.091	2.3	3.515	5.231	1.030	1.44	1.19	0.96
		0.095	2.4	3.670	5.480	1.080	1.503	1.18	1.002
		0.120	3.0	4.576	6.810	1.346	1.83	1.17	1.22
		0.125	3.2	4.751	7.070	1.400	1.89	1.163	1.26
		0.156	4.0	5.820	8.660	1.711	2.251	1.147	1.50
		0.180	4.6	6.620	9.850	1.947	2.52	1.14	1.68
		0.1875	4.8	6.860	10.200	2.019	2.60	1.13	1.73
		0.250	6.4	8.803	13.100	2.589	3.16	1.10	2.10
3-1/2 x 3-1/2	88.9 x 88.9	0.120	3.0	5.390	8.020	1.585	2.98	1.37	1.70
		0.125	3.2	5.600	8.330	1.651	3.10	1.367	1.76
		0.156	4.0	6.880	10.240	2.024	3.71	1.354	2.12
		0.177	4.5	7.739	11.518	2.27	4.10	1.34	2.34
		0.180	4.6	7.862	11.700	2.31	4.16	1.34	2.38
		0.1875	4.8	8.140	12.113	2.394	4.29	1.34	2.45
		0.236	6.0	10.006	14.891	2.99	5.25	1.33	3.00
		0.250	6.4	10.500	15.626	3.10	5.29	1.31	3.02
4 x 4	101.6 x 101.6	0.120	3.0	6.210	9.241	1.825	4.53	1.58	2.27
		0.125	3.2	6.450	9.681	1.902	4.70	1.57	2.34
		0.156	4.0	7.950	11.810	2.34	5.66	1.56	2.83
		0.177	4.5	8.945	13.312	2.63	6.28	1.55	3.14
		0.180	4.6	9.070	13.500	2.67	6.38	1.55	3.19
		0.1875	4.8	9.410	14.003	2.769	6.59	1.54	3.30
		0.236	6.0	11.614	17.285	3.39	7.82	1.52	3.91
		0.250	6.4	12.200	18.200	3.54	8.22	1.51	4.11
		0.3125	7.9	14.800	22.024	4.358	9.58	1.48	4.79
		0.375	9.5	17.300	25.745	5.075	10.7	1.45	5.35
		0.500	12.7	21.600	32.200	6.36	12.3	1.39	6.13
5 x 5	127 x 127	0.156	4.0	10.100	15.000	2.961	11.43	1.97	4.57
		0.177	4.5	11.356	16.901	3.33	12.7	1.97	5.08
		0.180	4.6	11.500	17.113	3.39	12.9	1.96	5.18
		0.1875	4.8	12.000	17.857	3.519	13.4	1.95	5.36
		0.236	6.0	14.830	22.070	4.34	16.0	1.92	6.42
		0.250	6.4	15.656	23.298	4.54	16.9	1.92	6.78
		0.3125	7.9	19.100	28.424	5.608	20.1	1.89	8.02
		0.375	9.5	22.400	33.334	6.575	22.8	1.86	9.11
		0.500	12.7	28.400	42.300	8.356	27.0	1.80	10.8
6 x 6	152.4 x 152.4	0.156	4.0	12.200	18.155	3.583	20.2	2.40	6.73
		0.177	4.5	13.768	20.490	4.04	22.5	2.36	7.50
		0.180	4.6	14.000	20.834	4.103	22.9	2.36	7.65