


COLD FORMED HOLLOW SECTIONS



SQUARE

Section size		Wall thickness t		Unit weight M		Section area A	Moment of inertia I	Radius of gyration i	Modulus of section Z
in	mm	in	mm	lb/ft	kg/m	in ²	in ⁴	in	in ³
6 x 6	152.4 x 152.4	0.1875	4.8	14.5	21.60	4.269	23.8	2.36	7.93
		0.236	6.0	18.045	26.856	5.28	28.7	2.33	9.58
		0.250	6.4	19.016	28.30	5.535	30.3	2.33	10.1
		0.3125	7.9	23.317	34.70	6.858	36.3	2.30	12.1
		0.375	9.5	27.5	40.924	8.075	41.6	2.27	13.9
		0.500	12.7	35.2	52.40	10.360	50.5	2.21	16.8
7 x 7	177.8 x 177.8	0.180	4.6	16.4	24.405	4.827	37.1	2.77	10.6
		0.1875	4.8	17.1	25.447	5.019	38.5	2.77	11.0
		0.250	6.4	22.4	33.334	6.589	49.4	2.74	14.1
		0.3125	7.9	27.6	41.073	8.108	59.5	2.71	17.0
		0.375	9.5	32.0	48.00	9.575	68.7	2.68	19.6
		0.500	12.7	42.0	62.502	12.360	84.6	2.62	24.2
8 x 8	203.2 x 203.2	0.180	4.6	18.9	28.126	5.547	56.1	3.18	14.0
		0.1875	4.8	19.6	29.20	5.769	58.2	3.18	14.6
		0.250	6.4	25.8	38.40	7.589	75.1	3.15	18.8
		0.3125	7.9	31.8	47.323	9.358	90.9	3.12	22.7
		0.375	9.5	37.7	56.103	11.08	106	3.09	26.4
		0.500	12.7	48.8	72.622	14.36	131	3.03	32.9
10 x 10	254 x 254	0.250	6.4	32.5	48.512	9.589	151	3.96	30.1
		0.3125	7.9	40.3	60.00	11.86	183	3.93	36.7
		0.375	9.5	47.9	71.282	14.08	214	3.90	42.9
		0.500	12.7	62.4	92.90	18.36	271	3.84	54.2
		0.625	15.9	76.3	113.546	22.40	321	3.78	64.2
12 x 12	304.8 x 304.8	0.250	6.4	39.4	58.63	11.59	265	4.78	44.1
		0.3125	7.9	48.8	72.62	14.36	324	4.75	54.0
		0.375	9.5	58.0	86.40	17.08	380	4.72	63.4
		0.500	12.7	76.0	113.10	22.36	485	4.66	80.9
		0.625	15.9	93.3	139.00	27.43	580	4.60	96.7
14 x 14	355.6 x 355.6	0.375	9.5	68.2	102.00	20.08	615	5.54	87.9
		0.500	12.7	89.6	33.33	26.36	791	5.48	113
		0.625	15.9	110.0	164.00	32.43	952	5.42	136
16 x 16	406.4 x 406.4	0.500	12.7	103.0	154.00	30.36	1,200	6.29	150
		0.625	15.9	127.0	189.00	37.43	1,450	6.23	182