

Clipping, Rasterization

김준호

Visual Computing Lab.


국민대학교 소프트웨어학부

Clipping

Where we are in Rendering Pipeline is ...


- Pipeline architecture

- This is everything for interactive computer graphics!
 - First, we focus on the *fixed rendering pipeline*
- Mechanism: a *state machine*
 - All information for image formations should be specified




Clipping

- To eliminate objects that lie outside of viewing volume
 - Performed in several places in the pipeline
 - Accept / Reject(or cull)
 - Supported by H/W or S/W





Line-Segment Clipping

- From an input line, to clip out a portion which passes through the view volume




Line-Segment Clipping

- From an input line, to clip out a portion which passes through the view volume




Polygon Clipping

- From a given polygon, to clip out portions which are inside of the view volume




Bounding Boxes and Volumes

- Rather than doing clipping on a complex polygon, we can use an axis-aligned bounding box or extent
 - Usually, used in the game-engine



Bounding Boxes and Volumes

- Determine accept/reject based only on bounding box




Rasterization

Where we are in Rendering Pipeline is ...


- Pipeline architecture

- This is **everything** for interactive computer graphics!
 - First, we focus on the *fixed rendering pipeline*
- Mechanism: a *state machine*
 - All information for image formations should be specified



Rasterization

- Rasterization (Scan conversion)
 - The process of converting a primitive into a set of pixels
 - It computes
 - Fragment location
 - Which pixels that are inside primitive specified by a set of vertices
 - Per-fragment attributes
 - Attributes, such as color and texture coordinates are determined by **interpolating** values at vertices




Line Rasterization

- DDA algorithm
 - With a given line equation (i.e., $y = mx + h$), compute y by increasing x by Δx


$$y = mx + h$$

$$m = \frac{\Delta y}{\Delta x}$$




Line Rasterization

- DDA algorithm
 - We have to consider the slope of each line



DDA Algorithm w/o
considering slopes





DDA Algorithm w
considering slopes

- [Bresenham's line algorithm](#) is implemented in graphics HW, in practice

Polygon Rasterization


- Bilinear interpolation
 - First, colors on the line is interpolated
 - Second, colors on each scan line interpolated
- Here, several attributes are interpolated over the fragments in a triangle



Hidden Surface Removal


Hidden Surface Removal

- General concept





Hidden Surface Removal – z-buffer Algorithm

- z-buffer (or depth-buffer) algorithm
 - It uses a buffer called z- or depth-buffer to store the depth of the closest object at each pixel found so far
 - As we render each polygon, compare the depth of each pixel to depth in z-buffer
 - If less, place shade of pixel in color buffer and update z-buffer




Hidden Surface Removal – z-buffer Algorithm

- z-buffer (or depth-buffer) algorithm
 - We have an additional buffer whose size is identical to the color buffer
 - Each pixel in the depth buffer keeps a depth-value, which is the distance to the point on the nearest object from the synthetic camera





Color buffer



Depth buffer

Hidden Surface Removal – z-buffer Algorithm

- z-buffer (or depth-buffer) algorithm
 - We have an additional buffer whose size is identical to the color buffer
 - Each pixel in the depth buffer keeps a depth-value, which is the distance to the point on the nearest object from the synthetic camera




Color buffer





Depth buffer

Hidden Surface Removal – z-buffer Algorithm



- Advantages
 - The programmer do not need to care about the rendering order of objects in a scene
 - $A \rightarrow B$
 - $B \rightarrow A$



$A \rightarrow B$




$B \rightarrow A$



Hidden Surface Removal – z-buffer Algorithm

- Advantage
 - Z-buffer algorithm can combine shading and hidden surface removal through scan line algorithm




scan line i : no need for depth information, can only be in no or one polygon

scan line j : need depth information only when in more than one polygon

Hidden Surface Removal – Painter's Algorithm

- A kind of S/W approach
- Render polygons a back to front order so that polygons behind others are simply painted over
 - We need to perform a sorting algorithm




B behind A as seen by viewer

- 1) Fill B
- 2) Fill A


Hidden Surface Removal – Painter's Algorithm

- Requires ordering of polygons first
 - $O(n \log n)$ calculation for ordering
 - Not every polygon is either in front or behind all other polygons




Hidden Surface Removal – Painter's Algorithm


- There are non-trivial cases exist for depth sorts
- Why?



Overlap in all directions
but can one is fully on
one side of the other



cyclic overlap



penetration

Hidden Surface Removal – Painter's Algorithm

- Why we should learn about painter's algorithm, even though graphics HW supports the z-buffer algorithm
 - For using alpha blending, we have to render polygons a back to front order



[AMD DirectX 11 Demo for H/W accelerated alpha blending]
([video](#), [youtube](#))

Hidden-Surface Removal – Back-face Removal

- Back-face removal (culling) algorithm
 - Face is visible iff $90 \geq \theta \geq -90$
 - equivalently $\cos\theta \geq 0$ or $\mathbf{v} \cdot \mathbf{n} \geq 0$
 - Recall that you always send the vertices in a polygon in the order of CCW.
 - Simply, almost 50% polygons are culled from the back-face removal

