



Algorithm Design X

Dynamic Programming II

Guoqiang Li
School of Software



SHANGHAI JIAO TONG
UNIVERSITY

Shortest Reliable Paths

Shortest Reliable Paths



In a network, even if edge lengths faithfully reflect transmission delays, there may be **other considerations** involved in choosing a path.

Shortest Reliable Paths



In a network, even if edge lengths faithfully reflect transmission delays, there may be **other considerations** involved in choosing a path.

For instance, each extra edge in the path might be an extra “**hop**” fraught with uncertainties and dangers of packet loss.

Shortest Reliable Paths



In a network, even if edge lengths faithfully reflect transmission delays, there may be **other considerations** involved in choosing a path.

For instance, each extra edge in the path might be an extra “**hop**” fraught with uncertainties and dangers of packet loss.

We would like to avoid paths with too many edges.


Shortest Reliable Paths



In a network, even if edge lengths faithfully reflect transmission delays, there may be **other considerations** involved in choosing a path.

For instance, each extra edge in the path might be an extra “hop” fraught with uncertainties and dangers of packet loss.

We would like to avoid paths with too many edges.



Shortest Reliable Paths



Suppose then that we are given a graph G with lengths on the edges, along with two nodes s and t and an integer k ,

Shortest Reliable Paths



SHANGHAI JIAO TONG
UNIVERSITY

Suppose then that we are given a graph G with lengths on the edges, along with two nodes s and t and an integer k , and we want the shortest path from s to t that uses at most k edges.

Shortest Reliable Paths



Suppose then that we are given a graph G with lengths on the edges, along with two nodes s and t and an integer k , and we want the shortest path from s to t that uses at most k edges.

Dynamic programming will work!

Dynamic Programming



SHANGHAI JIAO TONG
UNIVERSITY



For each vertex v and each integer $i \leq k$, let

$dist(v, i) =$ the length of the shortest path from s to v that uses i edges



For each vertex v and each integer $i \leq k$, let

$dist(v, i) =$ the length of the shortest path from s to v that uses i edges

The starting values $dist(v, 0)$ are ∞ for all vertices except s , for which it is 0.



For each vertex v and each integer $i \leq k$, let

$dist(v, i) =$ the length of the shortest path from s to v that uses i edges


The starting values $dist(v, 0)$ are ∞ for all vertices except s , for which it is 0.

$$dist(v, i) = \min_{(u,v) \in E} \{dist(u, i-1) + l(u, v)\}$$


Shortest Reliable Paths




Find out the shortest reliable path from S to T , when $k = 3$.



An Example



Bellman-Ford Algorithm



	Iteration							
Node	0	1	2	3	4	5	6	7
S	0	0	0	0	0	0	0	0
A	∞	10	10	5	5	5	5	5
B	∞	∞	∞	10	6	5	5	5
C	∞	∞	∞	∞	11	7	6	6
D	∞	∞	∞	∞	∞	14	10	9
E	∞	∞	12	8	7	7	7	7
F	∞	∞	9	9	9	9	9	9
G	∞	8	8	8	8	8	8	8

All-Pairs Shortest Path

All-Pairs Shortest Path



SHANGHAI JIAO TONG
UNIVERSITY

What if we want to find the shortest path not just between s and t but between **all pairs of vertices**?

All-Pairs Shortest Path



What if we want to find the shortest path not just between s and t but between **all pairs of vertices**?

One approach would be to execute **Bellman-Ford-Moore algorithm** $|V|$ times, once for each starting node.

All-Pairs Shortest Path



What if we want to find the shortest path not just between s and t but between **all pairs of vertices**?

One approach would be to execute **Bellman-Ford-Moore algorithm** $|V|$ times, once for each starting node.

The total running time would then be $O(|V|^2|E|)$.

We'll now see a better alternative, the $O(|V|^3)$, named **Floyd-Warshall** algorithm.

Floyd-Warshall Algorithm



SHANGHAI JIAO TONG
UNIVERSITY

Dynamic programming again!

The Subproblems



Number the vertices in V as $\{1, 2, \dots, n\}$,

The Subproblems



Number the vertices in V as $\{1, 2, \dots, n\}$, and let

$dist(i, j, k)$ = the length of the shortest path from i to j in which only nodes $\{1, 2, \dots, k\}$ can be used as intermediates.

The Subproblems



Number the vertices in V as $\{1, 2, \dots, n\}$, and let

$dist(i, j, k)$ = the length of the shortest path from i to j in which only nodes $\{1, 2, \dots, k\}$ can be used as intermediates.

Initially, $dist(i, j, 0)$ is the length of the direct edge between i and j , if it exists, and is ∞ otherwise.

The Subproblems



Number the vertices in V as $\{1, 2, \dots, n\}$, and let

$dist(i, j, k)$ = the length of the shortest path from i to j in which only nodes $\{1, 2, \dots, k\}$ can be used as intermediates.

Initially, $dist(i, j, 0)$ is the length of the direct edge between i and j , if it exists, and is ∞ otherwise.

For $k \geq 1$

$$dist(i, j, k) = \min\{dist(i, j, k-1), dist(i, k, k-1) + dist(k, j, k-1)\}$$

The Program



```
for  $i = 1$  to  $n$  do
  for  $j = 1$  to  $n$  do
     $dist(i, j, 0) = \infty$ ;
  end
end
for all  $(i, j) \in E$  do
   $dist(i, j, 0) = l(i, j)$ ;
end
for  $k = 1$  to  $n$  do
  for  $i = 1$  to  $n$  do
    for  $j = 1$  to  $n$  do
       $dist(i, j, k) = \min\{dist(i, j, k-1), dist(i, k, k-1) + dist(k, j, k-1)\}$ ;
    end
  end
end
end
```


The Traveling Salesman Problem



A traveling salesman is getting ready for a big sales tour.

The Traveling Salesman Problem



A traveling salesman is getting ready for a big sales tour. Starting at his hometown, he will conduct a journey in which each of his target cities is visited exactly once before he returns home.

The Traveling Salesman Problem



A traveling salesman is getting ready for a big sales tour. Starting at his hometown, he will conduct a journey in which each of his target cities is visited exactly once before he returns home.

Q: Given the pairwise distances between cities, what is the best order in which to visit them, so as to minimize the overall distance traveled?


The Traveling Salesman Problem



A traveling salesman is getting ready for a big sales tour. Starting at his hometown, he will conduct a journey in which each of his target cities is visited exactly once before he returns home.

Q: Given the pairwise distances between cities, what is the best order in which to visit them, so as to minimize the overall distance traveled?

The **brute-force approach** is to evaluate every possible tour and return the best one. Since there are $(n - 1)!$ possibilities, this strategy takes $O(n!)$ time.



The Traveling Salesman Problem



SHANGHAI JIAO TONG
UNIVERSITY

Denote the cities by $1, \dots, n$, the salesman's hometown being 1,

The Traveling Salesman Problem



Denote the cities by $1, \dots, n$, the salesman's hometown being 1, and let $D = (d_{ij})$ be the matrix of intercity distances.

The Traveling Salesman Problem



Denote the cities by $1, \dots, n$, the salesman's hometown being 1, and let $D = (d_{ij})$ be the matrix of intercity distances.

The goal is to design a tour that starts and ends at 1, includes all other cities **exactly once**, and has **minimum total length**.

The Subproblems



For a subset of cities $S \subseteq \{1, 2, \dots, n\}$ that includes 1, and $j \in S$, let $C(S, j)$ be the length of the shortest path visiting each node in S exactly once, starting at 1 and ending at j .

The Subproblems



For a subset of cities $S \subseteq \{1, 2, \dots, n\}$ that includes 1, and $j \in S$, let $C(S, j)$ be the length of the shortest path visiting each node in S exactly once, starting at 1 and ending at j .

When $|S| > 1$, we define $C(S, 1) = \infty$.

The Subproblems




For a subset of cities $S \subseteq \{1, 2, \dots, n\}$ that includes 1, and $j \in S$, let $C(S, j)$ be the length of the shortest path visiting each node in S exactly once, starting at 1 and ending at j .

When $|S| > 1$, we define $C(S, 1) = \infty$.

For $j \neq 1$ with $j \in S$ we have

$$C(S, j) = \min_{i \in S: i \neq j} C(S \setminus \{j\}, i) + d_{ij}$$

Exercise



The Program



```
 $C(1, 1) = 0;$   
for  $s = 2$  to  $n$  do  
  | for all subsets  $S \subseteq \{1, 2, \dots, n\}$  do  
    |  $C(S, 1) = \infty;$   
    | for all  $j \in S$  and  $j \neq 1$  do  
      |  $C(S, j) = \min_{i \in S: i \neq j} C(S \setminus \{j\}, i) + d_{ij};$   
    | end  
  | end  
end  
return ( $\min_j C(\{1, 2, \dots, n\}, j) + d_{j1}$ );
```

The Program



```
 $C(1, 1) = 0;$   
for  $s = 2$  to  $n$  do  
  | for all subsets  $S \subseteq \{1, 2, \dots, n\}$  do  
    |  $C(S, 1) = \infty;$   
    | for all  $j \in S$  and  $j \neq 1$  do  
      |  $C(S, j) = \min_{i \in S: i \neq j} C(S \setminus \{j\}, i) + d_{ij};$   
    | end  
  | end  
end  
return ( $\min_j C(\{1, 2, \dots, n\}, j) + d_{j1}$ );
```

There are at most $2^n \cdot n$ subproblems, and each one takes linear time.

The Program



```

C(1, 1) = 0;
for  $s = 2$  to  $n$  do
    for all subsets  $S \subseteq \{1, 2, \dots, n\}$  do
         $C(S, 1) = \infty$ ;
        for all  $j \in S$  and  $j \neq 1$  do
             $C(S, j) = \min_{i \in S: i \neq j} C(S \setminus \{j\}, i) + d_{ij}$ ;
        end
    end
end
return ( $\min_j C(\{1, 2, \dots, n\}, j) + d_{j1}$ );

```

There are at most $2^n \cdot n$ subproblems, and each one takes linear time.

The total running time is therefore $O(n^2 \cdot 2^n)$.

The Problem



A subset of nodes $S \subseteq V$ is an independent set of graph $G = (V, E)$ if there are no edges between them.

The Problem



A subset of nodes $S \subseteq V$ is an independent set of graph $G = (V, E)$ if there are no edges between them.

Finding the largest independent set in a graph is believed to be intractable.


The Problem



A subset of nodes $S \subseteq V$ is an independent set of graph $G = (V, E)$ if there are no edges between them.

Finding the largest independent set in a graph is believed to be intractable.

However, when the graph happens to be a tree, the problem can be solved in linear time, using dynamic programming.



The Subproblems

The Subproblems



$I(u)$ = size of largest independent set of subtree hanging from u .

The Subproblems



$I(u)$ = size of largest independent set of subtree hanging from u .

$$I(u) = \max\{1 + \sum_{\text{grandchildren } w \text{ of } u} I(w), \sum_{\text{children } w \text{ of } u} I(w)\}$$

Homework

Homework



SHANGHAI JIAO TONG
UNIVERSITY

Assignment 4. Exercises 6.17, 6.20, 6.21, and 6.22.