

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

# Mathematics Methods for Computer Science

Instructor: Xubo Yang

SJTU-SE DALAB

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

# Lecture

## Singular Value Decomposition

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Critical points of the ratio:

$$R(\vec{v}) = \frac{\|A\vec{v}\|_2}{\|\vec{v}\|_2}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Critical points of the ratio:

$$R(\vec{v}) = \frac{\|A\vec{v}\|_2}{\|\vec{v}\|_2}$$

- $R(\alpha\vec{v}) = R(\vec{v}) \Rightarrow$  take  $\|\vec{v}\|_2 = 1$
- $R(\vec{v}) \geq 0 \Rightarrow$  study  $R^2(\vec{v})$  instead

$$R^2(\vec{v}) = \|A\vec{v}\|_2^2 = \vec{v}A^\top A\vec{v}$$

Critical points of  $\vec{v}A^\top A\vec{v}$  s.t.  $\|\vec{v}\|_2 = 1$   
 $\Rightarrow \vec{v}_i$  satisfying  $A^\top A\vec{v}_i = \lambda_i \vec{v}_i$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$R^2(\vec{v}) = \|A\vec{v}\|_2^2 = \vec{v}A^\top A\vec{v}$$

Critical points of  $\vec{v}A^\top A\vec{v}$  s.t.  $\|\vec{v}\|_2 = 1$   
 $\Rightarrow \vec{v}_i$  satisfying  $A^\top A\vec{v}_i = \lambda_i \vec{v}_i$

**Properties:**  $A^\top A$  is symmetric positive semidefinite

- $\lambda_i \geq 0 \ \forall i$
- Basis is full and orthonormal

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

What about  $A$  instead of  $A^T A$ ?

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

What about  $A$  instead of  $A^\top A$ ?

Object of study:  $\vec{u}_i \equiv A\hat{v}_i$



Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

## Lemma

Either  $\vec{u}_i = \vec{0}$  or  $\vec{u}_i$  is an eigenvector of  $AA^\top$  with  $\|\vec{u}_i\|_2 = \sqrt{\lambda_i} \|\hat{v}_i\|_2 = \sqrt{\lambda_i}$ .

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Simpler proof than in book (top p. 132):

$$A^{\top} A \hat{v}_i = \lambda_i \hat{v}_i$$

$$A A^{\top} (A \hat{v}_i) = \lambda_i A \hat{v}_i$$

$$A A^{\top} \vec{u}_i = \lambda_i \vec{u}_i$$

Length of  $\vec{u}_i = A \hat{v}_i$  follows from

$$\|\vec{u}_i\|_2^2 = \|A \hat{v}_i\|_2^2 = \hat{v}_i^{\top} A^{\top} A \hat{v}_i = \lambda_i \hat{v}_i^{\top} \hat{v}_i = \lambda_i$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

 $k = \text{number of } \lambda_i > 0$ 

$$A^\top A \hat{v}_i = \lambda_i \hat{v}_i$$

$$A A^\top \hat{u}_i = \lambda_i \hat{u}_i$$

 $\bar{U} \in \mathbb{R}^{n \times k} = \text{matrix of unit } \hat{u}_i \text{ 's}$  $\bar{V} \in \mathbb{R}^{m \times k} = \text{matrix of unit } \hat{v}_i \text{ 's}$

Simpler lemma + proof than book (bottom p.132):

### Lemma

$$\hat{u}_i^\top A \hat{v}_j = \sqrt{\lambda_i} \delta_{ij}$$

$$\begin{aligned}\bar{\Sigma} &\equiv \text{diag}(\sqrt{\lambda_1}, \dots, \sqrt{\lambda_k}) \\ &= \text{diag}(\sigma_1, \dots, \sigma_k) (\sigma_i \text{ are singular values})\end{aligned}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Simpler lemma + proof than book (bottom p.132):

### Lemma

$$\hat{u}_i^\top A \hat{v}_j = \sqrt{\lambda_i} \delta_{ij}$$

$$\begin{aligned}\bar{\Sigma} &\equiv \text{diag}(\sqrt{\lambda_1}, \dots, \sqrt{\lambda_k}) \\ &= \text{diag}(\sigma_1, \dots, \sigma_k) (\sigma_i \text{ are singular values})\end{aligned}$$

### Corollary

$$\bar{U}^\top A \bar{V} = \bar{\Sigma}$$

Add  $\hat{v}_i$  with  $A^\top A \hat{v}_i = \vec{0}$  and  $\hat{u}_i$  with  $AA^\top \hat{u}_i = \vec{0}$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Add  $\hat{v}_i$  with  $A^\top A \hat{v}_i = \vec{0}$  and  $\hat{u}_i$  with  $AA^\top \hat{u}_i = \vec{0}$

$$\begin{aligned}\bar{U} \in \mathbb{R}^{m \times k}, \bar{V} \in \mathbb{R}^{n \times k} &\mapsto \\ U \in \mathbb{R}^{m \times m}, V \in \mathbb{R}^{n \times n}\end{aligned}$$

Add  $\hat{v}_i$  with  $A^\top A \hat{v}_i = \vec{0}$  and  $\hat{u}_i$  with  $AA^\top \hat{u}_i = \vec{0}$

$$\begin{aligned}\bar{U} \in \mathbb{R}^{m \times k}, \bar{V} \in \mathbb{R}^{n \times k} &\mapsto \\ U \in \mathbb{R}^{m \times m}, V \in \mathbb{R}^{n \times n}\end{aligned}$$

$$\Sigma_{ij} \equiv \begin{cases} \sqrt{\lambda_i}, & i = j \text{ and } i \leq k \\ 0, & \text{otherwise} \end{cases}$$



Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$A = U\Sigma V^T$$

U/V为正交矩阵， $\Sigma$ 是对角矩阵

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms


Regularization

Procrustes Problem

PCA

$$A = U\Sigma V^{\top}$$

- 1 Rotate ( $V^{\top}$ )
- 2 Scale ( $\Sigma$ )
- 3 Rotate ( $U$ )



Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$A = U\Sigma V^\top$$

- **Left singular vectors:**

Columns of  $U$ ; span *col*  $A$

- **Right singular vectors:**

Columns of  $V$ ; span *row*  $A$

- **Singular values:**

Diagonal  $\sigma_i$  of  $\Sigma$ ; sort  $\sigma_1 \geq \sigma_2 \geq \dots \geq 0$

- 1 Columns of  $V$  are eigenvectors of  $A^T A$
- 2  $AV = U\Sigma \Rightarrow$  columns of  $U$  corresponding to nonzero singular values are normalized columns of  $AV$
- 3 Remaining columns of  $U$  satisfy  $AA^T \vec{u}_i = \vec{0}$ .

- ① Columns of  $V$  are eigenvectors of  $A^T A$
- ②  $AV = U\Sigma \Rightarrow$  columns of  $U$  corresponding to nonzero singular values are normalized columns of  $AV$
- ③ Remaining columns of  $U$  satisfy  $AA^T \vec{u}_i = \vec{0}$ .  
 **$\exists$  more specialized methods!**

Motivation

SVD

**Pseudoinverses**

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\begin{aligned} A\vec{x} &= \vec{b} \\ \implies U\Sigma V^\top \vec{x} &= \vec{b} \\ \implies \vec{x} &= V\Sigma^{-1}U^\top \vec{b} \end{aligned}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\begin{aligned} A\vec{x} &= \vec{b} \\ \implies U\Sigma V^\top \vec{x} &= \vec{b} \\ \implies \vec{x} &= V\Sigma^{-1}U^\top \vec{b} \end{aligned}$$

**What is  $\Sigma^{-1}$  ?**为  $\Sigma$  中对角线上元素全部取倒数得到的矩阵

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\text{minimize } \|\vec{x}\|_2^2$$
$$\text{such that } A^\top A \vec{x} = A^\top \vec{b}$$



$$\begin{aligned} A^{\top} A &= \left( U \Sigma V^{\top} \right)^{\top} \left( U \Sigma V^{\top} \right) \\ &= V \Sigma^{\top} U^{\top} U \Sigma V^{\top} \text{ since } (AB)^{\top} = B^{\top} A^{\top} \\ &= V \Sigma^{\top} \Sigma V^{\top} \text{ since } U \text{ is orthogonal.} \end{aligned}$$

$$A^{\top} A = V \Sigma^{\top} \Sigma V^{\top}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\begin{aligned} A^{\top} A &= (U \Sigma V^{\top})^{\top} (U \Sigma V^{\top}) \\ &= V \Sigma^{\top} U^{\top} U \Sigma V^{\top} \text{ since } (AB)^{\top} = B^{\top} A^{\top} \\ &= V \Sigma^{\top} \Sigma V^{\top} \text{ since } U \text{ is orthogonal.} \end{aligned}$$

$$A^{\top} A = V \Sigma^{\top} \Sigma V^{\top}$$

$$A^{\top} A \vec{x} = A^{\top} \vec{b} \Leftrightarrow \Sigma^{\top} \Sigma \vec{y} = \Sigma^{\top} \vec{d}$$

$$\vec{y} \equiv V^{\top} \vec{x}$$

$$\vec{d} \equiv U^{\top} \vec{b}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\begin{aligned} &\text{minimize } \|\vec{y}\|_2^2 \\ &\text{such that } \Sigma^\top \Sigma \vec{y} = \Sigma^\top \vec{d} \end{aligned}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\begin{aligned} &\text{minimize } \|\vec{y}\|_2^2 \\ &\text{such that } \Sigma^\top \Sigma \vec{y} = \Sigma^\top \vec{d} \end{aligned}$$

因为对角阵与其转置的乘积就是原对角矩阵对角线上的元素平方得到的矩阵

$$\Sigma^\top \Sigma \vec{y} = \Sigma^\top \vec{d} \implies \sigma_i^2 y_i = \sigma_i d_i$$

$$y_i = \begin{cases} \frac{d_i}{\sigma_i} & \sigma_i \neq 0 \\ \text{no constraint (take 0)} & \sigma_i = 0 \end{cases}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\Sigma_{ij}^+ \equiv \begin{cases} 1/\sigma_i & i = j, \sigma_i \neq 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\implies \vec{y} = \Sigma^+ \vec{d}$$

$$\implies \vec{x} = V \vec{y} = V \Sigma^+ U^\top \vec{b}$$

矩阵 $A^+$ 称为矩阵 $A$ 的伪逆矩阵

The **Pseudoinverse** of  $A = U\Sigma V^T \in R^{m \times n}$  :

$$A^+ = V\Sigma^+U^T$$

$$A^+ \in R^{n \times m}$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

- A **square and invertible**  $\Rightarrow A^+ = A^{-1}$
- A **overdetermined**  $\Rightarrow A^+ \vec{b}$  gives least-squares
- A **underdetermined**  $\Rightarrow A^+ \vec{b}$  gives least-squares solution to  $A\vec{x} \approx \vec{b}$  with least (Euclidean) norm

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$A = U\Sigma V^{\top} \implies A = \sum_{i=1}^{\ell} \sigma_i \vec{u}_i \vec{v}_i^{\top}$$

$$\ell \equiv \min\{m, n\}$$



Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\vec{u} \otimes \vec{v} \equiv \vec{u} \vec{v}^T$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$A\vec{x} = \sum_i \sigma_i (\vec{v}_i \cdot \vec{x}) \vec{u}_i$$

是一个标量

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$A\vec{x} = \sum_i \sigma_i (\vec{v}_i \cdot \vec{x}) \vec{u}_i$$

**Trick:**  
**Ignore small  $\sigma_i$ .**

这里的small指的是乘上以后趋于0

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$A^+ = \sum_{\sigma_i \neq 0} \frac{\vec{v}_i \vec{u}_i^\top}{\sigma_i}$$

**Trick:**  
**Ignore large  $\sigma_i$ .**

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Do not compute large (small)  $\sigma_i$  at  
all!

## Theorem

Suppose  $\tilde{A}$  is obtained from  $A = U\Sigma V^\top$  by truncating all but the  $k$  largest singular values  $\sigma_i$  of  $A$  to zero. Then,  $\tilde{A}$  minimizes both  $\|A - \tilde{A}\|_{Fro}$  and  $\|A - \tilde{A}\|_2$  subject to the constraint that the column space of  $\tilde{A}$  has at most dimension  $k$ .

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$\|A\|_{Fro}^2 = \sum \sigma_i^2$$

$$\|A\|_2 = \max\{\sigma_i\}$$

$$\text{cond } A = \sigma_{\max}/\sigma_{\min}$$

Regularized least-squares problem:

$$(A^{\top}A + \alpha I)\vec{x} = A^{\top}\vec{b}.$$

Perform SVD analysis.

What does  $\alpha$  do to the singular values?

Solution:  $\hat{x} = VDU^{\top}\vec{b}$

$$D_{ii} = \frac{\sigma_i}{\sigma_i^2 + \alpha^2}$$



刚体的

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem


PCA



Point cloud 1



Point cloud 2



Initial alignment



Final alignment

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Given  $\vec{x}_{1i} \mapsto \vec{x}_{2i}$ 

$$\min_{R^T R = I_{3 \times 3}, \vec{t} \in \mathbb{R}^3} \sum_i \|R\vec{x}_{1i} + \vec{t} - \vec{x}_{2i}\|_2^2$$

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

Given  $\vec{x}_{1i} \mapsto \vec{x}_{2i}$ 

$$\min_{R^T R = I_{3 \times 3}, \vec{t} \in \mathbb{R}^3} \sum_i \|R\vec{x}_{1i} + \vec{t} - \vec{x}_{2i}\|_2^2$$

**Alternate:**

- 1 Minimize with respect to  $\vec{t}$ : Least-squares
- 2 Minimize with respect to  $R$ : SVD

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

**Procrustes Problem**

PCA

$$\min_{R^{\top}R=I_{3\times 3}} \|RX_1 - X_2^t\|_{Fro}^2$$

$$\min_{R^T R = I_{3 \times 3}} \|RX_1 - X_2^t\|_{Fro}^2$$

## Orthogonal Procrustes Theorem


The orthogonal matrix  $R$  minimizing  $\|RX - Y\|^2$  is given by  $UV^T$ , where SVD is applied to factor  $YX^T = U\Sigma V^T$ .

## As-Rigid-As-Possible Surface Modeling

Olga Sorkine and Marc Alexa

Eurographics/ACM SIGGRAPH Symposium on  
Geometry Processing 2007.

<https://igl.ethz.ch/projects/ARAP/>



Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

$$F = RU$$

Special case:

- $F$  is square real-valued matrix;
- $R$  is best rotation matrix approximation;
- $U$  is right symmetric PSD stretch matrix.
- Proof by SVD.

**Given:** Collection of data points  $\vec{x}_i$

- Age
- Weight
- Blood pressure
- Heart rate

**Find:** Correlations between different dimensions



Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA

# One-dimensional subspace

$$\vec{x}_i \approx c_i \vec{v}$$

## Principal Component Analysis

The matrix  $C \in \mathbb{R}^{n \times d}$  minimizing  $\|X - CC^\top X\|_{Fro}$  subject to  $C^\top C = I_{d \times d}$  is given by the first  $d$  columns of  $U$ , for  $X = U\Sigma V^\top$ .

**Proved in textbook.**

# Application: Eigenfaces

Motivation

SVD

Pseudoinverses

Low-Rank Approx.

Matrix Norms


Regularization

Procrustes Problem

PCA



(a) Input faces



(b) Eigenfaces



(c) Projection

# Application: CNN Fluid Simulation

Mathematics Methods  
for Computer Science

Motivation

SVD

Pseudoinverses


Low-Rank Approx.

Matrix Norms

Regularization

Procrustes Problem

PCA



Xiao, X., Zhou, Y., Wang, H. and Yang, X., 2020. A novel cnn-based poisson solver for fluid simulation. IEEE transactions on visualization and computer graphics, 26(3).

[http://dalab.se.sjtu.edu.cn/www/home/?page\\_id=790](http://dalab.se.sjtu.edu.cn/www/home/?page_id=790)