Take nothing on its looks; take everything on evidence. There's no better rule.

Charles Dickens, "Great Expectations."

Repairing Bugs in Conditional Expressions

Favio DeMarco

Universidad de Buenos Aires - INRIA

August 28th, 2013

Bug fixing continues to be a mostly manual, time consuming, and therefore expensive activity in software development.

Hoang Duong Thien Nguyen et al, "SemFix: Program Repair via Semantic Analysis"

```
public static int gcd(int u, int v) {
  if (u * v == 0) {
    return (Math.abs(u) + Math.abs(v));
  }
...
```

Case study Commons Math

```
assertEquals (3 * (1<<15) , gcd (3 * (1<<20), 9 * (1<<15)));
```

```
public static int gcd(int u, int v) {
    if ((u == 0) || (v == 0)) {
        return (Math.abs(u) + Math.abs(v));
    }
    // ...
}
```



SemFix: Program Repair via Semantic Analysis

- ullet Statement ranking (Tarantula) o
- ullet Symbolic Execution (KLEE) ightarrow
- ullet Repair Constraint o Program Synthesis (SOLFP¹ -paper-)



¹Synthesis of Loop-free Programs

GenProg: A Generic Method for Automatic Software Repair Claire Le Goues, ThanhVu Nguyen, Stephanie Forrest, Westley Weimer

ClearView, AutoFix-E, Gopinath et al, Pachika.

Problems

Unwillingness to share code.

Problems Test quality

Quality is free, but only to those who are willing to pay heavily for it.

Tom DeMarco, Peopleware

Limitations

Resources (time, code monkeys, knowledge, tools, etc.).

Contributions Process

- ullet Statement ranking (GZoltar) o
- Ad hoc code manipulation and values capturing (OGCBPS²
 -paper-) →
- ullet Repair Constraint o
- Program Synthesis (SOLFP³ -paper-)



²Oracle-Guided Component-Based Program Synthesis

³Synthesis of Loop-free Programs

Experimental methodology

Seeded and wild bugs.

Evaluation / Validation

Generated patches vs. reality.

Perspectives

Conclusion

Contribution

Can't and shouldn't.









```
411: public static int gcd(int u, int v) {
412: if (\mathbf{u} * \mathbf{v} == \mathbf{0}) {
413: return (Math.abs(u) + Math.abs(v));
414: }
```

Case study Commons Math

```
assertEquals (3 * (1<<15) , gcd (3 * (1<<20), 9 * (1<<15)));
```

Case study Statement ranking (GZoltar)

```
MathUtils:413 Suspiciousness 0.23570226039551587 MathUtils:431 Suspiciousness 0.1543033499620919
```

. . .

MathUtils:460 Suspiciousness 0.11322770341445956 MathUtils:412 Suspiciousness 0.11180339887498948

Case study

Ad hoc code manipulation and values capturing (OGCBPS -paper-)

```
411: public static int gcd(int u, int v) {
412:    if (true) {
413:       return (Math.abs(u) + Math.abs(v));
414:    }
...
```

$$(u = 0 \land v = 0 \Rightarrow output = true) \land$$

 $(u = 0 \land v = 55 \Rightarrow output = true) \land$
...
 $(u = 77 \land v = 55 \Rightarrow output = false)$

```
public static int gcd(int u, int v) {
    if ((u == 0) || (v == 0)) {
        return (Math.abs(u) + Math.abs(v));
    }
    // ...
}
```