



planetmath.org

Math for the people, by the people.

generated subring

Canonical name	GeneratedSubring
Date of creation	2013-03-22 16:57:27
Last modified on	2013-03-22 16:57:27
Owner	polarbear (3475)
Last modified by	polarbear (3475)
Numerical id	9
Author	polarbear (3475)
Entry type	Definition
Classification	msc 20-00
Classification	msc 13-00
Classification	msc 16-00
Related topic	RingAdjunction
Defines	subring generated by
Defines	monomials in rings

Definition 1 *Let M be a nonempty subset of a ring A . The intersection of all subrings of A that include M is the smallest subring of A that includes M . It is called the subring generated by M and is denoted by $\langle M \rangle$.*

The subring generated by M is formed by finite sums of monomials of the form :

$$a_1 a_2 \cdots a_n, \text{ where } a_1, \dots, a_n \in M.$$

Of particular interest is the subring generated by a family of subrings $E = \{A_i \mid i \in I\}$. It is the ring R formed by finite sums of monomials of the form:

$$a_{i_1} a_{i_2} \cdots a_{i_n}, \text{ where } a_{i_k} \in A_{i_k}.$$

If A, B are rings, the subring generated by $A \cup B$ is also denoted by AB . In the case when A_i are fields included in a larger field A then the set of all quotients of elements of R (the quotient field of R) is the composite field $\bigvee_{i \in I} A_i$ of the family E . In other words, it is the subfield generated by $\bigcup_{i \in I} A_i$. The notation $\bigvee_{i \in I} A_i$ comes from the fact that the family of all subfields of a field forms a complete lattice.

The \bigvee of fields is defined only when the respective fields are all included in a larger field.