

# Kobe Bryant Make His Next Shot: Linear Discriminant Analysis and Logistic Regression

*Paul Adams*

*Reannan McDaniel*

*Jeff Nguyen*

*Southern Methodist University*

*21 November 2019*

## Abstract

This project investigates the correlation between multiple potential explanatory variables and Kobe Bryant's ability to make a shot while playing for the NBA team Los Angeles Lakers using data gathered from 1996-2015.

## R Markdown

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see <http://rmarkdown.rstudio.com>.

In preparation for analysis, derived data was needed to simplify overly complicated variables for the model. The over-complication is with respect to the availability of other predictor variables.

```
df[which(df$action_type == "Alley Oop Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Cutting Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Driving Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Driving Finger Roll Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Driving Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Driving Reverse Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Driving Slam Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Finger Roll Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Follow Up Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Putback Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Putback Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Putback Slam Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Reverse Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Reverse Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Reverse Slam Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Running Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Running Finger Roll Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Running Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Running Reverse Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Running Slam Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Running Tip Shot"), "action_type"] = "short"
df[which(df$action_type == "Slam Dunk Shot"), "action_type"] = "short"
df[which(df$action_type == "Tip Layup Shot"), "action_type"] = "short"
df[which(df$action_type == "Tip Shot"), "action_type"] = "short"

df$action_type <- ifelse(df$action_type=="short", "short", "long")

df[which(df$combined_shot_type == "Jump Shot"), "combined_shot_type"] = "short"
```

```
df[which(df$combined_shot_type == "Dunk"), "combined_shot_type"] = "short"
df[which(df$combined_shot_type == "Layup"), "combined_shot_type"] = "short"
df[which(df$combined_shot_type == "Tip Shot"), "combined_shot_type"] = "short"
df[which(df$combined_shot_type == "Hook Shot"), "combined_shot_type"] = "short"
df[which(df$combined_shot_type == "Bank Shot"), "combined_shot_type"] = "short"

df$combined_shot_type <- ifelse(df$combined_shot_type=="short", "short", "long")
```

Remove one-level factors. These will never change so are not useful to the model; including can cause issues with model sensitivity since linear trajectories will be down-weighted. Therefore, their significance will be lessened by the constant state of the additional parameters. While this is may not be significant, it is not conducive to model quality.

```
#
badNews <- "Sorry, but your math is off. Please try again..."

tryCatch(
  {
    df <- df %>% subset(select=-c("team_id", "team_name"))
  },
  error = function(e)
  {
    badNews
  }
)
```

```
## [1] "Sorry, but your math is off. Please try again..."
```

```
# create numeric dataframe for correlation plot
```

```
df.numeric <- df %>% subset(select=-c(team_id, team_name, season, shot_zone_area, shot_zone_basic, shot_
```

```
# Convert all remaining integers to numeric and characters to factors with levels:
```

```
df <- df %>% mutate_if(is.integer, as.numeric) %>% mutate_if(is.character, as.factor) %>% data.frame()
```

```
summary(cars)
```

```
##      speed      dist
##  Min.   : 4.0    Min.   : 2.00
##  1st Qu.:12.0    1st Qu.: 26.00
##  Median :15.0    Median : 36.00
##  Mean   :15.4    Mean   : 42.98
##  3rd Qu.:19.0    3rd Qu.: 56.00
##  Max.   :25.0    Max.    :120.00
```

## Including Plots

You can also embed plots, for example:



Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.