



尺寸未注公差参考±0.10

RECOMMENDED PCB LAYOUT

- 特性:Specifications:  
电 器:Electrical:  
    接触电阻:Contact Resistance  
        50 milliohms MAX  
耐电压:Dielectric Withstanding Voltage:  
    100 V AC At Sea Level  
绝缘电阻:Insulation Resistance:  
    100 MEGA ohms MIN
- 材料:Material:  
    塑胶:Housing:High Temperature Thermoplastics,  
        UL 94V-0 耐高温塑胶
- 端子:Contact: Copper Alloy 铜合金  
铁壳:Shell: Copper Alloy 铜合金  
电镀:Finish:  
    端子:Contact: Plated Gold in Mating Area;  
        Tin On Solder Tails  
        接触点镀金, 脚镀锡
- 铁壳:Shell:  
    Nickel/ Plating 镀镍

Ordering Informating  
X - 5 - XX

- X  
└─┬─┘  
    Contact plating  
    01-Gold Flash  
    02-5u"Gold/ Tin  
    03-15u"Gold/ Tin  
    04-30u"Gold/Tin
- X  
└─┬─┘  
    Plastic Color  
    A=Black

深圳尚格科技有限公司



成品图

品 名	MINT USB B-TYPE 5P 90度 母座内脚插板	材 质		单 位	MM
图 号	A004-2B-7D	图纸编号		比例	1:1
制 图		审 核		日期	2007.03.29