Study guide: Finite difference methods for wave motion

Hans Petter Langtangen[1,2]

Center for Biomedical Computing, Simula Research Laboratory[1]

Department of Informatics, University of Oslo[2]

Oct 12, 2015

Waves on a string can be modeled by the *wave equation*

$$\frac{\partial^2 u}{\partial t^2} = c^2 \frac{\partial^2 u}{\partial x^2}$$

$u(x, t)$ is the displacement of the string

Demo of waves on a string.

$$\frac{\partial^2 u}{\partial t^2} = c^2 \frac{\partial^2 u}{\partial x^2}, \qquad x \in (0, L), \ t \in (0, T] \qquad (1)$$

$$u(x, 0) = I(x), \qquad x \in [0, L] \qquad (2)$$

$$\frac{\partial}{\partial t} u(x, 0) = 0, \qquad x \in [0, L] \qquad (3)$$

$$u(0, t) = 0, \qquad t \in (0, T] \qquad (4)$$

$$u(L, t) = 0, \qquad t \in (0, T] \qquad (5)$$

- Initial condition $u(x, 0) = I(x)$: initial string shape
- Initial condition $u_t(x, 0) = 0$: string starts from rest
- $c = \sqrt{T/\varrho}$: velocity of waves on the string
- (T is the tension in the string, ϱ is density of the string)
- Two boundary conditions on u: $u = 0$ means fixed ends (no displacement)

Rule for number of initial and boundary conditions:

- u_{tt} in the PDE: two initial conditions, on u and u_t
- u_t (and no u_{tt}) in the PDE: one initial conditions, on u
- u_{xx} in the PDE: one boundary condition on u at each boundary point

- Our numerical method is sometimes exact (!)
- Our numerical method is sometimes subject to serious non-physical effects

Ooops!

Mesh in time:

$$0 = t_0 < t_1 < t_2 < \cdots < t_{N_t-1} < t_{N_t} = T \qquad (6)$$

Mesh in space:

$$0 = x_0 < x_1 < x_2 < \cdots < x_{N_x-1} < x_{N_x} = L \qquad (7)$$

Uniform mesh with constant mesh spacings Δt and Δx:

$$x_i = i\Delta x, \ i = 0, \ldots, N_x, \quad t_i = n\Delta t, \ n = 0, \ldots, N_t \qquad (8)$$

The discrete solution

- The numerical solution is a mesh function: $u_i^n \approx u_e(x_i, t_n)$
- Finite difference stencil (or scheme): equation for u_i^n involving neighboring space-time points

Stencil at interior point

Let the PDE be satisfied at all *interior* mesh points:

$$\frac{\partial^2}{\partial t^2} u(x_i, t_n) = c^2 \frac{\partial^2}{\partial x^2} u(x_i, t_n), \tag{9}$$

for $i = 1, \ldots, N_x - 1$ and $n = 1, \ldots, N_t - 1$.

For $n = 0$ we have the initial conditions $u = I(x)$ and $u_t = 0$, and at the boundaries $i = 0, N_x$ we have the boundary condition $u = 0$.

Widely used finite difference formula for the second-order derivative:

$$\frac{\partial^2}{\partial t^2} u(x_i, t_n) \approx \frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2} = [D_t D_t u]_i^n$$

and

$$\frac{\partial^2}{\partial x^2} u(x_i, t_n) \approx \frac{u_{i+1}^n - 2u_i^n + u_{i-1}^n}{\Delta x^2} = [D_x D_x u]_i^n$$

Replace derivatives by differences:

$$\frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2} = c^2 \frac{u_{i+1}^n - 2u_i^n + u_{i-1}^n}{\Delta x^2}, \qquad (10)$$

In operator notation:

$$[D_t D_t u = c^2 D_x D_x]_i^n \qquad (11)$$

- Need to replace the derivative in the initial condition $u_t(x, 0) = 0$ by a finite difference approximation
- The differences for u_{tt} and u_{xx} have second-order accuracy
- Use a centered difference for $u_t(x, 0)$

$$[D_{2t} u]_i^n = 0, \quad n = 0 \quad \Rightarrow \quad u_i^{n-1} = u_i^{n+1}, \quad i = 0, \ldots, N_x$$

The other initial condition $u(x, 0) = I(x)$ can be computed by

$$u_i^0 = I(x_i), \quad i = 0, \ldots, N_x$$

- Nature of the algorithm: compute u in space at $t = \Delta t, 2\Delta t, 3\Delta t, \ldots$
- Three time levels are involved in the general discrete equation: $n + 1$, n, $n - 1$
- u_i^n and u_i^{n-1} are then already computed for $i = 0, \ldots, N_x$, and u_i^{n+1} is the unknown quantity

Write out $[D_t D_t u = c^2 D_x D_x]_i^n$ and solve for u_i^{n+1},

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n \right) \qquad (12)$$

$$C = c\frac{\Delta t}{\Delta x}, \qquad (13)$$

is known as the (dimensionless) *Courant number*

Observe

There is only one parameter, C, in the discrete model: C lumps mesh parameters Δt and Δx with the only physical parameter, the wave velocity c. The value C and the smoothness of $I(x)$ govern the quality of the numerical solution.

Stencil at interior point

- Problem: the stencil for $n = 1$ involves u_i^{-1}, but time $t = -\Delta t$ is outside the mesh
- Remedy: use the initial condition $u_t = 0$ together with the stencil to eliminate u_i^{-1}

Initial condition:

$$[D_{2t} u = 0]_i^0 \quad \Rightarrow \quad u_i^{-1} = u_i^1$$

Insert in stencil $[D_t D_t u = c^2 D_x D_x]_i^0$ to get

$$u_i^1 = u_i^0 - \frac{1}{2} C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n \right) \tag{14}$$

1. Compute $u_i^0 = I(x_i)$ for $i = 0, \ldots, N_x$
2. Compute u_i^1 by (14) and set $u_i^1 = 0$ for the boundary points $i = 0$ and $i = N_x$, for $n = 1, 2, \ldots, N - 1$,
3. For each time level $n = 1, 2, \ldots, N_t - 1$
   1. apply (12) to find u_i^{n+1} for $i = 1, \ldots, N_x - 1$
   2. set $u_i^{n+1} = 0$ for the boundary points $i = 0$, $i = N_x$.

web page or a movie file.

- Arrays:
  - u[i] stores u_i^{n+1}
  - u_1[i] stores u_i^n
  - u_2[i] stores u_i^{n-1}

Naming convention

u is the unknown to be computed (a spatial mesh function), u_k is the computed spatial mesh function k time steps back in time.

Important to minimize the memory usage

The algorithm only needs to access the *three most recent time levels*, so we need only three arrays for u_i^{n+1}, u_i^n, and u_i^{n-1}, $i = 0, \ldots, N_x$. Storing all the solutions in a two-dimensional array of size $(N_x + 1) \times (N_t + 1)$ would be possible in this simple one-dimensional PDE problem, but not in large 2D problems and not even in small 3D problems.

Sketch of an implementation (2)

```python
# Given mesh points as arrays x and t (x[i], t[n])
dx = x[1] - x[0]
dt = t[1] - t[0]
C = c*dt/dx                # Courant number
Nt = len(t)-1
C2 = C**2                  # Help variable in the scheme

# Set initial condition u(x,0) = I(x)
for i in range(0, Nx+1):
    u_1[i] = I(x[i])

# Apply special formula for first step, incorporating du/dt=0
for i in range(1, Nx):
    u[i] = u_1[i] - 0.5*C**2(u_1[i+1] - 2*u_1[i] + u_1[i-1])
u[0] = 0;  u[Nx] = 0   # Enforce boundary conditions

# Switch variables before next step
u_2[:], u_1[:] = u_1, u

for n in range(1, Nt):
    # Update all inner mesh points at time t[n+1]
    for i in range(1, Nx):
        u[i] = 2u_1[i] - u_2[i] - \
               C**2(u_1[i+1] - 2*u_1[i] + u_1[i-1])

    # Insert boundary conditions
    u[0] = 0;  u[Nx] = 0
```

- Think about testing and verification before you start implementing the algorithm!
- Powerful testing tool: method of manufactured solutions and computation of convergence rates
- Will need a source term in the PDE and $u_t(x, 0) \neq 0$
- Even more powerful method: exact solution of the scheme

Add source term f and nonzero initial condition $u_t(x, 0)$:

$$
\begin{align}
u_{tt} &= c^2 u_{xx} + f(x, t), & & \text{(15)} \\
u(x, 0) &= I(x), & x \in [0, L] & \text{(16)} \\
u_t(x, 0) &= V(x), & x \in [0, L] & \text{(17)} \\
u(0, t) &= 0, & t > 0, & \text{(18)} \\
u(L, t) &= 0, & t > 0 & \text{(19)}
\end{align}
$$

$$[D_t D_t u = c^2 D_x D_x + f]_i^n \qquad (20)$$

Writing out and solving for the unknown u_i^{n+1}:

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2\left(u_{i+1}^n - 2u_i^n + u_{i-1}^n\right) + \Delta t^2 f_i^n \qquad (21)$$

Centered difference for $u_t(x, 0) = V(x)$:

$$[D_{2t}u = V]_i^0 \quad \Rightarrow \quad u_i^{-1} = u_i^1 - 2\Delta t V_i,$$

Inserting this in the stencil (21) for $n = 0$ leads to

$$u_i^1 = u_i^0 - \Delta t V_i + \frac{1}{2}C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n\right) + \frac{1}{2}\Delta t^2 f_i^n \qquad (22)$$

- Standing waves occur in real life on a string
- Can be analyzed mathematically (known exact solution)

$$u_e(x, y, t)) = A \sin\left(\frac{\pi}{L}x\right) \cos\left(\frac{\pi}{L}ct\right) \qquad (23)$$

- PDE data: $f = 0$, boundary conditions $u_e(0, t) = u_e(L, 0) = 0$, initial conditions $I(x) = A \sin\left(\frac{\pi}{L}x\right)$ and $V = 0$
- Note: $u_i^{n+1} \neq u_e(x_i, t_{n+1}$, and we do not know the error, so testing must aim at reproducing the expected convergence rates

- Disadvantage with the previous physical solution: it does not test $V \neq 0$ and $f \neq 0$
- Method of manufactured solution:
  - Choose some $u_e(x, t)$
  - Insert in PDE and fit f
  - Set boundary and initial conditions compatible with the chosen $u_e(x, t)$

$$u_e(x, t) = x(L - x) \sin t$$

PDE $u_{tt} = c^2 u_{xx} + f$:

$$-x(L - x) \sin t = -2 \sin t + f \quad \Rightarrow f = (2 - x(L - x)) \sin t$$

Implied initial conditions:

$$u(x, 0) = I(x) = 0$$
$$u_t(x, 0) = V(x) = -x(L - x)$$

Boundary conditions:

$$u(x, 0) = u(x, L) = 0$$

- Introduce common mesh parameter: $h = \Delta t$, $\Delta x = ch/C$
- This h keeps C and $\Delta t/\Delta x$ constant
- Select coarse mesh h: h_0
- Run experiments with $h_i = 2^{-i} h_0$ (halving the cell size), $i = 0, \ldots, m$
- Record the error E_i and h_i in each experiment
- Compute pariwise convergence rates
  $r_i = \ln E_{i+1}/E_i / \ln h_{i+1}/h_i$
- Verification: $r_i \to 2$ as i increases

- Manufactured solution with computation of convergence rates: much manual work
- Simpler and more powerful: use an exact solution for u_i^n
- A linear or quadratic u_e in x and t is often a good candidate

Here, choose u_e such that $u_e(x,0) = u_e(L,0) = 0$:

$$u_e(x,t) = x(L-x)(1 + \frac{1}{2}t),$$

Insert in the PDE and find f:

$$f(x,t) = 2(1+t)c^2$$

Initial conditions:

$$I(x) = x(L-x), \quad V(x) = \frac{1}{2}x(L-x)$$

We want to show that u_e also solves the discrete equations!

Useful preliminary result:

$$[D_t D_t t^2]^n = \frac{t_{n+1}^2 - 2t_n^2 + t_{n-1}^2}{\Delta t^2} = (n+1)^2 - n^2 + (n-1)^2 = 2$$

$$\tag{24}$$

$$[D_t D_t t]^n = \frac{t_{n+1} - 2t_n + t_{n-1}}{\Delta t^2} = \frac{((n+1) - n + (n-1))\Delta t}{\Delta t^2} = 0$$

$$\tag{25}$$

Hence,

$$[D_t D_t u_e]_i^n = x_i(L - x_i)[D_t D_t (1 + \frac{1}{2}t)]^n = x_i(L - x_i)\frac{1}{2}[D_t D_t t]^n = 0$$

$$[D_x D_x u_e]_i^n = (1 + \frac{1}{2}t_n)[D_x D_x(xL - x^2)]_i = (1 + \frac{1}{2}t_n)[LD_x D_x x - D_x D_x x^2]$$

$$= -2(1 + \frac{1}{2}t_n)$$

Now, $f_i^n = 2(1 + \frac{1}{2}t_n)c^2$ and we get

$$[D_t D_t u_e - c^2 D_x D_x u_e - f]_i^n = 0 - c^2(-1)2(1 + \frac{1}{2}t_n) + 2(1 + \frac{1}{2}t_n)c^2 = 0$$

Moreover, $u_e(x_i, 0) = I(x_i)$, $\partial u_e/\partial t = V(x_i)$ at $t = 0$, and $u_e(x_0, t) = u_e(x_{N_x}, 0) = 0$. Also the modified scheme for the first time step is fulfilled by $u_e(x_i, t_n)$.

- We have established that
  $u_i^{n+1} = u_e(x_i, t_{n+1}) = x_i(L - x_i)(1 + t_{n+1}/2)$
- Run *one* simulation with one choice of c, Δt, and Δx
- Check that $\max_i |u_i^{n+1} - u_e(x_i, t_{n+1})| < \epsilon$, $\epsilon \sim 10^{-14}$
  (machine precision + some round-off errors)
- This is the simplest and best verification test

Later we show that the exact solution of the discrete equations can
be obtained by $C = 1$ (!)

- We have established that
  $u_i^{n+1} = u_e(x_i, t_{n+1}) = x_i(L - x_i)(1 + t_{n+1}/2)$
- Run *one* simulation with one choice of c, Δt, and Δx
- Check that $\max_i |u_i^{n+1} - u_e(x_i, t_{n+1})| < \epsilon$, $\epsilon \sim 10^{-14}$
  (machine precision + some round-off errors)
- This is the simplest and best verification test

Later we show that the exact solution of the discrete equations can
be obtained by $C = 1$ (!)

1. Compute $u_i^0 = I(x_i)$ for $i = 0, \ldots, N_x$
2. Compute u_i^1 by (14) and set $u_i^1 = 0$ for the boundary points $i = 0$ and $i = N_x$, for $n = 1, 2, \ldots, N - 1$,
3. For each time level $n = 1, 2, \ldots, N_t - 1$
   1. apply (12) to find u_i^{n+1} for $i = 1, \ldots, N_x - 1$
   2. set $u_i^{n+1} = 0$ for the boundary points $i = 0$, $i = N_x$.

- Different problem settings demand different actions with the computed u_i^{n+1} at each time step
- Solution: let the solver function make a callback to a user function where the user can do whatever is desired with the solution
- Advantage: solver just solves and user uses the solution

```python
def user_action(u, x, t, n):
    # u[i] at spatial mesh points x[i] at time t[n]
    # plot u
    # or store u
```

We specify Δt and C, and let the solver function compute $\Delta x = c\Delta t / C$.

```python
def solver(I, V, f, c, L, dt, C, T, user_action=None):
    """Solve u_tt=c^2*u_xx + f on (0,L)x(0,T]."""
    Nt = int(round(T/dt))
    t = linspace(0, Nt*dt, Nt+1)    # Mesh points in time
    dx = dt*c/float(C)
    Nx = int(round(L/dx))
    x = linspace(0, L, Nx+1)        # Mesh points in space
    dx = x[1] - x[0]
    C2 = C**2                       # Help variable in the scheme
    if f is None or f == 0 :
        f = lambda x, t: 0
    if V is None or V == 0:
        V = lambda x: 0

    u   = zeros(Nx+1)   # Solution array at new time level
    u_1 = zeros(Nx+1)   # Solution at 1 time level back
    u_2 = zeros(Nx+1)   # Solution at 2 time levels back

    import time;  t0 = time.clock()  # for measuring CPU time

    # Load initial condition into u_1
    for i in range(0,Nx+1):
        u_1[i] = I(x[i])
```

```python
def solver(I, V, f, c, L, dt, C, T, user_action=None):
    ...
    # Special formula for first time step
    n = 0
    for i in range(1, Nx):
        u[i] = u_1[i] + dt*V(x[i]) + \
               0.5*C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1]) + \
               0.5*dt**2*f(x[i], t[n])
    u[0] = 0;  u[Nx] = 0

    if user_action is not None:
        user_action(u, x, t, 1)

    # Switch variables before next step
    u_2[:], u_1[:] = u_1, u

def solver(I, V, f, c, L, Nx, C, T, user_action=None):
    ...
    # Time loop

    for n in range(1, Nt):
        # Update all inner points at time t[n+1]
        for i in range(1, Nx):
            u[i] = - u_2[i] + 2*u_1[i] + \
                   C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1]) + \
                   dt**2*f(x[i], t[n])
```

Verification: exact quadratic solution

Exact solution of the PDE problem *and* the discrete equations:
$u_e(x, t) = x(L - x)(1 + \frac{1}{2}t)$

```python
def test_quadratic():
    """Check that u(x,t)=x(L-x)(1+t/2) is exactly reproduced."""

    def u_exact(x, t):
        return x*(L-x)*(1 + 0.5*t)

    def I(x):
        return u_exact(x, 0)

    def V(x):
        return 0.5*u_exact(x, 0)

    def f(x, t):
        return 2*(1 + 0.5*t)*c**2

    L = 2.5
    c = 1.5
    C = 0.75
    Nx = 6  # Very coarse mesh for this exact test
    dt = C*(L/Nx)/c
    T = 18

    def assert_no_error(u, x, t, n):
        u_e = u_exact(x, t[n])
```

Visualization: animating $u(x,t)$

Make a `viz` function for animating the curve, with plotting in a `user_action` function `plot_u`:

```python
def viz(
    I, V, f, c, L, dt, C, T,    # PDE paramteres
    umin, umax,                 # Interval for u in plots
    animate=True,               # Simulation with animation?
    tool='matplotlib',          # 'matplotlib' or 'scitools'
    solver_function=solver,     # Function with numerical algorithm
    ):
    """Run solver and visualize u at each time level."""

    def plot_u_st(u, x, t, n):
        """user_action function for solver."""
        plt.plot(x, u, 'r-',
                 xlabel='x', ylabel='u',
                 axis=[0, L, umin, umax],
                 title='t=%f' % t[n], show=True)
        # Let the initial condition stay on the screen for 2
        # seconds, else insert a pause of 0.2 s between each plot
        time.sleep(2) if t[n] == 0 else time.sleep(0.2)
        plt.savefig('frame_%04d.png' % n)  # for movie making

    class PlotMatplotlib:
        def __call__(self, u, x, t, n):
            """user_action function for solver."""
            if n == 0:
```

- Store spatial curve in a file, for each time level
- Name files like 'something_%04d.png' % frame_counter
- Combine files to a movie

```
Terminal> scitools movie encoder=html output_file=movie.html \
          fps=4 frame_*.png  # web page with a player
Terminal> avconv -r 4 -i frame_%04d.png -c:v flv       movie.flv
Terminal> avconv -r 4 -i frame_%04d.png -c:v libtheora movie.ogg
Terminal> avconv -r 4 -i frame_%04d.png -c:v libx264   movie.mp4
Terminal> avconv -r 4 -i frame_%04d.png -c:v libpvx    movie.webm
```

Important

- Zero padding (%04d) is essential for correct sequence of frames in `something_*.png` (Unix alphanumeric sort)
- Remove old `frame_*.png` files before making a new movie

- Vibrations of a guitar string
- Triangular initial shape (at rest)

$$I(x) = \begin{cases} ax/x_0, & x < x_0 \\ a(L-x)/(L-x_0), & \text{otherwise} \end{cases} \qquad (26)$$

Appropriate data:

- $L = 75$ cm, $x_0 = 0.8L$, $a = 5$ mm, time frequency $\nu = 440$ Hz

```python
def guitar(C):
    """Triangular wave (pulled guitar string)."""
    L = 0.75
    x0 = 0.8*L
    a = 0.005
    freq = 440
    wavelength = 2*L
    c = freq*wavelength
    omega = 2*pi*freq
    num_periods = 1
    T = 2*pi/omega*num_periods
    # Choose dt the same as the stability limit for Nx=50
    dt = L/50./c

    def I(x):
        return a*x/x0 if x < x0 else a/(L-x0)*(L-x)

    umin = -1.2*a;  umax = -umin
    cpu = viz(I, 0, 0, c, L, dt, C, T, umin, umax,
              animate=True, tool='scitools')
```

Program: wave1D_u0.py.

Movie of the vibrating string

The benefits of scaling

- It is difficult to figure out all the physical parameters of a case
- And it is not necessary because of a powerful: *scaling*

Introduce new x, t, and u without dimension:

$$\bar{x} = \frac{x}{L}, \quad \bar{t} = \frac{c}{L}t, \quad \bar{u} = \frac{u}{a}$$

Insert this in the PDE (with $f = 0$) and dropping bars

$$u_{tt} = u_{xx}$$

Initial condition: set $a = 1$, $L = 1$, and $x_0 \in [0, 1]$ in (26).

In the code: set a=c=L=1, x0=0.8, and there is no need to calculate with wavelengths and frequencies to estimate c!

Just one challenge: determine the period of the waves and an appropriate end time (see the text for details).

- Problem: Python loops over long arrays are slow
- One remedy: use vectorized (`numpy`) code instead of explicit loops
- Other remedies: use Cython, port spatial loops to Fortran or C
- Speedup: 100-1000 (varies with N_x)

Next: vectorized loops

- Introductory example: compute $d_i = u_{i+1} - u_i$

```
n = u.size
for i in range(0, n-1):
    d[i] = u[i+1] - u[i]
```

- Note: all the differences here are independent of each other.
- Therefore $d = (u_1, u_2, \ldots, u_n) - (u_0, u_1, \ldots, u_{n-1})$
- In numpy code: `u[1:n]` - `u[0:n-1]` or just `u[1:]` - `u[:-1]`

Newcomers to vectorization are encouraged to choose a small array u, say with five elements, and simulate with pen and paper both the loop version and the vectorized version.

Finite difference schemes basically contains differences between array elements with shifted indices. Consider the updating formula

```
for i in range(1, n-1):
    u2[i] = u[i-1] - 2*u[i] + u[i+1]
```

The vectorization consists of replacing the loop by arithmetics on slices of arrays of length n-2:

```
u2 = u[:-2] - 2*u[1:-1] + u[2:]
u2 = u[0:n-2] - 2*u[1:n-1] + u[2:n]     # alternative
```

Note: u2 gets length n-2.

If u2 is already an array of length n, do update on "inner" elements

```
u2[1:-1]  = u[:-2] - 2*u[1:-1] + u[2:]
u2[1:n-1] = u[0:n-2] - 2*u[1:n-1] + u[2:n]     # alternative
```

Include a function evaluation too:

```python
def f(x):
    return x**2 + 1

# Scalar version
for i in range(1, n-1):
    u2[i] = u[i-1] - 2*u[i] + u[i+1] + f(x[i])

# Vectorized version
u2[1:-1] = u[:-2] - 2*u[1:-1] + u[2:] + f(x[1:-1])
```

Scalar loop:

```python
for i in range(1, Nx):
    u[i] = 2*u_1[i] - u_2[i] + \
           C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1])
```

Vectorized loop:

```python
u[1:-1] = - u_2[1:-1] + 2*u_1[1:-1] + \
          C2*(u_1[:-2] - 2*u_1[1:-1] + u_1[2:])
```

or

```python
u[1:Nx] = 2*u_1[1:Nx]- u_2[1:Nx] + \
          C2*(u_1[0:Nx-1] - 2*u_1[1:Nx] + u_1[2:Nx+1])
```

Program: `wave1D_u0v.py`

Verification of the vectorized version

```python
def test_quadratic():
    """
    Check the scalar and vectorized versions work for
    a quadratic u(x,t)=x(L-x)(1+t/2) that is exactly reproduced.
    """
    # The following function must work for x as array or scalar
    u_exact = lambda x, t: x*(L - x)*(1 + 0.5*t)
    I = lambda x: u_exact(x, 0)
    V = lambda x: 0.5*u_exact(x, 0)
    # f is a scalar (zeros_like(x) works for scalar x too)
    f = lambda x, t: np.zeros_like(x) + 2*c**2*(1 + 0.5*t)

    L = 2.5
    c = 1.5
    C = 0.75
    Nx = 3  # Very coarse mesh for this exact test
    dt = C*(L/Nx)/c
    T = 18

    def assert_no_error(u, x, t, n):
        u_e = u_exact(x, t[n])
        tol = 1E-13
        diff = np.abs(u - u_e).max()
        assert diff < tol

    solver(I, V, f, c, L, dt, C, T,
           user_action=assert_no_error, version='scalar')
    solver(I, V, f, c, L, dt, C, T,
```

- Run `wave1D_u0v.py` for N_x as 50,100,200,400,800 and measuring the CPU time
- Observe substantial speed-up: vectorized version is about $N_x/5$ times faster

Much bigger improvements for 2D and 3D codes!

- Boundary condition $u = 0$: u changes sign
- Boundary condition $u_x = 0$: wave is perfectly reflected
- How can we implement u_x? (more complicated than $u = 0$)

Demo of boundary conditions

$$\frac{\partial u}{\partial n} \equiv \boldsymbol{n} \cdot \nabla u = 0 \qquad (27)$$

For a 1D domain $[0, L]$:

$$\frac{\partial}{\partial n}\bigg|_{x=L} = \frac{\partial}{\partial x}, \qquad \frac{\partial}{\partial n}\bigg|_{x=0} = -\frac{\partial}{\partial x}$$

Boundary condition terminology:

- u_x specified: Neumann condition
- u specified: Dirichlet condition

- How can we incorporate the condition $u_x = 0$ in the finite difference scheme?
- We used centeral differences for u_{tt} and u_{xx}: $\mathcal{O}(\Delta t^2, \Delta x^2)$ accuracy
- Also for $u_t(x, 0)$
- Should use central difference for u_x to preserve second order accuracy

$$\frac{u^n_{-1} - u^n_1}{2\Delta x} = 0 \tag{28}$$

$$\frac{u_{-1}^n - u_1^n}{2\Delta x} = 0$$

- Problem: u_{-1}^n is outside the mesh (fictitious value)
- Remedy: use the stencil at the boundary to eliminate u_{-1}^n; just replace u_{-1}^n by u_1^n

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + 2C^2 \left(u_{i+1}^n - u_i^n \right), \quad i = 0 \qquad (29)$$

Discrete equation for computing u_0^3 in terms of u_0^2, u_0^1, and u_1^2:

Animation in a web page or a movie file.

- Use the general stencil for interior points also on the boundary
- Replace u_{i-1}^n by u_{i+1}^n for $i = 0$
- Replace u_{i+1}^n by u_{i-1}^n for $i = N_x$

```
i = 0
ip1 = i+1
im1 = ip1  # i-1 -> i+1
u[i] = u_1[i] + C2*(u_1[im1] - 2*u_1[i] + u_1[ip1])

i = Nx
im1 = i-1
ip1 = im1  # i+1 -> i-1
u[i] = u_1[i] + C2*(u_1[im1] - 2*u_1[i] + u_1[ip1])

# Or just one loop over all points

for i in range(0, Nx+1):
    ip1 = i+1 if i < Nx else i-1
    im1 = i-1 if i > 0  else i+1
    u[i] = u_1[i] + C2*(u_1[im1] - 2*u_1[i] + u_1[ip1])
```

Program wave1D_dn0.py

web page or a movie file.

- Tedious to write index sets like $i = 0, \ldots, N_x$ and $n = 0, \ldots, N_t$
- Notation not valid if i or n starts at 1 instead...
- Both in math and code it is advantageous to use *index sets*
- $i \in \mathcal{I}_x$ instead of $i = 0, \ldots, N_x$
- Definition: $\mathcal{I}_x = \{0, \ldots, N_x\}$
- The first index: $i = \mathcal{I}_x^0$
- The last index: $i = \mathcal{I}_x^{-1}$
- All interior points: $i \in \mathcal{I}_x^i$, $\mathcal{I}_x^i = \{1, \ldots, N_x - 1\}$
- $\mathcal{I}_x^-$ means $\{0, \ldots, N_x - 1\}$
- $\mathcal{I}_x^+$ means $\{1, \ldots, N_x\}$

Notation	Python
$\mathcal{I}_x$	`Ix`
$\mathcal{I}_x^0$	`Ix[0]`
$\mathcal{I}_x^{-1}$	`Ix[-1]`
$\mathcal{I}_x^-$	`Ix[1:]`
$\mathcal{I}_x^+$	`Ix[:-1]`
$\mathcal{I}_x^i$	`Ix[1:-1]`

Index sets for a problem in the x, t plane:

$$\mathcal{I}_x = \{0, \ldots, N_x\}, \quad \mathcal{I}_t = \{0, \ldots, N_t\}, \tag{30}$$

Implemented in Python as

```
Ix = range(0, Nx+1)
It = range(0, Nt+1)
```

A finite difference scheme can with the index set notation be specified as

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n \right), \quad i \in \mathcal{I}_x^i, \ n \in \mathcal{I}_t^i$$

$$u_i = 0, \quad i = \mathcal{I}_x^0, \ n \in \mathcal{I}_t^i$$

$$u_i = 0, \quad i = \mathcal{I}_x^{-1}, \ n \in \mathcal{I}_t^i$$

Corresponding implementation:

```
for n in It[1:-1]:
    for i in Ix[1:-1]:
        u[i] = - u_2[i] + 2*u_1[i] + \
               C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1])
    i = Ix[0];  u[i] = 0
    i = Ix[-1]; u[i] = 0
```

Program wave1D_dn.py

- Instead of modifying the stencil at the boundary, we extend the mesh to cover u_{-1}^n and $u_{N_x+1}^n$
- The extra left and right cell are called *ghost cells*
- The extra points are called *ghost points*
- The u_{-1}^n and $u_{N_x+1}^n$ values are called *ghost values*
- Update ghost values as $u_{i-1}^n = u_{i+1}^n$ for $i = 0$ and $i = N_x$
- Then the stencil becomes right at the boundary

Add ghost points:

```
u   = zeros(Nx+3)
u_1 = zeros(Nx+3)
u_2 = zeros(Nx+3)

x = linspace(0, L, Nx+1)   # Mesh points without ghost points
```

- A major indexing problem arises with ghost cells since Python indices *must* start at 0.
- u[-1] will always mean the last element in u
- Math indexing: $-1, 0, 1, 2, \ldots, N_x + 1$
- Python indexing: 0,..,Nx+2
- Remedy: use index sets

```
u = zeros(Nx+3)
Ix = range(1, u.shape[0]-1)

# Boundary values: u[Ix[0]], u[Ix[-1]]

# Set initial conditions
for i in Ix:
    u_1[i] = I(x[i-Ix[0]])  # Note i-Ix[0]

# Loop over all physical mesh points
for i in Ix:
    u[i] = - u_2[i] + 2*u_1[i] + \
           C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1])

# Update ghost values
i = Ix[0]              # x=0 boundary
u[i-1] = u[i+1]
i = Ix[-1]             # x=L boundary
u[i-1] = u[i+1]
```

Program: wave1D_dn0_ghost.py.

Heterogeneous media: varying $c = c(x)$

$$\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right) + f(x, t) \qquad (31)$$

This equation sampled at a mesh point (x_i, t_n):

$$\frac{\partial^2}{\partial t^2}u(x_i, t_n) = \frac{\partial}{\partial x}\left(q(x_i)\frac{\partial}{\partial x}u(x_i, t_n)\right) + f(x_i, t_n),$$

The principal idea is to *first discretize the outer derivative*.

Define

$$\phi = q(x)\frac{\partial u}{\partial x}$$

Then use a centered derivative around $x = x_i$ for the derivative of ϕ:

$$\left[\frac{\partial \phi}{\partial x}\right]_i^n \approx \frac{\phi_{i+\frac{1}{2}} - \phi_{i-\frac{1}{2}}}{\Delta x} = [D_x \phi]_i^n$$

Then discretize the inner operators:

$$\phi_{i+\frac{1}{2}} = q_{i+\frac{1}{2}} \left[\frac{\partial u}{\partial x}\right]^n_{i+\frac{1}{2}} \approx q_{i+\frac{1}{2}} \frac{u^n_{i+1} - u^n_i}{\Delta x} = [qD_x u]^n_{i+\frac{1}{2}}$$

Similarly,

$$\phi_{i-\frac{1}{2}} = q_{i-\frac{1}{2}} \left[\frac{\partial u}{\partial x}\right]^n_{i-\frac{1}{2}} \approx q_{i-\frac{1}{2}} \frac{u^n_i - u^n_{i-1}}{\Delta x} = [qD_x u]^n_{i-\frac{1}{2}}$$

These intermediate results are now combined to

$$\left[\frac{\partial}{\partial x} \left(q(x) \frac{\partial u}{\partial x} \right) \right]_i^n \approx \frac{1}{\Delta x^2} \left(q_{i+\frac{1}{2}} \left(u_{i+1}^n - u_i^n \right) - q_{i-\frac{1}{2}} \left(u_i^n - u_{i-1}^n \right) \right)$$

$$(32)$$

In operator notation:

$$\left[\frac{\partial}{\partial x} \left(q(x) \frac{\partial u}{\partial x} \right) \right]_i^n \approx [D_x q D_x u]_i^n \qquad (33)$$

Remark

Many are tempted to use the chain rule on the term $\frac{\partial}{\partial x} \left(q(x) \frac{\partial u}{\partial x} \right)$, but this is not a good idea!

- Given $q(x)$: compute $q_{i+\frac{1}{2}}$ as $q(x_{i+\frac{1}{2}})$
- Given q at the mesh points: q_i, use an average

$$q_{i+\frac{1}{2}} \approx \frac{1}{2}(q_i + q_{i+1}) = [\overline{q}^x]_i \qquad \text{(arithmetic mean)} \qquad (34)$$

$$q_{i+\frac{1}{2}} \approx 2\left(\frac{1}{q_i} + \frac{1}{q_{i+1}}\right)^{-1} \qquad \text{(harmonic mean)} \qquad (35)$$

$$q_{i+\frac{1}{2}} \approx (q_i q_{i+1})^{1/2} \qquad \text{(geometric mean)} \qquad (36)$$

The arithmetic mean in (34) is by far the most used averaging technique.

$$[D_t D_t u = D_x \overline{q}^x D_x u + f]_i^n \qquad (37)$$

We clearly see the type of finite differences and averaging!

Write out and solve wrt u_i^{n+1}:

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + \left(\frac{\Delta t}{\Delta x}\right)^2 \times$$
$$\left(\frac{1}{2}(q_i + q_{i+1})(u_{i+1}^n - u_i^n) - \frac{1}{2}(q_i + q_{i-1})(u_i^n - u_{i-1}^n)\right) +$$
$$\Delta t^2 f_i^n \qquad (38)$$

Consider $\partial u/\partial x = 0$ at $x = L = N_x \Delta x$:

$$\frac{u_{i+1}^n - u_{i-1}^n}{2\Delta x} = 0 \quad u_{i+1}^n = u_{i-1}^n, \quad i = N_x$$

Insert $u_{i+1}^n = u_{i-1}^n$ in the stencil (38) for $i = N_x$ and obtain

$$u_i^{n+1} \approx -u_i^{n-1} + 2u_i^n + \left(\frac{\Delta t}{\Delta x}\right)^2 2q_i(u_{i-1}^n - u_i^n) + \Delta t^2 f_i^n$$

(We have used $q_{i+\frac{1}{2}} + q_{i-\frac{1}{2}} \approx 2q_i$.)

Alternative: assume $dq/dx = 0$ (simpler).

Assume c[i] holds c_i the spatial mesh points

```
for i in range(1, Nx):
    u[i] = - u_2[i] + 2*u_1[i] + \
           C2*(0.5*(q[i] + q[i+1])*(u_1[i+1] - u_1[i])  - \
               0.5*(q[i] + q[i-1])*(u_1[i] - u_1[i-1])) + \
           dt2*f(x[i], t[n])
```

Here: C2=(dt/dx)**2

Vectorized version:

```
u[1:-1] = - u_2[1:-1] + 2*u_1[1:-1] + \
          C2*(0.5*(q[1:-1] + q[2:])*(u_1[2:] - u_1[1:-1]) -
              0.5*(q[1:-1] + q[:-2])*(u_1[1:-1] - u_1[:-2])) + \
          dt2*f(x[1:-1], t[n])
```

Neumann condition $u_x = 0$: same ideas as in 1D (modified stencil or ghost cells).

$$\varrho(x)\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right) + f(x, t) \tag{39}$$

A natural scheme is

$$[\varrho D_t D_t u = D_x \overline{q}^x D_x u + f]_i^n \tag{40}$$

Or

$$[D_t D_t u = \varrho^{-1} D_x \overline{q}^x D_x u + f]_i^n \tag{41}$$

No need to average ϱ, just sample at i

Why do waves die out?

- Damping (non-elastic effects, air resistance)
- 2D/3D: conservation of energy makes an amplitude reduction by $1/\sqrt{r}$ (2D) or $1/r$ (3D)

Simplest damping model (for physical behavior, see demo):

$$\frac{\partial^2 u}{\partial t^2} + b\frac{\partial u}{\partial t} = c^2 \frac{\partial^2 u}{\partial x^2} + f(x, t), \tag{42}$$

$b \geq 0$: prescribed damping coefficient.

Discretization via centered differences to ensure $\mathcal{O}(\Delta t^2)$ error:

$$[D_t D_t u + b D_{2t} u = c^2 D_x D_x u + f]_i^n \tag{43}$$

Need special formula for u_i^1 + special stencil (or ghost cells) for Neumann conditions.

The program `wave1D_dn_vc.py` solves a fairly general 1D wave equation:

$$u_t = (c^2(x)u_x)_x + f(x, t), \qquad x \in (0, L), \ t \in (0, T] \tag{44}$$

$$u(x, 0) = I(x), \qquad x \in [0, L] \tag{45}$$

$$u_t(x, 0) = V(t), \qquad x \in [0, L] \tag{46}$$

$$u(0, t) = U_0(t) \text{ or } u_x(0, t) = 0, \qquad t \in (0, T] \tag{47}$$

$$u(L, t) = U_L(t) \text{ or } u_x(L, t) = 0, \qquad t \in (0, T] \tag{48}$$

Can be adapted to many needs.

The function `pulse` in `wave1D_dn_vc.py` offers four initial conditions:

1. a rectangular pulse ("plug")
2. a Gaussian function (`gaussian`)
3. a "cosine hat": one period of $1 + \cos(\pi x$, $x \in [-1, 1]$
4. half a "cosine hat": half a period of $\cos \pi x$, $x \in [-\frac{1}{2}, \frac{1}{2}]$

Can locate the initial pulse at $x = 0$ or in the middle

```
>>> import wave1D_dn_vc as w
>>> w.pulse(loc='left', pulse_tp='cosinehat', Nx=50, every_frame=10)
```

Constant wave velocity c:

$$\frac{\partial^2 u}{\partial t^2} = c^2 \nabla^2 u \text{ for } \boldsymbol{x} \in \Omega \subset \mathbb{R}^d, \ t \in (0, T] \tag{49}$$

Variable wave velocity:

$$\varrho \frac{\partial^2 u}{\partial t^2} = \nabla \cdot (q \nabla u) + f \text{ for } \boldsymbol{x} \in \Omega \subset \mathbb{R}^d, \ t \in (0, T] \tag{50}$$

3D, constant c:

$$\nabla^2 u = \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} + \frac{\partial^2 u}{\partial z^2}$$

2D, variable c:

$$\varrho(x,y)\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x}\left(q(x,y)\frac{\partial u}{\partial x}\right) + \frac{\partial}{\partial y}\left(q(x,y)\frac{\partial u}{\partial y}\right) + f(x,y,t) \tag{51}$$

Compact notation:

$$u_{tt} = c^2(u_{xx} + u_{yy} + u_{zz}) + f, \tag{52}$$

$$\varrho u_{tt} = (qu_x)_x + (qu_z)_z + (qu_z)_z + f \tag{53}$$

We need *one* boundary condition at *each point* on $\partial\Omega$:

1. u is prescribed ($u = 0$ or known incoming wave)
2. $\partial u/\partial n = \boldsymbol{n} \cdot \nabla u$ prescribed ($= 0$: reflecting boundary)
3. open boundary (radiation) condition: $u_t + \boldsymbol{c} \cdot \nabla u = 0$ (let waves travel undisturbed out of the domain)

PDEs with *second-order* time derivative need *two* initial conditions:

1. $u = I$,
2. $u_t = V$.

Mesh

- Mesh point: $\left(x_i, y_j, z_k, t_n\right)$
- x direction: $x_0 < x_1 < \cdots < x_{N_x}$
- y direction: $y_0 < y_1 < \cdots < y_{N_y}$
- z direction: $z_0 < z_1 < \cdots < z_{N_z}$
- $u_{i,j,k}^n \approx u_{\mathrm{e}}(x_i, y_j, z_k, t_n)$

$$[D_t D_t u = c^2 (D_x D_x u + D_y D_y u) + f]_{i,j,k}^n,$$

Written out in detail:

$$\frac{u_{i,j}^{n+1} - 2u_{i,j}^n + u_{i,j}^{n-1}}{\Delta t^2} = c^2 \frac{u_{i+1,j}^n - 2u_{i,j}^n + u_{i-1,j}^n}{\Delta x^2} +$$

$$c^2 \frac{u_{i,j+1}^n - 2u_{i,j}^n + u_{i,j-1}^n}{\Delta y^2} + f_{i,j}^n,$$

$u_{i,j}^{n-1}$ and $u_{i,j}^n$ are known, solve for $u_{i,j}^{n+1}$:

$$u_{i,j}^{n+1} = 2u_{i,j}^n + u_{i,j}^{n-1} + c^2 \Delta t^2 [D_x D_x u + D_y D_y u]_{i,j}^n$$

- The stencil for $u_{i,j}^1$ ($n = 0$) involves $u_{i,j}^{-1}$ which is outside the time mesh
- Remedy: use discretized $u_t(x, 0) = V$ and the stencil for $n = 0$ to develop a special stencil (as in the 1D case)

$$[D_{2t}u = V]_{i,j}^0 \quad \Rightarrow \quad u_{i,j}^{-1} = u_{i,j}^1 - 2\Delta t V_{i,j}$$

$$u_{i,j}^{n+1} = u_{i,j}^n - 2\Delta V_{i,j} + \frac{1}{2}c^2\Delta t^2[D_x D_x u + D_y D_y u]_{i,j}^n$$

3D wave equation:

$$\varrho u_{tt} = (q u_x)_x + (q u_y)_y + (q u_z)_z + f(x, y, z, t)$$

Just apply the 1D discretization for each term:

$$[\varrho D_t D_t u = (D_x \overline{q}^x D_x u + D_y \overline{q}^y D_y u + D_z \overline{q}^z D_z u) + f]_{i,j,k}^n \quad (54)$$

Need special formula for $u_{i,j,k}^1$ (use $[D_{2t} u = V]^0$ and stencil for $n = 0$).

Written out:

$$
\begin{aligned}
u_{i,j,k}^{n+1} &= -u_{i,j,k}^{n-1} + 2u_{i,j,k}^n + \\
&= \frac{1}{\varrho_{i,j,k}} \frac{1}{\Delta x^2} \big(\frac{1}{2}(q_{i,j,k} + q_{i+1,j,k})(u_{i+1,j,k}^n - u_{i,j,k}^n) - \\
&\quad \frac{1}{2}(q_{i-1,j,k} + q_{i,j,k})(u_{i,j,k}^n - u_{i-1,j,k}^n)) + \\
&= \frac{1}{\varrho_{i,j,k}} \frac{1}{\Delta x^2} \big(\frac{1}{2}(q_{i,j,k} + q_{i,j+1,k})(u_{i,j+1,k}^n - u_{i,j,k}^n) - \\
&\quad \frac{1}{2}(q_{i,j-1,k} + q_{i,j,k})(u_{i,j,k}^n - u_{i,j-1,k}^n)) + \\
&= \frac{1}{\varrho_{i,j,k}} \frac{1}{\Delta x^2} \big(\frac{1}{2}(q_{i,j,k} + q_{i,j,k+1})(u_{i,j,k+1}^n - u_{i,j,k}^n) - \\
&\quad \frac{1}{2}(q_{i,j,k-1} + q_{i,j,k})(u_{i,j,k}^n - u_{i,j,k-1}^n)) + \\
&+ \quad \Delta t^2 f_{i,j,k}^n
\end{aligned}
$$

Use ideas from 1D! Example: $\frac{\partial u}{\partial n}$ at $y = 0$, $\frac{\partial u}{\partial n} = -\frac{\partial u}{\partial y}$

Boundary condition discretization:

$$[-D_{2y} u = 0]_{i,0}^n \quad \Rightarrow \quad \frac{u_{i,1}^n - u_{i,-1}^n}{2\Delta y} = 0, \ i \in \mathcal{I}_x$$

Insert $u_{i,-1}^n = u_{i,1}^n$ in the stencil for $u_{i,j=0}^{n+1}$ to obtain a modified stencil on the boundary.

Pattern: use interior stencil also on the bundary, but replace $j - 1$ by $j + 1$

Alternative: use ghost cells and ghost values

$$u_t = c^2(u_{xx} + u_{yy}) + f(x, y, t), \qquad (x, y) \in \Omega, \ t \in (0, T] \tag{55}$$

$$u(x, y, 0) = I(x, y), \qquad (x, y) \in \Omega \tag{56}$$

$$u_t(x, y, 0) = V(x, y), \qquad (x, y) \in \Omega \tag{57}$$

$$u = 0, \qquad (x, y) \in \partial\Omega, \ t \in (0, T] \tag{58}$$

$\Omega = [0, L_x] \times [0, L_y]$

Discretization:

$$[D_t D_t u = c^2(D_x D_x u + D_y D_y u) + f]_{i,j}^n,$$

1. Set initial condition $u_{i,j}^0 = I(x_i, y_j)$
2. Compute $u_{i,j}^1 = \cdots$ for $i \in \mathcal{I}_x^i$ and $j \in \mathcal{I}_y^i$
3. Set $u_{i,j}^1 = 0$ for the boundaries $i = 0, N_x, j = 0, N_y$
4. For $n = 1, 2, \ldots, N_t$:
   1. Find $u_{i,j}^{n+1} = \cdots$ for $i \in \mathcal{I}_x^i$ and $j \in \mathcal{I}_y^i$
   2. Set $u_{i,j}^{n+1} = 0$ for the boundaries $i = 0, N_x, j = 0, N_y$

Program: `wave2D_u0.py`

```
def solver(I, V, f, c, Lx, Ly, Nx, Ny, dt, T,
           user_action=None, version='scalar'):
```

Mesh:

```
x = linspace(0, Lx, Nx+1)                    # mesh points in x dir
y = linspace(0, Ly, Ny+1)                    # mesh points in y dir
dx = x[1] - x[0]
dy = y[1] - y[0]
Nt = int(round(T/float(dt)))
t = linspace(0, N*dt, N+1)                   # mesh points in time
Cx2 = (c*dt/dx)**2;  Cy2 = (c*dt/dy)**2      # help variables
dt2 = dt**2
```

Store $u_{i,j}^{n+1}$, $u_{i,j}^n$, and $u_{i,j}^{n-1}$ in three two-dimensional arrays:

```
u   = zeros((Nx+1,Ny+1))    # solution array
u_1 = zeros((Nx+1,Ny+1))    # solution at t-dt
u_2 = zeros((Nx+1,Ny+1))    # solution at t-2*dt
```

$u_{i,j}^{n+1}$ corresponds to u[i,j], etc.

```
Ix = range(0, u.shape[0])
Iy = range(0, u.shape[1])
It = range(0, t.shape[0])

for i in Ix:
    for j in Iy:
        u_1[i,j] = I(x[i], y[j])

if user_action is not None:
    user_action(u_1, x, xv, y, yv, t, 0)
```

Arguments xv and yv: for vectorized computations

```python
def advance_scalar(u, u_1, u_2, f, x, y, t, n, Cx2, Cy2, dt2,
                   V=None, step1=False):
    Ix = range(0, u.shape[0]);  Iy = range(0, u.shape[1])
    if step1:
        dt = sqrt(dt2)    # save
        Cx2 = 0.5*Cx2;  Cy2 = 0.5*Cy2; dt2 = 0.5*dt2   # redefine
        D1 = 1;  D2 = 0
    else:
        D1 = 2;  D2 = 1
    for i in Ix[1:-1]:
        for j in Iy[1:-1]:
            u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
            u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
            u[i,j] = D1*u_1[i,j] - D2*u_2[i,j] + \
                     Cx2*u_xx + Cy2*u_yy + dt2*f(x[i], y[j], t[n])
            if step1:
                u[i,j] += dt*V(x[i], y[j])
    # Boundary condition u=0
    j = Iy[0]
    for i in Ix: u[i,j] = 0
    j = Iy[-1]
    for i in Ix: u[i,j] = 0
    i = Ix[0]
    for j in Iy: u[i,j] = 0
    i = Ix[-1]
    for j in Iy: u[i,j] = 0
    return u
```

Mesh with 30×30 cells: vectorization reduces the CPU time by a factor of 70 (!).

Need special coordinate arrays xv and yv such that $I(x, y)$ and $f(x, y, t)$ can be vectorized:

```
from numpy import newaxis
xv = x[:,newaxis]
yv = y[newaxis,:]

u_1[:,:] = I(xv, yv)
f_a[:,:] = f(xv, yv, t)
```

```python
def advance_vectorized(u, u_1, u_2, f_a, Cx2, Cy2, dt2,
                       V=None, step1=False):
    if step1:
        dt = sqrt(dt2)    # save
        Cx2 = 0.5*Cx2;  Cy2 = 0.5*Cy2; dt2 = 0.5*dt2   # redefine
        D1 = 1;  D2 = 0
    else:
        D1 = 2;  D2 = 1
    u_xx = u_1[:-2,1:-1] - 2*u_1[1:-1,1:-1] + u_1[2:,1:-1]
    u_yy = u_1[1:-1,:-2] - 2*u_1[1:-1,1:-1] + u_1[1:-1,2:]
    u[1:-1,1:-1] = D1*u_1[1:-1,1:-1] - D2*u_2[1:-1,1:-1] + \
                   Cx2*u_xx + Cy2*u_yy + dt2*f_a[1:-1,1:-1]
    if step1:
        u[1:-1,1:-1] += dt*V[1:-1, 1:-1]
    # Boundary condition u=0
    j = 0
    u[:,j] = 0
    j = u.shape[1]-1
    u[:,j] = 0
    i = 0
    u[i,:] = 0
    i = u.shape[0]-1
    u[i,:] = 0
    return u

def quadratic(Nx, Ny, version):
    """Exact discrete solution of the scheme."""
```

Manufactured solution:

$$u_e(x, y, t) = x(L_x - x)y(L_y - y)(1 + \frac{1}{2}t) \qquad (59)$$

Requires $f = 2c^2(1 + \frac{1}{2}t)(y(L_y - y) + x(L_x - x))$.

This u_e is ideal because it also solves the discrete equations!

- $[D_t D_t 1]^n = 0$
- $[D_t D_t t]^n = 0$
- $[D_t D_t t^2] = 2$
- $D_t D_t$ is a linear operator:
  $[D_t D_t (au + bv)]^n = a[D_t D_t u]^n + b[D_t D_t v]^n$

$$[D_x D_x u_e]^n_{i,j} = [y(L_y - y)(1 + \frac{1}{2}t)D_x D_x x(L_x - x)]^n_{i,j}$$
$$= y_j(L_y - y_j)(1 + \frac{1}{2}t_n)2$$

- Similar calculations for $[D_y D_y u_e]^n_{i,j}$ and $[D_t D_t u_e]^n_{i,j}$ terms
- Must also check the equation for $u^1_{i,j}$

$$\frac{\partial^2 u}{\partial t^2} = c^2 \frac{\partial^2 u}{\partial x^2}$$

Solutions:

$$u(x, t) = g_R(x - ct) + g_L(x + ct)$$

If $u(x, 0) = I(x)$ and $u_t(x, 0) = 0$:

$$u(x, t) = \frac{1}{2} I(x - ct) + \frac{1}{2} I(x + ct)$$

Two waves: one traveling to the right and one to the left

A wave propagates perfectly ($C = 1$) and hits a medium with 1/4 of the wave velocity ($C = 0.25$). A part of the wave is reflected and the rest is transmitted.

Build $I(x)$ of wave components $e^{ikx} = \cos kx + i \sin kx$:

$$I(x) \approx \sum_{k \in K} b_k e^{ikx}$$

- Fit b_k by a least squares or projection method
- k is the frequency of a component ($\lambda = 2\pi/k$ is the wave length in space)
- K is some set of all k needed to approximate $I(x)$ well
- b_k must be computed (Fourier coefficients)

Since $u(x, t) = \frac{1}{2}I(x - ct) + \frac{1}{2}I(x + ct)$, the exact solution is

$$u(x, t) = \frac{1}{2} \sum_{k \in K} b_k e^{ik(x-ct)} + \frac{1}{2} \sum_{k \in K} b_k e^{ik(x+ct)}$$

Our interest: one component $e^{i(kx - \omega t)}$, $\omega = kc$

Idea: a similar discrete $u_q^n = e^{i(kx_q - \tilde{\omega}t_n)}$ solution (corresponding to the exact $e^{i(kx - \omega t)}$) solves

$$[D_t D_t u = c^2 D_x D_x u]_q^n$$

Note: we expect numerical frequency $\tilde{\omega} \neq \omega$

- How accurate is $\tilde{\omega}$ compared to ω?
- What about the wave amplitude (can $\tilde{\omega}$ become complex)?

$$[D_t D_t e^{i\omega t}]^n = -\frac{4}{\Delta t^2} \sin^2\left(\frac{\omega \Delta t}{2}\right) e^{i\omega n \Delta t}$$

By $\omega \to k$, $t \to x$, $n \to q$) it follows that

$$[D_x D_x e^{ikx}]_q = -\frac{4}{\Delta x^2} \sin^2\left(\frac{k\Delta x}{2}\right) e^{ikq\Delta x}$$

Inserting a basic wave component $u = e^{i(kx_q - \tilde{\omega}t_n)}$ in the scheme requires computation of

$$[D_t D_t e^{ikx} e^{-i\tilde{\omega}t}]_q^n = [D_t D_t e^{-i\tilde{\omega}t}]^n e^{ikq\Delta x}$$

$$= -\frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) e^{-i\tilde{\omega}n\Delta t} e^{ikq\Delta x}$$

$$[D_x D_x e^{ikx} e^{-i\tilde{\omega}t}]_q^n = [D_x D_x e^{ikx}]_q e^{-i\tilde{\omega}n\Delta t}$$

$$= -\frac{4}{\Delta x^2} \sin^2\left(\frac{k\Delta x}{2}\right) e^{ikq\Delta x} e^{-i\tilde{\omega}n\Delta t}$$

The complete scheme,

$$[D_t D_t e^{ikx} e^{-i\tilde{\omega}t} = c^2 D_x D_x e^{ikx} e^{-i\tilde{\omega}t}]_q^n$$

leads to an equation for $\tilde{\omega}$ (which can readily be solved):

$$\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = C^2 \sin^2\left(\frac{k\Delta x}{2}\right), \quad C = \frac{c\Delta t}{\Delta x} \text{ (Courant number)}$$

Taking the square root:

$$\sin\left(\frac{\tilde{\omega}\Delta t}{2}\right) = C \sin\left(\frac{k\Delta x}{2}\right)$$

Can easily solve for an explicit formula for $\tilde{\omega}$:

$$\tilde{\omega} = \frac{2}{\Delta t} \sin^{-1} \left(C \sin \left(\frac{k \Delta x}{2} \right) \right)$$

Note:

- This $\tilde{\omega} = \tilde{\omega}(k, c, \Delta x, \Delta t)$ is the *numerical dispersion relation*
- Inserting $e^{kx - \omega t}$ in the PDE leads to $\omega = kc$, which is the *analytical/exact dispersion relation*
- Speed of waves might be easier to imagine:
  - Exact speed: $c = \omega/k$,
  - Numerical speed: $\tilde{c} = \tilde{\omega}/k$
- We shall investigate $\tilde{c}/c$ to see how wrong the speed of a numerical wave component is

- For $C = 1$, $\tilde{\omega} = \omega$
- The numerical solution is exact (at the mesh points), regardless of Δx and $\Delta t = c^{-1}\Delta x$!
- The only requirement is constant c
- The numerical scheme is then a simple-to-use analytical solution method for the wave equation

- Introduce $p = k\Delta x/2$
  (the important *dimensionless* spatial discretization parameter)
- p measures no of mesh points in space per wave length in space
- Shortest possible wave length in mesh: $\lambda = 2\Delta x$,
  $k = 2\pi/\lambda = \pi/\Delta x$, and $p = k\Delta x/2 = \pi/2 \Rightarrow p \in (0, \pi/2]$
- Study error in wave velocity through $\tilde{c}/c$ as function of p

$$r(C, p) = \frac{\tilde{c}}{c} = \frac{2}{kc\Delta t} \sin^{-1}(C \sin p) = \frac{2}{kC\Delta x} \sin^{-1}(C \sin p) = \frac{1}{Cp} \sin^{-1}(C$$

Can plot $r(C, p)$ for $p \in (0, \pi/2]$, $C \in (0, 1]$

```
def r(C, p):
    return 1/(C*p)*asin(C*sin(p))
```


Note: the shortest waves have the largest error, and short waves

For small p, Taylor expand $\tilde{\omega}$ as polynomial in p:

```
>>> C, p = symbols('C p')
>>> rs = r(C, p).series(p, 0, 7)
>>> print rs
1 - p**2/6 + p**4/120 - p**6/5040 + C**2*p**2/6 -
C**2*p**4/12 + 13*C**2*p**6/720 + 3*C**4*p**4/40 -
C**4*p**6/16 + 5*C**6*p**6/112 + O(p**7)

>>> # Drop the remainder O(...) term
>>> rs = rs.removeO()
>>> # Factorize each term
>>> rs = [factor(term) for term in rs.as_ordered_terms()]
>>> rs = sum(rs)
>>> print rs
p**6*(C - 1)*(C + 1)*(225*C**4 - 90*C**2 + 1)/5040 +
p**4*(C - 1)*(C + 1)*(3*C - 1)*(3*C + 1)/120 +
p**2*(C - 1)*(C + 1)/6 + 1
```

Leading error term is $\frac{1}{6}(C^2 - 1)p^2$ or

$$\frac{1}{6}\left(\frac{k\Delta x}{2}\right)^2 (C^2 - 1) = \frac{k^2}{24}\left(c^2 \Delta t^2 - \Delta x^2\right) = \mathcal{O}(\Delta t^2, \Delta x^2)$$

Smooth wave, few short waves (large k) in $I(x)$:

Not so smooth wave, significant short waves (large k) in $I(x)$:

$$\sin\left(\frac{\tilde{\omega}\Delta t}{2}\right) = C \sin\left(\frac{k\Delta x}{2}\right)$$

- Exact ω is real
- Complex $\tilde{\omega}$ will lead to exponential growth of the amplitude
- Stability criterion: real $\tilde{\omega}$
- Then $\sin(\tilde{\omega}\Delta t/2) \in [-1, 1]$
- $k\Delta x/2$ is always real, so right-hand side is in $[-C, C]$
- Then we must have $C \leq 1$

Stability criterion:

$$C = \frac{c\Delta t}{\Delta x} \leq 1$$

Recall that right-hand side is in $[-C, C]$. Then $C > 1$ means

$$\underbrace{\sin\left(\frac{\tilde{\omega}\Delta t}{2}\right)}_{>1} = C \sin\left(\frac{k\Delta x}{2}\right)$$

- $|\sin x| > 1$ implies complex x
- Here: complex $\tilde{\omega} = \tilde{\omega}_r \pm i\tilde{\omega}_i$
- One $\tilde{\omega}_i < 0$ gives $\exp(i \cdot i\tilde{\omega}_i) = \exp(-\tilde{\omega}_i)$ and *exponential growth*
- This wave component will after some time dominate the solution give an overall exponentially increasing amplitude (non-physical!)

$$u(x, y, t) = g(k_x x + k_y y - \omega t)$$

is a typically solution of

$$u_{tt} = c^2 (u_{xx} + u_{yy})$$

Can build solutions by adding complex Fourier components of the form

$$e^{i(k_x x + k_y y - \omega t)}$$

$$[D_t D_t u = c^2 (D_x D_x u + D_y D_y u)]_{q,r}^n$$

This equation admits a Fourier component

$$u_{q,r}^n = e^{i(k_x q \Delta x + k_y r \Delta y - \tilde{\omega} n \Delta t)}$$

Inserting the expression and using formulas from the 1D analysis:

$$\sin^2 \left(\frac{\tilde{\omega} \Delta t}{2} \right) = C_x^2 \sin^2 p_x + C_y^2 \sin^2 p_y$$

where

$$C_x = \frac{c^2 \Delta t^2}{\Delta x^2}, \quad C_y = \frac{c^2 \Delta t^2}{\Delta y^2}, \quad p_x = \frac{k_x \Delta x}{2}, \quad p_y = \frac{k_y \Delta y}{2}$$

Rreal-valued $\tilde{\omega}$ requires

$$C_x^2 + C_y^2 \leq 1$$

or

$$\Delta t \leq \frac{1}{c} \left(\frac{1}{\Delta x^2} + \frac{1}{\Delta y^2} \right)^{-1/2}$$

$$\Delta t \leq \frac{1}{c} \left(\frac{1}{\Delta x^2} + \frac{1}{\Delta y^2} + \frac{1}{\Delta z^2} \right)^{-1/2}$$

For $c^2 = c^2(\boldsymbol{x})$ we must use the worst-case value $\bar{c} = \sqrt{\max_{\boldsymbol{x} \in \Omega} c^2(\boldsymbol{x})}$ and a safety factor $\beta \leq 1$:

$$\Delta t \leq \beta \frac{1}{\bar{c}} \left(\frac{1}{\Delta x^2} + \frac{1}{\Delta y^2} + \frac{1}{\Delta z^2} \right)^{-1/2}$$

$$\tilde{\omega} = \frac{2}{\Delta t} \sin^{-1}\left(\left(C_x^2 \sin^2 p_x + C_y^2 \sin_y^p \right)^{\frac{1}{2}} \right)$$

For visualization, introduce θ:

$$k_x = k\sin\theta, \quad k_y = k\cos\theta, \quad p_x = \frac{1}{2}kh\cos\theta, \quad p_y = \frac{1}{2}kh\sin\theta$$

Also: $\Delta x = \Delta y = h$. Then $C_x = C_y = c\Delta t/h \equiv C$.

Now $\tilde{\omega}$ depends on

- C reflecting the number cells a wave is displaced during a time step
- kh reflecting the number of cells per wave length in space
- θ expressing the direction of the wave

$$\frac{\tilde{c}}{c} = \frac{1}{Ckh} \sin^{-1}\left(C \left(\sin^2(\frac{1}{2}kh\cos\theta) + \sin^2(\frac{1}{2}kh\sin\theta) \right)^{\frac{1}{2}} \right)$$

Can make color contour plots of $1 - \tilde{c}/c$ in *polar coordinates* with θ as the angular coordinate and kh as the radial coordinate.