Finite difference methods for wave motion

Hans Petter Langtangen[1,2]

[1]Center for Biomedical Computing, Simula Research Laboratory
[2]Department of Informatics, University of Oslo

Aug 28, 2014

This is still a **preliminary version**.

Contents

A very wide range of physical processes lead to wave motion, where signals are propagated through a medium in space and time, normally with little or no permanent movement of the medium itself. The shape of the signals may undergo changes as they travel through matter, but usually not so much that the signals cannot be recognized at some later point in space and time. Many types of wave motion can be described by the equation $u_{tt} = \nabla \cdot (c^2 \nabla u) + f$, which we will solve in the forthcoming text by finite difference methods.

Simulation of waves on a string

We begin our study of wave equations by simulating one-dimensional waves on a string, say on a guitar or violin string. Let the string in the deformed state coincide with the interval $[0, L]$ on the x axis, and let $u(x, t)$ be the displacement

---

at time t in the y direction of a point initially at x. The displacement u is governed by the mathematical model

$$\frac{\partial^2 u}{\partial t^2} = c^2 \frac{\partial^2 u}{\partial x^2}, \qquad x \in (0, L), \ t \in (0, T]$$
$$u(x, 0) = I(x), \qquad x \in [0, L]$$
$$\frac{\partial}{\partial t} u(x, 0) = 0, \qquad x \in [0, L]$$
$$u(0, t) = 0, \qquad t \in (0, T]$$
$$u(L, t) = 0, \qquad t \in (0, T]$$

The constant c and the function $I(x)$ must be prescribed.

Equation (1) is known as the one-dimensional *wave equation*. Since the contains a second-order derivative in time, we need *two initial conditio* (2) specifying the initial shape of the string, $I(x)$, and (3) reflecting the initial velocity of the string is zero. In addition, PDEs need *boundary con* here (4) and (5), specifying that the string is fixed at the ends, i.e., the displacement u is zero.

The solution $u(x, t)$ varies in space and time and describes waves to moving with velocity c to the left and right.

Sometimes we will use a more compact notation for the partial deriva save space:

$$u_t = \frac{\partial u}{\partial t}, \quad u_{tt} = \frac{\partial^2 u}{\partial t^2},$$

and similar expressions for derivatives with respect to other variables. The wave equation can be written compactly as $u_{tt} = c^2 u_{xx}$.

The PDE problem (1)-(5) will now be discretized in space and time finite difference method.

1.1 Discretizing the domain

The temporal domain $[0, T]$ is represented by a finite number of mesh p

$$0 = t_0 < t_1 < t_2 < \cdots < t_{N_t - 1} < t_{N_t} = T.$$

Similarly, the spatial domain $[0, L]$ is replaced by a set of mesh points

$$0 = x_0 < x_1 < x_2 < \cdots < x_{N_x - 1} < x_{N_x} = L.$$

One may view the mesh as two-dimensional in the x, t plane, consisting of (x_i, t_n), with $i = 0, \ldots, N_x$ and $n = 0, \ldots, N_t$.

Uniform meshes. For uniformly distributed mesh points we can introduce the constant mesh spacings Δt and Δx. We have that

$$x_i = i\Delta x, \ i = 0, \ldots, N_x, \quad t_i = n\Delta t, \ n = 0, \ldots, N_t. \qquad (9)$$

We also have that $\Delta x = x_i - x_{i-1}$, $i = 1, \ldots, N_x$, and $\Delta t = t_n - t_{n-1}$, $n = 1, \ldots, N_t$. Figure 1 displays a mesh in the x, t plane with $N_t = 5$, $N_x = 5$, and constant mesh spacings.

1.2 The discrete solution

The solution $u(x, t)$ is sought at the mesh points. We introduce the mesh function u_i^n, which approximates the exact solution at the mesh point (x_i, t_n) for $i = 0, \ldots, N_x$ and $n = 0, \ldots, N_t$. Using the finite difference method, we shall develop algebraic equations for computing the mesh function. The circles in Figure 1 illustrate neighboring mesh points where values of u_i^n are connected through an algebraic equation. In this particular case, u_2^1, u_1^2, u_2^2, u_3^2, and u_2^3 are connected in an algebraic equation associated with the center point $(2, 2)$. The term *stencil* is often used about the algebraic equation at a mesh point, and the geometry of a typical stencil is illustrated in Figure 1. One also often refers to the algebraic equations as *discrete equations*, *(finite) difference equations* or a *finite difference scheme*.

Figure 1: Mesh in space and time for a 1D wave equation.

1.3 Fulfilling the equation at the mesh points

For a numerical solution by the finite difference method, we relax the co[...] that (1) holds at all points in the space-time domain $(0, L) \times (0, T]$[...] requirement that the PDE is fulfilled at the *interior* mesh points:

$$\frac{\partial^2}{\partial t^2} u(x_i, t_n) = c^2 \frac{\partial^2}{\partial x^2} u(x_i, t_n),$$

for $i = 1, \ldots, N_x - 1$ and $n = 1, \ldots, N_t - 1$. For $n = 0$ we have the[...] conditions $u = I(x)$ and $u_t = 0$, and at the boundaries $i = 0, N_x$ we h[...] boundary condition $u = 0$.

1.4 Replacing derivatives by finite differences

The second-order derivatives can be replaced by central differences. T[...] widely used difference approximation of the second-order derivative is

$$\frac{\partial^2}{\partial t^2} u(x_i, t_n) \approx \frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2}.$$

It is convenient to introduce the finite difference operator notation

$$[D_t D_t u]_i^n = \frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2}.$$

A similar approximation of the second-order derivative in the x directio[...]

$$\frac{\partial^2}{\partial x^2} u(x_i, t_n) \approx \frac{u_{i+1}^n - 2u_i^n + u_{i-1}^n}{\Delta x^2} = [D_x D_x u]_i^n.$$

Algebraic version of the PDE. We can now replace the derivative[...] and get

$$\frac{u_i^{n+1} - 2u_i^n + u_i^{n-1}}{\Delta t^2} = c^2 \frac{u_{i+1}^n - 2u_i^n + u_{i-1}^n}{\Delta x^2},$$

or written more compactly using the operator notation:

$$[D_t D_t u = c^2 D_x D_x]_i^n.$$

Algebraic version of the initial conditions. We also need to rep[...] derivative in the initial condition (3) by a finite difference approxima[...] centered difference of the type

$$\frac{\partial}{\partial t} u(x_i, t_n) \approx \frac{u_i^1 - u_i^{-1}}{2\Delta t} = [D_{2t} u]_i^0,$$

seems appropriate. In operator notation the initial condition is written

$$[D_{2t} u]_i^n = 0, \quad n = 0.$$

Writing out this equation and ordering the terms give

$$u_i^{n-1} = u_i^{n+1}, \quad i = 0, \ldots, N_x, \; n = 0 \,. \tag{13}$$

The other initial condition can be computed by

$$u_i^0 = I(x_i), \quad i = 0, \ldots, N_x \,.$$

.5 Formulating a recursive algorithm

We assume that u_i^n and u_i^{n-1} are already computed for $i = 0, \ldots, N_x$. The only unknown quantity in (11) is therefore u_i^{n+1}, which we can solve for:

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n \right), \tag{14}$$

where we have introduced the parameter

$$C = c\frac{\Delta t}{\Delta x}, \tag{15}$$

known as the *Courant number*.

C is the key parameter in the discrete diffusion equation.

We see that the discrete version of the PDE features only one parameter, C, which is therefore the key parameter that governs the quality of the numerical solution (see Section 10 for details). Both the primary physical parameter c and the numerical parameters Δx and Δt are lumped together in C. Note that C is a dimensionless parameter.

Given that u_i^{n-1} and u_i^n are computed for $i = 0, \ldots, N_x$, we find new values at the next time level by applying the formula (14) for $i = 1, \ldots, N_x - 1$. Figure 1 illustrates the points that are used to compute u_2^3. For the boundary points, $i = 0$ and $i = N_x$, we apply the boundary conditions $u_i^{n+1} = 0$.

A problem with (14) arises when $n = 0$ since the formula for u_i^1 involves u_i^{-1}, which is an undefined quantity outside the time mesh (and the time domain). However, we can use the initial condition (13) in combination with (14) when $n = 0$ to arrive at a special formula for u_i^1:

$$u_i^1 = u_i^0 - \frac{1}{2}C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n \right) \,. \tag{16}$$

Figure 2 illustrates how (16) connects four instead of five points: u_2^1, u_1^0, u_2^0, and u_3^0.

We can now summarize the computational algorithm:

1. Compute $u_i^0 = I(x_i)$ for $i = 0, \ldots, N_x$

Figure 2: Modified stencil for the first time step.

2. Compute u_i^1 by (16) and set $u_i^1 = 0$ for the boundary points $i =$ $i = N_x$, for $n = 1, 2, \ldots, N - 1$,

3. For each time level $n = 1, 2, \ldots, N_t - 1$

   (a) apply (14) to find u_i^{n+1} for $i = 1, \ldots, N_x - 1$

   (b) set $u_i^{n+1} = 0$ for the boundary points $i = 0$, $i = N_x$.

The algorithm essentially consists of moving a finite difference stencil all the mesh points, which is illustrated by an animation in a web pa movie file[2].

1.6 Sketch of an implementation

In a Python implementation of this algorithm, we use the array elemen to store u_i^{n+1}, `u_1[i]` to store u_i^n, and `u_2[i]` to store u_i^{n-1}. Our convention is use `u` for the unknown new spatial field to be computed the solution at one time step back in time, `u_2` as the solution two tim back in time and so forth.

The algorithm only needs to access the three most recent time level need only three arrays for u_i^{n+1}, u_i^n, and u_i^{n-1}, $i = 0, \ldots, N_x$. Storing solutions in a two-dimensional array of size $(N_x + 1) \times (N_t + 1)$ would be

---

[1]`http://tinyurl.com/k3sdbuv/pub/mov-wave/wave1D_PDE_Dirichlet_stencil_g`
[2]`http://tinyurl.com/k3sdbuv/pub/mov-wave/wave1D_PDE_Dirichlet_stencil_g`

in this simple one-dimensional PDE problem, but is normally out of the question in three-dimensional (3D) and large two-dimensional (2D) problems. We shall therefore in all our programs for solving PDEs have the unknown in memory at as few time levels as possible.

The following Python snippet realizes the steps in the computational algorithm.

```
# Given mesh points as arrays x and t (x[i], t[n])
dx = x[1] - x[0]
dt = t[1] - t[0]
C = c*dt/dx              # Courant number
Nt = len(t)-1
C2 = C**2                # Help variable in the scheme

# Set initial condition u(x,0) = I(x)
for i in range(0, Nx+1):
    u_1[i] = I(x[i])

# Apply special formula for first step, incorporating du/dt=0
for i in range(1, Nx):
    u[i] = u_1[i] - 0.5*C**2(u_1[i+1] - 2*u_1[i] + u_1[i-1])
u[0] = 0;  u[Nx] = 0   # Enforce boundary conditions

# Switch variables before next step
u_2[:], u_1[:] = u_1, u

for n in range(1, Nt):
    # Update all inner mesh points at time t[n+1]
    for i in range(1, Nx):
        u[i] = 2u_1[i] - u_2[i] - \
                C**2(u_1[i+1] - 2*u_1[i] + u_1[i-1])

    # Insert boundary conditions
    u[0] = 0;  u[Nx] = 0

    # Switch variables before next step
    u_2[:], u_1[:] = u_1, u
```

Verification

Before implementing the algorithm, it is convenient to add a source term to the PDE (1) since it gives us more freedom in finding test problems for verification. In particular, the source term allows us to use *manufactured solutions* for software testing, where we simply choose some function as solution, fit the corresponding source term, and define boundary and initial conditions consistent with the chosen solution. Such solutions will seldom fulfill the initial condition (3) so we need to generalize this condition to $u_t = V(x)$.

.1 A slightly generalized model problem

We now address the following extended initial-boundary value problem for one-dimensional wave phenomena:

$$u_{tt} = c^2 u_{xx} + f(x,t), \qquad x \in (0,L),\ t \in (0,T]$$
$$u(x,0) = I(x), \qquad x \in [0,L]$$
$$u_t(x,0) = V(x), \qquad x \in [0,L]$$
$$u(0,t) = 0, \qquad t > 0$$
$$u(L,t) = 0, \qquad t > 0$$

Sampling the PDE at (x_i, t_n) and using the same finite difference approximations as above, yields

$$[D_t D_t u = c^2 D_x D_x + f]_i^n .$$

Writing this out and solving for the unknown u_i^{n+1} results in

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2(u_{i+1}^n - 2u_i^n + u_{i-1}^n) + \Delta t^2 f_i^n .$$

The equation for the first time step must be rederived. The discretiz the initial condition $u_t = V(x)$ at $t = 0$ becomes

$$[D_{2t} u = V]_i^0 \quad \Rightarrow \quad u_i^{-1} = u_i^1 - 2\Delta t V_i,$$

which, when inserted in (23) for $n = 0$, gives the special formula

$$u_i^1 = u_i^0 - \Delta t V_i + \frac{1}{2} C^2 \left(u_{i+1}^n - 2u_i^n + u_{i-1}^n \right) + \frac{1}{2}\Delta t^2 f_i^n .$$

2.2 Using an analytical solution of physical significa

Many wave problems feature sinusoidal oscillations in time and spa example, the original PDE problem (1)-(5) allows a solution

$$u_e(x, y, t)) = A \sin\left(\frac{\pi}{L} x\right) \cos\left(\frac{\pi}{L} ct\right) .$$

This u_e fulfills the PDE with $f = 0$, boundary conditions $u_e(0,t) = u_e(L$ as well as initial conditions $I(x) = A \sin\left(\frac{\pi}{L} x\right)$ and $V = 0$.

It is common to use such exact solutions of physical interest to verif mentations. However, the numerical solution u_i^n will only be an approx to $u_e(x_i, t_n)$. We no have knowledge of the precise size of the error in this imation, and therefore we can never know if discrepancies between the co u_i^n and $u_e(x_i, t_n)$ are caused by mathematical approximations or progra errors. In particular, if a plot of the computed solution u_i^n and the ex (25) looks similar, many are attempted to claim that the implementatio but there can still be serious programming errors although color plots lo

The only way to use exact physical solutions like (25) for serious and th verification is to run a series of finer and finer meshes, measure the int error in each mesh, and from this information estimate the convergence these rates are very close to 2, we have strong evidence that the impleme works.

.3 Manufactured solution

ne problem with the exact solution (25) is that it requires a simplification
$\gamma = 0, f = 0$) of the implemented problem (17)-(21). An advantage of using
manufactured solution is that we can test all terms in the PDE problem.
he idea of this approach is to set up some chosen solution and fit the source
erm, boundary conditions, and initial conditions to be compatible with the
hosen solution. Given that our boundary conditions in the implementation are
$(0, t) = u(L, t) = 0$, we must choose a solution that fulfills these conditions.
ne example is

$$u_e(x, t) = x(L - x) \sin t.$$

serted in the PDE $u_{tt} = c^2 u_{xx} + f$ we get

$$-x(L - x) \sin t = -2 \sin t + f \quad \Rightarrow f = (2 - x(L - x)) \sin t.$$

he initial conditions become

$$u(x, 0) = I(x) = 0,$$
$$u_t(x, 0) = V(x) = (2 - x(L - x)) \cos t.$$

To verify the code, we run a series of refined meshes and compute the
onvergence rates. In more detail, we keep $\Delta t / \Delta x$ constant for each mesh,
mplying that C is also constant throughout the experiments. A common
iscretization parameter $h = \Delta t$ is introduced. For a given C (and c), $\Delta x ch/C$.
Ve choose an initial time cell size h_0 and run experiments with decreasing h:
$_i = 2^{-i} h_0$, $i = 1, 2, \ldots, m$. Halving the cell size in each experiment is not
ecessary, but common. For each experiment we must record a scalar measure
f the error. As will be shown later, it is expected that such error measures are
roportional to h^2. A standard choice of error measure is the ℓ^2 or ℓ^∞ norm of
he error mesh function e_i^n:

$$||e_i^n||_{\ell^2} = \left(\Delta t \Delta x \sum_{n=0}^{N_t} \sum_{i=0}^{N_x} (e_i^n)^2 \right)^{\frac{1}{2}}, \quad e_i^n = u_e(x_i, t_n) - u_i^n, \tag{26}$$

$$||e_i^n||_{\ell^\infty} = \max_{i,n} |e_n^i|. \tag{27}$$

n Python, one can compute $\sum_i (e_i^{n+1})^2$ at each time step and accumulate the
alue in some sum variable, say `e2_sum`. At the final time step one can do
`qrt(dt*dx*e2_sum)`. For the ℓ^∞ norm one must compare the maximum error
t a time level (`e.max()`) with the global maximum over the time domain:
`_max = max(e_max, e.max())`.
An alternative error measure is to use a spatial norm at one time step only,
g., the end time T:

$$||e_i^n||_{\ell^2} = \left(\Delta x \sum_{i=0}^{N_x} (e_i^n)^2 \right)^{\frac{1}{2}}, \quad e_i^n = u_e(x_i, t_n) - u_i^n,$$
$$||e_i^n||_{\ell^\infty} = \max_{0 \le i \le N_x} |e_n^i|.$$

Let E_i be the error measure in experiment (mesh) number i and let h
corresponding discretization parameter (h). We expect an error model E_i
here with $r = 0$. To estimate r, we can compare two consecutive expe
and compute

$$r_i = \frac{\ln E_{i+1}/E_i}{\ln h_{i+1}/h_i}, \quad i = 0, \ldots, m - 1.$$

We should observe that r_i approaches 2 as i increases.
The next section describes a method of manufactured solutions wher
need to compute error measures and check that they converge as expe
the mesh is refined.

2.4 Constructing an exact solution of the discrete tions

For verification purposes we shall use a solution that is quadratic in sp
linear in time. More specifically, our choice of the manufactured solutic

$$u_e(x, t) = x(L - x)(1 + \frac{1}{2}t),$$

which by insertion in the PDE leads to $f(x, t) = 2(1 + t)c^2$. This u_e
the boundary conditions and is compatible with $I(x) = x(L - x)$ and
$\frac{1}{2}x(L - x)$.
A key feature of the chosen u_e is that it is also *an exact solutio*
discrete equations. To realize this very important result, we first estab
results

$$[D_t D_t t^2]^n = \frac{t_{n+1}^2 - 2t_n^2 + t_{n-1}^2}{\Delta t^2} = (n+1)^2 - n^2 + (n-1)^2 = 2,$$
$$[D_t D_t t]^n = \frac{t_{n+1} - 2t_n + t_{n-1}}{\Delta t^2} = \frac{((n+1) - n + (n-1))\Delta t}{\Delta t^2} = 0.$$

Hence,

$$[D_t D_t u_e]_i^n = x_i(L - x_i)[D_t D_t(1 + \frac{1}{2}t)]^n = x_i(L - x_i)\frac{1}{2}[D_t D_t t]^n =$$

and

$$[D_x D_x u_e]_i^n = (1 + \frac{1}{2}t_n)[D_x D_x(xL - x^2)]_i = (1 + \frac{1}{2}t_n)[LD_x D_x x - D_x]$$
$$= -2(1 + \frac{1}{2}t_n).$$

Now, $f_i^n = 2(1 + \frac{1}{2}t_n)c^2$ and we get

$$[D_t D_t u_{\mathrm{e}} - c^2 D_x D_x u_{\mathrm{e}} - f]_i^n = 0 - c^2(-1)2(1 + \frac{1}{2}t_n + 2(1 + \frac{1}{2}t_n)c^2 = 0\,.$$

Moreover, $u_{\mathrm{e}}(x_i, 0) = I(x_i)$, $\partial u_{\mathrm{e}}/\partial t = V(x_i)$ at $t = 0$, and $u_{\mathrm{e}}(x_0, t) =$ $_{\mathrm{e}}(x_{N_x}, 0) = 0$. Also the modified scheme for the first time step is fulfilled by $_{\mathrm{e}}(x_i, t_n)$.

Therefore, the exact solution $u_{\mathrm{e}}(x, t) = x(L - x)(1 + t/2)$ of the PDE problem also an exact solution of the discrete problem. We can use this result to check hat the computed u_i^n vales from an implementation equals $u_{\mathrm{e}}(x_i, t_n)$ within nachine precision, *regardless of the mesh spacings* Δx and Δt! Nevertheless, here might be stability restrictions on Δx and Δt, so the test can only be run or a mesh that is compatible with the stability criterion (which in the present ase is $C \leq 1$, to be derived later).

Notice.

A product of quadratic or linear expressions in the various independent variables, as shown above, will often fulfill both the continuous and discrete PDE problem and can therefore be very useful solutions for verifying implementations. However, for 1D wave equations of the type $u_t = c^2 u_{xx}$ we shall see that there is always another much more powerful way of generating exact solutions (just set $C = 1$).

Implementation

his section present the complete computational algorithm, its implementation in ython code, animation of the solution, and verification of the implementation.

A real implementation of the basic computational algorithm from Sections 1.5 nd 1.6 can be encapsulated in a function, taking all the input data for the roblem as arguments. The physical input data consists of c, $I(x)$, $V(x)$, $f(x,t)$, , and T. The numerical input is the mesh parameters Δt and Δx.

Instead of specifying Δt *and* Δx, we can specify one of them and the Courant umber C instead, since having explicit control of the Courant number is onvenient when investigating the numerical method. Many find it natural to rescribe the resolution of the spatial grid and set N_x. The solver function an then compute $\Delta t = CL/(cN_x)$. However, for comparing $u(x,t)$ curves (as nctions of x) for various Courant numbers, especially in animations in time, is more convenient to keep Δt fixed for all C and let Δx vary according to $x = c\Delta t/C$. (With Δt fixed, all frames correspond to the same time t, and lotting curves with different spatial resolution is trivial.)

The solution at all spatial points at a new time level is stored in an array (of length $N_x + 1$). We need to decide what do to with this solution, e.g.,

visualize the curve, analyze the values, or write the array to file for l The decision what to do is left to the user in a suppled function

```
def user_action(u, x, t, n):
```

where `u` is the solution at the spatial points `x` at time `t[n]`.

3.1 Making a solver function

A first attempt at a solver function is listed below.

```
from numpy import *

def solver(I, V, f, c, L, dt, C, T, user_action=None):
    """Solve u_tt=c^2*u_xx + f on (0,L)x(0,T)."""
    Nt = int(round(T/dt))
    t = linspace(0, Nt*dt, Nt+1)    # Mesh points in time
    dx = dt*c/float(C)
    Nx = int(round(L/dx))
    x = linspace(0, L, Nx+1)        # Mesh points in space
    C2 = C**2                       # Help variable in the scheme
    if f is None or f == 0 :
        f = lambda x, t: 0
    if V is None or V == 0:
        V = lambda x: 0

    u   = zeros(Nx+1)   # Solution array at new time level
    u_1 = zeros(Nx+1)   # Solution at 1 time level back
    u_2 = zeros(Nx+1)   # Solution at 2 time levels back

    import time;  t0 = time.clock()  # for measuring CPU time

    # Load initial condition into u_1
    for i in range(0,Nx+1):
        u_1[i] = I(x[i])

    if user_action is not None:
        user_action(u_1, x, t, 0)

    # Special formula for first time step
    n = 0
    for i in range(1, Nx):
        u[i] = u_1[i] + dt*V(x[i]) + \
               0.5*C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1]) + \
               0.5*dt**2*f(x[i], t[n])
    u[0] = 0;   u[Nx] = 0

    if user_action is not None:
        user_action(u, x, t, 1)

    # Switch variables before next step
    u_2[:], u_1[:] = u_1, u

    for n in range(1, Nt):
        # Update all inner points at time t[n+1]
        for i in range(1, Nx):
            u[i] = - u_2[i] + 2*u_1[i] + \
                   C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1]) + \
```

```
                    dt**2*f(x[i], t[n])

        # Insert boundary conditions
        u[0] = 0;  u[Nx] = 0
        if user_action is not None:
            if user_action(u, x, t, n+1):
                break

        # Switch variables before next step
        u_2[:], u_1[:] = u_1, u

    cpu_time = t0 - time.clock()
    return u, x, t, cpu_time
```

.2 Verification: exact quadratic solution

We use the test problem derived in Section 2.1 for verification. Here is a function realizing this verification as a nose test:

```
import nose.tools as nt

def test_quadratic():
    """Check that u(x,t)=x(L-x)(1+t/2) is exactly reproduced."""
    def u_exact(x, t):
        return x*(L-x)*(1 + 0.5*t)

    def I(x):
        return u_exact(x, 0)

    def V(x):
        return 0.5*u_exact(x, 0)

    def f(x, t):
        return 2*(1 + 0.5*t)*c**2

    L = 2.5
    c = 1.5
    C = 0.75
    Nx = 3  # Very coarse mesh for this exact test
    dt = C*(L/Nx)/c
    T = 18

    u, x, t, cpu = solver(I, V, f, c, L, dt, C, T)
    u_e = u_exact(x, t[-1])
    diff = abs(u - u_e).max()
    nt.assert_almost_equal(diff, 0, places=14)
```

.3 Visualization: animating the solution

Now that we have verified the implementation it is time to do a real computation where we also display the evolution of the waves on the screen.

Visualization via SciTools. The following viz function defines a user_action callback function for plotting the solution at each time level:

```
def viz(I, V, f, c, L, dt, C, T, umin, umax, animate=True):
    """Run solver and visualize u at each time level."""
    import scitools.std as plt
    import time, glob, os

    def plot_u(u, x, t, n):
        """user_action function for solver."""
        plt.plot(x, u, 'r-',
                 xlabel='x', ylabel='u',
                 axis=[0, L, umin, umax],
                 title='t=%f' % t[n], show=True)
        # Let the initial condition stay on the screen for 2
        # seconds, else insert a pause of 0.2 s between each plot
        time.sleep(2) if t[n] == 0 else time.sleep(0.2)
        plt.savefig('frame_%04d.png' % n)  # for movie making

    # Clean up old movie frames
    for filename in glob.glob('frame_*.png'):
        os.remove(filename)

    user_action = plot_u if animate else None
    u, x, t, cpu = solver(I, V, f, c, L, dt, C, T, user_action)

    # Make movie files
    fps = 4  # Frames per second
    plt.movie('frame_*.png', encoder='html', fps=fps,
              output_file='movie.html')
    codec2ext = dict(flv='flv', libx264='mp4', libvpx='webm',
                     libtheora='ogg')
    filespec = 'frame_%04d.png'
    movie_program = 'avconv'  # or 'ffmpeg'
    for codec in codec2ext:
        ext = codec2ext[codec]
        cmd = '%(movie_program)s -r %(fps)d -i %(filespec)s '\
              '-vcodec %(codec)s movie.%(ext)s' % vars()
        os.system(cmd)
```

A function inside another function, like plot_u in the above code segm access to *and remembers* all the local variables in the surrounding cod the viz function (!). This is known in computer science as a *closure* very convenient to program with. For example, the plt and time n defined outside plot_u are accessible for plot_u when the function is ca user_action) in the solver function. Some may think, however, that instead of a closure is a cleaner and easier-to-understand implementatio user action function, see Section 8.

Making movie files. Several hardcopies of the animation are ma the frame_*.png files. We use the avconv (or ffmpeg) programs to c individual plot files to movies in modern formats: Flash, MP4, Wel Ogg. A typical avconv (or ffmpeg) command for creating a movie file format with 4 frames per second built from a collection of plot files with generated by frame_%04d.png, look like

```
Terminal> avconv -r 4 -i frame_%04d.png -c:v libtheora movie.ogg
```

The different formats require different video encoders (`-c:v`) to be installed: Flash applies `flv`, WebM applies `libvpx`, and MP4 applies `libx264`:

```
Terminal> avconv -r 4 -i frame_%04d.png -c:v flv movie.flv
Terminal> avconv -r 4 -i frame_%04d.png -c:v libvpx movie.webm
Terminal> avconv -r 4 -i frame_%04d.png -c:v libx264 movie.mp4
```

Players like `vlc`, `mplayer`, `gxine`, and `totem` can be used to play these movie files.

Note that padding the frame counter with zeros in the `frame_*.png` files, as specified by the `%04d` format, is essential so that the wildcard notation `frame_*.png` expands to the correct set of files.

The `plt.movie` function also creates a `movie.html` file with a movie player for displaying the `frame_*.png` files in a web browser. This movie player can be generated from the command line too

```
Terminal> scitools movie encoder=html output_file=movie.html \
          fps=4 frame_*.png
```

Skipping frames for animation speed. Sometimes the time step is small and T is large, leading to an inconveniently large number of plot files and a slow animation on the screen. The solution to such a problem is to decide on a total number of frames in the animation, `num_frames`, and plot the solution only at every `every` frame. The total number of time levels (i.e., maximum possible number of frames) is the length of `t`, `t.size`, and if we want `num_frames`, we need to plot every `t.size/num_frames` frame:

```
every = int(t.size/float(num_frames))
if n % every == 0 or n == t.size-1:
    st.plot(x, u, 'r-', ...)
```

The initial condition (`n=0`) is natural to include, and as `n % every == 0` will very seldom be true for the very final frame, we also ensure that `n == t.size-1` and hence the final frame is included.

A simple choice of numbers may illustrate the formulas: say we have 801 frames in total (`t.size`) and we allow only 60 frames to be plotted. Then we need to plot every 801/60 frame, which with integer division yields 13 as `every`. Using the mod function, `n % every`, this operation is zero every time `n` can be divided by 13 without a remainder. That is, the `if` test is true when `n` equals $0, 13, 26, 39, ..., 780, 801$. The associated code is included in the `plot_u` function in the file `wave1D_u0v.py`[3].

_____
[3] `http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_u0v.py`

Visualization via Matplotlib. The previous code based on the `plot` in from `scitools.std` can be run with Matplotlib as the visualization b but if one desires to program directly with Matplotlib, quite different needed. Matplotlib's interactive mode must be turned on:

```
import matplotlib.pyplot as plt
plt.ion()  # interactive mode on
```

The most commonly used animation technique with Matplotlib is to up data in the plot at each time level:

```
# Make a first plot
lines = plt.plot(t, u)
# call plt.axis, plt.xlabel, plt.ylabel, etc. as desired

# At later time levels
lines[0].set_ydata(u)
plt.legend('t=%g' % t[n])
plt.draw()  # make updated plot
plt.savefig(...)
```

An alternative is to rebuild the plot at every time level:

```
plt.clf()         # delete any previous curve(s)
plt.axis([...])
plt.plot(t, u)
# plt.xlabel, plt.legend and other decorations
plt.draw()
plt.savefig(...)
```

Many prefer to work with figure and axis objects as in MATLAB:

```
fig = plt.figure()
...
fig.clf()
ax = fig.gca()
ax.axis(...)
ax.plot(t, u)
# ax.set_xlabel, ax.legend and other decorations
plt.draw()
fig.savefig(...)
```

hpl 1: hardcopies via scitools movie or mencoder directly
hpl 2: need implementations!

3.4 Running a case

The first demo of our 1D wave equation solver concerns vibrations of that is initially deformed to a triangular shape, like when picking a guita

$$I(x) = \begin{cases} ax/x_0, & x < x_0, \\ a(L-x)/(L-x_0), & \text{otherwise} \end{cases}$$

We choose $L = 75$ cm, $x_0 = 0.8L$, $a = 5$ mm, and a time frequency $\nu = 440$ Hz. The relation between the wave speed c and ν is $c = \nu\lambda$, where λ is the wavelength, taken as $2L$ because the longest wave on the string form half a wavelength. There is no external force, so $f = 0$, and the string is at rest initially so that $V = 0$.

Regarding numerical parameters, we need to specify a Δt. Sometimes it is more natural to think of a spatial resolution instead of a time step. A natural semi-coarse spatial resolution in the present problem is $N_x = 50$. We can then choose the associated Δt (as required by the `viz` and `solver` functions) as the stability limit: $\Delta t = L/(N_x c)$. This is the Δt to be specified, but notice that if $C < 1$, the actual Δx computed in `solver` gets larger than L/N_x: $\Delta x = c\Delta t/C = L/(N_x C)$. (The reason is that we fix Δt and adjust Δx, so if C gets smaller, the code implements this effect in terms of a larger Δx.)

A function for setting the physical and numerical parameters and calling `viz` in this application goes as follows:

```python
def guitar(C):
    """Triangular wave (pulled guitar string)."""
    L = 0.75
    x0 = 0.8*L
    a = 0.005
    freq = 440
    wavelength = 2*L
    c = freq*wavelength
    omega = 2*pi*freq
    num_periods = 1
    T = 2*pi/omega*num_periods
    # Choose dt the same as the stability limit for Nx=50
    dt = L/50./c

    def I(x):
        return a*x/x0 if x < x0 else a/(L-x0)*(L-x)

    umin = -1.2*a;  umax = -umin
    cpu = viz(I, 0, 0, c, L, dt, C, T, umin, umax, animate=True)
```

The associated program has the name `wave1D_u0.py`[4]. Run the program and watch the movie of the vibrating string[5].

hpl 3: Must recompute these movies as Δt is different when $C < 1$.

.5 The benefits of scaling

The previous example demonstrated that quite some work is needed with establishing relevant physical parameters for a case. By *scaling* the mathematical problem we can often reduce the need to estimate physical parameters dramatically. A scaling consists of introducing new independent and dependent variables, with the aim that the absolute value of these vary between 0 and 1:

$$\bar{x} = \frac{x}{L}, \quad \bar{t} = \frac{c}{L}t, \quad \bar{u} = \frac{u}{a}.$$

---

[4] `http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_u0.py`
[5] `http://tinyurl.com/k3sdbuv/pub/mov-wave/guitar_C0.8/index.html`

Replacing old by new variables in the PDE, using $f = 0$, and dropping results in the *scaled equation* $u_{tt} = u_{xx}$. This equation has no physical pa (!).

If we have a program implemented for the physical wave equati dimensions, we can obtain the dimensionless, scaled version by settin The initial condition corresponds to (185), but with setting $a = 1$, L $x_0 \in [0, 1]$. This means that we only need to decide on the x_0 value as a of unity, because the scaled problem corresponds to setting all other par to unity! In the code we can just set `a=c=L=1`, `x0=0.8`, and there is no calculate with wavelengths and frequencies to estimate c.

The only non-trivial parameter to estimate in the scaled problem is end time of the simulation, or more precisely, how it relates to periods in solutions in time, since we often want to express the end time as a number of periods. Suppose as u behaves as $\sin(\omega t)$ in time in variab dimension. The corresponding period is $P = 2\pi/\omega$. The frequency ω is re the wavelength λ of the waves through the relations $\omega = kc$ and $k = 2\pi/\lambda$ $\omega = 2\pi c/\lambda$ and $P = \lambda/c$. It remains to estimate λ. With $u(x,t) = F(x$ we find from $u_{tt} = c^2 u_{xx}$ that $c^2 F'' + \omega^2 F = 0$, and the boundary con demand $F(0) = F(L) = 0$. The solution is $F(x) = \sin(x\pi/L)$, wh wavelength $\lambda = 2\pi/(\pi/L) = 2L$. One period is therefore given by P The dimensionless period is $\bar{P} = Pc/L = 2$.

4 Vectorization

The computational algorithm for solving the wave equation visits or point at a time and evaluates a formula for the new value u_i^{n+1} at tha Technically, this is implemented by a loop over array elements in a p Such loops may run slowly in Python (and similar interpreted languages R and MATLAB). One technique for speeding up loops is to perform op on entire arrays instead of working with one element at a time. This is to as *vectorization*, *vector computing*, or *array computing*. Operations o arrays are possible if the computations involving each element is indeper each other and therefore can, at least in principle, be performed simulta Vectorization not only speeds up the code on serial computers, but it als it easy to exploit parallel computing.

4.1 Operations on slices of arrays

Efficient computing with `numpy` arrays demands that we avoid loops and with entire arrays at once (or at least large portions of them). Consi calculation of differences $d_i = u_{i+1} - u_i$:

```python
n = u.size
for i in range(0, n-1):
    d[i] = u[i+1] - u[i]
```

ll the differences here are independent of each other. The computation of `d` can
therefore alternatively be done by subtracting the array $(u_0, u_1, \ldots, u_{n-1})$ from
the array where the elements are shifted one index upwards: $(u_1, u_2, \ldots, u_n)$,
see Figure 3. The former subset of the array can be expressed by `u[0:n-1]`,
`[0:-1]`, or just `u[:-1]`, meaning from index 0 up to, but not including, the
last element (`-1`). The latter subset is obtained by `u[1:n]` or `u[1:]`, meaning
from index 1 and the rest of the array. The computation of `d` can now be done
without an explicit Python loop:

```
d = u[1:] - u[:-1]
```

or with explicit limits if desired:

```
d = u[1:n] - u[0:n-1]
```

Indices with a colon, going from an index to (but not including) another index
are called *slices*. With `numpy` arrays, the computations are still done by loops,
but in efficient, compiled, highly optimized code in C or Fortran. Such array
operations can also easily be distributed among many processors on parallel
computers. We say that the *scalar code* above, working on an element (a scalar)
at a time, has been replaced by an equivalent *vectorized code*. The process of
vectorizing code is called *vectorization*.

Figure 3: Illustration of subtracting two slices of two arrays.

Test the understanding.

Newcomers to vectorization are encouraged to choose a small array `u`, say
with five elements, and simulate with pen and paper both the loop version
and the vectorized version.

Finite difference schemes basically contains differences between array elements
with shifted indices. Consider the updating formula

```
for i in range(1, n-1):
    u2[i] = u[i-1] - 2*u[i] + u[i+1]
```

The vectorization consists of replacing the loop by arithmetics on slices of
of length `n-2`:

```
u2 = u[:-2] - 2*u[1:-1] + u[2:]
u2 = u[0:n-2] - 2*u[1:n-1] + u[2:n]    # alternative
```

Note that `u2` here gets length `n-2`. If `u2` is already an array of length n
want to use the formula to update all the "inner" elements of `u2`, as we w
solving a 1D wave equation, we can write

```
u2[1:-1]  = u[:-2] - 2*u[1:-1] + u[2:]
u2[1:n-1] = u[0:n-2] - 2*u[1:n-1] + u[2:n]    # alternative
```

Pen and paper calculations with a small array will demonstrate what is
going on. The expression on the right-hand side are done in the following
involving temporary arrays with intermediate results, since we can on
with two arrays at a time in arithmetic expressions:

```
temp1 = 2*u[1:-1]
temp2 = u[0:-2] - temp1
temp3 = temp2 + u[2:]
u2[1:-1] = temp3
```

We can extend the previous example to a formula with an addition
computed by calling a function:

```
def f(x):
    return x**2 + 1

for i in range(1, n-1):
    u2[i] = u[i-1] - 2*u[i] + u[i+1] + f(x[i])
```

Assuming `u2`, `u`, and `x` all have length `n`, the vectorized version become

```
u2[1:-1] = u[:-2] - 2*u[1:-1] + u[2:] + f(x[1:-1])
```

4.2   Finite difference schemes expressed as slices

We now have the necessary tools to vectorize the algorithm for the wave e
There are three loops: one for the initial condition, one for the first tin
and finally the loop that is repeated for all subsequent time levels. Sir
the latter is repeated a potentially large number of times, we limit the e
vectorizing the code to this loop:

```
for i in range(1, Nx):
    u[i] = 2*u_1[i] - u_2[i] + \
           C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1])
```

The vectorized version becomes

```
u[1:-1] = - u_2[1:-1] + 2*u_1[1:-1] + \
            C2*(u_1[:-2] - 2*u_1[1:-1] + u_1[2:])
```

or

```
u[1:Nx] = 2*u_1[1:Nx]- u_2[1:Nx] + \
            C2*(u_1[0:Nx-1] - 2*u_1[1:Nx] + u_1[2:Nx+1])
```

The program `wave1D_u0v.py`[6] contains a new version of the function `solver` where both the scalar and the vectorized loops are included (the argument version is set to `scalar` or `vectorized`, respectively).

.3   Verification

We may reuse the quadratic solution $u_e(x,t) = x(L-x)(1+\frac{1}{2}t)$ for verifying also the vectorized code. A nose test can now test both the scalar and the vectorized version. Moreover, we may use a `user_action` function that compares the computed and exact solution at each time level and performs a test:

```
def test_quadratic():
    """
    Check the scalar and vectorized versions work for
    a quadratic u(x,t)=x(L-x)(1+t/2) that is exactly reproduced.
    """
    # The following function must work for x as array or scalar
    u_exact = lambda x, t: x*(L - x)*(1 + 0.5*t)
    I = lambda x: u_exact(x, 0)
    V = lambda x: 0.5*u_exact(x, 0)
    # f is a scalar (zeros_like(x) works for scalar x too)
    f = lambda x, t: zeros_like(x) + 2*c**2*(1 + 0.5*t)

    L = 2.5
    c = 1.5
    C = 0.75
    Nx = 3  # Very coarse mesh for this exact test
    dt = C*(L/Nx)/c
    T = 18

    def assert_no_error(u, x, t, n):
        u_e = u_exact(x, t[n])
        diff = abs(u - u_e).max()
        nt.assert_almost_equal(diff, 0, places=13)

    solver(I, V, f, c, L, dt, C, T,
           user_action=assert_no_error, version='scalar')
    solver(I, V, f, c, L, dt, C, T,
           user_action=assert_no_error, version='vectorized')
```

---
[6]http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_u0v.py

> **Lambda functions.**
>
> The code segment above demonstrates how to achieve very compact with the use of lambda functions for the various input parameters require a Python function. In essence,
>
> ```
> f = lambda x, t: L*(x-t)**2
> ```
>
> is equivalent to
>
> ```
> def f(x, t):
>     return L(x-t)**2
> ```
>
> Note that lambda functions can just contain a single expression an statements.
>
> One advantage with lambda functions is that they can be used di in calls:
>
> ```
> solver(I=lambda x: sin(pi*x/L), V=0, f=0, ...)
> ```

4.4   Efficiency measurements

Running the `wave1D_u0v.py` code with the previous string vibration ple for $N_x = 50, 100, 200, 400, 800$, and measuring the CPU time (`run_efficiency_experiments` function), shows that the vectorized co substantially faster: the scalar code uses approximately a factor $N_{x/}$ time!

5   Exercises

Exercise 1: Simulate a standing wave

The purpose of this exercise is to simulate standing waves on $[0, L]$ and il the error in the simulation. Standing waves arise from an initial condit

$$u(x,0) = A\sin\left(\frac{\pi}{L}mx\right),$$

where m is an integer and A is a freely chosen amplitude. The corresp exact solution can be computed and reads

$$u_e(x,t) = A\sin\left(\frac{\pi}{L}mx\right)\cos\left(\frac{\pi}{L}mct\right).$$

) Explain that for a function $\sin kx \cos \omega t$ the wave length in space is $\lambda = 2\pi/k$
nd the period in time is $P = 2\pi/\omega$. Use these expressions to find the wave
ength in space and period in time of u_e above.

) Import the `solver` function `wave1D_u0.py` into a new file where the `viz`
unction is reimplemented such that it plots either the numerical *and* the exact
olution, *or* the error.

) Make animations where you illustrate how the error $e_i^n = u_e(x_i, t_n) - u_i^n$
evelops and increases in time. Also make animations of u and u_e simultaneously.

Hint 1. Quite long time simulations are needed in order to display significant
iscrepancies between the numerical and exact solution.

Hint 2. A possible set of parameters is $L = 12$, $m = 9$, $c = 2$, $A = 1$, $N_x = 80$,
$' = 0.8$. The error mesh function e^n can be simulated for 10 periods, while
0-30 periods are needed to show significant differences between the curves for
he numerical and exact solution.
ilename: `wave_standing.py`.

Remarks. The important parameters for numerical quality are C and $k\Delta x$,
here $C = c\Delta t/\Delta x$ is the Courant number and k is defined above ($k\Delta x$ is
roportional to how many mesh points we have per wave length in space, see
ection 10.4 for explanation).

xercise 2: Add storage of solution in a user action function

xtend the `plot_u` function in the file `wave1D_u0.py` to also store the solutions
in a list. To this end, declare `all_u` as an empty list in the `viz` function,
utside `plot_u`, and perform an append operation inside the `plot_u` function.
ote that a function, like `plot_u`, inside another function, like `viz`, remembers
ll local variables in `viz` function, including `all_u`, even when `plot_u` is called
s `user_action`) in the `solver` function. Test both `all_u.append(u)` and
ll_u.append(u.copy())`. Why does one of these constructions fail to store
he solution correctly? Let the `viz` function return the `all_u` list converted to a
wo-dimensional `numpy` array. Filename: `wave1D_u0_s_store.py`.

xercise 3: Use a class for the user action function

edo Exercise 2 using a class for the user action function. That is, define a class
ction where the `all_u` list is an attribute, and implement the user action func-
on as a method (the special method `__call__` is a natural choice). The class
ersions avoids that the user action function depends on parameters defined out-
de the function (such as `all_u` in Exercise 2). Filename: `wave1D_u0_s2c.py`.

Exercise 4: Compare several Courant numbers in one

The goal of this exercise is to make movies where several curves, corres
to different Courant numbers, are visualized. Import the `solver` functi
the `wave1D_u0_s` movie in a new file `wave_compare.py`. Reimplement
function such that it can take a list of `C` values as argument and create
with solutions corresponding to the given `C` values. The `plot_u` functi
be changed to store the solution in an array (see Exercise 2 or 3 for
`solver` must be computed for each value of the Courant number, and
one must run through each time step and plot all the spatial solution c
one figure and store it in a file.

The challenge in such a visualization is to ensure that the curves in
corresponds to the same time point. The easiest remedy is to keep the t
space resolution constant and change the wave velocity c to change the
number. Filename: `wave_numerics_comparison.py`.

Project 5: Calculus with 1D mesh functions

This project explores integration and differentiation of mesh functions, b
scalar and vectorized implementations. We are given a mesh function
spatial one-dimensional mesh $x_i = i\Delta x$, $i = 0, \ldots, N_x$, over the interval

a) Define the discrete derivative of f_i by using centered differences at
mesh points and one-sided differences at the end points. Implement
version of the computation in a Python function and supply a nose test
linear case $f(x) = 4x - 2.5$ where the discrete derivative should be exa

b) Vectorize the implementation of the discrete derivative. Extend the
to check the validity of the implementation.

c) To compute the discrete integral F_i of f_i, we assume that the mesh
f_i varies linearly between the mesh points. Let $f(x)$ be such a linear int
of f_i. We then have

$$F_i = \int_{x_0}^{x_i} f(x)dx.$$

The exact integral of a piecewise linear function $f(x)$ is given by the Tra
rule. S how that if F_i is already computed, we can find F_{i+1} from

$$F_{i+1} = F_i + \frac{1}{2}(f_i + f_{i+1})\Delta x.$$

Make a function for a scalar implementation of the discrete integral as
function. That is, the function should return F_i for $i = 0, \ldots, N_x$. For
test one can use the fact that the above defined discrete integral of
function (say $f(x) = 4x - 2.5$) is exact.

d) Vectorize the implementation of the discrete integral. Extend the
to check the validity of the implementation.

Hint. Interpret the recursive formula for F_{i+1} as a sum. Make an array with each element of the sum and use the "cumsum" (`numpy.cumsum`) operation to compute the accumulative sum: `numpy.cumsum([1,3,5])` is `[1,4,9]`.

) Create a class `MeshCalculus` that can integrate and differentiate mesh functions. The class can just define some methods that call the previously implemented Python functions. Here is an example on the usage:

```python
import numpy as np
calc = MeshCalculus(vectorized=True)
x = np.linspace(0, 1, 11)        # mesh
f = np.exp(x)                    # mesh function
df = calc.differentiate(f, x)    # discrete derivative
F = calc.integrate(f, x)         # discrete anti-derivative
```

ilename: `mesh_calculus_1D.py`.

Generalization: reflecting boundaries

he boundary condition $u = 0$ makes u change sign at the boundary, while he condition $u_x = 0$ perfectly reflects the wave, see a web page[7] or a movie le[8] for demonstration. Our next task is to explain how to implement the oundary condition $u_x = 0$, which is more complicated to express numerically nd also to implement than a given value of u. We shall present two methods or implementing $u_x = 0$ in a finite difference scheme, one based on deriving a nodified stencil at the boundary, and another one based on extending the mesh ith ghost cells and ghost points.

.1 Neumann boundary condition

When a wave hits a boundary and is to be reflected back, one applies the ondition

$$\frac{\partial u}{\partial n} \equiv \boldsymbol{n} \cdot \nabla u = 0. \tag{34}$$

he derivative $\partial/\partial n$ is in the outward normal direction from a general boundary. or a 1D domain $[0, L]$, we have that

$$\left.\frac{\partial}{\partial n}\right|_{x=L} = \frac{\partial}{\partial x}, \quad \left.\frac{\partial}{\partial n}\right|_{x=0} = -\frac{\partial}{\partial x}.$$

Boundary condition terminology.

---
[7]`http://tinyurl.com/k3sdbuv/pub/mov-wave/demo_BC_gaussian/index.html`
[8]`http://tinyurl.com/k3sdbuv/pub/mov-wave/demo_BC_gaussian/movie.flv`

Boundary conditions that specify the value of $\partial u/\partial n$, or shorter u_n known as Neumann[a] conditions, while Dirichlet conditions[b] refer to : fications of u. When the values are zero ($\partial u/\partial n = 0$ or $u = 0$) we s about *homogeneous* Neumann or Dirichlet conditions.

---
[a]`http://en.wikipedia.org/wiki/Neumann_boundary_condition`
[b]`http://en.wikipedia.org/wiki/Dirichlet_conditions`

6.2 Discretization of derivatives at the boundary

How can we incorporate the condition (34) in the finite difference scheme we have used central differences in all the other approximations to der in the scheme, it is tempting to implement (34) at $x = 0$ and $t = t_n$ difference

$$\frac{u_{-1}^n - u_1^n}{2\Delta x} = 0.$$

The problem is that u_{-1}^n is not a u value that is being computed since the is outside the mesh. However, if we combine (35) with the scheme for i

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2\left(u_{i+1}^n - 2u_i^n + u_{i-1}^n\right),$$

we can eliminate the fictitious value u_{-1}^n. We see that $u_{-1}^n = u_1^n$ from (35 can be used in (36) to arrive at a modified scheme for the boundary poir

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + 2C^2\left(u_{i+1}^n - u_i^n\right), \quad i = 0.$$

Figure 4 visualizes this equation for computing u_0^3 in terms of u_0^2, u_0^1, a
Similarly, (34) applied at $x = L$ is discretized by a central difference

$$\frac{u_{N_x+1}^n - u_{N_x-1}^n}{2\Delta x} = 0.$$

Combined with the scheme for $i = N_x$ we get a modified scheme for the b value $u_{N_x}^{n+1}$:

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + 2C^2\left(u_{i-1}^n - u_i^n\right), \quad i = N_x.$$

The modification of the scheme at the boundary is also required special formula for the first time step. How the stencil moves through the and is modified at the boundary can be illustrated by an animation in page[9] or a movie file[10].

---
[9]`http://tinyurl.com/k3sdbuv/pub/mov-wave/wave1D_PDE_Neumann_stencil_gpl`
[10]`http://tinyurl.com/k3sdbuv/pub/mov-wave/wave1D_PDE_Neumann_stencil_gpl`

27

28

Figure 4: Modified stencil at a boundary with a Neumann condition.

.3 Implementation of Neumann conditions

he implementation of the special formulas for the boundary points can benefit rom using the general formula for the interior points also at the boundaries, ut replacing u_{i-1}^n by u_{i+1}^n when computing u_i^{n+1} for $i = 0$ and u_{i+1}^n by u_{i-1}^n for $= N_x$. This is achieved by just replacing the index $i - 1$ by $i + 1$ for $i = 0$ and $+ 1$ by $i - 1$ for $i = N_x$. In a program, we introduce variables to hold the value f the offset indices: `im1` for `i-1` and `ip1` for `i+1`. It is now just a manner of efining `im1` and `ip1` properly for the internal points and the boundary points. he coding for the latter reads

```
i = 0
ip1 = i+1
im1 = ip1  # i-1 -> i+1
u[i] = u_1[i] + C2*(u_1[im1] - 2*u_1[i] + u_1[ip1])

i = Nx
im1 = i-1
ip1 = im1  # i+1 -> i-1
u[i] = u_1[i] + C2*(u_1[im1] - 2*u_1[i] + u_1[ip1])
```

We can in fact create one loop over both the internal and boundary points nd use only one updating formula:

```
for i in range(0, Nx+1):
    ip1 = i+1 if i < Nx else i-1
    im1 = i-1 if i > 0  else i+1
    u[i] = u_1[i] + C2*(u_1[im1] - 2*u_1[i] + u_1[ip1])
```

The program `wave1D_n0.py`[11] contains a complete implementation 1D wave equation with boundary conditions $u_x = 0$ at $x = 0$ and $x = L$

It would be nice to modify the `test_quadratic` test case from the `wave` with Dirichlet conditions, described in Section 4.3. However, the Neuma ditions requires the polynomial variation in x directory to be of third which causes challenging problems with designing a test where the nu solution is known exactly. Exercise 10 outlines ideas and code for this p The only test in `wave1D_n0.py` is to start with a plug wave at rest and the initial condition is reached again perfectly after one period of mo $C = 1$.

6.4 Index set notation

We shall introduce a special notation for index sets, consisting of wri $i \in \mathcal{I}_x$, instead of $i = 0, \ldots, N_x$. Obviously, $\mathcal{I}_x$ must be the set $\mathcal{I}_x = \{0, \ldots\}$ but it is often advantageous to have a symbol for this set rather than sp all its elements. This saves writing and makes specification of algorith implementation of computer code easier.

The first index in the set will be denoted $\mathcal{I}_x^0$ and the last $\mathcal{I}_x^{-1}$. Somet need to count from the second element in the set, and the notation $\mathcal{I}_x^+$ used. Correspondingly, $\mathcal{I}_x^-$ means $\{0, \ldots, N_x - 1\}$. All the indices corres to inner grid points are $\mathcal{I}_x^i = \{1, \ldots, N_x - 1\}$. For the time domain we natural to explicitly use 0 as the first index, so we will usually write n t_0 rather than $n = \mathcal{I}_t^0$. We also avoid notation like $x_{\mathcal{I}_x^{-1}}$ and will instead $i = \mathcal{I}_x^{-1}$.

The Python code associated with index sets applies the following conv

Notation	Python
$\mathcal{I}_x$	`Ix`
$\mathcal{I}_x^0$	`Ix[0]`
$\mathcal{I}_x^{-1}$	`Ix[-1]`
$\mathcal{I}_x^-$	`Ix[:-1]`
$\mathcal{I}_x^+$	`Ix[1:]`
$\mathcal{I}_x^i$	`Ix[1:-1]`

An important feature of the index set notation is that it keeps our formu code independent of how we count mesh points. For example, the notatio or $i = \mathcal{I}_x^0$ remains the same whether $\mathcal{I}_x$ is defined as above or as starti i.e., $\mathcal{I}_x = \{1, \ldots, Q\}$. Similarly, we can in the code define `Ix=range(N` `Ix=range(1,Q)`, and expressions like `Ix[0]` and `Ix[1:-1]` remain corre application where the index set notation is convenient is conversion of co a language where arrays has base index 0 (e.g., Python and C) to la where the base index is 1 (e.g., MATLAB and Fortran). Another im application is implementation of Neumann conditions via ghost points (section).

---

[11] http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_n0.py

For the current problem setting in the x, t plane, we work with the index sets

$$\mathcal{I}_x = \{0, \ldots, N_x\}, \quad \mathcal{I}_t = \{0, \ldots, N_t\}, \tag{40}$$

efined in Python as

```
Ix = range(0, Nx+1)
It = range(0, Nt+1)
```

A finite difference scheme can with the index set notation be specified as

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n + C^2\left(u_{i+1}^n - 2u_i^n + u_{i-1}^n\right), \quad i \in \mathcal{I}_x^i, \ n \in \mathcal{I}_t^i,$$
$$u_i = 0, \quad i = \mathcal{I}_x^0, \ n \in \mathcal{I}_t^i,$$
$$u_i = 0, \quad i = \mathcal{I}_x^{-1}, \ n \in \mathcal{I}_t^i,$$

nd implemented by code like

```
for n in It[1:-1]:
    for i in Ix[1:-1]:
        u[i] = - u_2[i] + 2*u_1[i] + \
               C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1])
    i = Ix[0];  u[i] = 0
    i = Ix[-1]; u[i] = 0
```

Notice.

The program `wave1D_dn.py`[a] applies the index set notation and solves the 1D wave equation $u_{tt} = c^2 u_{xx} + f(x, t)$ with quite general boundary and initial conditions:

- $x = 0$: $u = U_0(t)$ or $u_x = 0$

- $x = L$: $u = U_L(t)$ or $u_x = 0$

- $t = 0$: $u = I(x)$

- $t = 0$: $u_t = I(x)$

The program combines Dirichlet and Neumann conditions, scalar and vectorized implementation of schemes, and the index notation into one piece of code. A lot of test examples are also included in the program:

- A rectangular plug profile as initial condition (easy to use as test example as the rectangle should jump one cell per time step when $C = 1$, without any numerical errors).

- A Gaussian function as initial condition.

- A triangular profile as initial condition, which resembles the ty initial shape of a guitar string.

- A sinusoidal variation of u at $x = 0$ and either $u = 0$ or $u_x =$ $x = L$.

- An exact analytical solution $u(x, t) = \cos(m\pi t/L)\sin(\frac{1}{2}m\pi$ which can be used for convergence rate tests.

[a] http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_dn.py

hpl 4: Should include some experiments here or make exercises. Qu behavior of the wave equation can be exemplified.

6.5 Alternative implementation via ghost cells

Idea. Instead of modifying the scheme at the boundary, we can introdu points outside the domain such that the fictitious values u_{-1}^n and u_N^n defined in the mesh. Adding the intervals $[-\Delta x, 0]$ and $[L, L+\Delta x]$, often to as *ghost cells*, to the mesh gives us all the needed mesh points, corres to $i = -1, 0, \ldots, N_x, N_x + 1$. The extra points $i = -1$ and $i = N_x + 1$ ar as *ghost points*, and values at these points, u_{-1}^n and $u_{N_x+1}^n$, are call *values*.

The important idea is to ensure that we always have

$$u_{-1}^n = u_1^n \text{ and } u_{N_x+1}^n = u_{N_x-1}^n,$$

because then the application of the standard scheme at a boundary poi or $i = N_x$ will be correct and guarantee that the solution is compatible v boundary condition $u_x = 0$.

Implementation. The `u` array now needs extra elements correspor the ghost cells and points. Two new point values are needed:

```
u   = zeros(Nx+3)
```

The arrays `u_1` and `u_2` must be defined accordingly.

Unfortunately, a major indexing problem arises with ghost cells. Th is that Python indices *must* start at 0 and `u[-1]` will always mean element in `u`. This fact gives, apparently, a mismatch between the math indices $i = -1, 0, \ldots, N_x + 1$ and the Python indices running over `u`: $0, .$ One remedy is to change the mathematical notation of the scheme, as i

$$u_i^{n+1} = \cdots, \quad i = 1, \ldots, N_x + 1,$$

meaning that the ghost points correspond to $i = 0$ and $i = N_x + 1$. A better solution is to use the ideas of Section 6.4: we hide the specific index value in an index set and operate with inner and boundary points using the index set notation.

To this end, we define `u` with proper length and `Ix` to be the corresponding indices for the real physical points $(1, 2, \ldots, N_x + 1)$:

```
u = zeros(Nx+3)
Ix = range(1, u.shape[0]-1)
```

That is, the boundary points have indices `Ix[0]` and `Ix[-1]` (as before). We first update the solution at all physical mesh points (i.e., interior points in the mesh extended with ghost cells):

```
for i in Ix:
    u[i] = - u_2[i] + 2*u_1[i] + \
           C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1])
```

It remains to update the ghost points. For a boundary condition $u_x = 0$, the ghost value must equal to the value at the associated inner mesh point. Computer code makes this statement precise:

```
i = Ix[0]            # x=0 boundary
u[i-1] = u[i+1]
i = Ix[-1]           # x=L boundary
u[i+1] = u[i-1]
```

The physical solution to be plotted is now in `u[1:-1]`, or equivalently `u[Ix[0]:Ix[-1]+1]`, so this slice is the quantity to be returned from a solver function. A complete implementation appears in the program `wave1D_n0_ghost.py`[12].

> **Warning.**
>
> We have to be careful with how the spatial and temporal mesh points are stored. Say we let `x` be the physical mesh points,
>
> ```
> x = linspace(0, L, Nx+1)
> ```
>
> "Standard coding" of the initial condition,
>
> ```
> for i in Ix:
>     u_1[i] = I(x[i])
> ```
>
> becomes wrong, since `u_1` and `x` have different lengths and the index `i` corresponds to two different mesh points. In fact, `x[i]` corresponds to `u[1+i]`. A correct implementation is

---
[12]http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_n0_ghost.py

```
for i in Ix:
    u_1[i] = I(x[i-Ix[0]])
```

Similarly, a source term usually coded as `f(x[i], t[n])` is incorrect if defined to be the physical points, so `x[i]` must be replaced by `x[i-Ix[0]]`.

An alternative remedy is to let `x` also cover the ghost points such that `u[i]` is the value at `x[i]`.

The ghost cell is only added to the boundary where we have a Neumann condition. Suppose we have a Dirichlet condition at $x = L$ and a homogeneous Neumann condition at $x = 0$. One ghost cell $[-\Delta x, 0]$ is added to the mesh, so the index set for the physical points becomes $\{1, \ldots, N_x + 1\}$. A relevant implementation is

```
u = zeros(Nx+2)
Ix = range(1, u.shape[0])
...
for i in Ix[:-1]:
    u[i] = - u_2[i] + 2*u_1[i] + \
           C2*(u_1[i-1] - 2*u_1[i] + u_1[i+1]) + \
           dt2*f(x[i-Ix[0]], t[n])
i = Ix[-1]
u[i] = U_0        # set Dirichlet value
i = Ix[0]
u[i-1] = u[i+1]   # update ghost value
```

The physical solution to be plotted is now in `u[1:]` or (as always) `u[Ix[0]...]`

7 Generalization: variable wave velocity

Our next generalization of the 1D wave equation (1) or (17) is to allow for a variable wave velocity c: $c = c(x)$, usually motivated by wave motion in a domain composed of different physical media with different properties for propagating waves and hence different wave velocities c. Figure


Figure 5: Left: wave entering another medium; right: transmitted and reflected wave .

.1 The model PDE with a variable coefficient

Instead of working with the squared quantity $c^2(x)$ we shall for notational convenience introduce $q(x) = c^2(x)$. A 1D wave equation with variable wave velocity often takes the form

$$\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right) + f(x,t). \tag{41}$$

This equation sampled at a mesh point (x_i, t_n) reads

$$\frac{\partial^2}{\partial t^2} u(x_i, t_n) = \frac{\partial}{\partial x}\left(q(x_i)\frac{\partial}{\partial x} u(x_i, t_n)\right) + f(x_i, t_n),$$

where the only new term is

$$\frac{\partial}{\partial x}\left(q(x_i)\frac{\partial}{\partial x} u(x_i, t_n)\right) = \left[\frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right)\right]_i^n.$$

.2 Discretizing the variable coefficient

The principal idea is to first discretize the outer derivative. Define

$$\phi = q(x)\frac{\partial u}{\partial x},$$

and use a centered derivative around $x = x_i$ for the derivative of ϕ:

$$\left[\frac{\partial \phi}{\partial x}\right]_i^n \approx \frac{\phi_{i+\frac{1}{2}} - \phi_{i-\frac{1}{2}}}{\Delta x} = [D_x \phi]_i^n.$$

Then discretize

$$\phi_{i+\frac{1}{2}} = q_{i+\frac{1}{2}}\left[\frac{\partial u}{\partial x}\right]_{i+\frac{1}{2}}^n \approx q_{i+\frac{1}{2}}\frac{u_{i+1}^n - u_i^n}{\Delta x} = [qD_x u]_{i+\frac{1}{2}}^n.$$

Similarly,

$$\phi_{i-\frac{1}{2}} = q_{i-\frac{1}{2}}\left[\frac{\partial u}{\partial x}\right]_{i-\frac{1}{2}}^n \approx q_{i-\frac{1}{2}}\frac{u_i^n - u_{i-1}^n}{\Delta x} = [qD_x u]_{i-\frac{1}{2}}^n.$$

These intermediate results are now combined to

$$\left[\frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right)\right]_i^n \approx \frac{1}{\Delta x^2}\left(q_{i+\frac{1}{2}}\left(u_{i+1}^n - u_i^n\right) - q_{i-\frac{1}{2}}\left(u_i^n - u_{i-1}^n\right)\right). \tag{42}$$

With operator notation we can write the discretization as

$$\left[\frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right)\right]_i^n \approx [D_x q D_x u]_i^n. \tag{43}$$

> **Remark.**
>
> Many are tempted to use the chain rule on the term $\frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right)$, but is not a good idea when discretizing such a term.

7.3 Computing the coefficient between mesh points

If q is a known function of x, we can easily evaluate $q_{i+\frac{1}{2}}$ simply as $q(x_{i+}$ $x_{i+\frac{1}{2}} = x_i + \frac{1}{2}\Delta x$. However, in many cases c, and hence q, is only kno discrete function, often at the mesh points x_i. Evaluating q between tw points x_i and x_{i+1} can then be done by averaging in three ways:

$$q_{i+\frac{1}{2}} \approx \frac{1}{2}\left(q_i + q_{i+1}\right) = [\overline{q}^x]_i, \qquad \text{(arithmetic mean)}$$

$$q_{i+\frac{1}{2}} \approx 2\left(\frac{1}{q_i} + \frac{1}{q_{i+1}}\right)^{-1}, \qquad \text{(harmonic mean)}$$

$$q_{i+\frac{1}{2}} \approx \left(q_i q_{i+1}\right)^{1/2}, \qquad \text{(geometric mean)}$$

The arithmetic mean in (44) is by far the most commonly used av technique.

With the operator notation from (44) we can specify the discretiz the complete variable-coefficient wave equation in a compact way:

$$[D_t D_t u = D_x \overline{q}^x D_x u + f]_i^n.$$

From this notation we immediately see what kind of differences that each approximated with. The notation $\overline{q}^x$ also specifies that the variable coef approximated by an arithmetic mean, the definition being $[\overline{q}^x]_{i+\frac{1}{2}} = (q_i +$ With the notation $[D_x q D_x u]_i^n$, we specify that q is evaluated direct function, between the mesh points: $q(x_{i-\frac{1}{2}})$ and $q(x_{i+\frac{1}{2}})$.

Before any implementation, it remains to solve (47) with respect to

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n +$$
$$\left(\frac{\Delta x}{\Delta t}\right)^2\left(\frac{1}{2}(q_i + q_{i+1})(u_{i+1}^n - u_i^n) - \frac{1}{2}(q_i + q_{i-1})(u_i^n - u_{i-1}^n)\right)$$
$$\Delta t^2 f_i^n.$$

7.4 How a variable coefficient affects the stability

The stability criterion derived in Section 10.3 reads $\Delta t \le \Delta x / c$. If c the criterion will depend on the spatial location. We must therefore c

t that is small enough such that no mesh cell has $\Delta x/c(x) > \Delta t$. That is, we must use the largest c value in the criterion:

$$\Delta t \leq \beta \frac{\Delta x}{\max_{x\in[0,L]} c(x)}\,. \tag{49}$$

The parameter β is included as a safety factor: in some problems with a significantly varying c it turns out that one must choose $\beta < 1$ to have stable solutions ($\beta = 0.9$ may act as an all-round value).

.5 Neumann condition and a variable coefficient

Consider a Neumann condition $\partial u/\partial x = 0$ at $x = L = N_x\Delta x$, discretized as

$$\frac{u_{i+1}^n - u_{i-1}^n}{2\Delta x} = 0 \quad u_{i+1}^n = u_{i-1}^n,$$

for $i = N_x$. Using the scheme (48) at the end point $i = N_x$ with $u_{i+1}^n = u_{i-1}^n$ results in

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n +$$
$$\left(\frac{\Delta x}{\Delta t}\right)^2 \left(q_{i+\frac{1}{2}}(u_{i-1}^n - u_i^n) - q_{i-\frac{1}{2}}(u_i^n - u_{i-1}^n)\right) +$$
$$\Delta t^2 f_i^n \tag{50}$$
$$= -u_i^{n-1} + 2u_i^n + \left(\frac{\Delta x}{\Delta t}\right)^2 (q_{i+\frac{1}{2}} + q_{i-\frac{1}{2}})(u_{i-1}^n - u_i^n) + \Delta t^2 f_i^n \tag{51}$$
$$\approx -u_i^{n-1} + 2u_i^n + \left(\frac{\Delta x}{\Delta t}\right)^2 2q_i(u_{i-1}^n - u_i^n) + \Delta t^2 f_i^n\,. \tag{52}$$

Here we used the approximation

$$q_{i+\frac{1}{2}} + q_{i-\frac{1}{2}} = q_i + \left(\frac{dq}{dx}\right)_i \Delta x + \left(\frac{d^2q}{dx^2}\right)_i \Delta x^2 + \cdots +$$
$$q_i - \left(\frac{dq}{dx}\right)_i \Delta x + \left(\frac{d^2q}{dx^2}\right)_i \Delta x^2 + \cdots$$
$$= 2q_i + 2\left(\frac{d^2q}{dx^2}\right)_i \Delta x^2 + \mathcal{O}(\Delta x^4)$$
$$\approx 2q_i\,. \tag{53}$$

An alternative derivation may apply the arithmetic mean of q in (48), leading to the term

$$(q_i + \frac{1}{2}(q_{i+1} + q_{i-1}))(u_{i-1}^n - u_i^n)\,.$$

Since $\frac{1}{2}(q_{i+1} + q_{i-1}) = q_i + \mathcal{O}(\Delta x^2)$, we end up with $2q_i(u_{i-1}^n - u_i^n)$ for as we did above.

A common technique in implementations of $\partial u/\partial x = 0$ boundary co is to assume $dq/dx = 0$ as well. This implies $q_{i+1} = q_{i-1}$ and $q_{i+1/2} = q_i$ $i = N_x$. The implications for the scheme are

$$u_i^{n+1} = -u_i^{n-1} + 2u_i^n +$$
$$\left(\frac{\Delta x}{\Delta t}\right)^2 \left(q_{i+\frac{1}{2}}(u_{i-1}^n - u_i^n) - q_{i-\frac{1}{2}}(u_i^n - u_{i-1}^n)\right) +$$
$$\Delta t^2 f_i^n$$
$$= -u_i^{n-1} + 2u_i^n + \left(\frac{\Delta x}{\Delta t}\right)^2 2q_{i-\frac{1}{2}}(u_{i-1}^n - u_i^n) + \Delta t^2 f_i^n\,.$$

7.6 Implementation of variable coefficients

The implementation of the scheme with a variable wave velocity may that c is available as an array `c[i]` at the spatial mesh points. The f loop is a straightforward implementation of the scheme (48):

```
for i in range(1, Nx):
    u[i] = - u_2[i] + 2*u_1[i] + \
           C2*(0.5*(q[i] + q[i+1])*(u_1[i+1] - u_1[i])  - \
               0.5*(q[i] + q[i-1])*(u_1[i] - u_1[i-1])) + \
           dt2*f(x[i], t[n])
```

The coefficient `C2` is now defined as `(dt/dx)**2` and *not* as the squared number since the wave velocity is variable and appears inside the paren

With Neumann conditions $u_x = 0$ at the boundary, we need to this scheme with the discrete version of the boundary condition, as sl Section 7.5. Nevertheless, it would be convenient to reuse the formula interior points and just modify the indices `ip1=i+1` and `im1=i-1` as w Section 6.3. Assuming $dq/dx = 0$ at the boundaries, we can implem scheme at the boundary with the following code.

```
i = 0
ip1 = i+1
im1 = ip1
u[i] = - u_2[i] + 2*u_1[i] + \
       C2*(0.5*(q[i] + q[ip1])*(u_1[ip1] - u_1[i])  - \
           0.5*(q[i] + q[im1])*(u_1[i] - u_1[im1])) + \
       dt2*f(x[i], t[n])
```

With ghost cells we can just reuse the formula for the interior poi at the boundary, provided that the ghost values of both u and q are c updated to ensure $u_x = 0$ and $q_x = 0$.

A vectorized version of the scheme with a variable coefficient at points in the mesh becomes

```
u[1:-1] = - u_2[1:-1] + 2*u_1[1:-1] + \
        C2*(0.5*(q[1:-1] + q[2:])*(u_1[2:] - u_1[1:-1]) -
            0.5*(q[1:-1] + q[:-2])*(u_1[1:-1] - u_1[:-2])) + \
        dt2*f(x[1:-1], t[n])
```

.7 A more general model PDE with variable coefficients

ometimes a wave PDE has a variable coefficient also in front of the time-
erivative term:

$$\varrho(x)\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x}\left(q(x)\frac{\partial u}{\partial x}\right) + f(x,t). \tag{56}$$

natural scheme is

$$[\varrho D_t D_t u = D_x \overline{q}^x D_x u + f]_i^n. \tag{57}$$

Te realize that the ϱ coefficient poses no particular difficulty because the only
alue ϱ_i^n enters the formula above (when written out). There is hence no need for
ny averaging of ϱ. Often, ϱ will be moved to the right-hand side, also without
ny difficulty:

$$[D_t D_t u = \varrho^{-1} D_x \overline{q}^x D_x u + f]_i^n. \tag{58}$$

.8 Generalization: damping

Javes die out by two mechanisms. In 2D and 3D the energy of the wave spreads
ut in space, and energy conservation then requires the amplitude to decrease.
his effect is not present in 1D. Damping is another cause of amplitude reduction.
or example, the vibrations of a string die out because of damping due to air
esistance and non-elastic effects in the string.

The simplest way of including damping is to add a first-order derivative to
ne equation (in the same way as friction forces enter a vibrating mechanical
ystem):

$$\frac{\partial^2 u}{\partial t^2} + b\frac{\partial u}{\partial t} = c^2\frac{\partial^2 u}{\partial x^2} + f(x,t), \tag{59}$$

here $b \geq 0$ is a prescribed damping coefficient.

A typical discretization of (59) in terms of centered differences reads

$$[D_t D_t u + b D_{2t} u = c^2 D_x D_x u + f]_i^n. \tag{60}$$

Jriting out the equation and solving for the unknown u_i^{n+1} gives the scheme

$$_i^{n+1} = (1 + \frac{1}{2}b\Delta t)^{-1}((\frac{1}{2}b\Delta t - 1)u_i^{n-1} + 2u_i^n + C^2\left(u_{i+1}^n - 2u_i^n + u_{i-1}^n\right) + \Delta t^2 f_i^n), \tag{61}$$

---

for $i \in \mathcal{I}_x^i$ and $n \geq 1$. New equations must be derived for u_i^1, and for be
points in case of Neumann conditions.

The damping is very small in many wave phenomena and then only
for very long time simulations. This makes the standard wave equation
damping relevant for a lot of applications.

8 Building a general 1D wave equation sol

The program `wave1D_dn_vc.py`[13] is a fairly general code for 1D wave prop
problems that targets the following initial-boundary value problem

$$u_t = (c^2(x)u_x)_x + f(x,t), \qquad x \in (0,L),\ t \in (0,T]$$
$$u(x,0) = I(x), \qquad x \in [0,L]$$
$$u_t(x,0) = V(t), \qquad x \in [0,L]$$
$$u(0,t) = U_0(t) \text{ or } u_x(0,t) = 0, \qquad t \in (0,T]$$
$$u(L,t) = U_L(t) \text{ or } u_x(L,t) = 0, \qquad t \in (0,T]$$

The `solver` function is a natural extension of the simplest `solver` fun
the initial `wave1D_u0.py` program, extended with Neumann boundary co
($u_x = 0$), a possibly time-varying boundary condition on u ($U_0(t)$, $U_L($
a variable wave velocity. The different code segments needed to mak
extensions are shown and commented upon in the preceding text.

The vectorization is only applied inside the time loop, not for the
condition or the first time steps, since this initial work is negligible for lo
simulations in 1D problems.

The following sections explain various more advanced programming tec
applied in the general 1D wave equation solver.

8.1 User action function as a class

A useful feature in the `wave1D_dn_vc.py` program is the specification
`user_action` function as a class. Although the `plot_u` function in
function of previous `wave1D*.py` programs remembers the local variable
`viz` function, it is a cleaner solution to store the needed variables togeth
the function, which is exactly what a class offers.

A class for flexible plotting, cleaning up files, and making a movie f
function `viz` and `plot_u` did can be coded as follows:

```
class PlotSolution:
    """
    Class for the user_action function in solver.
    Visualizes the solution only.
    """
    def __init__(self,
```

---
[13] http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_dn_vc.py

```
                casename='tmp',     # Prefix in filenames
                umin=-1, umax=1,    # Fixed range of y axis
                pause_between_frames=None,  # Movie speed
                backend='matplotlib',       # or 'gnuplot'
                screen_movie=True, # Show movie on screen?
                title='',          # Extra message in title
                every_frame=1):    # Show every_frame frame
        self.casename = casename
        self.yaxis = [umin, umax]
        self.pause = pause_between_frames
        module = 'scitools.easyviz.' + backend + '_'
        exec('import %s as plt' % module)
        self.plt = plt
        self.screen_movie = screen_movie
        self.title = title
        self.every_frame = every_frame

        # Clean up old movie frames
        for filename in glob('frame_*.png'):
            os.remove(filename)

    def __call__(self, u, x, t, n):
        if n % self.every_frame != 0:
            return
        title = 't=%.3g' % t[n]
        if self.title:
            title = self.title + ' ' + title
        self.plt.plot(x, u, 'r-',
                    xlabel='x', ylabel='u',
                    axis=[x[0], x[-1],
                          self.yaxis[0], self.yaxis[1]],
                    title=title,
                    show=self.screen_movie)
        # pause
        if t[n] == 0:
            time.sleep(2)  # let initial condition stay 2 s
        else:
            if self.pause is None:
                pause = 0.2 if u.size < 100 else 0
            time.sleep(pause)

        self.plt.savefig('%s_frame_%04d.png' % (self.casename, n))
```

Understanding this class requires quite some familiarity with Python in general and class programming in particular.

The constructor shows how we can flexibly import the plotting engine as (typically) `scitools.easyviz.gnuplot_` or `scitools.easyviz.matplotlib_` (note the trailing underscore). With the `screen_movie` parameter we can suppress displaying each movie frame on the screen. Alternatively, for slow movies associated with fine meshes, one can set `every_frame` to, e.g., 10, causing every 10 frames to be shown.

The `__call__` method makes `PlotSolution` instances behave like functions, so we can just pass an instance, say p, as the `user_action` argument in the solver function, and any call to `user_action` will be a call to `p.__call__`.

8.2 Pulse propagation in two media

The function `pulse` in `wave1D_dn_vc.py` demonstrates wave motion in homogeneous media where c varies. One can specify an interval where the wave velocity is decreased by a factor `slowness_factor` (or increased by making this factor less than one). Four types of initial conditions are available: a rectangular pulse (`plug`), a Gaussian function (`gaussian`), a "cosine hat" consisting of one period of the cosine function (`cosinehat`), and half a period of a "cosine hat" (`half-cosinehat`). These peak-shaped initial conditions can be placed in the middle (`loc='center'`) or at the left end (`loc='left'`) of the domain. The `pulse` function is a flexible tool for playing around with various wave shapes and location of a medium with a different wave velocity:

```
def pulse(C=1, Nx=200, animate=True, version='vectorized', T=2,
          loc='center', pulse_tp='gaussian', slowness_factor=2,
          medium=[0.7, 0.9], every_frame=1, sigma=0.05):
    """
    Various peaked-shaped initial conditions on [0,1].
    Wave velocity is decreased by the slowness_factor inside
    medium. The loc parameter can be 'center' or 'left',
    depending on where the initial pulse is to be located.
    The sigma parameter governs the width of the pulse.
    """
    # Use scaled parameters: L=1 for domain length, c_0=1
    # for wave velocity outside the domain.
    L = 1.0
    c_0 = 1.0
    if loc == 'center':
        xc = L/2
    elif loc == 'left':
        xc = 0

    if pulse_tp in ('gaussian','Gaussian'):
        def I(x):
            return exp(-0.5*((x-xc)/sigma)**2)
    elif pulse_tp == 'plug':
        def I(x):
            return 0 if abs(x-xc) > sigma else 1
    elif pulse_tp == 'cosinehat':
        def I(x):
            # One period of a cosine
            w = 2
            a = w*sigma
            return 0.5*(1 + cos(pi*(x-xc)/a)) \
                   if xc - a <= x <= xc + a else 0

    elif pulse_tp == 'half-cosinehat':
        def I(x):
            # Half a period of a cosine
            w = 4
            a = w*sigma
            return cos(pi*(x-xc)/a) \
                   if xc - 0.5*a <= x <= xc + 0.5*a else 0
    else:
        raise ValueError('Wrong pulse_tp="%s"' % pulse_tp)

    def c(x):
```

```
        return c_0/slowness_factor \
               if medium[0] <= x <= medium[1] else c_0

    umin=-0.5; umax=1.5*I(xc)
    casename = '%s_Nx%s_sf%s' % \
               (pulse_tp, Nx, slowness_factor)
    action = PlotMediumAndSolution(
        medium, casename=casename, umin=umin, umax=umax,
        every_frame=every_frame, screen_movie=animate)

    dt = (L/Nx)/c  # choose the stability limit with given Nx
    # Lower C will then use this dt, but smaller Nx
    solver(I=I, V=None, f=None, c=c, U_0=None, U_L=None,
           L=L, dt=dt, C=C, T=T,
           user_action=action, version=version,
           stability_safety_factor=1)
```

The `PlotMediumAndSolution` class used here is a subclass of `PlotSolution` where the medium with reduced c value, as specified by the `medium` interval, is visualized in the plots.

> **Notice.**
>
> The argument N_x in the `pulse` function does not correspond to the actual spatial resolution of $C < 1$, since the `solver` function takes a fixed Δt and C, and adjusts Δx accordingly. As seen in the `pulse` function, the specified Δt is chosen according to the limit $C = 1$, so if $C < 1$, Δt remains the same, but the `solver` function operates with a larger Δx and smaller N_x than was specified in the call to `pulse`. The practical reason is that we always want to keep Δt fixed such that plot frames and movies are synchronized in time regardless of the value of C (i.e., Δx is varies when the Courant number varies).

The reader is encouraged to play around with the `pulse` function:

```
>>> import wave1D_dn_vc as w
>>> w.pulse(loc='left', pulse_tp='cosinehat', Nx=50, every_frame=10)
```

To easily kill the graphics by Ctrl-C and restart a new simulation it might be easier to run the above two statements from the command line with

```
Terminal> python -c 'import wave1D_dn_vc as w; w.pulse(...)'
```

9   Exercises

Exercise 6: Find the analytical solution to a damped equation

Consider the wave equation with damping (59). The goal is to find a solution to a wave problem with damping. A starting point is the standing solution from Exercise 1. It becomes necessary to include a damping term and also have both a sine and cosine component in time:

$$u_{\mathrm{e}}(x,t) = e^{-\beta t} \sin kx \, (A \cos \omega t + B \sin \omega t) \ .$$

Find k from the boundary conditions $u(0,t) = u(L,t) = 0$. Then use the to find constraints on β, ω, A, and B. Set up a complete initial-boundary problem and its solution. Filename: `damped_waves.pdf`.

Problem 7: Explore symmetry boundary conditions

Consider the simple "plug" wave where $\Omega = [-L, L]$ and

$$I(x) = \left\{ \begin{array}{ll} 1, & x \in [-\delta, \delta], \\ 0, & \text{otherwise} \end{array} \right.$$

for some number $0 < \delta < L$. The other initial condition is $u_t(x,0) = 0$ and is no source term f. The boundary conditions can be set to $u = 0$. The to this problem is symmetric around $x = 0$. This means that we can s the wave process in only the half of the domain $[0, L]$.

a) Argue why the symmetry boundary condition is $u_x = 0$ at $x = 0$.

Hint.   Symmetry of a function about $x = x_0$ means that $f(x_0 + h) = f$

b) Perform simulations of the complete wave problem from on $[-L, L]$ after, utilize the symmetry of the solution and run a simulation in hal domain $[0, L]$, using a boundary condition at $x = 0$. Compare the two s and make sure that they are the same.

c) Prove the symmetry property of the solution by setting up the c initial-boundary value problem and showing that if $u(x,t)$ is a soluti also $u(-x,t)$ is a solution.
Filename: `wave1D_symmetric`.

Exercise 8: Send pulse waves through a layered medi

Use the `pulse` function in `wave1D_dn_vc.py` to investigate sending located with its peak at $x = 0$, through the medium to the right wher another medium for $x \in [0.7, 0.9]$ where the wave velocity is decreas factor s_f. Report what happens with a Gaussian pulse, a "cosine hat half a "cosine hat" pulse, and a plug pulse for resolutions $N_x = 40, 80, 1$

$_f = 2, 4$. Use $C = 1$ in the medium outside $[0.7, 0.9]$. Simulate until $T = 2$.
[F]ilename: `pulse1D.py`.

[E]xercise 9: Compare discretizations of a Neumann condi[ti]on

[W]e have a 1D wave equation with variable wave velocity: $u_t = (qu_x)_x$. A
[N]eumann condition u_x at $x = 0, L$ can be discretized as shown in (52) and (55).

The aim of this exercise is to examine the rate of the numerical error when
[u]sing different ways of discretizing the Neumann condition. As test problem,
$[q] = 1 + (x - L/2)^4$ can be used, with $f(x, t)$ adapted such that the solution has
[a] simple form, say $u(x, t) = \cos(\pi x / L) \cos(\omega t)$ for some $\omega = \sqrt{q}\pi/L$.

[a]) Perform numerical experiments and find the convergence rate of the error
[u]sing the approximation and (55).

[b]) Switch to $q(x) = \cos(\pi x / L)$, which is symmetric at $x = 0, L$, and check the
[c]onvergence rate of the scheme (55). Now, $q_{i-1/2}$ is a 2nd-order approximation to
$_i$, $q_{i-1/2} = q_i + 0.25q_i'' \Delta x^2 + \cdots$, because $q_i' = 0$ for $i = N_x$ (a similar argument
[c]an be applied to the case $i = 0$).

[c]) A third discretization can be based on a simple and convenient, but less
[a]ccurate, one-sided difference: $u_i - u_{i-1} = 0$ at $i = N_x$ and $u_{i+1} - u_i = 0$ at
$_i = 0$. Derive the resulting scheme in detail and implement it. Run experiments
[t]o establish the rate of convergence.

[d]) A fourth technique is to view the scheme as

$$[D_t D_t u]_i^n = \frac{1}{\Delta x} \left([qD_x u]_{i+\frac{1}{2}}^n - [qD_x u]_{i-\frac{1}{2}}^n \right) + [f]_i^n,$$

[a]nd place the boundary at $x_{i+\frac{1}{2}}$, $i = N_x$, instead of exactly at the physical
[b]oundary. With this idea, we can just set $[qD_x u]_{i+\frac{1}{2}}^n = 0$. Derive the complete
[s]cheme using this technique. The implementation of the boundary condition at
$[L] - \Delta x/2$ is $\mathcal{O}(\Delta x^2)$ accurate, but the interesting question is what impact the
[m]ovement of the boundary has on the convergence rate (compute the errors as
[u]sual over the entire mesh).

[E]xercise 10: Verification by a cubic polynomial in space

[T]he purpose of this exercise is to verify the implementation of the `solver`
[fu]nction in the program `wave1D_n0.py`[14] by using an exact numerical solution
[fo]r the wave equation $u_{tt} = c^2 u_{xx} + f$ with Neumann boundary conditions
$_x(0, t) = u_x(L, t) = 0$.

A similar verification is used in the file `wave1D_u0.py`[15], which solves the
[sa]me PDE, but with Dirichlet boundary conditions $u(0, t) = u(L, t) = 0$. The

---

[14]`http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_n0.py`
[15]`http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_u0.py`

idea of the verification test in function `test_quadratic` in `wave1D_u0.`
a solution that is a lower-order polynomial such that both the PDE prob[lem]
boundary conditions, and all the discrete equations are exactly fulfille[d]
the `solver` function should reproduce this exact solution to machine p[recision].
More precisely, we seek $u = X(x)T(t)$, with $T(t)$ as a linear function a[nd]
as a parabola that fulfills the boundary conditions. Inserting this u in t[he PDE]
determines f. It tuns out that u also fulfills the discrete equations, bec[ause the]
truncation error of the discretized PDE has derivatives in x and t of or[der]
and higher. These derivatives all vanish for a quadratic $X(x)$ and linea[r]

It would be attractive to use a similar approach in the case of N[eumann]
conditions. We set $u = X(x)T(t)$ and seek lower-order polynomials X
To force u_x to vanish at the boundary, we let X_x be a parabola. The[n]
cubic polynomial. The fourth-order derivative of a cubic polynomial van[ishes]
$u = X(x)T(t)$ will fulfill the discretized PDE also in this case, if f is a[dapted]
such that u fulfills the PDE.

However, the discrete boundary condition is not exactly fulfilled [by our]
choice of u. The reason is that

$$[D_{2x} u]_i^n = u_x(x_i, t_n) + \frac{1}{6} u_{xxx}(x_i, t_n)\Delta x^2 + \mathcal{O}(\Delta x^4).$$

At the boundary two boundary points, $X_x(x) = 0$ such that $u_x = 0$. [But]
u_{xxx} is a constant and not zero when $X(x)$ is a cubic polynomial. Th[erefore]
our $u = X(x)T(t)$ fulfills

$$[D_{2x} u]_i^n = \frac{1}{6} u_{xxx}(x_i, t_n)\Delta x^2,$$

and not

$$[D_{2x} u]_i^n = 0, \quad i = 0, N_x,$$

as it should. (Note that all the higher-order terms $\mathcal{O}(\Delta x^4)$ also have [higher-]
order derivatives that vanish for a cubic polynomial.) So to summar[ize, the]
fundamental problem is that u as a product of a cubic polynomial and [a linear]
or quadratic polynomial in time is not an exact solution of the discrete b[oundary]
conditions.

To make progress, we assume that $u = X(x)T(t)$, where T for simp[licity is]
taken as a prescribed linear function $1 + \frac{1}{2}t$, and $X(x)$ is taken as an $u[nknown]$
cubic polynomial $\sum_{j=0}^{3} a_j x^j$. There are two different ways of determin[ing the]
coefficients $a_0, \ldots, a_3$ such that both the discretized PDE and the dis[cretized]
boundary conditions are fulfilled, under the constraint that we can sp[ecify a]
function $f(x, t)$ for the PDE to feed to the `solver` function in `wave1[D_n0.py`.]
Both approaches are explained in the subexercises.

a) One can insert u in the discretized PDE and find the corresponding [f. Then]
one can insert u in the discretized boundary conditions. This yields two e[quations]
for the four coefficients $a_0, \ldots, a_3$. To find the coefficients, one can se[t]

nd $a_1 = 1$ for simplicity and then determine a_2 and a_3. This approach will make a_2 and a_3 depend on Δx and f will depend on both Δx and Δt.

Use `sympy` to perform analytical computations. A starting point is to define as follows:

```python
def test_cubic1():
    import sympy as sm
    x, t, c, L, dx, dt = sm.symbols('x t c L dx dt')
    i, n = sm.symbols('i n', integer=True)

    # Assume discrete solution is a polynomial of degree 3 in x
    T = lambda t: 1 + sm.Rational(1,2)*t  # Temporal term
    a = sm.symbols('a_0 a_1 a_2 a_3')
    X = lambda x: sum(a[q]*x**q for q in range(4))  # Spatial term
    u = lambda x, t: X(x)*T(t)
```

he symbolic expression for u is reached by calling `u(x,t)` with `x` and `t` as ympy symbols.

Define `DxDx(u, i, n)`, `DtDt(u, i, n)`, and `D2x(u, i, n)` as Python func- ons for returning the difference approximations $[D_x D_x u]_i^n$, $[D_t D_t u]_i^n$, and $[D_{2x}u]_i^n$. The next step is to set up the residuals for the equations $[D_{2x}u]_i^n = 0$ nd $[D_{2x}u]_{N_x}^n = 0$, where $N_x = L/\Delta x$. Call the residuals `R_0` and `R_L`. Substi- te a_0 and a_1 by 0 and 1, respectively, in `R_0`, `R_L`, and `a`:

```python
R_0 = R_0.subs(a[0], 0).subs(a[1], 1)
R_L = R_L.subs(a[0], 0).subs(a[1], 1)
a = list(a)  # enable in-place assignment
a[0:2] = 0, 1
```

etermining a_2 and a_3 from the discretized boundary conditions is then about olving two equations with respect to a_2 and a_3, i.e., `a[2:]`:

```python
s = sm.solve([R_0, R_L], a[2:])
# s is dictionary with the unknowns a[2] and a[3] as keys
a[2:] = s[a[2]], s[a[3]]
```

ow, `a` contains computed values and `u` will automatically use these new values nce X accesses `a`.

Compute the source term f from the discretized PDE: $f_i^n = [D_t D_t u - ^2 D_x D_x u]_i^n$. Turn u, the time derivative u_t (needed for the initial condition $V(x)$), nd f into Python functions. Set numerical values for L, N_x, C, and c. Prescribe he time interval as $\Delta t = CL/(N_x c)$, which imply $\Delta x = c\Delta t/C = L/N_x$. Define ew functions `I(x)`, `V(x)`, and `f(x,t)` as wrappers of the ones made above, here fixed values of L, c, Δx, and Δt are inserted, such that `I`, `V`, and `f` can e passed on to the `solver` function. Finally, call `solver` with a `user_action` nction that compares the numerical solution to this exact solution u of the iscrete PDE problem.

Hint. To turn a `sympy` expression `e`, depending on a series of symbols, say `x`, , `dx`, `dt`, `L`, and `c`, into plain Python function `e_exact(x,t,L,dx,dt,c)`, one an write

```python
e_exact = sm.lambdify([x,t,L,dx,dt,c], e, 'numpy')
```

The `'numpy'` argument is a good habit as the `e_exact` function will th with array arguments if it contains mathematical functions (but here we plain arithmetics, which automatically work with arrays).

b) An alternative way of determining $a_0, \ldots, a_3$ is to reason as follows. construct $X(x)$ such that the boundary conditions are fulfilled: $X = x$ However, to compensate for the fact that this choice of X does not fu discrete boundary condition, we seek u such that

$$u_x = \frac{\partial}{\partial x} x(L-x)T(t) - \frac{1}{6}u_{xxx}\Delta x^2,$$

since this u will fit the discrete boundary condition. Assuming $u = T(t)\sum$ we can use the above equation to determine the coefficients a_1, a_2, a_3. e.g., 1 can be used for a_0. The following `sumpy` code computes this u:

```python
def test_cubic2():
    import sympy as sm
    x, t, c, L, dx = sm.symbols('x t c L dx')
    T = lambda t: 1 + sm.Rational(1,2)*t  # Temporal term
    # Set u as a 3rd-degree polynomial in space
    X = lambda x: sum(a[i]*x**i for i in range(4))
    a = sm.symbols('a_0 a_1 a_2 a_3')
    u = lambda x, t: X(x)*T(t)
    # Force discrete boundary condition to be zero by adding
    # a correction term the analytical suggestion x*(L-x)*T
    # u_x = x*(L-x)*T(t) - 1/6*u_xxx*dx**2
    R = sm.diff(u(x,t), x) - (
        x*(L-x) - sm.Rational(1,6)*sm.diff(u(x,t), x, x, x)*dx**2
    # R is a polynomial: force all coefficients to vanish.
    # Turn R to Poly to extract coefficients:
    R = sm.poly(R, x)
    coeff = R.all_coeffs()
    s = sm.solve(coeff, a[1:])  # a[0] is not present in R
    # s is dictionary with a[i] as keys
    # Fix a[0] as 1
    s[a[0]] = 1
    X = lambda x: sm.simplify(sum(s[a[i]]*x**i for i in range(4))
    u = lambda x, t: X(x)*T(t)
    print 'u:', u(x,t)
```

The next step is to find the source term `f_e` by inserting `u_e` in th Thereafter, turn `u`, `f`, and the time derivative of `u` into plain Python fu as in a), and then wrap these functions in new functions `I`, `V`, and `f`, w right signature as required by the `solver` function. Set parameters as in check that the solution is exact to machine precision at each time level u appropriate `user_action` function.

Filename: `wave1D_n0_test_cubic.py`.

10   Analysis of the difference equations

10.1   Properties of the solution of the wave equation

he wave equation

$$\frac{\partial^2 u}{\partial t^2} = c^2 \frac{\partial^2 u}{\partial x^2}$$

as solutions of the form

$$u(x,t) = g_R(x - ct) + g_L(x + ct), \tag{68}$$

or any functions g_R and g_L sufficiently smooth to be differentiated twice. The
esult follows from inserting (68) in the wave equation. A function of the form
$_R(x - ct)$ represents a signal moving to the right in time with constant velocity
This feature can be explained as follows. At time $t = 0$ the signal looks like
$_R(x)$. Introducing a moving x axis with coordinates $\xi = x - ct$, we see the
unction $g_R(\xi)$ is "at rest" in the ξ coordinate system, and the shape is always the
ame. Say the $g_R(\xi)$ function has a peak at $\xi = 0$. This peak is located at $x = ct$,
hich means that it moves with the velocity $dx/dt = c$ in the x coordinate
/stem. Similarly, $g_L(x + ct)$ is a function initially with shape $g_L(x)$ that moves
1 the negative x direction with constant velocity c (introduce $\xi = x + ct$, look
t the point $\xi = 0$, $x = -ct$, which has velocity $dx/dt = -c$).
With the particular initial conditions

$$u(x,0) = I(x), \quad \frac{\partial}{\partial t} u(x,0) = 0,$$

e get, with u as in (68),

$$g_R(x) + g_L(x) = I(x), \quad -cg_R'(x) + cg_L'(x) = 0,$$

hich have the solution $g_R = g_L = I/2$, and consequently

$$u(x,t) = \frac{1}{2} I(x - ct) + \frac{1}{2} I(x + ct). \tag{69}$$

he interpretation of (69) is that the initial shape of u is split into two parts,
ach with the same shape as I but half of the initial amplitude. One part is
raveling to the left and the other one to the right.
The solution has two important physical features: constant amplitude of the
ft and right wave, and constant velocity of these two waves. It turns out that
he numerical solution will also preserve the constant amplitude, but the velocity
epends on the mesh parameters Δt and Δx.
The solution (69) will be influenced by boundary conditions when the parts
$I(x - ct)$ and $\frac{1}{2} I(x + ct)$ hit the boundaries and get, e.g., reflected back into
he domain. However, when $I(x)$ is nonzero only in a small part in the middle of
he spatial domain $[0, L]$, which means that the boundaries are placed far away

from the initial disturbance of u, the solution (69) is very clearly obser
simulation.
A useful representation of solutions of wave equations is a linear com
of sine and/or cosine waves. Such a sum of waves is a solution if the g
PDE is linear and each sine or cosine wave fulfills the equation. To ease an
calculations by hand we shall work with complex exponential functions
of real-valued sine or cosine functions. The real part of complex exp
will typically be taken as the physical relevant quantity (whenever a p
relevant quantity is strictly needed). The idea now is to build $I(x)$ of c
wave components e^{ikx}:

$$I(x) \approx \sum_{k \in K} b_k e^{ikx}.$$

Here, k is the frequency of a component, K is some set of all the discrete
needed to approximate $I(x)$ well, and b_k are constants that must be det
We will very seldom need to compute the b_k coefficients: most of the ins
look for and the understanding of the numerical methods we want to e
come from investigating how the PDE and the scheme treat a single con
e^{ikx} wave.
Letting the number of k values in K tend to infinity makes the s
converge to $I(x)$, and this sum is known as a *Fourier series* represent
$I(x)$. Looking at (69), we see that the solution $u(x, t)$, when $I(x)$ is rep
as in (70), is also built of basic complex exponential wave component
form $e^{ik(x \pm ct)}$ according to

$$u(x,t) = \frac{1}{2} \sum_{k \in K} b_k e^{ik(x-ct)} + \frac{1}{2} \sum_{k \in K} b_k e^{ik(x+ct)}.$$

It is common to introduce the frequency in time $\omega = kc$ and assume tha
is a sum of basic wave components written as $e^{ikx - \omega t}$. (Observe that i
such a wave component in the governing PDE reveals that $\omega^2 = k^2 c^2$, or
reflecting the two solutions: one $(+kc)$ traveling to the right and the othe
traveling to the left.)

10.2   More precise definition of Fourier representati

The quick intuitive introduction above to representing a function by a
sine and cosine waves suffices as background for the forthcoming mat
analyzing a single wave component. However, to understand all details
different wave components sum up to the analytical and numerical sol
more precise mathematical treatment is helpful and therefore summarize
It is well known that periodic functions can be represented by Fourie
A generalization of the Fourier series idea to non-periodic functions def
the real line is the *Fourier transform*:

$$I(x) = \int_{-\infty}^{\infty} A(k)e^{ikx}dk, \tag{72}$$

$$A(k) = \int_{-\infty}^{\infty} I(x)e^{-ikx}dx. \tag{73}$$

he function $A(k)$ reflects the weight of each wave component e^{ikx} in an infinite m of such wave components. That is, $A(k)$ reflects the frequency content in he function $I(x)$. Fourier transforms are particularly fundamental for analyzing nd understanding time-varying signals.

The solution of the linear 1D wave PDE can be expressed as

$$u(x,t) = \int_{-\infty}^{\infty} A(k)e^{i(kx-\omega(k)t)}dx.$$

In a finite difference method, we represent u by a mesh function u_q^n, where n ounts temporal mesh points and q counts the spatial ones (the usual counter r spatial points, i, is here already used as imaginary unit). Similarly, $I(x)$ approximated by the mesh function I_q, $q = 0, \dots, N_x$. On a mesh, it does ot make sense to work with wave components e^{ikx} for very large k, because he shortest possible sine or cosine wave that can be represented on a mesh ith spacing Δx is the wave with wavelength $2\Delta x$ (the sine/cosine signal mps up and down between each mesh point). The corresponding k value is $= 2\pi/(2\Delta x) = \pi/\Delta x$, known as the *Nyquist frequency*. Within the range of elevant frequencies $(0, \pi/\Delta x]$ one defines the discrete Fourier transform[16], using $_x + 1$ discrete frequencies:

$$I_q = \frac{1}{N_x + 1}\sum_{k=0}^{N_x} A_k e^{i2\pi kj/(N_x+1)}, \quad i = 0, \dots, N_x, \tag{74}$$

$$A_k = \sum_{q=0}^{N_x} I_q e^{-i2\pi kq/(N_x+1)}, \quad k = 0, \dots, N_x + 1. \tag{75}$$

he A_k values is the discrete Fourier transform of the I_q values, and the latter re the inverse discrete Fourier transform of the A_k values.

The discrete Fourier transform is efficiently computed by the *Fast Fourier ansform* algorithm. For a real function $I(x)$ the relevant Python code for omputing and plotting the discrete Fourier transform appears in the example elow.

```
import numpy as np
from numpy import sin

def I(x):
```

---
[16]http://en.wikipedia.org/wiki/Discrete_Fourier_transform

```
    return sin(2*pi*x) + 0.5*sin(4*pi*x) + 0.1*sin(6*pi*x)

# Mesh
L = 10; Nx = 100
x = np.linspace(0, L, Nx+1)
dx = L/float(Nx)

# Discrete Fourier transform
A = np.fft.rfft(I(x))
A_amplitude = np.abs(A)

# Compute the corresponding frequencies
freqs = np.linspace(0, pi/dx, A_amplitude.size)

import matplotlib.pyplot as plt
plt.plot(freqs, A_amplitude)
plt.show()
```

10.3 Stability

The scheme

$$[D_t D_t u = c^2 D_x D_x u]_q^n$$

for the wave equation $u_t = c^2 u_{xx}$ allows basic wave components

$$u_q^n = e^{i(kx_q - \tilde{\omega}t_n)}$$

as solution, but it turns out that the frequency in time, $\tilde{\omega}$, is not equa exact $\omega = kc$. The idea now is to study how the scheme treats an arbitra component with a given k. We ask two key questions:

- How accurate is $\tilde{\omega}$ compared to ω?

- Does the amplitude of such a wave component preserve its (unit) am as it should, or does it get amplified or damped in time (due to a $\tilde{\omega}$)?

The following analysis will answer these questions. Note the need for us counter for the mesh point in x direction since i is already used as the in unit (in this analysis).

Preliminary results. A key result needed in the investigations is th difference approximation of a second-order derivative acting on a compl component:

$$[D_t D_t e^{i\omega t}]^n = -\frac{4}{\Delta t^2}\sin^2\left(\frac{\omega \Delta t}{2}\right)e^{i\omega n\Delta t}.$$

By just changing symbols ($\omega \to k$, $t \to x$, $n \to q$) it follows that

$$[D_x D_x e^{ikx}]_q = -\frac{4}{\Delta x^2}\sin^2\left(\frac{k\Delta x}{2}\right)e^{ikq\Delta x}.$$

Numerical wave propagation. Inserting a basic wave component $u_q^n = e^{i(kx_q - \tilde{\omega} t_n)}$ in (76) results in the need to evaluate two expressions:

$$[D_t D_t e^{ikx} e^{-i\tilde{\omega} t}]_q^n = [D_t D_t e^{-i\tilde{\omega} t}]^n e^{ikq\Delta x}$$

$$= -\frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) e^{-i\tilde{\omega} n\Delta t} e^{ikq\Delta x} \qquad (77)$$

$$[D_x D_x e^{ikx} e^{-i\tilde{\omega} t}]_q^n = [D_x D_x e^{ikx}]_q e^{-i\tilde{\omega} n\Delta t}$$

$$= -\frac{4}{\Delta x^2} \sin^2\left(\frac{k\Delta x}{2}\right) e^{ikq\Delta x} e^{-i\tilde{\omega} n\Delta t}. \qquad (78)$$

Then the complete scheme,

$$[D_t D_t e^{ikx} e^{-i\tilde{\omega} t} = c^2 D_x D_x e^{ikx} e^{-i\tilde{\omega} t}]_q^n$$

leads to the following equation for the unknown numerical frequency $\tilde{\omega}$ (after dividing by $-e^{ikx} e^{-i\tilde{\omega} t}$):

$$\frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = c^2 \frac{4}{\Delta x^2} \sin^2\left(\frac{k\Delta x}{2}\right),$$

or

$$\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = C^2 \sin^2\left(\frac{k\Delta x}{2}\right), \qquad (79)$$

where

$$C = \frac{c\Delta t}{\Delta x} \qquad (80)$$

is the Courant number. Taking the square root of (79) yields

$$\sin\left(\frac{\tilde{\omega}\Delta t}{2}\right) = C \sin\left(\frac{k\Delta x}{2}\right), \qquad (81)$$

Since the exact ω is real it is reasonable to look for a real solution $\tilde{\omega}$ of (81). The right-hand side of (81) must then be in $[-1, 1]$ because the sine function on the left-hand side has values in $[-1, 1]$ for real $\tilde{\omega}$. The sine function on the right-hand side can attain the value 1 when

$$\frac{k\Delta x}{2} = m\frac{\pi}{2}, \quad m \in \mathbb{Z}.$$

With $m = 1$ we have $k\Delta x = \pi$, which means that the wavelength $\lambda = 2\pi/k$ becomes $2\Delta x$. This is the absolutely shortest wavelength that can be represented on the mesh: the wave jumps up and down between each mesh point. Larger values of $|m|$ are irrelevant since these correspond to k values whose waves are too short to be represented on a mesh with spacing Δx. For the shortest possible wave in the mesh, $\sin(k\Delta x/2) = 1$, and we must require

$$C \leq 1.$$

Consider a right-hand side in (81) of magnitude larger than unit solution $\tilde{\omega}$ of (81) must then be a complex number $\tilde{\omega} = \tilde{\omega}_r + i\tilde{\omega}_i$ beca sine function is larger than unity for a complex argument. One can sh for any ω_i there will also be a corresponding solution with $-\omega_i$. The cor with $\omega_i > 0$ gives an amplification factor $e^{\omega_i t}$ that grows exponentially We cannot allow this and must therefore require $C \leq 1$ as a *stability cri*

> **Remark.**
>
> For smoother wave components with longer wave lengths per lengt (82) can in theory be relaxed. However, small round-off errors are al present in a numerical solution and these vary arbitrarily from mesh to mesh point and can be viewed as unavoidable noise with wavele $2\Delta x$. As explained, $C > 1$ will for this very small noise lead to expone growth of the shortest possible wave component in the mesh. This will therefore grow with time and destroy the whole solution.

10.4 Numerical dispersion relation

Equation (81) can be solved with respect to $\tilde{\omega}$:

$$\tilde{\omega} = \frac{2}{\Delta t} \sin^{-1}\left(C \sin\left(\frac{k\Delta x}{2}\right)\right).$$

The relation between the numerical frequency $\tilde{\omega}$ and the other paramet Δx, and Δt is called a *numerical dispersion relation*. Correspondingly, ω the *analytical dispersion relation*.

The special case $C = 1$ deserves attention since then the right-hand (83) reduces to

$$\frac{2}{\Delta t} \frac{k\Delta x}{2} = \frac{1}{\Delta t} \frac{\omega\Delta x}{c} = \frac{\omega}{C} = \omega.$$

That is, $\tilde{\omega} = \omega$ and the numerical solution is exact at all mesh points rega Δx and Δt! This implies that the numerical solution method is also an ar solution method, at least for computing u at discrete points (the nu method says nothing about the variation of u *between* the mesh poin employing the common linear interpolation for extending the discrete : gives a curve that deviates from the exact one).

For a closer examination of the error in the numerical dispersion when $C < 1$, we can study $\tilde{\omega} - \omega$, $\tilde{\omega}/\omega$, or the similar error measures velocity: $\tilde{c} - c$ and $\tilde{c}/c$, where $c = \omega/k$ and $\tilde{c} = \tilde{\omega}/k$. It appears that th convenient expression to work with is $\tilde{c}/c$:

$$\frac{\tilde{c}}{c} = \frac{1}{Cp}\sin^{-1}(C\sin p),$$

ith $p = k\Delta x/2$ as a non-dimensional measure of the spatial frequency. In ssence, p tells how many spatial mesh points we have per wave length in space f the wave component with frequency k (the wave length is $2\pi/k$). That is, p eflects how well the spatial variation of the wave component is resolved in the nesh. Wave components with wave length less than $2\Delta x$ ($2\pi/k < 2\Delta x$) are not isible in the mesh, so it does not make sense to have $p > \pi/2$.

We may introduce the function $r(C, p) = \tilde{c}/c$ for further investigation of numerical errors in the wave velocity:

$$r(C, p) = \frac{1}{Cp}\sin^{-1}(C\sin p), \quad C \in (0, 1], \ p \in (0, \pi/2]. \tag{84}$$

his function is very well suited for plotting since it combines several parameters n the problem into a dependence on two non-dimensional numbers, C and p.


igure 6: The fractional error in the wave velocity for different Courant numbers.

Defining

```
def r(C, p):
    return 2/(C*p)*asin(C*sin(p))
```

we can plot $r(C, p)$ as a function of p for various values of C, see Figure that the shortest waves have the most erroneous velocity, and that shor move more slowly than they should.

With `sympy` we can also easily make a Taylor series expansion in cretization parameter p:

```
>>> C, p = symbols('C p')
>>> rs = r(C, p).series(p, 0, 7)
>>> print rs
1 - p**2/6 + p**4/120 - p**6/5040 + C**2*p**2/6 -
C**2*p**4/12 + 13*C**2*p**6/720 + 3*C**4*p**4/40 -
C**4*p**6/16 + 5*C**6*p**6/112 + O(p**7)
>>> # Factorize each term and drop the remainder O(...) term
>>> rs_factored = [factor(term) for term in rs.lseries(p)]
>>> rs_factored = sum(rs_factored)
>>> print rs_factored
p**6*(C - 1)*(C + 1)*(225*C**4 - 90*C**2 + 1)/5040 +
p**4*(C - 1)*(C + 1)*(3*C - 1)*(3*C + 1)/120 +
p**2*(C - 1)*(C + 1)/6 + 1
```

We see that $C = 1$ makes all the terms in `rs_factored` vanish, except one. Since we already know that the numerical solution is exact for C : remaining terms in the Taylor series expansion will also contain factors $\cdot$ and cancel for $C = 1$.

From the `rs_factored` expression above we also see that the leadir terms in the error of this series expansion are

$$\frac{1}{6}\left(\frac{k\Delta x}{2}\right)^2(C^2 - 1) = \frac{k^2}{24}\left(c^2\Delta t^2 - \Delta x^2\right),$$

pointing to an error $\mathcal{O}(\Delta t^2, \Delta x^2)$, which is compatible with the error difference approximations ($D_t D_t$ and $D_x D_x$).

10.5 Extending the analysis to 2D and 3D

The typical analytical solution of a 2D wave equation

$$u_{tt} = c^2(u_{xx} + u_{yy}),$$

is a wave traveling in the direction of $\boldsymbol{k} = k_x\boldsymbol{i} + k_y\boldsymbol{j}$, where $\boldsymbol{i}$ and $\boldsymbol{j}$: vectors in the x and y directions, respectively. Such a wave can be expr

$$u(x, y, t) = g(k_x x + k_y y - kct)$$

for some twice differentiable function g, or with $\omega = kc$, $k = |\boldsymbol{k}|$:

$$u(x, y, t) = g(k_x x + k_y y - \omega t).$$

We can in particular build a solution by adding complex Fourier compo the form

$$\exp\left(i(k_x x + k_y y - \omega t)\right).$$

A discrete 2D wave equation can be written as

$$[D_t D_t u = c^2(D_x D_x u + D_y D_y u)]_{q,r}^n .\tag{86}$$

his equation admits a Fourier component

$$u_{q,r}^n = \exp\left(i(k_x q \Delta x + k_y r \Delta y - \tilde{\omega} n \Delta t)\right),\tag{87}$$

s solution. Letting the operators $D_t D_t$, $D_x D_x$, and $D_y D_y$ act on $u_{q,r}^n$ from (87)
ansforms (86) to

$$\frac{4}{\Delta t^2} \sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = c^2 \frac{4}{\Delta x^2} \sin^2\left(\frac{k_x \Delta x}{2}\right) + c^2 \frac{4}{\Delta y^2} \sin^2\left(\frac{k_y \Delta y}{2}\right) .\tag{88}$$

r

$$\sin^2\left(\frac{\tilde{\omega}\Delta t}{2}\right) = C_x^2 \sin^2 p_x + C_y^2 \sin^2 p_y,\tag{89}$$

here we have eliminated the factor 4 and introduced the symbols

$$C_x = \frac{c^2 \Delta t^2}{\Delta x^2}, \quad C_y = \frac{c^2 \Delta t^2}{\Delta y^2}, \quad p_x = \frac{k_x \Delta x}{2}, \quad p_y = \frac{k_y \Delta y}{2} .$$

or a real-valued $\tilde{\omega}$ the right-hand side must be less than or equal to unity in
bsolute value, requiring in general that

$$C_x^2 + C_y^2 \leq 1 .\tag{90}$$

his gives the stability criterion, more commonly expressed directly in an
nequality for the time step:

$$\Delta t \leq \frac{1}{c} \left(\frac{1}{\Delta x^2} + \frac{1}{\Delta y^2}\right)^{-1/2}\tag{91}$$

similar, straightforward analysis for the 3D case leads to

$$\Delta t \leq \frac{1}{c} \left(\frac{1}{\Delta x^2} + \frac{1}{\Delta y^2} + \frac{1}{\Delta z^2}\right)^{-1/2}\tag{92}$$

 the case of a variable coefficient $c^2 = c^2(\boldsymbol{x})$, we must use the worst-case value

$$\bar{c} = \sqrt{\max_{\boldsymbol{x} \in \Omega} c^2(\boldsymbol{x})}\tag{93}$$

 the stability criteria. Often, especially in the variable wave velocity case, it is
ise to introduce a safety factor $\beta \in (0, 1]$ too:

$$\Delta t \leq \beta \frac{1}{\bar{c}} \left(\frac{1}{\Delta x^2} + \frac{1}{\Delta y^2} + \frac{1}{\Delta z^2}\right)^{-1/2}\tag{94}$$

The exact numerical dispersion relations in 2D and 3D becomes, for constant

$$\tilde{\omega} = \frac{2}{\Delta t} \sin^{-1}\left(\left(C_x^2 \sin^2 p_x + C_y^2 \sin_y^p\right)^{\frac{1}{2}}\right),$$
$$\tilde{\omega} = \frac{2}{\Delta t} \sin^{-1}\left(\left(C_x^2 \sin^2 p_x + C_y^2 \sin_y^p + C_z^2 \sin_z^p\right)^{\frac{1}{2}}\right) .$$

We can visualize the numerical dispersion error in 2D much like we di
To this end, we need to reduce the number of parameters in $\tilde{\omega}$. The dire
the wave is parameterized by the polar angle θ, which means that

$$k_x = k \sin\theta, \quad k_y = k \cos\theta .$$

A simplification is to set $\Delta x = \Delta y = h$. Then $C_x = C_y = c\Delta t/h$, which
C. Also,

$$p_x = \frac{1}{2}kh\cos\theta, \quad p_y = \frac{1}{2}kh\sin\theta .$$

The numerical frequency $\tilde{\omega}$ is now a function of three parameters:

- C reflecting the number cells a wave is displaced during a time st

- kh reflecting the number of cells per wave length in space

- θ expressing the direction of the wave

We want to visualize the error in the numerical frequency. To avoid ha
as a free parameter in $\tilde{\omega}$, we work with $\tilde{c}/c$, because the fraction $2/\Delta t$
rewritten as

$$\frac{2}{kc\Delta t} = \frac{2}{2kc\Delta t h/h} = \frac{1}{Ckh},$$

and

$$\frac{\tilde{c}}{c} = \frac{1}{Ckh} \sin^{-1}\left(C\left(\sin^2(\frac{1}{2}kh\cos\theta) + \sin^2(\frac{1}{2}kh\sin\theta)\right)^{\frac{1}{2}}\right) .$$

We want to visualize this quantity as a function of kh and θ for some v
$C \leq 1$. It is instructive to make color contour plots of $1 - \tilde{c}/c$ in *polar coo*
with θ as the angular coordinate and kh as the radial coordinate.

The stability criterion (90) becomes $C \leq C_{\max} = 1/\sqrt{2}$ in the pre
case with the C defined above. Let us plot $1 - \tilde{c}/c$ in polar coordin
$C_{\max}, 0.9C_{\max}, 0.5C_{\max}, 0.2C_{\max}$. The program below does the somewha
work in Matplotlib, and the result appears in Figure 7. From the fig
clearly see that the maximum C value gives the best results, and tha
whose propagation direction makes an angle of 45 degrees with an axis
most accurate.

```
def dispersion_relation_2D(kh, theta, C):
    arg = C*sqrt(sin(0.5*kh*cos(theta))**2 +
                 sin(0.5*kh*sin(theta))**2)
    c_frac = 2./(C*kh)*arcsin(arg)

    return c_frac

from numpy import exp, sin, cos, linspace, \
    pi, meshgrid, arcsin, sqrt
r = kh = linspace(0.001, pi, 101)
theta = linspace(0, 2*pi, 51)
r, theta = meshgrid(r, theta)

# Make 2x2 filled contour plots for 4 values of C
import matplotlib.pyplot as plt
C_max = 1/sqrt(2)
C = [[C_max, 0.9*C_max], [0.5*C_max, 0.2*C_max]]
fix, axes = plt.subplots(2, 2, subplot_kw=dict(polar=True))
for row in range(2):
    for column in range(2):
        error = 1 - dispersion_relation_2D(
            kh, theta, C[row][column])
        print error.min(), error.max()
        cax = axes[row][column].contourf(
            theta, r, error, 50, vmin=0, vmax=0.36)
        axes[row][column].set_xticks([])
        axes[row][column].set_yticks([])

# Add colorbar to the last plot
cbar = plt.colorbar(cax)
cbar.ax.set_ylabel('error in wave velocity')
plt.savefig('disprel2D.png')
plt.savefig('disprel2D.pdf')
plt.show()
```


Figure 7: Error in numerical dispersion in 2D.

11   Finite difference methods for 2D and 3D equations

A natural next step is to consider extensions of the methods for vari
ants of the one-dimensional wave equation to two-dimensional (2D) an
dimensional (3D) versions of the wave equation.

11.1   Multi-dimensional wave equations

The general wave equation in d space dimensions, with constant wave ve
can be written in the compact form

$$\frac{\partial^2 u}{\partial t^2} = c^2 \nabla^2 u \text{ for } \boldsymbol{x} \in \Omega \subset \mathbb{R}^d, \ t \in (0, T].$$

In a 2D problem $(d = 2)$,

$$\nabla^2 u = \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2},$$

while in three space dimensions $(d = 3)$,

$$\nabla^2 u = \frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} + \frac{\partial^2 u}{\partial z^2}.$$

Many applications involve variable coefficients, and the general wave equation
in d dimensions is in this case written as

$$\varrho\frac{\partial^2 u}{\partial t^2} = \nabla \cdot (q\nabla u) + f \text{ for } \boldsymbol{x} \in \Omega \subset \mathbb{R}^d, \ t \in (0, T], \tag{98}$$

which in 2D becomes

$$\varrho(x,y)\frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x}\left(q(x,y)\frac{\partial u}{\partial x}\right) + \frac{\partial}{\partial y}\left(q(x,y)\frac{\partial u}{\partial y}\right) + f(x,y,t). \tag{99}$$

To save some writing and space we may use the index notation, where subscript
x, y, or z means differentiation with respect to that coordinate. For example,

$$\frac{\partial^2 u}{\partial t^2} = u_{tt},$$

$$\frac{\partial}{\partial y}\left(q(x,y)\frac{\partial u}{\partial y}\right) = (qu_y)_y.$$

The 3D versions of the two model PDEs, with and without variable coefficients,
can with now with the aid of the index notation for differentiation be stated as

$$u_{tt} = c^2(u_{xx} + u_{yy} + u_{zz}) + f, \tag{100}$$

$$\varrho u_{tt} = (qu_x)_x + (qu_z)_z + (qu_z)_z + f. \tag{101}$$

At *each point* of the boundary $\partial\Omega$ of Ω we need *one* boundary condition
involving the unknown u. The boundary conditions are of three principal types:

1. u is prescribed ($u = 0$ or a known time variation for an incoming wave),

2. $\partial u/\partial n = \boldsymbol{n} \cdot \nabla u$ prescribed (zero for reflecting boundaries),

3. an open boundary condition (also called radiation condition) is specified to let waves travel undisturbed out of the domain, see Exercise ?? for details.

All the listed wave equations with *second-order* derivatives in time need *two*
initial conditions:

1. $u = I$,

2. $u_t = V$.

11.2 Mesh

We introduce a mesh in time and in space. The mesh in time consists
points

$$t_0 = 0 < t_1 < \cdots < t_{N_t},$$

often with a constant spacing $\Delta t = t_{n+1} - t_n$, $n \in \mathcal{I}_t^-$.

Finite difference methods are easy to implement on simple rectangle-
shaped domains. More complicated shapes of the domain require subst
more advanced techniques and implementational efforts. On a recta
box-shaped domain mesh points are introduced separately in the variou
directions:

$$x_0 < x_1 < \cdots < x_{N_x} \text{ in } x \text{ direction,}$$

$$y_0 < y_1 < \cdots < y_{N_y} \text{ in } y \text{ direction,}$$

$$z_0 < z_1 < \cdots < z_{N_z} \text{ in } z \text{ direction}.$$

We can write a general mesh point as (x_i, y_j, z_k, t_n), with $i \in \mathcal{I}_x$, $j \in \mathcal{I}_y$
and $n \in \mathcal{I}_t$.

It is a very common choice to use constant mesh spacings: $\Delta x = x_i$
$i \in \mathcal{I}_x^-$, $\Delta y = y_{j+1} - y_j$, $j \in \mathcal{I}_y^-$, and $\Delta z = z_{k+1} - z_k$, $k \in \mathcal{I}_z^-$. With equ
spacings one often introduces $h = \Delta x = \Delta y = \Delta z$.

The unknown u at mesh point (x_i, y_j, z_k, t_n) is denoted by $u_{i,j,k}^n$.
problems we just skip the z coordinate (by assuming no variation
direction: $\partial/\partial z = 0$) and write $u_{i,j}^n$.

11.3 Discretization

Two- and three-dimensional wave equations are easily discretized by ass
building blocks for discretization of 1D wave equations, because th
dimensional versions just contain terms of the same type that occurs in

Discretizing the PDEs. Equation (100) can be discretized as

$$[D_t D_t u = c^2(D_x D_x u + D_y D_y u + D_z D_z u) + f]_{i,j,k}^n.$$

A 2D version might be instructive to write out in detail:

$$[D_t D_t u = c^2(D_x D_x u + D_y D_y u) + f]_{i,j,k}^n,$$

which becomes

$$\frac{u_{i,j}^{n+1} - 2u_{i,j}^n + u_{i,j}^{n-1}}{\Delta t^2} = c^2\frac{u_{i+1,j}^n - 2u_{i,j}^n + u_{i-1,j}^n}{\Delta x^2} + c^2\frac{u_{i,j+1}^n - 2u_{i,j}^n + u_{i,j}^n}{\Delta y^2}$$

ssuming as usual that all values at the time levels n and $n-1$ are known, we
an solve for the only unknown $u_{i,j}^{n+1}$. The result can be compactly written as

$$u_{i,j}^{n+1} = 2u_{i,j}^n + u_{i,j}^{n-1} + c^2\Delta t^2[D_xD_xu + D_yD_yu]_{i,j}^n. \tag{103}$$

As in the 1D case, we need to develop a special formula for $u_{i,j}^1$ where we
ombine the general scheme for $u_{i,j}^{n+1}$, when $n=0$, with the discretization of the
itial condition:

$$[D_{2t}u = V]_{i,j}^0 \quad \Rightarrow \quad u_{i,j}^{-1} = u_{i,j}^1 - 2\Delta tV_{i,j}.$$

he result becomes, in compact form,

$$u_{i,j}^{n+1} = u_{i,j}^n - 2\Delta V_{i,j} + \frac{1}{2}c^2\Delta t^2[D_xD_xu + D_yD_yu]_{i,j}^n. \tag{104}$$

The PDE (101) with variable coefficients is discretized term by term using
he corresponding elements from the 1D case:

$$[\varrho D_tD_tu = (D_x\overline{q}^xD_xu + D_y\overline{q}^yD_yu + D_z\overline{q}^zD_zu) + f]_{i,j,k}^n. \tag{105}$$

hen written out and solved for the unknown $u_{i,j,k}^{n+1}$, one gets the scheme

$$\begin{aligned}
u_{i,j,k}^{n+1} &= -u_{i,j,k}^{n-1} + 2u_{i,j,k}^n + \\
&= \frac{1}{\varrho_{i,j,k}}\frac{1}{\Delta x^2}(\frac{1}{2}(q_{i,j,k} + q_{i+1,j,k})(u_{i+1,j,k}^n - u_{i,j,k}^n) - \\
&\quad \frac{1}{2}(q_{i-1,j,k} + q_{i,j,k})(u_{i,j,k}^n - u_{i-1,j,k}^n)) + \\
&= \frac{1}{\varrho_{i,j,k}}\frac{1}{\Delta x^2}(\frac{1}{2}(q_{i,j,k} + q_{i,j+1,k})(u_{i,j+1,k}^n - u_{i,j,k}^n) - \\
&\quad \frac{1}{2}(q_{i,j-1,k} + q_{i,j,k})(u_{i,j,k}^n - u_{i,j-1,k}^n)) + \\
&= \frac{1}{\varrho_{i,j,k}}\frac{1}{\Delta x^2}(\frac{1}{2}(q_{i,j,k} + q_{i,j,k+1})(u_{i,j,k+1}^n - u_{i,j,k}^n) - \\
&\quad \frac{1}{2}(q_{i,j,k-1} + q_{i,j,k})(u_{i,j,k}^n - u_{i,j,k-1}^n)) + \\
&\quad + \quad \Delta t^2 f_{i,j,k}^n.
\end{aligned}$$

Also here we need to develop a special formula for $u_{i,j,k}^1$ by combining the
cheme for $n=0$ with the discrete initial condition, which is just a matter of
iserting $u_{i,j,k}^{-1} = u_{i,j,k}^1 - 2\Delta tV_{i,j,k}$ in the scheme and solving for $u_{i,j,k}^1$.

Iandling boundary conditions where is u known. The schemes listed
bove are valid for the internal points in the mesh. After updating these, we
eed to visit all the mesh points at the boundaries and set the prescribed u
alue.

Discretizing the Neumann condition. The condition $\partial u/\partial n = 0$
plemented in 1D by discretizing it with a $D_{2x}u$ centered difference, and th
eliminating the fictitious u point outside the mesh by using the general
at the boundary point. Alternatively, one can introduce ghost cells and
a ghost value to for use in the Neumann condition. Exactly the same i
reused in multi dimensions.

Consider $\partial u/\partial n = 0$ at a boundary $y = 0$. The normal direction is
$-y$ direction, so

$$\frac{\partial u}{\partial n} = -\frac{\partial u}{\partial y},$$

and we set

$$[-D_{2y}u = 0]_{i,0}^n \quad \Rightarrow \quad \frac{u_{i,1}^n - u_{i,-1}^n}{2\Delta y} = 0.$$

From this it follows that $u_{i,-1}^n = u_{i,1}^n$. The discretized PDE at the b
point $(i,0)$ reads

$$\frac{u_{i,0}^{n+1} - 2u_{i,0}^n + u_{i,0}^{n-1}}{\Delta t^2} = c^2\frac{u_{i+1,0}^n - 2u_{i,0}^n + u_{i-1,0}^n}{\Delta x^2} + c^2\frac{u_{i,1}^n - 2u_{i,0}^n + u_{i,-}^n}{\Delta y^2}$$

We can then just insert $u_{i,1}^1$ for $u_{i,-1}^n$ in this equation and then solve
boundary value $u_{i,0}^{n+1}$ as done in 1D.

From these calculations, we see a pattern: the general scheme ap
the boundary $j = 0$ too if we just replace $j-1$ by $j+1$. Such a pa
particularly useful for implementations. The details follow from the ex
1D case in Section 6.3.

The alternative approach to eliminating fictitious values outside the
to have $u_{i,-1}^n$ available as a ghost value. The mesh is extended with or
line (2D) or plane (3D) of ghost cells at a Neumann boundary. In the
example it means that we need a line ghost cells below the y axis. Th
values must be updated according to $u_{i,-1}^{n+1} = u_{i,1}^{n+1}$.

12 Implementation

We shall now describe in detail various Python implementations for s
standard 2D, linear wave equation with constant wave velocity and $u = $
boundary. The wave equation is to be solved in the space-time domain Ω
where $\Omega = (0, L_x) \times (0, L_y)$ is a rectangular spatial domain. More precis
complete initial-boundary value problem is defined by

$$\begin{aligned}
u_t &= c^2(u_{xx} + u_{yy}) + f(x,y,t), & (x,y) \in \Omega, \ t \in (0,T], \\
u(x,y,0) &= I(x,y), & (x,y) \in \Omega, \\
u_t(x,y,0) &= V(x,y), & (x,y) \in \Omega, \\
u &= 0, & (x,y) \in \partial\Omega, \ t \in (0,T],
\end{aligned}$$

here $\partial\Omega$ is the boundary of Ω, in this case the four sides of the rectangle $[0, L_x] \times [0, L_y]$: $x = 0$, $x = L_x$, $y = 0$, and $y = L_y$.

The PDE is discretized as

$$[D_t D_t u = c^2(D_x D_x u + D_y D_y u) + f]_{i,j}^n,$$

which leads to an explicit updating formula to be implemented in a program:

$$u^{n+1} = -u_{i,j}^{n-1} + 2u_{i,j}^n +$$
$$C_x^2(u_{i+1,j}^n - 2u_{i,j}^n + u_{i-1,j}^n) + C_y^2(u_{i,j+1}^n - 2u_{i,j}^n + u_{i,j-1}^n) + \Delta t^2 f_{i,j}^n, \tag{110}$$

for all interior mesh points $i \in \mathcal{I}_x^i$ and $j \in \mathcal{I}_y^i$, and for $n \in \mathcal{I}_t^+$. The constants C_x and C_y are defined as

$$C_x = c\frac{\Delta t}{\Delta x}, \quad C_x = c\frac{\Delta t}{\Delta y}.$$

At the boundary we simply set $u_{i,j}^{n+1} = 0$ for $i = 0$, $j = 0, \ldots, N_y$; $i = N_x$, $j = 0, \ldots, N_y$; $j = 0$, $i = 0, \ldots, N_x$; and $j = N_y$, $i = 0, \ldots, N_x$. For the first step, $n = 0$, (111) is combined with the discretization of the initial condition $u_t = V$, $[D_{2t}u = V]_{i,j}^0$ to obtain a special formula for $u_{i,j}^1$ at the interior mesh points:

$$u^1 = u_{i,j}^0 + \Delta t V_{i,j} +$$
$$\frac{1}{2}C_x^2(u_{i+1,j}^0 - 2u_{i,j}^0 + u_{i-1,j}^0) + \frac{1}{2}C_y^2(u_{i,j+1}^0 - 2u_{i,j}^0 + u_{i,j-1}^0) + \frac{1}{2}\Delta t^2 f_{i,j}^n, \tag{111}$$

The algorithm is very similar to the one in 1D:

1. Set initial condition $u_{i,j}^0 = I(x_i, y_j)$

2. Compute $u_{i,j}^1$ from (111)

3. Set $u_{i,j}^1 = 0$ for the boundaries $i = 0, N_x$, $j = 0, N_y$

4. For $n = 1, 2, \ldots, N_t$:

    (a) Find $u_{i,j}^{n+1}$ from (111) for all internal mesh points, $i \in \mathcal{I}_x^i$, $j \in \mathcal{I}_y^i$

    (b) Set $u_{i,j}^{n+1} = 0$ for the boundaries $i = 0, N_x$, $j = 0, N_y$

2.1 Scalar computations

The `solver` function for a 2D case with constant wave velocity and $u = 0$ as boundary condition follows the setup from the similar function for the 1D case in `wave1D_u0.py`, but there are a few necessary extensions. The code is in the program `wave2D_u0.py`[17].

[17]http://tinyurl.com/jvzzcfn/wave/wave2D_u0/wave2D_u0.py

65

Domain and mesh. The spatial domain is now $[0, L_x] \times [0, L_y]$, spec the arguments `Lx` and `Ly`. Similarly, the number of mesh points [in the directions, N_x and N_y, become the arguments `Nx` and `Ny`. In multi-dim problems it makes less sense to specify a Courant number as the wave is a vector and the mesh spacings may differ in the various spatial di We therefore give Δt explicitly. The signature of the `solver` function i

```
def solver(I, V, f, c, Lx, Ly, Nx, Ny, dt, T,
           user_action=None, version='scalar'):
```

Key parameters used in the calculations are created as

```
x = linspace(0, Lx, Nx+1)              # mesh points in x dir
y = linspace(0, Ly, Ny+1)              # mesh points in y dir
dx = x[1] - x[0]
dy = y[1] - y[0]
Nt = int(round(T/float(dt)))
t = linspace(0, N*dt, N+1)             # mesh points in time
Cx2 = (c*dt/dx)**2;  Cy2 = (c*dt/dy)**2    # help variables
dt2 = dt**2
```

Solution arrays. We store $u_{i,j}^{n+1}$, $u_{i,j}^n$, and $u_{i,j}^{n-1}$ in three two-dime arrays,

```
u   = zeros((Nx+1,Ny+1))    # solution array
u_1 = zeros((Nx+1,Ny+1))    # solution at t-dt
u_2 = zeros((Nx+1,Ny+1))    # solution at t-2*dt
```

where $u_{i,j}^{n+1}$ corresponds to `u[i,j]`, $u_{i,j}^n$ to `u_1[i,j]`, and $u_{i,j}^{n-1}$ to `u_2`

Index sets. It is also convenient to introduce the index sets (cf. Sect

```
Ix = range(0, u.shape[0])
Iy = range(0, u.shape[1])
It = range(0, t.shape[0])
```

Computing the solution. Inserting the initial condition `I` in `u_1` and a callback to the user in terms of the `user_action` function is a straight generalization of the 1D code from Section 1.6:

```
for i in Ix:
    for j in Iy:
        u_1[i,j] = I(x[i], y[j])

if user_action is not None:
    user_action(u_1, x, xv, y, yv, t, 0)
```

66

The `user_action` function has additional arguments compared to the 1D case. The arguments `xv` and `yv` fact will be commented upon in Section 12.2.

The key finite difference formula (103) for updating the solution at a time level is implemented in a separate function as

```
def advance_scalar(u, u_1, u_2, f, x, y, t, n, Cx2, Cy2, dt2,
                   V=None, step1=False):
    Ix = range(0, u.shape[0]);  Iy = range(0, u.shape[1])
    if step1:
        dt = sqrt(dt2)  # save
        Cx2 = 0.5*Cx2;  Cy2 = 0.5*Cy2; dt2 = 0.5*dt2  # redefine
        D1 = 1;  D2 = 0
    else:
        D1 = 2;  D2 = 1
    for i in Ix[1:-1]:
        for j in Iy[1:-1]:
            u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
            u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
            u[i,j] = D1*u_1[i,j] - D2*u_2[i,j] + \
                    Cx2*u_xx + Cy2*u_yy + dt2*f(x[i], y[j], t[n])
            if step1:
                u[i,j] += dt*V(x[i], y[j])
    # Boundary condition u=0
    j = Iy[0]
    for i in Ix: u[i,j] = 0
    j = Iy[-1]
    for i in Ix: u[i,j] = 0
    i = Ix[0]
    for j in Iy: u[i,j] = 0
    i = Ix[-1]
    for j in Iy: u[i,j] = 0
    return u
```

The `step1` variable has been introduced to allow the formula to be reused for first step $u_{i,j}^1$:

```
u = advance_scalar(u, u_1, u_2, f, x, y, t,
                   n, Cx2, Cy2, dt, V, step1=True)
```

Below, we will make many alternative implementations of the `advance_scalar` function to speed up the code since most of the CPU time in simulations is spent in this function.

2.2   Vectorized computations

The scalar code above turns out to be extremely slow for large 2D meshes, and probably useless in 3D beyond debugging of small test cases. Vectorization is therefore a must for multi-dimensional finite difference computations in Python. For example, with a mesh consisting of 30×30 cells, vectorization brings down the CPU time by a factor of 70 (!).

In the vectorized case we must be able to evaluate user-given functions like (x, y) and $f(x, y, t)$, provided as Python functions `I(x,y)` and `f(x,y,t)`, for the entire mesh in one array operation. Having the one-dimensional coordinate arrays `x` and `y` is not sufficient: these must be extended to vectorized versions,

```
from numpy import newaxis
xv = x[:,newaxis]
yv = y[newaxis,:]
# or
xv = x.reshape((x.size, 1))
yv = y.reshape((1, y.size))
```

This is a standard required technique when evaluating functions over a 2 say `sin(xv)*cos(xv)`, which then gives a result with shape (Nx+1,Ny+

With the `xv` and `yv` arrays for vectorized computing, setting the condition is just a matter of

```
u_1[:,:] = I(xv, yv)
```

One could also have written `u_1 = I(xv, yv)` and let `u_1` point to a new but vectorized operations often makes use of direct insertion in the origin through `u_1[:,:]` because sometimes not all of the array is to be filled a function evaluation. This is the case with the computational scheme f

```
def advance_vectorized(u, u_1, u_2, f_a, Cx2, Cy2, dt2,
                       V=None, step1=False):
    if step1:
        dt = sqrt(dt2)  # save
        Cx2 = 0.5*Cx2;  Cy2 = 0.5*Cy2; dt2 = 0.5*dt2  # redefine
        D1 = 1;  D2 = 0
    else:
        D1 = 2;  D2 = 1
    u_xx = u_1[:-2,1:-1] - 2*u_1[1:-1,1:-1] + u_1[2:,1:-1]
    u_yy = u_1[1:-1,:-2] - 2*u_1[1:-1,1:-1] + u_1[1:-1,2:]
    u[1:-1,1:-1] = D1*u_1[1:-1,1:-1] - D2*u_2[1:-1,1:-1] + \
                Cx2*u_xx + Cy2*u_yy + dt2*f_a[1:-1,1:-1]
    if step1:
        u[1:-1,1:-1] += dt*V[1:-1, 1:-1]
    # Boundary condition u=0
    j = 0
    u[:,j] = 0
    j = u.shape[1]-1
    u[:,j] = 0
    i = 0
    u[i,:] = 0
    i = u.shape[0]-1
    u[i,:] = 0
    return u
```

Array slices in 2D are more complicated to understand than those in the logic from 1D applies to each dimension separately. For example, whe $u_{i,j}^n - u_{i-1,j}^n$ for $i \in \mathcal{I}_x^+$, we just keep `j` constant and make a slice in index: `u_1[1:,j] - u_1[:-1,j]`, exactly as in 1D. The `1:` slice spe the indices $i = 1, 2, \ldots, N_x$ (up to the last valid index), while `:-1` spec relevant indices for the second term: $0, 1, \ldots, N_x - 1$ (up to, but not in the last index).

In the above code segment, the situation is slightly more complicated, each displaced slice in one direction is accompanied by a `1:-1` slice in th

irection. The reason is that we only work with the internal points for the index
nat is kept constant in a difference.

The boundary conditions along the four sides makes use of a slice consisting
f all indices along a boundary:

```
u[: ,0] = 0
u[:,Ny] = 0
u[0 ,:] = 0
u[Nx,:] = 0
```

The f function is in the above vectorized update of u first computed as an
rray over all mesh points:

```
f_a = f(xv, yv, t[n])
```

Ve could, alternatively, used the call `f(xv, yv, t[n])[1:-1,1:-1]` in the last
erm of the update statement, but other implementations in compiled languages
enefit from having `f` available in an array rather than calling our Python
unction `f(x,y,t)` for every point.

Also in the `advance_vectorized` function we have introduced a boolean
tep1 to reuse the formula for the first time step in the same way as we did
ith `advance_scalar`. We refer to the `solver` function in `wave2D_u0.py` for
he details on how the overall algorithm is implemented.

The callback function now has the arguments `u, x, xv, y, yv, t, n`.
he inclusion of `xv` and `yv` makes it easy to, e.g., compute an exact 2D so-
ltion in the callback function and compute errors, through an expression like
 `- u_exact(xv, yv, t[n])`.

2.3 Verification

esting a quadratic solution. The 1D solution from Section 2.4 can be
eneralized to multi-dimensions and provides a test case where the exact solution
lso fulfills the discrete equations such that we know (to machine precision)
hat numbers the solver function should produce. In 2D we use the following
eneralization of (30):

$$u_e(x, y, t) = x(L_x - x)y(L_y - y)(1 + \tfrac{1}{2}t). \tag{112}$$

his solution fulfills the PDE problem if $I(x,y) = u_e(x,y,0)$, $V = \frac{1}{2}u_e(x,y,0)$,
nd $f = 2c^2(1 + \frac{1}{2}t)(y(L_y - y) + x(L_x - x))$. To show that u_e also solves the
iscrete equations, we start with the general results $[D_t D_t 1]^n = 0$, $[D_t D_t t]^n = 0$,
nd $[D_t D_t t^2] = 2$, and use these to compute

$$D_x D_x u_e]^n_{i,j} = [y(L_y - y)(1 + \tfrac{1}{2}t)D_x D_x x(L_x - x)]^n_{i,j} = y_j(L_y - y_j)(1 + \tfrac{1}{2}t_n)2.$$

 similar calculation must be carried out for the $[D_y D_y u_e]^n_{i,j}$ and $[D_t D_t u_e]^n_{i,j}$
rms. One must also show that the quadratic solution fits the special formula

for $u^1_{i,j}$. The details are left as Exercise 11. The `test_quadratic` fun
the `wave2D_u0.py`[18] program implements this verification as a nose tes

13 Migrating loops to Cython

Although vectorization can bring down the CPU time dramatically compar
scalar code, there is still some factor 5-10 to win in these types of applica
implementing the finite difference scheme in compiled code, typically in
C, or C++. This can quite easily be done by adding a little extra cod
program. Cython is an extension of Python that offers the easiest way
our Python loops in the scalar code down to machine code and the effic
C.

Cython can be viewed as an extended Python language where varia
declared with types and where functions are marked to be implement
Migrating Python code to Cython is done by copying the desired code s
to functions (or classes) and placing them in one or more separate fil
extension `.pyx`.

13.1 Declaring variables and annotating the code

Our starting point is the plain `advance_scalar` function for a scalar im
tation of the updating algorithm for new values $u^{n+1}_{i,j}$:

```
def advance_scalar(u, u_1, u_2, f, x, y, t, n, Cx2, Cy2, dt2,
                   V=None, step1=False):
    Ix = range(0, u.shape[0]);  Iy = range(0, u.shape[1])
    if step1:
        dt = sqrt(dt2)  # save
        Cx2 = 0.5*Cx2;  Cy2 = 0.5*Cy2; dt2 = 0.5*dt2  # redefine
        D1 = 1;  D2 = 0
    else:
        D1 = 2;  D2 = 1
    for i in Ix[1:-1]:
        for j in Iy[1:-1]:
            u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
            u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
            u[i,j] = D1*u_1[i,j] - D2*u_2[i,j] + \
                     Cx2*u_xx + Cy2*u_yy + dt2*f(x[i], y[j], t[n]
            if step1:
                u[i,j] += dt*V(x[i], y[j])
    # Boundary condition u=0
    j = Iy[0]
    for i in Ix: u[i,j] = 0
    j = Iy[-1]
    for i in Ix: u[i,j] = 0
    i = Ix[0]
    for j in Iy: u[i,j] = 0
    i = Ix[-1]
    for j in Iy: u[i,j] = 0
    return u
```

---

[18]http://tinyurl.com/jvzzcfn/wave/wave2D_u0/wave2D_u0.py

We simply take a copy of this function and put it in a file `wave2D_u0_loop_cy.pyx`. he relevant Cython implementation arises from declaring variables with types nd adding some important annotations to speed up array computing in Cython. et us first list the complete code in the `.pyx` file:

```python
import numpy as np
cimport numpy as np
cimport cython
ctypedef np.float64_t DT    # data type

@cython.boundscheck(False)  # turn off array bounds check
@cython.wraparound(False)   # turn off negative indices (u[-1,-1])
cpdef advance(
    np.ndarray[DT, ndim=2, mode='c'] u,
    np.ndarray[DT, ndim=2, mode='c'] u_1,
    np.ndarray[DT, ndim=2, mode='c'] u_2,
    np.ndarray[DT, ndim=2, mode='c'] f,
    double Cx2, double Cy2, double dt2):

    cdef:
        int Ix_start = 0
        int Iy_start = 0
        int Ix_end = u.shape[0]-1
        int Iy_end = u.shape[1]-1
        int i, j
        double u_xx, u_yy

    for i in range(Ix_start+1, Ix_end):
        for j in range(Iy_start+1, Iy_end):
            u_xx = u_1[i-1,j] - 2*u_1[i,j] + u_1[i+1,j]
            u_yy = u_1[i,j-1] - 2*u_1[i,j] + u_1[i,j+1]
            u[i,j] = 2*u_1[i,j] - u_2[i,j] + \
                     Cx2*u_xx + Cy2*u_yy + dt2*f[i,j]
    # Boundary condition u=0
    j = Iy_start
    for i in range(Ix_start, Ix_end+1): u[i,j] = 0
    j = Iy_end
    for i in range(Ix_start, Ix_end+1): u[i,j] = 0
    i = Ix_start
    for j in range(Iy_start, Iy_end+1): u[i,j] = 0
    i = Ix_end
    for j in range(Iy_start, Iy_end+1): u[i,j] = 0
    return u
```

This example may act as a recipe on how to transform array-intensive code ith loops into Cython.

1. Variables are declared with types: for example, `double v` in the argument list instead of just `v`, and `cdef double v` for a variable `v` in the body of the function. A Python `float` object is declared as `double` for translation to C by Cython, while an `int` object is declared by `int`.

2. Arrays need a comprehensive type declaration involving
   - the type `np.ndarray`,
   - the data type of the elements, here 64-bit floats, abbreviated as `DT` through `ctypedef np.float64_t DT` (instead of `DT` we could use the

full name of the data type: `np.float64_t`, which is a Cython type),
   - the dimensions of the array, here `ndim=2` and `ndim=1`,
   - specification of contiguous memory for the array (`mode='c'`)

3. Functions declared with `cpdef` are translated to C but also accessib Python.

4. In addition to the standard `numpy` import we also need a special import of `numpy`: `cimport numpy as np`, to appear *after* the s import.

5. By default, array indices are checked to be within their legal lim speed up the code one should turn off this feature for a specific f by placing `@cython.boundscheck(False)` above the function hea

6. Also by default, array indices can be negative (counting from the e this feature has a performance penalty and is therefore here turne writing `@cython.wraparound(False)` right above the function he

7. The use of index sets `Ix` and `Iy` in the scalar code cannot be fully translated to C. One reason is that constructions like `Ix involve negative indices, and these are now turned off. Anothe is that Cython loops must take the form `for i in xrange` or fc `range` for being translated into efficient C loops. We have there troduced `Ix_start` as `Ix[0]` and `Ix_end` as `Ix[-1]` to hold t and end of the values of index $i$. Similar variables are introdu the $j$ index. A loop `for i in Ix` is with these new variables wr `for i in range(Ix_start, Ix_end+1)`.

Array declaration syntax in Cython.

We have used the syntax `np.ndarray[DT, ndim=2, mode='c']` to de `numpy` arrays in Cython. There is a simpler, alternative syntax, empl typed memory views[a], where the declaration looks like `double [` However, the full support for this functionality is not yet ready, and i text we use the full array declaration syntax.

[a]`http://docs.cython.org/src/userguide/memoryviews.html`

13.2   Visual inspection of the C translation

Cython can visually explain how successfully it can translate a code from to C. The command

```
Terminal> cython -a wave2D_u0_loop_cy.pyx
```

roduces an HTML file `wave2D_u0_loop_cy.html`, which can be loaded into a
eb browser to illustrate which lines of the code that have been translated to C.
igure 8 shows the illustrated code. Yellow lines indicate the lines that Cython
id not manage to translate to efficient C code and that remain in Python. For
he present code we see that Cython is able to translate all the loops with array
omputing to C, which is our primary goal.

Figure 8:   Visual illustration of Cython's ability to translate Python to C.

You can also inspect the generated C code directly, as it appears in the file
`ave2D_u0_loop_cy.c`. Nevertheless, understanding this C code requires some
miliarity with writing Python extension modules in C by hand. Deep down in
he file we can see in detail how the compute-intensive statements are translated
ome complex C code that is quite different from what we a human would write
it least if a direct correspondence to the mathematics was in mind).

3.3   Building the extension module

ython code must be translated to C, compiled, and linked to form what is known
1 the Python world as a *C extension module.* This is usually done by making a
etup.py script, which is the standard way of building and installing Python
oftware. For an extension module arising from Cython code, the following
etup.py script is all we need to build and install the module:

```
from distutils.core import setup
from distutils.extension import Extension
from Cython.Distutils import build_ext

cymodule = 'wave2D_u0_loop_cy'
```

```
setup(
    name=cymodule
    ext_modules=[Extension(cymodule, [cymodule + '.pyx'],)],
    cmdclass={'build_ext': build_ext},
)
```

We run the script by

```
Terminal> python setup.py build_ext --inplace
```

The `-inplace` option makes the extension module available in the
directory as the file `wave2D_u0_loop_cy.so`. This file acts as a normal
module that can be imported and inspected:

```
>>> import wave2D_u0_loop_cy
>>> dir(wave2D_u0_loop_cy)
['__builtins__', '__doc__', '__file__', '__name__',
 '__package__', '__test__', 'advance', 'np']
```

The important output from the `dir` function is our Cython function a
(the module also features the imported `numpy` module under the name `np`
as many standard Python objects with double underscores in their nam

The `setup.py` file makes use of the `distutils` package in Pyth
Cython's extension of this package. These tools know how Python was
the computer and will use compatible compiler(s) and options when b
other code in Cython, C, or C++. Quite some experience with buildi
program systems is needed to do the build process manually, so using a `se`
script is strongly recommended.

> **Simplified build of a Cython module.**
>
> When there is no need to link the C code with special libraries, Cy
> offers a shortcut for generating and importing the extension module:
>
> ```
> import pyximport; pyximport.install()
> ```
>
> This makes the `setup.py` script redundant. However, in the `wave2D_u`
> code we do not use `pyximport` and require an explicit build process o
> and many other modules.

13.4   Calling the Cython function from Python

The `wave2D_u0_loop_cy` module contains our `advance` function, which
may call from the Python program for the wave equation:

```
import wave2D_u0_loop_cy
advance = wave2D_u0_loop_cy.advance
...
for n in It[1:-1:                  # time loop
    f_a[:,:] = f(xv, yv, t[n])     # precompute, size as u
    u = advance(u, u_1, u_2, f_a, x, y, t, Cx2, Cy2, dt2)
```

Efficiency. For a mesh consisting of 120×120 cells, the scalar Python code require 1370 CPU time units, the vectorized version requires 5.5, while the Cython version requires only 1! For a smaller mesh with 60×60 cells Cython is about 1000 times faster than the scalar Python code, and the vectorized version about 6 times slower than the Cython version.

14 Migrating loops to Fortran

Instead of relying on Cython's (excellent) ability to translate Python to C, we can invoke a compiled language directly and write the loops ourselves. Let us start with Fortran 77, because this is a language with more convenient array handling than C (or plain C++). Or more precisely, we can with ease program with the same multi-dimensional indices in the Fortran code as in the `numpy` arrays in the Python code, while in C these arrays are one-dimensional and requires us to reduce multi-dimensional indices to a single index.

14.1 The Fortran subroutine

We write a Fortran subroutine `advance` in a file `wave2D_u0_loop_f77.f`[19] for implementing the updating formula (111) and setting the solution to zero at the boundaries:

```
      subroutine advance(u, u_1, u_2, f, Cx2, Cy2, dt2, Nx, Ny)
      integer Nx, Ny
      real*8 u(0:Nx,0:Ny), u_1(0:Nx,0:Ny), u_2(0:Nx,0:Ny)
      real*8 f(0:Nx,0:Ny), Cx2, Cy2, dt2
      integer i, j
      real*8 u_xx, u_yy
Cf2py intent(in, out) u

C     Scheme at interior points
      do j = 1, Ny-1
         do i = 1, Nx-1
            u_xx = u_1(i-1,j) - 2*u_1(i,j) + u_1(i+1,j)
            u_yy = u_1(i,j-1) - 2*u_1(i,j) + u_1(i,j+1)
            u(i,j) = 2*u_1(i,j) - u_2(i,j) + Cx2*u_xx + Cy2*u_yy +
     &                dt2*f(i,j)
         end do
      end do

C     Boundary conditions
```

---

[19]http://tinyurl.com/jvzzcfn/wave/wave2D_u0/wave2D_u0_loop_f77.f

```
      j = 0
      do i = 0, Nx
         u(i,j) = 0
      end do
      j = Ny
      do i = 0, Nx
         u(i,j) = 0
      end do
      i = 0
      do j = 0, Ny
         u(i,j) = 0
      end do
      i = Nx
      do j = 0, Ny
         u(i,j) = 0
      end do
      return
      end
```

This code is plain Fortran 77, except for the special `Cf2py` comment line here specifies that `u` is both an input argument *and* an object to be r from the `advance` routine. Or more precisely, Fortran is not able return from a function, but we need a *wrapper code* in C for the Fortran subro enable calling it from Python, and in this wrapper code one can return calling Python code.

> **Remark.**
>
> It is not strictly necessary to return `u` to the calling Python code the `advance` function will modify the elements of `u`, but the conventi Python is to get all output from a function as returned values. Th the right way of calling the above Fortran subroutine from Python is
>
> ```
> u = advance(u, u_1, u_2, f, Cx2, Cy2, dt2)
> ```
>
> The less encouraged style, which works and resembles the way the Fo subroutine is called from Fortran, reads
>
> ```
> advance(u, u_1, u_2, f, Cx2, Cy2, dt2)
> ```

14.2 Building the Fortran module with f2py

The nice feature of writing loops in Fortran is that the tool `f2py` can w little work produce a C extension module such that we can call the version of `advance` from Python. The necessary commands to run are

```
erminal> f2py -m wave2D_u0_loop_f77 -h wave2D_u0_loop_f77.pyf \
         --overwrite-signature wave2D_u0_loop_f77.f
erminal> f2py -c wave2D_u0_loop_f77.pyf --build-dir build_f77 \
         -DF2PY_REPORT_ON_ARRAY_COPY=1 wave2D_u0_loop_f77.f
```

he first command asks **f2py** to interpret the Fortran code and make a Fortran 90 pecification of the extension module in the file `wave2D_u0_loop_f77.pyf`. The econd command makes **f2py** generate all necessary wrapper code, compile our ortran file and the wrapper code, and finally build the module. The build process akes place in the specified subdirectory `build_f77` so that files can be inspected something goes wrong. The option `-DF2PY_REPORT_ON_ARRAY_COPY=1` makes 2py write a message for every array that is copied in the communication between ortran and Python, which is very useful for avoiding unnecessary array copying ee below). The name of the module file is `wave2D_u0_loop_f77.so`, and this le can be imported and inspected as any other Python module:

```
>>> import wave2D_u0_loop_f77
>>> dir(wave2D_u0_loop_f77)
['__doc__', '__file__', '__name__', '__package__',
 '__version__', 'advance']
>>> print wave2D_u0_loop_f77.__doc__
This module 'wave2D_u0_loop_f77' is auto-generated with f2py....
Functions:
  u = advance(u,u_1,u_2,f,cx2,cy2,dt2,
      nx=(shape(u,0)-1),ny=(shape(u,1)-1))
```

Examine the doc strings!

Printing the doc strings of the module and its functions is extremely important after having created a module with **f2py**, because **f2py** makes Python interfaces to the Fortran functions that are different from how the functions are declared in the Fortran code (!). The rationale for this behavior is that **f2py** creates *Pythonic* interfaces such that Fortran routines can be called in the same way as one calls Python functions. Output data from Python functions is always returned to the calling code, but this is technically impossible in Fortran. Also, arrays in Python are passed to Python functions without their dimensions because that information is packed with the array data in the array objects, but this is not possible in Fortran. Therefore, **f2py** removes array dimensions from the argument list, and **f2py** makes it possible to return objects back to Python.

Let us follow the advice of examining the doc strings and take a close look t the documentation **f2py** has generated for our Fortran `advance` subroutine:

```
>>> print wave2D_u0_loop_f77.advance.__doc__
This module 'wave2D_u0_loop_f77' is auto-generated with f2py
Functions:
```

```
  u = advance(u,u_1,u_2,f,cx2,cy2,dt2,
              nx=(shape(u,0)-1),ny=(shape(u,1)-1))
.
advance - Function signature:
  u = advance(u,u_1,u_2,f,cx2,cy2,dt2,[nx,ny])
Required arguments:
  u : input rank-2 array('d') with bounds (nx + 1,ny + 1)
  u_1 : input rank-2 array('d') with bounds (nx + 1,ny + 1)
  u_2 : input rank-2 array('d') with bounds (nx + 1,ny + 1)
  f : input rank-2 array('d') with bounds (nx + 1,ny + 1)
  cx2 : input float
  cy2 : input float
  dt2 : input float
Optional arguments:
  nx := (shape(u,0)-1) input int
  ny := (shape(u,1)-1) input int
Return objects:
  u : rank-2 array('d') with bounds (nx + 1,ny + 1)
```

Here we see that the `nx` and `ny` parameters declared in Fortran are arguments that can be omitted when calling `advance` from Python.

We strongly recommend to print out the documentation of *every* function to be called from Python and make sure the call syntax is ex listed in the documentation.

14.3   How to avoid array copying

Multi-dimensional arrays are stored as a stream of numbers in memo a two-dimensional array consisting of rows and columns there are tw of creating such a stream: *row-major ordering*, which means that r stored consecutively in memory, or *column-major ordering*, which means columns are stored one after each other. All programming languages in from C, including Python, apply the row-major ordering, but Fortr column-major storage. Thinking of a two-dimensional array in Python o matrix, it means that Fortran works with the transposed matrix.

Fortunately, **f2py** creates extra code so that accessing `u(i,j)` in the subroutine corresponds to the element `u[i,j]` in the underlying nump (without the extra code, `u(i,j)` in Fortran would access `u[j,i]` in th array). Technically, **f2py** takes a copy of our `numpy` array and reorders t before sending the array to Fortran. Such copying can be costly. For 2 simulations on a 60×60 grid the overhead of copying is a factor of 5 means that almost the whole performance gain of Fortran over vectorize code is lost!

To avoid having **f2py** to copy arrays with C storage to the corresp Fortran storage, we declare the arrays with Fortran storage:

```
order = 'Fortran' if version == 'f77' else 'C'
u   = zeros((Nx+1,Ny+1), order=order)   # solution array
u_1 = zeros((Nx+1,Ny+1), order=order)   # solution at t-dt
u_2 = zeros((Nx+1,Ny+1), order=order)   # solution at t-2*dt
```

In the compile and build step of using `f2py`, it is recommended to add an extra option for making `f2py` report on array copying:

```
erminal> f2py -c wave2D_u0_loop_f77.pyf --build-dir build_f77 \
         -DF2PY_REPORT_ON_ARRAY_COPY=1 wave2D_u0_loop_f77.f
```

It can sometimes be a challenge to track down which array that causes a opying. There are two principal reasons for copying array data: either the array oes not have Fortran storage or the element types do not match those declared n the Fortran code. The latter cause is usually effectively eliminated by using eal*8 data in the Fortran code and `float64` (the default `float` type in `numpy`) n the arrays on the Python side. The former reason is more common, and to heck whether an array before a Fortran call has the right storage one can print he result of `isfortran(a)`, which is `True` if the array `a` has Fortran storage.

Let us look at an example where we face problems with array storage. A ypical problem in the `wave2D_u0.py` code is to set

```
_a = f(xv, yv, t[n])
```

efore the call to the Fortran `advance` routine. This computation creates a new rray with C storage. An undesired copy of `f_a` will be produced when sending _a to a Fortran routine. There are two remedies, either direct insertion of data n an array with Fortran storage,

```
_a = zeros((Nx+1, Ny+1), order='Fortran')
...
_a[:,:] = f(xv, yv, t[n])
```

r remaking the `f(xv, yv, t[n])` array,

```
_a = asarray(f(xv, yv, t[n]), order='Fortran')
```

he former remedy is most efficient if the `asarray` operation is to be performed large number of times.

fficiency. The efficiency of this Fortran code is very similar to the Cython ode. There is usually nothing more to gain, from a computational efficiency oint of view, by implementing the *complete* Python program in Fortran or C. hat will just be a lot more code for all administering work that is needed in cientific software, especially if we extend our sample program `wave2D_u0.py` to andle a real scientific problem. Then only a small portion will consist of loops ith intensive array calculations. These can be migrated to Cython or Fortran s explained, while the rest of the programming can be more conveniently done n Python.

15 Migrating loops to C via Cython

The computationally intensive loops can alternatively be implemente code. Just as Fortran calls for care regarding the storage of two-dime arrays, working with two-dimensional arrays in C is a bit tricky. The r that `numpy` arrays are viewed as one-dimensional arrays when transferre while C programmers will think of u, u_1, and u_2 as two dimensiona and index them like `u[i][j]`. The C code must declare u as `double` translate an index pair `[i][j]` to a corresponding single index when u is as one-dimensional. This translation requires knowledge of how the num u are stored in memory.

15.1 Translating index pairs to single indices

Two-dimensional `numpy` arrays with the default C storage are stored row In general, multi-dimensional arrays with C storage are stored such that index has the fastest variation, then the next last index, and so on, en with the slowest variation in the first index. For a two-dimensional u c as `zeros((Nx+1,Ny+1))` in Python, the individual elements are store following order:

```
u[0,0], u[0,1], u[0,2], ..., u[0,Ny], u[1,0], u[1,1], ...,
u[1,Ny], u[2,0], ..., u[Nx,0], u[Nx,1], ..., u[Nx, Ny]
```

Viewing u as one-dimensional, the index pair (i,j) translates to $i(N_y$ So, where a C programmer would naturally write an index `u[i][j]`, the i must read `u[i*(Ny+1) + j]`. This is tedious to write, so it can be h define a C macro,

```
#define idx(i,j) (i)*(Ny+1) + j
```

so that we can write `u[idx(i,j)]`, which reads much better and is e debug.

> **Be careful with macro definitions.**
>
> Macros just perform simple text substitutions: `idx(hello,world)` panded to `(hello)*(Ny+1) + world`. The parenthesis in `(i)` are esse - using the natural mathematical formula `i*(Ny+1) + j` in the m definition, `idx(i-1,j)` would expand to `i-1*(Ny+1) + j`, which i wrong formula. Macros are handy, but requires careful use. In C++, i functions are safer and replace the need for macros.

15.2 The complete C code

The C version of our function `advance` can be coded as follows.

```
#define idx(i,j) (i)*(Ny+1) + j

void advance(double* u, double* u_1, double* u_2, double* f,
             double Cx2, double Cy2, double dt2, int Nx, int Ny)
{
  int i, j;
  double u_xx, u_yy;
  /* Scheme at interior points */
  for (i=1; i<=Nx-1; i++) {
    for (j=1; j<=Ny-1; j++) {
      u_xx = u_1[idx(i-1,j)] - 2*u_1[idx(i,j)] + u_1[idx(i+1,j)];
      u_yy = u_1[idx(i,j-1)] - 2*u_1[idx(i,j)] + u_1[idx(i,j+1)];
      u[idx(i,j)] = 2*u_1[idx(i,j)] - u_2[idx(i,j)] +
        Cx2*u_xx + Cy2*u_yy + dt2*f[idx(i,j)];
    }
  }
  /* Boundary conditions */
  j = 0;  for (i=0; i<=Nx; i++) u[idx(i,j)] = 0;
  j = Ny; for (i=0; i<=Nx; i++) u[idx(i,j)] = 0;
  i = 0;  for (j=0; j<=Ny; j++) u[idx(i,j)] = 0;
  i = Nx; for (j=0; j<=Ny; j++) u[idx(i,j)] = 0;
}
```

5.3 The Cython interface file

ll the code above appears in a file `wave2D_u0_loop_c.c`[20]. We need to compile
his file together with C wrapper code such that `advance` can be called from
ython. Cython can be used to generate appropriate wrapper code. The relevant
ython code for interfacing C is placed in a file with extension `.pyx`. Here this
le, called `wave2D_u0_loop_c_cy.pyx`[21], looks like

```
import numpy as np
cimport numpy as np
cimport cython

cdef extern from "wave2D_u0_loop_c.h":
    void advance(double* u, double* u_1, double* u_2, double* f,
                 double Cx2, double Cy2, double dt2,
                 int Nx, int Ny)

@cython.boundscheck(False)
@cython.wraparound(False)
def advance_cwrap(
    np.ndarray[double, ndim=2, mode='c'] u,
    np.ndarray[double, ndim=2, mode='c'] u_1,
    np.ndarray[double, ndim=2, mode='c'] u_2,
    np.ndarray[double, ndim=2, mode='c'] f,
    double Cx2, double Cy2, double dt2):
    advance(&u[0,0], &u_1[0,0], &u_2[0,0], &f[0,0],
            Cx2, Cy2, dt2,
            u.shape[0]-1, u.shape[1]-1)
    return u
```

---

[20]http://tinyurl.com/jvzzcfn/wave//wave2D_u0/wave2D_u0_loop_c.c
[21]http://tinyurl.com/jvzzcfn/wave/wave2D_u0/wave2D_u0_loop_c_cy.pyx

We first declare the C functions to be interfaced. These must also appea
header file, `wave2D_u0_loop_c.h`[22],

```
extern void advance(double* u, double* u_1, double* u_2, double*
                    double Cx2, double Cy2, double dt2,
                    int Nx, int Ny);
```

The next step is to write a Cython function with Python objects as arg
The name `advance` is already used for the C function so the function to b
from Python is named `advance_cwrap`. The contents of this function is
a call to the `advance` version in C. To this end, the right information f
Python objects must be passed on as arguments to `advance`. Arrays a
with their C pointers to the first element, obtained in Cython as `&u[0,`
`&` takes the address of a C variable). The `Nx` and `Ny` arguments in `adva`
easily obtained from the shape of the `numpy` array `u`. Finally, `u` must be i
such that we can set `u = advance(...)` in Python.

15.4 Building the extension module

It remains to build the extension module. An appropriate `setup.py` fil

```
from distutils.core import setup
from distutils.extension import Extension
from Cython.Distutils import build_ext

sources = ['wave2D_u0_loop_c.c', 'wave2D_u0_loop_c_cy.pyx']
module = 'wave2D_u0_loop_c_cy'
setup(
    name=module,
    ext_modules=[Extension(module, sources,
                           libraries=[], # C libs to link with
                           )],
    cmdclass={'build_ext': build_ext},
)
```

All we need to specify is the `.c` file(s) and the `.pyx` interface file. Cytho
tomatically run to generate the necessary wrapper code. Files are then c
and linked to an extension module residing in the file `wave2D_u0_loop_c`
Here is a session with running `setup.py` and examining the resulting m
Python

```
Terminal> python setup.py build_ext --inplace
Terminal> python
>>> import wave2D_u0_loop_c_cy as m
>>> dir(m)
['__builtins__', '__doc__', '__file__', '__name__', '__package__',
 '__test__', 'advance_cwrap', 'np']
```

---

[22]http://tinyurl.com/jvzzcfn/wave/wave2D_u0/wave2D_u0_loop_c.h

he call to the C version of `advance` can go like this in Python:

```
import wave2D_u0_loop_c_cy
advance = wave2D_u0_loop_c_cy.advance_cwrap
...
f_a[:,:] = f(xv, yv, t[n])
u = advance(u, u_1, u_2, f_a, Cx2, Cy2, dt2)
```

Efficiency. In this example, the C and Fortran code runs at the same speed, and there are no significant differences in the efficiency of the wrapper code. The overhead implied by the wrapper code is negligible as long as we do not work with very small meshes and consequently little numerical work in the `advance` function.

16 Migrating loops to C via f2py

An alternative to using Cython for interfacing C code is to apply `f2py`. The C code is the same, just the details of specifying how it is to be called from Python differ. The `f2py` tool requires the call specification to be a Fortran 90 module defined in a `.pyf` file. This file was automatically generated when we interfaced a Fortran subroutine. With a C function we need to write this module ourselves, or we can use a trick and let `f2py` generate it for us. The trick consists in writing the signature of the C function with Fortran syntax and place it in a Fortran file, here `wave2D_u0_loop_c_f2py_signature.f`:

```
      subroutine advance(u, u_1, u_2, f, Cx2, Cy2, dt2, Nx, Ny)
Cf2py intent(c) advance
      integer Nx, Ny, N
      real*8 u(0:Nx,0:Ny), u_1(0:Nx,0:Ny), u_2(0:Nx,0:Ny)
      real*8 f(0:Nx, 0:Ny), Cx2, Cy2, dt2
Cf2py intent(in, out) u
Cf2py intent(c) u, u_1, u_2, f, Cx2, Cy2, dt2, Nx, Ny
      return
      end
```

Note that we need a special `f2py` instruction, through a `Cf2py` comment line, for telling that all the function arguments are C variables. We also need to specify that the function is actually in C: `intent(c) advance`.

Since `f2py` is just concerned with the function signature and not the complete contents of the function body, it can easily generate the Fortran 90 module specification based solely on the signature above:

```
Terminal> f2py -m wave2D_u0_loop_c_f2py \
          -h wave2D_u0_loop_c_f2py.pyf --overwrite-signature \
          wave2D_u0_loop_c_f2py_signature.f
```

The compile and build step is as for the Fortran code, except that we list instead of Fortran files:

```
Terminal> f2py -c wave2D_u0_loop_c_f2py.pyf \
          --build-dir tmp_build_c \
          -DF2PY_REPORT_ON_ARRAY_COPY=1 wave2D_u0_loop_c.c
```

As when interfacing Fortran code with `f2py`, we need to print out the doc to see the exact call syntax from the Python side. This doc string is id for the C and Fortran versions of `advance`.

16.1 Migrating loops to C++ via f2py

C++ is a much more versatile language than C or Fortran and has over two decades become very popular for numerical computing. Many will t prefer to migrate compute-intensive Python code to C++. This is, in p easy: just write the desired C++ code and use some tool for interf from Python. A tool like SWIG[23] can interpret the C++ code and g interfaces for a wide range of languages, including Python, Perl, Ruby, a However, SWIG is a comprehensive tool with a correspondingly steep l curve. Alternative tools, such as Boost Python[24], SIP[25], and Shibok similarly comprehensive. Simpler tools include PyBindGen[27],

A technically much easier way of interfacing C++ code is to d possibility to use C++ classes directly from Python, but instead ma interface to the C++ code. The C interface can be handled by `f2py` a in the example with pure C code. Such a solution means that classes in and C++ cannot be mixed and that only primitive data types like n strings, and arrays can be transferred between Python and C++. Actua is often a very good solution because it forces the C++ code to work c data, which usually gives faster code than if fancy data structures with are used. The arrays coming from Python, and looking like plain C/C++ can be efficiently wrapped in more user-friendly C++ array classes in t code, if desired.

17 Using classes to implement a simulator

- Introduce classes `Mesh`, `Function`, `Problem`, `Solver`, `Visualizer`

---

[23] http://swig.org/
[24] http://www.boost.org/doc/libs/1_51_0/libs/python/doc/index.html
[25] http://riverbankcomputing.co.uk/software/sip/intro
[26] http://qt-project.org/wiki/Category:LanguageBindings::PySide::Shiboke
[27] http://code.google.com/p/pybindgen/

Exercise 11: Check that a solution fulfills the discrete model

Carry out all mathematical details to show that (112) is indeed a solution of the discrete model for a 2D wave equation with $u = 0$ on the boundary. One must check the boundary conditions, the initial conditions, the general discrete equation at a time level and the special version of this equation for the first time level. Filename: `check_quadratic_solution.pdf`.

Project 12: Calculus with 2D/3D mesh functions

The goal of this project is to redo Project 5 with 2D and 3D mesh functions ($f_{i,j}$ and $f_{i,j,k}$).

Differentiation. The differentiation results in a discrete gradient function, which in the 2D case can be represented by a three-dimensional array `df[d,i,j]` where `d` represents the direction of the derivative and `i` and `j` are mesh point counters in 2D (the 3D counterpart is `df[d,i,j,k]`).

Integration. The integral of a 2D mesh function $f_{i,j}$ is defined as

$$F_{i,j} = \int_{y_0}^{y_j} \int_{x_0}^{x_i} f(x,y)dxdy,$$

where $f(x,y)$ is a function that takes on the values of the discrete mesh function $f_{i,j}$ at the mesh points, but can also be evaluated in between the mesh points. The particular variation between mesh points can be taken as bilinear, but this is not important as we will use a product Trapezoidal rule to approximate the integral over a cell in the mesh and then we only need to evaluate $f(x,y)$ at the mesh points.

Suppose $F_{i,j}$ is computed. The calculation of $F_{i+1,j}$ is then

$$F_{i+1,j} = F_{i,j} + \int_{x_i}^{x_{i+1}} \int_{y_0}^{y_j} f(x,y)dydx$$
$$\approx \Delta x \int_{y_0}^{y_j} f(x_{i+\frac{1}{2}},y)dy$$
$$\approx \Delta x \frac{1}{2} \left(\int_{y_0}^{y_j} f(x_i,y)dy + \int_{y_0}^{y_j} f(x_{i+1},y)dy \right)$$

The integrals in the y direction can be approximated by a Trapezoidal rule. A similar idea can be used to compute $F_{i,j+1}$. Thereafter, $F_{i+1,j+1}$ can be computed by adding the integral over the final corner cell to $F_{i+1,j} + F_{i,j+1} - F_{i,j}$. Carry out the details of these computations and extend the ideas to 3D. Filename: `mesh_calculus_3D.py`.

Exercise 13: Implement Neumann conditions in 2D

Modify the `wave2D_u0.py`[28] program, which solves the 2D wave equation $c^2(u_{xx} + u_{yy})$ with constant wave velocity c and $u = 0$ on the boundary have Neumann boundary conditions: $\partial u / \partial n = 0$. Include both scalar c debugging and reference) and vectorized code (for speed).

To test the code, use $u = 1.2$ as solution ($I(x,y) = 1.2$, $V = f = 0$ arbitrary), which should be exactly reproduced with any mesh as long stability criterion is satisfied. Another test is to use the plug-shaped puls `pulse` function from Section 8 and the `wave1D_dn_vc.py`[29] program. The is exactly propagated in 1D if $c\Delta t/\Delta x = 1$. Check that also the 2D p can propagate this pulse exactly in x direction ($c\Delta t/\Delta x = 1$, Δy arbitra y direction ($c\Delta t/\Delta y = 1$, Δx arbitrary). Filename: `wave2D_dn.py`.

Exercise 14: Test the efficiency of compiled loops in

Extend the `wave2D_u0.py` code and the Cython, Fortran, and C version Set up an efficiency experiment to determine the relative efficiency of pu Python code, vectorized code, Cython-compiled loops, Fortran-compile and C-compiled loops. Normalize the CPU time for each mesh by the version. Filename: `wave3D_u0.py`.

19   Applications of wave equations

This section presents a range of wave equation models for different p phenomena. Although many wave motion problems in physics can be mo the standard linear wave equation, or a similar formulation with a system order equations, there are some exceptions. Perhaps the most important waves: these are modeled by the Laplace equation with time-dependent b conditions at the water surface (long water waves, however, can be appro by a standard wave equation, see Section 19.7). Quantum mechanica constitute another example where the waves are governed by the Schr equation and not a standard wave equation. Many wave phenomena al to take nonlinear effects into account when the wave amplitude is sig Shock waves in the air is a primary example.

The derivations in the following are very brief. Those with a firm bac in continuum mechanics will probably have enough information to fil details, while other readers will hopefully get some impression of the phy approximations involved when establishing wave equation models.

19.1   Waves on a string

Figure 9 shows a model we may use to derive the equation for waves on The string is modeled as a set of discrete point masses (at mesh point

[28] http://tinyurl.com/jvzzcfn/wave/wave2D_u0/wave2D_u0.py
[29] http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_dn_vc.py

Discrete string model with point masses connected by elastic strings.

astic strings in between. The strings are at a high constant tension T. We t the mass at mesh point x_i be m_i. The displacement of this mass point in y irection is denoted by $u_i(t)$.

The motion of mass m_i is governed by Newton's second law of motion. The osition of the mass at time t is $x_i\boldsymbol{i} + u_i(t)\boldsymbol{j}$, where $\boldsymbol{i}$ and $\boldsymbol{j}$ are unit vectors in he x and y direction, respectively. The acceleration is then $u_i''(t)\boldsymbol{j}$. Two forces re acting on the mass as indicated in Figure 9. The force $\boldsymbol{T}^-$ acting toward the oint x_{i-1} can be decomposed as

$$\boldsymbol{T}^- = -T\sin\phi\boldsymbol{i} - T\cos\phi\boldsymbol{j},$$

here ϕ is the angle between the force and the line $x = x_i$. Let $\Delta u_i = u_i - u_{i-1}$ nd let $\Delta s_i = \sqrt{\Delta u_i^2 + (x_i - x_{i-1})^2}$ be the distance from mass m_{i-1} to mass

m_i. It is seen that $\cos\phi = \Delta u_i/\Delta s_i$ and $\sin\phi = (x_i - x_{i-1})/\Delta s$ or Δ we introduce a constant mesh spacing $\Delta x = x_i - x_{i-1}$. The force can written

$$\boldsymbol{T}^- = -T\frac{\Delta x}{\Delta s_i}\boldsymbol{i} - T\frac{\Delta u_i}{\Delta s_i}\boldsymbol{j}.$$

The force $\boldsymbol{T}^+$ acting toward x_{i+1} can be calculated in a similar way:

$$\boldsymbol{T}^+ = T\frac{\Delta x}{\Delta s_{i+1}}\boldsymbol{i} + T\frac{\Delta u_{i+1}}{\Delta s_{i+1}}\boldsymbol{j}.$$

Newton's second law becomes

$$m_i u_i''(t)\boldsymbol{j} = \boldsymbol{T}^+ + \boldsymbol{T}^-,$$

which gives the component equations

$$T\frac{\Delta x}{\Delta s_i} = T\frac{\Delta x}{\Delta s_{i+1}},$$

$$m_i u_i''(t) = T\frac{\Delta u_{i+1}}{\Delta s_{i+1}} - T\frac{\Delta u_i}{\Delta s_i}.$$

A basic reasonable assumption for a string is small displacements small displacement gradients $\Delta u_i/\Delta x$. For small $g = \Delta u_i/\Delta x$ we have

$$\Delta s_i = \sqrt{\Delta u_i^2 + \Delta x^2} = \Delta x\sqrt{1 + g^2} + \Delta x(1 + \frac{1}{2}g^2 + \mathcal{O}(g^4) \approx \Delta x$$

Equation (113) is then simply the identity $T = T$, while (114) can be wr

$$m_i u_i''(t) = T\frac{\Delta u_{i+1}}{\Delta x} - T\frac{\Delta u_i}{\Delta x},$$

which upon division by Δx and introducing the density $\varrho_i = m_i/\Delta x$ be

$$\varrho_i u_i''(t) = T\frac{1}{\Delta x^2}\left(u_{i+1} - 2u_i + u_{i-1}\right).$$

We can now choose to approximate u_i'' by a finite difference in time and discretized wave equation,

$$\varrho_i\frac{1}{\Delta t^2}\left(u_i^{n+1} - 2u_i^n - u_i^{n-1}\right) = T\frac{1}{\Delta x^2}\left(u_{i+1} - 2u_i + u_{i-1}\right).$$

On the other hand, we may go to the continuum limit $\Delta x \to 0$ and repl by $u(x,t)$, ϱ_i by $\varrho(x)$, and recognize that the right-hand side of (115) app $\partial^2 u/\partial x^2$ as $\Delta x \to 0$. We end up with the continuous model for wav string:

$$\varrho \frac{\partial^2 u}{\partial t^2} = T \frac{\partial^2 u}{\partial x^2}\,. \tag{117}$$

ote that the density ϱ may change along the string, while the tension T is a onstant. With variable wave velocity $c(x) = \sqrt{T/\varrho(x)}$ we can write the wave quation in the more standard form

$$\frac{\partial^2 u}{\partial t^2} = c^2(x) \frac{\partial^2 u}{\partial x^2}\,. \tag{118}$$

ecause of the way ϱ enters the equations, the variable wave velocity does *not* ppear inside the derivatives as in many other versions of the wave equation. owever, most strings of interest have constant ϱ.

The end point of a string are fixed so that the displacement u is zero. The oundary conditions are therefore $u = 0$.

Damping. Air resistance and non-elastic effects in the string will contribute o reduce the amplitudes of the waves so that the motion dies out after some me. This damping effect can be modeled by a term bu_t on the left-hand side of he equation

$$\varrho \frac{\partial^2 u}{\partial t^2} + b \frac{\partial u}{\partial t} = T \frac{\partial^2 u}{\partial x^2}\,. \tag{119}$$

he parameter b must normally be determined from physical experiments.

External forcing. It is easy to include an external force acting on the string. ay we have a vertical force $\tilde{f}_i \boldsymbol{j}$ acting on mass m_i. This force affects the ertical component of Newton's law and gives rise to an extra term $\tilde{f}(x,t)$ n the right-hand side of (117). In the model (118) we would add a term $(x,t) = \tilde{f}(x,y)/\varrho(x)$.

Modeling the tension via springs. We assumed, in the derivation above, hat the tension in the string, T, was constant. It is easy to check this assumption y modeling the string segments between the masses as standard springs, where he force (tension T) is proportional to the elongation of the spring segment. et k be the spring constant, and set $T_i = k\Delta\ell$ for the tension in the spring egment between x_{i-1} and x_i, where $\Delta\ell$ is the elongation of this segment from he tension-free state. A basic feature of a string is that it has high tension in he equilibrium position $u = 0$. Let the string segment have an elongation $\Delta\ell_0$ n the equilibrium position. After deformation of the string, the elongation is $\ell = \Delta\ell_0 + \Delta s_i$: $T_i = k(\Delta\ell_0 + \Delta s_i) \approx k(\Delta\ell_0 + \Delta x)$. This shows that T_i is ndependent of i. Moreover, the extra approximate elongation Δx is very small ompared to $\Delta\ell_0$, so we may well set $T_i = T = k\Delta\ell_0$. This means that the ension is completely dominated by the initial tension determined by the tuning f the string. The additional deformations of the spring during the vibrations o not introduce significant changes in the tension.

19.2 Waves on a membrane

19.3 Elastic waves in a rod

Consider an elastic rod subject to a hammer impact at the end. This exp will give rise to an elastic deformation pulse that travels through the mathematical model for longitudinal waves along an elastic rod starts general equation for deformations and stresses in an elastic medium,

$$\varrho \boldsymbol{u}_{tt} = \nabla \cdot \boldsymbol{\sigma} + \varrho \boldsymbol{f},$$

where ϱ is the density, $\boldsymbol{u}$ the displacement field, $\boldsymbol{\sigma}$ the stress tensor, and forces. The latter has normally no impact on elastic waves.

For stationary deformation of an elastic rod, one has that $\sigma_{xx} = E$ all other stress components being zero. Moreover, $\boldsymbol{u} = u(x)\boldsymbol{i}$. The para is known as Young's modulus. Assuming that this simple stress and defo field, which is exact in the stationary case, is a good approximation transient case with wave motion, (120) simplifies to

$$\varrho \frac{\partial^2 u}{\partial t^2} = \frac{\partial}{\partial x} \left(E \frac{\partial u}{\partial x} \right)\,.$$

The associated boundary conditions are u or $\sigma_{xx} = Eu_x$ known, $u = 0$ for a clamped end and $\sigma_{xx} = 0$ for a free end.

19.4 The acoustic model for seismic waves

Seismic waves are used to infer properties of subsurface geological str The physical model is a heterogeneous elastic medium where sound is pro by small elastic vibrations. The general mathematical model for deforma an elastic medium is based on Newton's second law,

$$\varrho \boldsymbol{u}_{tt} = \nabla \cdot \boldsymbol{\sigma} + \varrho \boldsymbol{f},$$

and a constitutive law relating $\boldsymbol{\sigma}$ to $\boldsymbol{u}$, often Hooke's generalized law,

$$\boldsymbol{\sigma} = K \nabla \cdot \boldsymbol{u}\, \boldsymbol{I} + G(\nabla \boldsymbol{u} + (\nabla \boldsymbol{u})^T - \frac{2}{3} \nabla \cdot \boldsymbol{u}\, \boldsymbol{I})\,.$$

Here, $\boldsymbol{u}$ is the displacement field, $\boldsymbol{\sigma}$ is the stress tensor, $\boldsymbol{I}$ is the identity t is the medium's density, $\boldsymbol{f}$ are body forces (such as gravity), K is the m bulk modulus and G is the shear modulus. All these quantities may space, while $\boldsymbol{u}$ and $\boldsymbol{\sigma}$ will also show significant variation in time duri motion.

The acoustic approximation to elastic waves arises from a basic assu that the second term in Hooke's law, representing the deformations tl rise to shear stresses, can be neglected. This assumption can be interp approximating the geological medium by a fluid. Neglecting also the bod $\boldsymbol{f}$, (122) becomes

$$\varrho\boldsymbol{u}_{tt} = \nabla(K\nabla \cdot \boldsymbol{u}) \tag{124}$$

ntroducing p as a pressure via

$$p = -K\nabla \cdot \boldsymbol{u}, \tag{125}$$

nd dividing (124) by ϱ, we get

$$\boldsymbol{u}_{tt} = -\frac{1}{\varrho}\nabla p\,. \tag{126}$$

aking the divergence of this equation, using $\nabla \cdot \boldsymbol{u} = -p/K$ from (125), gives he *acoustic approximation to elastic waves*:

$$p_{tt} = K\nabla \cdot \left(\frac{1}{\varrho}\nabla p\right)\,. \tag{127}$$

his is a standard, linear wave equation with variable coefficients. It is common o add a source term $s(x, y, z, t)$ to model the generation of sound waves:

$$p_{tt} = K\nabla \cdot \left(\frac{1}{\varrho}\nabla p\right) + s\,. \tag{128}$$

A common additional approximation of (128) is based on using the chain ule on the right-hand side,

$$K\nabla \cdot \left(\frac{1}{\varrho}\nabla p\right) = \frac{K}{\varrho}\nabla^2 p + K\nabla\left(\frac{1}{\varrho}\right) \cdot \nabla p \approx \frac{K}{\varrho}\nabla^2 p,$$

nder the assumption that the relative spatial gradient $\nabla\varrho^{-1} = -\varrho^{-2}\nabla\varrho$ is small. his approximation results in the simplified equation

$$p_{tt} = \frac{K}{\varrho}\nabla^2 p + s\,. \tag{129}$$

The acoustic approximations to seismic waves are used for sound waves in he ground, and the Earth's surface is then a boundary where p equals the tmospheric pressure p_0 such that the boundary condition becomes $p = p_0$.

nisotropy. Quite often in geological materials, the effective wave velocity $= \sqrt{K/\varrho}$ is different in different spatial directions because geological layers are ompacted such that the properties in the horizontal and vertical direction differ. Vith z as the vertical coordinate, we can introduce a vertical wave velocity c_z nd a horizontal wave velocity c_h, and generalize (129) to

$$p_{tt} = c_z^2 p_{zz} + c_h^2(p_{xx} + p_{yy}) + s\,. \tag{130}$$

19.5 Sound waves in liquids and gases

Sound waves arise from pressure and density variations in fluids. The point of modeling sound waves is the basic equations for a compressib where we omit viscous (frictional) forces, body forces (gravity, for instan temperature effects:

$$\varrho_t + \nabla \cdot (\varrho\boldsymbol{u}) = 0,$$
$$\varrho\boldsymbol{u}_t + \varrho\boldsymbol{u} \cdot \nabla\boldsymbol{u} = -\nabla p,$$
$$\varrho = \varrho(p)\,.$$

These equations are often referred to as the Euler equations for the mot fluid. The parameters involved are the density ϱ, the velocity $\boldsymbol{u}$, and the p. Equation (132) reflects mass balance, (131) is Newton's second law for with frictional and body forces omitted, and (133) is a constitutive law density to pressure by thermodynamics considerations. A typical model f is the so-called isentropic relation[30], valid for adiabatic processes where no heat transfer:

$$\varrho = \varrho_0 \left(\frac{p}{p_0}\right)^{1/\gamma}\,.$$

Here, p_0 and ϱ_0 are references values for p and ϱ when the fluid is at res is the ratio of specific heat at constant pressure and constant volume (for air).

The key approximation in a mathematical model for sound waves is to that these waves are small perturbations to the density, pressure, and We therefore write

$$p = p_0 + \hat{p},$$
$$\varrho = \varrho_0 + \hat{\varrho},$$
$$\boldsymbol{u} = \hat{\boldsymbol{u}},$$

where we have decomposed the fields in a constant equilibrium valu sponding to $\boldsymbol{u} = 0$, and a small perturbation marked with a hat sym inserting these decompositions in (131) and (132), neglecting all produc of small perturbations and/or their derivatives, and dropping the hat s one gets the following linearized PDE system for the small perturba density, pressure, and velocity:

$$\varrho_t + \varrho_0\nabla \cdot \boldsymbol{u} = 0,$$
$$\varrho_0\boldsymbol{u}_t = -\nabla p\,.$$

---

[30]http://en.wikipedia.org/wiki/Isentropic_process

ow we can eliminate ϱ_t by differentiating the relation $\varrho(p)$,

$$\varrho_t = \varrho_0 \frac{1}{\gamma} \left(\frac{p}{p_0}\right)^{1/\gamma-1} \frac{1}{p_0} p_t = \frac{\varrho_0}{\gamma p_0} \left(\frac{p}{p_0}\right)^{1/\gamma-1} p_t \,.$$

he product term $p^{1/\gamma-1} p_t$ can be linearized as $p_0^{1/\gamma-1} p_t$, resulting in

$$\varrho_t \approx \frac{\varrho_0}{\gamma p_0} p_t \,.$$

Ve then get

$$p_t + \gamma p_0 \nabla \cdot \boldsymbol{u} = 0, \tag{137}$$

$$\boldsymbol{u}_t = -\frac{1}{\varrho_0} \nabla p, \,. \tag{138}$$

aking the divergence of (138) and differentiating (137) with respect to time ives the possibility to easily eliminate $\nabla \cdot \boldsymbol{u}_t$ and arrive at a standard, linear ave equation for p:

$$p_{tt} = c^2 \nabla^2 p, \tag{139}$$

here $c = \sqrt{\gamma p_0/\varrho_0}$ is the speed of sound in the fluid.

9.6   Spherical waves

pherically symmetric three-dimensional waves propagate in the radial direction only so that $u = u(r,t)$. The fully three-dimensional wave equation

$$\frac{\partial^2 u}{\partial t^2} = \nabla \cdot (c^2 \nabla u) + f$$

hen reduces to the spherically symmetric wave equation

$$\frac{\partial^2 u}{\partial t^2} = \frac{1}{r^2} \frac{\partial}{\partial r} \left(c^2(r) r^2 \frac{\partial u}{\partial t} \right) + f(r,t), \quad r \in (0, R),\ t > 0 \,. \tag{140}$$

ne can easily show that the function $v(r,t) = ru(r,t)$ fulfills a standard wave quation in Cartesian coordinates if c is constant. To this end, insert $u = v/r$ in

$$\frac{1}{r^2} \frac{\partial}{\partial r} \left(c^2(r) r^2 \frac{\partial u}{\partial t} \right)$$

o obtain

$$r\left(\frac{dc^2}{dr} \frac{\partial v}{\partial r} + c^2 \frac{\partial^2 v}{\partial r^2} \right) - \frac{dc^2}{dr} v \,.$$

he two terms in the parenthesis can be combined to

$$r \frac{\partial}{\partial r} \left(c^2 \frac{\partial v}{\partial r} \right),$$

which is recognized as the variable-coefficient Laplace operator in one C coordinate. The spherically symmetric wave equation in terms of $v(r$ becomes

$$\frac{\partial^2 v}{\partial t^2} = \frac{\partial}{\partial r} \left(c^2(r) \frac{\partial v}{\partial r} \right) - \frac{1}{r} \frac{dc^2}{dr} v + r f(r,t), \quad r \in (0, R),\ t > 0 \,.$$

In the case of constant wave velocity c, this equation reduces to the wave in a single Cartesian coordinate called r:

$$\frac{\partial^2 v}{\partial t^2} = c^2 \frac{\partial^2 v}{\partial r^2} + r f(r,t), \quad r \in (0, R),\ t > 0 \,.$$

That is, any program for solving the one-dimensional wave equation in a C coordinate system can be used to solve (142), provided the source multiplied by the coordinate, and that we divide the Cartesian mesh sol r to get the spherically symmetric solution. Moreover, if $r = 0$ is include domain, spherical symmetry demands that $\partial u/\partial r = 0$ at $r = 0$, which that

$$\frac{\partial u}{\partial r} = \frac{1}{r^2} \left(r \frac{\partial v}{\partial r} - v \right) = 0, \quad r = 0,$$

implying $v(0,t) = 0$ as a necessary condition. For practical applicati exclude $r = 0$ from the domain and assume that some boundary con assigned at $r = \epsilon$, for some $\epsilon > 0$.

19.7   The linear shallow water equations

The next example considers water waves whose wavelengths are much la the depth and whose wave amplitudes are small. This class of waves generated by catastrophic geophysical events, such as earthquakes at bottom, landslides moving into water, or underwater slides (or a comb as earthquakes frequently release avalanches of masses). For example, a earthquake will normally have an extension of many kilometers but lift t only a few meters. The wave length will have a size dictated by the ear area, which is much lager than the water depth, and compared to th length, an amplitude of a few meters is very small. The water is essentiall film, and mathematically we can average the problem in the vertical d and approximate the 3D wave phenomenon by 2D PDEs. Instead of a water domain in three space dimensions, we get a horizontal 2D domain unknown function for the surface elevation and the water depth as a coefficient in the PDEs.

Let $\eta(x,y,t)$ be the elevation of the water surface, $H(x,y)$ the wate corresponding to a flat surface ($\eta = 0$), $u(x,y,t)$ and $v(x,y,t)$ the depth-a horizontal velocities of the water. Mass and momentum balance of th volume give rise to the PDEs involving these quantities:

$$\eta_t = -(Hu)_x - (Hv)_x \tag{143}$$

$$u_t = -g\eta_x, \tag{144}$$

$$v_t = -g\eta_y, \tag{145}$$

here g is the acceleration of gravity. Equation (143) corresponds to mass alance while the other two are derived from momentum balance (Newton's econd law).

The initial conditions associated with (143)-(145) are η, u, and v prescribed t $t = 0$. A common condition is to have some water elevation $\eta = I(x,y)$ and ssume that the surface is at rest: $u = v = 0$. A subsea earthquake usually neans a sufficiently rapid motion of the bottom and the water volume to say nat the bottom deformation is mirrored at the water surface as an initial lift (x,y) and that $u = v = 0$.

Boundary conditions may be η prescribed for incoming, known waves, or ero normal velocity at reflecting boundaries (steep mountains, for instance): $n_x + vn_y = 0$, where (n_x, n_y) is the outward unit normal to the boundary. More ophisticated boundary conditions are needed when waves run up at the shore, nd at open boundaries where we want the waves to leave the computational omain undisturbed.

Equations (143), (144), and (145) can be transformed to a standard, linear ave equation. First, multiply (144) and (145) by H, differentiate (144)) with espect to x and (145) with respect to y. Second, differentiate (143) with espect to t and use that $(Hu)_{xt} = (Hu_t)_x$ and $(Hv)_{yt} = (Hv_t)_y$ when H is ndependent of t. Third, eliminate $(Hu_t)_x$ and $(Hv_t)_y$ with the aid of the other vo differentiated equations. These manipulations results in a standard, linear ave equation for η:

$$\eta_{tt} = (gH\eta_x)_x + (gH\eta_y)_y = \nabla \cdot (gH\nabla\eta). \tag{146}$$

In the case we have an initial non-flat water surface at rest, the initial onditions become $\eta = I(x,y)$ and $\eta_t = 0$. The latter follows from (143) if $= v = 0$, or simply from the fact that the vertical velocity of the surface is η_t, hich is zero for a surface at rest.

The system (143)-(145) can be extended to handle a time-varying bottom opography, which is relevant for modeling long waves generated by underwater ides. In such cases the water depth function H is also a function of t, due to ne moving slide, and one must add a time-derivative term H_t to the left-hand de of (143). A moving bottom is best described by introducing $z = H_0$ as the till-water level, $z = B(x,y,t)$ as the time- and space-varying bottom topography, that $H = H_0 - B(x,y,t)$. In the elimination of u and v one may assume that ne dependence of H on t can be neglected in the terms $(Hu)_{xt}$ and $(Hv)_{yt}$. We nen end up with a source term in (146), because of the moving (accelerating) ottom:

$$\eta_{tt} = \nabla \cdot (gH\nabla\eta) + B_{tt}. \tag{147}$$

The reduction of (147) to 1D, for long waves in a straight channe approximately plane waves in the ocean, is trivial by assuming no cha direction ($\partial/\partial y = 0$):

$$\eta_t = (gH\eta_x)_x + B_{tt}.$$

Wind drag on the surface. Surface waves are influenced by the dr wind, and if the wind velocity some meters above the surface is (U, V), t drag gives contributions $C_V\sqrt{U^2 + V^2}U$ and $C_V\sqrt{U^2 + V^2}V$ to (144) ar respectively, on the right-hand sides.

Bottom drag. The waves will experience a drag from the botton roughly modeled by a term similar to the wind drag: $C_B\sqrt{u^2 + v^2}u$ right-hand side of (144) and $C_B\sqrt{u^2 + v^2}v$ on the right-hand side of (14! that in this case the PDEs (144) and (145) become nonlinear and the elir of u and v to arrive at a 2nd-order wave equation for η is not possible a

Effect of the Earth's rotation. Long geophysical waves will often be by the rotation of the Earth because of the Coriolis force. This force g to a term fv on the right-hand side of (144) and $-fu$ on the right-ha of (145). Also in this case one cannot eliminate u and v to work with equation for η. The Coriolis parameter is $f = 2\Omega\sin\phi$, where Ω is the velocity of the earth and ϕ is the latitude.

19.8 Waves in blood vessels

The flow of blood in our bodies is basically fluid flow in a network Unlike rigid pipes, the walls in the blood vessels are elastic and will their diameter when the pressure rises. The elastic forces will then push back and accelerate the fluid. This interaction between the flow of blood deformation of the vessel wall results in waves traveling along our blood

A model for one-dimensional waves along blood vessels can be deriv averaging the fluid flow over the cross section of the blood vessels. Let coordinate along the blood vessel and assume that all cross sections are though with different radius $R(x,t)$. The main quantities to comput cross section area $A(x,t)$, the averaged pressure $P(x,t)$, and the total flux $Q(x,t)$. The area of this cross section is

$$A(x,t) = 2\pi \int_0^{R(x,t)} r \, dr,$$

Let $v_x(x,t)$ be the velocity of blood averaged over the cross section at The volume flux, being the total volume of blood passing a cross sec time unit, becomes

$$Q(x,t) = A(x,t)v_x(x,t)$$

Mass balance and Newton's second law lead to the PDEs

$$\frac{\partial A}{\partial t} + \frac{\partial Q}{\partial x} = 0, \tag{151}$$

$$\frac{\partial Q}{\partial t} + \frac{\gamma+2}{\gamma+1}\frac{\partial}{\partial x}\left(\frac{Q^2}{A}\right) + \frac{A}{\varrho}\frac{\partial P}{\partial x} = -2\pi(\gamma+2)\frac{\mu}{\varrho}\frac{Q}{A}, \tag{152}$$

here γ is a parameter related to the velocity profile, ϱ is the density of blood, nd μ is the dynamic viscosity of blood.

We have three unknowns A, Q, and P, and two equations (151) and (152). third equation is needed to relate the flow to the deformations of the wall. A ommon form for this equation is

$$\frac{\partial P}{\partial t} + \frac{1}{C}\frac{\partial Q}{\partial x} = 0, \tag{153}$$

here C is the compliance of the wall, given by the constitutive relation

$$C = \frac{\partial A}{\partial P} + \frac{\partial A}{\partial t}, \tag{154}$$

hich require a relationship between A and P. One common model is to view ne vessel wall, locally, as a thin elastic tube subject to an internal pressure. his gives the relation

$$P = P_0 + \frac{\pi h E}{(1-\nu^2)A_0}(\sqrt{A} - \sqrt{A_0}),$$

here P_0 and A_0 are corresponding reference values when the wall is not deformed, is the thickness of the wall, and E and ν are Young's modulus and Poisson's atio of the elastic material in the wall. The derivative becomes

$$C = \frac{\partial A}{\partial P} = \frac{2(1-\nu^2)A_0}{\pi h E}\sqrt{A_0} + 2\left(\frac{(1-\nu^2)A_0}{\pi h E}\right)^2 (P - P_0). \tag{155}$$

nother (nonlinear) deformation model of the wall, which has a better fit with xperiments, is

$$P = P_0 \exp\left(\beta(A/A_0 - 1)\right),$$

here β is some parameter to be estimated. This law leads to

$$C = \frac{\partial A}{\partial P} = \frac{A_0}{\beta P}. \tag{156}$$

Reduction to standard wave equation. It is not uncommon to neglect the iscous term on the right-hand side of (152) and also the quadratic term with Q^2 n the left-hand side. The reduced equations (152) and (153) form a first-order near wave equation system:

$$C\frac{\partial P}{\partial t} = -\frac{\partial Q}{\partial x},$$
$$\frac{\partial Q}{\partial t} = -\frac{A}{\varrho}\frac{\partial P}{\partial x}.$$

These can be combined into standard 1D wave equation PDE by differe the first equation with respect t and the second with respect to x,

$$\frac{\partial}{\partial t}\left(CC\frac{\partial P}{\partial t}\right) = \frac{\partial}{\partial x}\left(\frac{A}{\varrho}\frac{\partial P}{\partial x}\right),$$

which can be approximated by

$$\frac{\partial^2 Q}{\partial t^2} = c^2 \frac{\partial^2 Q}{\partial x^2}, \quad c = \sqrt{\frac{A}{\varrho C}},$$

where the A and C in the expression for c are taken as constant referenc

19.9 Electromagnetic waves

Light and radio waves are governed by standard wave equations arisi Maxwell's general equations. When there are no charges and no curren a vacuum, Maxwell's equations take the form

$$\nabla \cdot \boldsymbol{E} = 0,$$
$$\nabla \cdot \boldsymbol{B} = 0,$$
$$\nabla \times \boldsymbol{E} = -\frac{\partial \boldsymbol{B}}{\partial t},$$
$$\nabla \times \boldsymbol{B} = \mu_0 \epsilon_0 \frac{\partial \boldsymbol{E}}{\partial t},$$

where $\epsilon_0 = 8.854187817620 \cdot 10^{-12}$ (F/m) is the permittivity of free spa known as the electric constant, and $\mu_0 = 1.2566370614 \cdot 10^{-6}$ (H/m permeability of free space, also known as the magnetic constant. Taking of the two last equations and using the identity

$$\nabla \times (\nabla \times \boldsymbol{E}) = \nabla(\nabla \cdot \boldsymbol{E}) - \nabla^2 \boldsymbol{E} = -\nabla^2 \boldsymbol{E} \text{ when } \nabla \cdot \boldsymbol{E} = 0,$$

immediately gives the wave equation governing the electric and magnet

$$\frac{\partial^2 \boldsymbol{E}}{\partial t^2} = c^2 \frac{\partial^2 \boldsymbol{E}}{\partial x^2},$$
$$\frac{\partial^2 \boldsymbol{E}}{\partial t^2} = c^2 \frac{\partial^2 \boldsymbol{E}}{\partial x^2},$$

with $c = 1/\sqrt{\mu_0 \epsilon_0}$ as the velocity of light. Each component of $\boldsymbol{E}$ and $\boldsymbol{B}$ wave equation and can hence be solved independently.

Exercise 15: Simulate waves on a non-homogeneous string

Simulate waves on a string that consists of two materials with different density. The tension in the string is constant, but the density has a jump at the middle of the string. Experiment with different sizes of the jump and produce animations that visualize the effect of the jump on the wave motion.

Hint. According to Section 19.1, the density enters the mathematical model as in $\varrho u_{tt} = T u_{xx}$, where T is the string tension. Modify, e.g., the `wave1D_u0v.py` code to incorporate the tension and two density values. Make a mesh function rho with density values at each spatial mesh point. A value for the tension may be 150 N. Corresponding density values can be computed from the wave velocity estimations in the `guitar` function in the `wave1D_u0v.py` file. Filename: `wave1D_u0_sv_discont.py`.

Exercise 16: Simulate damped waves on a string

Formulate a mathematical model for damped waves on a string. Use data from Section 3.4, and tune the damping parameter so that the string is very close to the rest state after 15 s. Make a movie of the wave motion. Filename: `wave1D_u0_sv_damping.py`.

Exercise 17: Simulate elastic waves in a rod

A hammer hits the end of an elastic rod. The exercise is to simulate the resulting wave motion using the model (121) from Section 19.3. Let the rod have length and let the boundary $x = L$ be stress free so that $\sigma_{xx} = 0$, implying that $u/\partial x = 0$. The left end $x = 0$ is subject to a strong stress pulse (the hammer), modeled as

$$\sigma_{xx}(t) = \begin{cases} S, & 0 < t \leq t_s, \\ 0, & t > t_s \end{cases}$$

The corresponding condition on u becomes $u_x = S/E$ for $t \leq t_s$ and zero afterwards (recall that $\sigma_{xx} = E u_x$). This is a non-homogeneous Neumann condition, and you will need to approximate this condition and combine it with the scheme (the ideas and manipulations follow closely the handling of a non-zero initial condition $u_t = V$ in wave PDEs or the corresponding second-order ODEs for vibrations). Filename: `wave_rod.py`.

Exercise 18: Simulate spherical waves

Implement a model for spherically symmetric waves using the method described in Section 19.6. The boundary condition at $r = 0$ must be $\partial u/\partial r = 0$, while the condition at $r = R$ can either be $u = 0$ or a radiation condition as described in

Problem 21. The $u = 0$ condition is sufficient if R is so large that the am of the spherical wave has become insignificant. Make movie(s) of the cas the source term is located around $r = 0$ and sends out pulses

$$f(r,t) = \begin{cases} Q \exp\left(-\frac{r^2}{2\Delta r^2}\right) \sin \omega t, & \sin \omega t \geq 0 \\ 0, & \sin \omega t < 0 \end{cases}$$

Here, Q and ω are constants to be chosen.

Hint. Use the program `wave1D_u0v.py` as a starting point. Let `solv` pute the v function and then set $u = v/r$. However, $u = v/r$ for $r = 0$ special treatment. One possibility is to compute `u[1:]  = v[1:]/r[1` then set `u[0]=u[1]`. The latter makes it evident that $\partial u/\partial r = 0$ in a p Filename: `wave1D_spherical.py`.

Exercise 19: Explain why numerical noise occurs

The experiments performed in Exercise 8 shows considerable numeric in the form of non-physical waves, especially for $s_f = 4$ and the plu or the half a "cosinehat" pulse. The noise is much less visible for a G pulse. Run the case with the plug and half a "cosinehat" pulses for $C = 0.9, 0.25$, and $N_x = 40, 80, 160$. Use the numerical dispersion rel explain the observations. Filename: `pulse1D_analysis.pdf`.

Exercise 20: Investigate harmonic averaging in a 1D

Harmonic means are often used if the wave velocity is non-smooth or tinuous. Will harmonic averaging of the wave velocity give less nu noise for the case $s_f = 4$ in Exercise 8? Filenames: `pulse1D_harmon` `pulse1D_harmonic.py`.

Problem 21: Implement open boundary conditions

To enable a wave to leave the computational domain and travel undi through the boundary $x = L$, one can in a one-dimensional problem imp following condition, called a *radiation condition* or *open boundary cond*

$$\frac{\partial u}{\partial t} + c \frac{\partial u}{\partial x} = 0.$$

The parameter c is the wave velocity.

Show that (162) accepts a solution $u = g_R(x - ct)$ (right-going wav not $u = g_L(x + ct)$ (left-going wave). This means that (162) will al right-going wave $g_R(x - ct)$ to pass through the boundary undisturbed

A corresponding open boundary condition for a left-going wave throu is

$$\frac{\partial u}{\partial t} - c\frac{\partial u}{\partial x} = 0 \,. \tag{163}$$

) A natural idea for discretizing the condition (162) at the spatial end point
$= N_x$ is to apply centered differences in time and space:

$$[D_{2t}u + cD_{2x}u = 0]_i^n, \quad i = N_x \,. \tag{164}$$

liminate the fictitious value $u_{N_x+1}^n$ by using the discrete equation at the same
oint.

The equation for the first step, u_i^1, is in principle also affected, but we can
hen use the condition $u_{N_x} = 0$ since the wave has not yet reached the right
oundary.

) A much more convenient implementation of the open boundary condition at
$= L$ can be based on an explicit discretization

$$[D_t^+u + cD_x^-u = 0]_i^n, \quad i = N_x \,. \tag{165}$$

rom this equation, one can solve for $u_{N_x}^{n+1}$ and apply the formula as a Dirichlet
ondition at the boundary point. However, the finite difference approximations
nvolved are of first order.

Implement this scheme for a wave equation $u_{tt} = c^2 u_{xx}$ in a domain $[0, L]$,
here you have $u_x = 0$ at $x = 0$, the condition (162) at $x = L$, and an initial
isturbance in the middle of the domain, e.g., a plug profile like

$$u(x, 0) = \begin{cases} 1, & L/2 - \ell \le x \le L/2 + \ell, \\ 0, \text{otherwise} \end{cases}$$

bserve that the initial wave is split in two, the left-going wave is reflected at
$= 0$, and both waves travel out of $x = L$, leaving the solution as $u = 0$ in $[0, L]$.
se a unit Courant number such that the numerical solution is exact. Make a
novie to illustrate what happens.

Because this simplified implementation of the open boundary condition works,
here is no need to pursue the more complicated discretization in a).

Hint. Modify the solver function in `wave1D_dn.py`[31].

) Add the possibility to have either $u_x = 0$ or an open boundary condition at
he left boundary. The latter condition is discretized as

$$[D_t^+u - cD_x^+u = 0]_i^n, \quad i = 0, \tag{166}$$

eading to an explicit update of the boundary value u_0^{n+1}.

The implementation can be tested with a Gaussian function as initial condi-
on:

---

[31]`http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_dn.py`

$$g(x; m, s) = \frac{1}{\sqrt{2\pi}s}e^{-\frac{(x-m)^2}{2s^2}} \,.$$

Run two tests:

1. Disturbance in the middle of the domain, $I(x) = g(x; L/2, s)$, an
   boundary condition at the left end.

2. Disturbance at the left end, $I(x) = g(x; 0, s)$, and $u_x = 0$ as sy
   boundary condition at this end.

Make nose tests for both cases, testing that the solution is zero after th
have left the domain.

d) In 2D and 3D it is difficult to compute the correct wave velocity no
the boundary, which is needed in generalizations of the open boundary co
in higher dimensions. Test the effect of having a slightly wrong wave vel
(165). Make a movies to illustrate what happens.
Filename: `wave1D_open_BC.py`.

Remarks. The condition (162) works perfectly in 1D when c is known
and 3D, however, the condition reads $u_t + c_x u_x + c_y u_y = 0$, where c_x
are the wave speeds in the x and y directions. Estimating these com
(i.e., the direction of the wave) is often challenging. Other methods are r
used in 2D and 3D to let waves move out of a computational domain.

Exercise 22: Implement periodic boundary condition

It is frequently of interest to follow wave motion over large distances a
times. A straightforward approach is to work with a very large doma
might lead to a lot of computations in areas of the domain where th
cannot be noticed. A more efficient approach is to let a right-going w
of the domain and at the same time let it enter the domain on the left.
called a *periodic boundary condition*.

The boundary condition at the right end $x = L$ is an open boundary co
(see Exercise 21) to let a right-going wave out of the domain. At the l
$x = 0$, we apply, in the beginning of the simulation, either a symmetry be
condition (see Exercise 7) $u_x = 0$, or an open boundary condition.

This initial wave will split in two and either reflected or transported
the domain at $x = 0$. The purpose of the exercise is to follow the righ
wave. We can do that with a *periodic boundary condition*. This means th
the right-going wave hits the boundary $x = L$, the open boundary condi
the wave out of the domain, but at the same time we use a boundary co
on the left end $x = 0$ that feeds the outgoing wave into the domain aga
periodic condition is simply $u(0) = u(L)$. The switch from $u_x = 0$ or a
boundary condition at the left end to a periodic condition can happe

$(L, t) > \epsilon$, where $\epsilon = 10^{-4}$ might be an appropriate value for determining when the right-going wave hits the boundary $x = L$.

The open boundary conditions can conveniently be discretized as explained in Exercise 21. Implement the described type of boundary conditions and test them on two different initial shapes: a plug $u(x, 0) = 1$ for $x \leq 0.1$, $u(x, 0) = 0$ for $x > 0.1$, and a Gaussian function in the middle of the domain: $u(x, 0) = \exp\left(-\frac{1}{2}(x - 0.5)^2/0.05\right)$. The domain is the unit interval $[0, 1]$. Run these two shapes for Courant numbers 1 and 0.5. Assume constant wave velocity. Make movies of the four cases. Reason why the solutions are correct. Filename: `periodic.py`.

Problem 23: Earthquake-generated tsunami over a subsea hill

A subsea earthquake leads to an immediate lift of the water surface, see Figure 10. The lifted water surface splits into two tsunamis, one traveling to the right and one to the left, as depicted in Figure 11. Since tsunamis are normally very long waves, compared to the depth, with a small amplitude, compared to the wave length, the wave equation model described in Section 19.7 is relevant:

$$\eta_{tt} = (gH(x)\eta_x)_x,$$

where g is the acceleration of gravity, and $H(x)$ is the still water depth.


Figure 10: Sketch of initial water surface due to a subsea earthquake.

To simulate the right-going tsunami, we can impose a symmetry boundary at $x = 0$: $\partial\eta/\partial x = 0$. We then simulate the wave motion in $[0, L]$. Unless the ocean ends at $x = L$, the waves should travel undisturbed through the boundary $x = L$. A radiation condition as explained in Problem 21 can be used for this purpose. Alternatively, one can just stop the simulations before the wave hits


Figure 11: An initial surface elevation is split into two waves.

the boundary at $x = L$. In that case it does not matter what kind of boundary condition we use at $x = L$. Imposing $\eta = 0$ and stopping the simulation $|\eta_i^n| > \epsilon$, $i = N_x - 1$, is a possibility (ϵ is a small parameter).

The shape of the initial surface can be taken as a Gaussian function

$$I(x; I_0, I_a, I_m, I_s) = I_0 + I_a \exp\left(-\left(\frac{x - I_m}{I_s}\right)^2\right),$$

with $I_m = 0$ reflecting the location of the peak of $I(x)$ and I_s being a measure of the width of the function $I(x)$ (I_s is $\sqrt{2}$ times the standard deviation of the familiar normal distribution curve).

Now we extend the problem with a hill at the sea bottom, see Figure. The wave speed $c = \sqrt{gH(x)} = \sqrt{g(H_0 - B(x))}$ will then be reduced in the water above the hill.

One possible form of the hill is a Gaussian function,

$$B(x; B_0, B_a, B_m, B_s) = B_0 + B_a \exp\left(-\left(\frac{x - B_m}{B_s}\right)^2\right),$$

but many other shapes are also possible, e.g., a "cosine hat" where

$$B(x; B_0, B_a, B_m, B_s) = B_0 + B_a \cos\left(\pi\frac{x - B_m}{2B_s}\right),$$

when $x \in [B_m - B_s, B_m + B_s]$ while $B = B_0$ outside this interval. Also an abrupt construction may be tried:

$$B(x; B_0, B_a, B_m, B_s) = B_0 + B_a,$$

for $x \in [B_m - B_s, B_m + B_s]$ while $B = B_0$ outside this interval.

Figure 12: Sketch of an earthquake-generated tsunami passing over a subsea hill.

The `wave1D_dn_vc.py`[32] program can be used as starting point for the implementation. Visualize both the bottom topography and the water surface elevation in the same plot. Allow for a flexible choice of bottom shape: (168), (169), (170), or $B(x) = B_0$ (flat).

The purpose of this problem is to explore the quality of the numerical solution u_i^n for different shapes of the bottom obstruction. The "cosine hat" and the box-shaped hills have abrupt changes in the derivative of $H(x)$ and are more likely to generate numerical noise than the smooth Gaussian shape of the hill. Investigate if this is true. Filenames: `tsunami1D_hill.py`, `tsunami1D_hill.pdf`.

Problem 24: Earthquake-generated tsunami over a 3D hill

This problem extends Problem 23 to a three-dimensional wave phenomenon, governed by the 2D PDE (146). We assume that the earthquake arise from a fault along the line $x = 0$ in the xy-plane so that the initial lift of the surface can be taken as $I(x)$ in Problem 23. That is, a plane wave is propagating to the right, but will experience bending because of the bottom.

The bottom shape is now a function of x and y. An "elliptic" Gaussian function in two dimensions, with its peak at (B_{mx}, B_{my}), generalizes (168):

$$B(x; B_0, B_a, B_{mx}, B_{my}, B_s, b) = B_0 + B_a \exp\left(-\left(\frac{x - B_{mx}}{B_s}\right)^2 - \left(\frac{y - B_{my}}{bB_s}\right)^2\right),$$
(171)

[32] http://tinyurl.com/jvzzcfn/wave/wave1D/wave1D_dn_vc.py

where b is a scaling parameter: $b = 1$ gives a circular Gaussian functi... circular contour lines, while $b \neq 1$ gives an elliptic shape with elliptic lines.

The "cosine hat" (169) can also be generalized to

$$B(x; B_0, B_a, B_{mx}, B_{my}, B_s) = B_0 + B_a \cos\left(\pi\frac{x - B_{mx}}{2B_s}\right)\cos\left(\pi\frac{y - B_{my}}{2B_s}\right)$$

when $0 \leq \sqrt{x^2 + y^2} \leq B_s$ and $B = B_0$ outside this circle.

A box-shaped obstacle means that

$$B(x; B_0, B_a, B_m, B_s, b) = B_0 + B_a$$

for x and y inside a rectangle

$$B_{mx} - B_s \leq x \leq B_{mx} + B_s, \quad B_{my} - bB_s \leq y \leq B_{my} + bB_s,$$

and $B = B_0$ outside this rectangle. The b parameter controls the rect... shape of the cross section of the box.

Note that the initial condition and the listed bottom shapes are sy... around the line $y = B_{my}$. We therefore expect the surface elevation... be symmetric with respect to this line. This means that we can ha... computational domain by working with $[0, L_x] \times [0, B_{my}]$. Along th... boundary, $y = B_{my}$, we must impose the symmetry condition $\partial\eta/\partial n =$... a symmetry condition $(-\eta_x = 0)$ is also needed at the $x = 0$ boundary... the initial condition has a symmetry here. At the lower boundary $y = 0$... set a Neumann condition (which becomes $-\eta_y = 0$). The wave motion... simulated until the wave hits the reflecting boundaries where $\partial\eta/\partial n =$... (one can also set $\eta = 0$ - the particular condition does not matter as lon... simulation is stopped before the wave is influenced by the boundary co...

Visualize the surface elevation. Investigate how different hill sha... ferent sizes of the water gap above the hill, and different resolutions... $\Delta y = h$ and Δt influence the numerical quality of the solution. Fil... `tsunami2D_hill.py`, `tsunami2D_hill.pdf`.

Problem 25: Investigate Matplotlib for visualization

Play with native Matplotlib code for visualizing 2D solutions of the wave e... with variable wave velocity. See if there are effective ways to visualize b... solution and the wave velocity. Filename: `tsunami2D_hill_mpl.py`.

Problem 26: Investigate visualization packages

Create some fancy 3D visualization of the water waves *and* the subse... Problem 24. Try to make the hill transparent. Possible visualization to...

- Mayavi[33]
- Paraview[34]
- OpenDX[35]

ilename: `tsunami2D_hill_viz.py`.

Problem 27: Implement loops in compiled languages

xtend the program from Problem 24 such that the loops over mesh points, inside he time loop, are implemented in compiled languages. Consider implementations 1 Cython, Fortran via `f2py`, C via Cython, C via `f2py`, C/C++ via Instant, nd C/C++ via `scipy.weave`. Perform efficiency experiments to investigate the elative performance of the various implementations. It is often advantageous o normalize CPU times by the fastest method on a given mesh. Filename: sunami2D_hill_compiled.py.

Exercise 28: Simulate seismic waves in 2D

he goal of this exercise is to simulate seismic waves using the PDE model .30) in a 2D xz domain with geological layers. Introduce m horizontal layers f thickness h_i, $i = 0, \ldots, m - 1$. Inside layer number i we have a vertical wave elocity $c_{z,i}$ and a horizontal wave velocity $c_{h,i}$. Make a program for simulating ach 2D waves. Test it on a case with 3 layers where

$$c_{z,0} = c_{z,1} = c_{z,2}, \quad c_{h,0} = c_{h,2}, \quad c_{h,1} \ll c_{h,0}.$$

et s be a localized point source at the middle of the Earth's surface (the pper boundary) and investigate how the resulting wave travels through the nedium. The source can be a localized Gaussian peak that oscillates in time or some time interval. Place the boundaries far enough from the expanding ave so that the boundary conditions do not disturb the wave. Then the type f boundary condition does not matter, except that we physically need to have $= p_0$, where p_0 is the atmospheric pressure, at the upper boundary. Filename: eismic2D.py.

Project 29: Model 3D acoustic waves in a room

he equation for sound waves in air is derived in Section 19.5 and reads

$$p_{tt} = c^2 \nabla^2 p,$$

here $p(x, y, z, t)$ is the pressure and c is the speed of sound, taken as 340 m/s. .owever, sound is absorbed in the air due to relaxation of molecules in the gas.

---

[33] http://code.enthought.com/projects/mayavi/
[34] http://www.paraview.org/
[35] http://www.opendx.org/

A model for simple relaxation, valid for gases consisting only of one molecules, is a term $c^2 \tau_s \nabla^2 p_t$ in the PDE, where τ_s is the relaxation tim generate sound from, e.g., a loudspeaker in the room, this sound sour also be added to the governing equation.

The PDE with the mentioned type of damping and source then bec

$$p_t t = c^2 \nabla^p + c^2 \tau_s \nabla^2 p_t + f,$$

where $f(x, y, z, t)$ is the source term.

The walls can absorb some sound. A possible model is to have a "wa (thicker than the physical wall) outside the room where c is changed su some of the wave energy is reflected and some is absorbed in the wa absorption of energy can be taken care of by adding a damping term bp equation:

$$p_t t + b p_t = c^2 \nabla^p + c^2 \tau_s \nabla^2 p_t + f.$$

Typically, $b = 0$ in the room and $b > 0$ in the wall. A discontinuity i will give rise to reflections. It can be wise to use a constant c in the control reflections because of the discontinuity between c in the air an wall, while b is gradually increased as we go into the wall to avoid ref because of rapid changes in b. At the outer boundary of the wall the co $p = 0$ or $\partial p / \partial n = 0$ can be imposed. The waves should anyway be appro dampened to $p = 0$ this far out in the wall layer.

There are two strategies for discretizing the $\nabla^2 p_t$ term: using a difference between times $n + 1$ and $n - 1$ (if the equation is sampled at or use a one-sided difference based on levels n and $n - 1$. The latter advantage of not leading to any equation system, while the former is secor accurate as the scheme for the simple wave equation $p_t t = c^2 \nabla^2 p$. To a equation system, go for the one-sided difference such that the overall becomes explicit and only of first order in time.

Develop a 3D solver for the specified PDE and introduce a wall layer. solver with the method of manufactured solutions. Make some demons where the wall reflects and absorbs the waves (reflection because of disco in b and absorption because of growing b). Experiment with the impac τ_s parameter. Filename: `acoustics.py`.

Project 30: Solve a 1D transport equation

We shall study the wave equation

$$u_t + c u_x = 0, \quad x \in (0, L], \ t \in (0, T],$$

with initial condition

$$u(x, 0) = I(x), \quad x \in [0, L],$$

and *one* periodic boundary condition

$$u(0, t) = u(L, t). \tag{178}$$

his boundary condition means that what goes out of the domain at $x = L$
omes in at $x = 0$. Roughly speaking, we need only one boundary condition
ecause of the spatial derivative is of first order only.

hysical interpretation. The parameter c can be constant or variable, $c =$
(x). The equation (176) arises in *transport* problems where a quantity u, which
ould be temperature or concentration of some contaminant, is transported with
ne velocity c of a fluid. In addition to the transport imposed by "travelling with
ne fluid", u may also be transported by diffusion (such as heat conduction or
ickian diffusion), but we have in the model $u_t + cu_x$ assumed that diffusion
fects are negligible, which they often are.

A widely used numerical scheme for (176) applies a forward difference in
me and a backward difference in space when $c > 0$:

$$[D_t^+ u + cD_x^- u = 0]_i^n. \tag{179}$$

or $c < 0$ we use a forward difference in space: $[cD_x^+ u]_i^n$.

We shall hereafter assume that $= c(x) > 0$.

To compute (184) we need to integrate $1/c$ to obtain C and then compute
ne inverse of C.

The inverse function computation can be easily done if we first think discretely.
ay we have some function $y = g(x)$ and seeks its inverse. Plotting (x_i, y_i),
here $y_i = g(x_i)$ for some mesh points x_i, displays g as a function of x. The
iverse function is simply x as a function of g, i.e., the curve with points (y_i, x_i).
Je can therefore quickly compute points at the curve of the inverse function.
ne way of extending these points to a continuous function is to assume a linear
ariation (known as linear interpolation) between the points (which actually
ieans to draw straight lines between the points, exactly as done by a plotting
rogram).

The function `wrap2callable` in `scitools.std` can take a set of points and
eturn a continuous function that corresponds to linear variation between the
oints. The computation of the inverse of a function g on $[0, L]$ can then be
one by

```
def inverse(g, domain, resolution=101):
    x = linspace(domain[0], domain[L], resolution)
    y = g(x)
    from scitools.std import wrap2callable
    g_inverse = wrap2callable((y, x))
    return g_inverse
```

To compute $C(x)$ we need to integrate $1/c$, which can be done by a Trapezoidal
ıle. Suppose we have computed $C(x_i)$ and need to compute $C(x_{i+1})$. Using
ne Trapezoidal rule with m subintervals over the integration domain $[x_i, x_{i+1}]$
ives

$$C(x_{i+1}) = C(x_i) + \int_{x_i}^{x_{i+1}} \frac{dx}{c} \approx h \left(\frac{1}{2} \frac{1}{c(x_i)} + \frac{1}{2} \frac{1}{c(x_{i+1})} + \sum_{j=1}^{m-1} \frac{1}{c(x_i + \ldots)} \right)$$

where $h = (x_{i+1} - x_i)/m$ is the length of the subintervals used for the
over $[x_i, x_{i+1}]$. We observe that (180) is a *difference equation* which we c
by repeatedly applying (180) for $i = 0, 1, \ldots, N_x - 1$ if a mesh $x_0, x, \ldots$
prescribed. Note that $C(0) = 0$.

a) Show that under the assumption of $a = $ const,

$$u(x, t) = I(x - ct)$$

fulfills the PDE as well as the initial and boundary condition (provided
$I(L)$).

b) Set up a computational algorithm and implement it in a function. A
is constant and positive.

c) Test implementation by using the remarkable property that the nu
solution is exact at the mesh points if $\Delta t = c^{-1} \Delta x$.

d) Make a movie comparing the numerical and exact solution for the f
two choices of initial conditions:

$$I(x) = \left[\sin \left(\pi \frac{x}{L} \right) \right]^{2n}$$

where n is an integer, typically $n = 5$, and

$$I(x) = \exp \left(-\frac{(x - L/2)^2}{2\sigma 2} \right).$$

Choose $\Delta t = c^{-1} \Delta x, 0.9c^{-1} \Delta x, 0.5c^{-1} \Delta x$.

e) The performance of the suggested numerical scheme can be inves
by analyzing the numerical dispersion relation. Analytically, we have t
Fourier component

$$u(x, t) = e^{i(kx - \omega t)},$$

is a solution of the PDE if $\omega = kc$. This is the *analytical dispersion rel*
complete solution of the PDE can be built by adding up such Fourier com
with different amplitudes, where the initial condition I determines the am
The solution u is then represented by a Fourier series.

A similar discrete Fourier component at (x_p, t_n) is

$$u_p^q = e^{i(kp\Delta x - \tilde{\omega} n \Delta t)},$$

here in general $\tilde{\omega}$ is a function of k, Δt, and Δx, and differs from the exact
$= kc$.

Insert the discrete Fourier component in the numerical scheme and derive an
xpression for $\tilde{\omega}$, i.e., the discrete dispersion relation. Show in particular that
the $\Delta t/(c\Delta x) = 1$, the discrete solution coincides with the exact solution at
he mesh points, regardless of the mesh resolution (!). Show that if the stability
ondition

$$\frac{\Delta t}{c\Delta x} \leq 1,$$

he discrete Fourier component cannot grow (i.e., $\tilde{\omega}$ is real).

) Write a test for your implementation where you try to use information from
he numerical dispersion relation.

) Set up a computational algorithm for the variable coefficient case and im-
lement it in a function. Make a test that the function works for constant
.

) It can be shown that for an observer moving with velocity $c(x)$, u is constant.
his can be used to derive an exact solution when a varies with x. Show first
hat

$$u(x,t) = f(C(x) - t), \tag{184}$$

here

$$C'(x) = \frac{1}{c(x)},$$

a solution of (176) for any differentiable function f.

olution. Let $\xi = C(x) - t$. We have that

$$u_t = f'(\xi)(-1),$$

hile

$$u_x = f'(\xi)C'(x) = f'(\xi)\frac{1}{c(x)},$$

nplying that $au_x = f'(\xi)$. Then we have $u_t + cu_x = -f'(\xi) + f'(\xi) = 0$.

Use the initial condition to show that an exact solution is

$$u(x,t) = I(C^{-1}(C(x) - t)),$$

ith C^{-1} being the inverse function of $C = \int c^1 dx$. Since $C(x)$ is an integral
$\int_0^x (1/c)dx$, $C(x)$ is monotonically increasing and there exists hence an inverse
unction C^{-1} with values in $[0, L]$.

Solution. In general we have $u(x,t) = f(C(x) - t)$ and the solution i
form with $f(\xi) = I(C^{-1}(\xi))$. Moreover, at $t = 0$ we have $I(C^{-1}(C(x)))$
which is the required initial condition.

j) Implement a function for computing $C(x_i)$ and one for computing C^-
any x. Use these two functions for computing the exact solution $I(C^{-1}(C$
End up with a function `u_exact_variable_c(x, n, c, I)` that retu
value of $I(C^{-1}(C(x) - t_n))$.

k) Make movies showing a comparison of the numerical and exact solut
the two initial conditions (182) and (30). Choose $\Delta t = \Delta x/\max_{0,L} c(x)$
velocity of the medium as

1. $c(x) = 1 + \epsilon \sin(k\pi x/L)$, $\epsilon < 1$,

2. $c(x) = 1 + I(x)$, where I is given by (182) or (30).

The PDE $u_t + cu_x = 0$ expresses that the initial condition $I(x)$ is tran
with velocity $c(x)$.
Filename: `advec1D.py`.

Problem 31: General analytical solution of a 1D da wave equation

We consider an initial-boundary value problem for the damped wave ec

$$\begin{aligned}
u_{tt} + bu_t &= c^2 u_{xx}, & x \in (0, L),\ t \in (0, T] \\
u(0, t) &= 0, \\
u(L, t) &= 0, \\
u(x, 0) &= I(x), \\
u_t(x, 0) &= V(x).
\end{aligned}$$

Here, $b \geq 0$ and c are given constants. The aim is to derive a general an
solution of this problem. Familiarity with the method of separation of v
for solving PDEs will be assumed.

a) Seek a solution on the form $u(x,t) = X(x)T(t)$. Insert this solutio
PDE and show that it leads to two differential equations for X and T:

$$T'' + bT' + \lambda T = 0, \quad c^2 X'' + \lambda X = 0,$$

with $X(0) = X(L) = 0$ as boundary conditions, and λ as a constar
determined.

b) Show that $X(x)$ is on the form

$$X_n(x) = C_n \sin kx, \quad k = \frac{n\pi}{L}, \quad n = 1, 2, \dots$$

where C_n is an arbitrary constant.

) Under the assumption that $(b/2)^2 < k^2$, show that $T(t)$ is on the form

$$T_n(t) = e^{-\frac{1}{2}bt}(a_n \cos \omega t + b_n \sin \omega t), \quad \omega = \sqrt{k^2 - \frac{1}{4}b^2}, \quad n = 1, 2, \ldots$$

he complete solution is then

$$u(x,t) = \sum_{n=1}^{\infty} \sin kx e^{-\frac{1}{2}bt}(A_n \cos \omega t + B_n \sin \omega t),$$

here the constants A_n and B_n must be computed from the initial conditions.

) Derive a formula for A_n from $u(x,0) = I(x)$ and developing $I(x)$ as a sine ourier series on $[0, L]$.

) Derive a formula for B_n from $u_t(x,0) = V(x)$ and developing $V(x)$ as a sine ourier series on $[0, L]$.

| Calculate A_n and B_n from vibrations of a string where $V(x) = 0$ and

$$I(x) = \begin{cases} ax/x_0, & x < x_0, \\ a(L-x)/(L-x_0), & \text{otherwise} \end{cases} \tag{185}$$

) Implement the series for $u(x,t)$ in a function `u_series(x, t, tol=1E-10)`, here `tol` is a tolerance for truncating the series. Simply sum the terms until $_n|$ and $|b_b|$ both are less than `tol`.

) What will change in the derivation of the analytical solution if we have $_x(0,t) = u_x(L,t) = 0$ as boundary conditions? And how will you solve the roblem with $u(0,t) = 0$ and $u_x(L,t) = 0$?
ilename: `damped_wave1D.pdf`.

roblem 32: General analytical solution of a 2D damped ave equation

arry out Problem 31 in the 2D case: $u_{tt} + bu_t = c^2(u_{xx} + u_{yy})$, where $(x,y) \in$ $, L_x) \times (0, L_y)$. Assume a solution on the form $u(x,y,t) = X(x)Y(y)T(t)$.
ilename: `damped_wave2D.pdf`.

113

Index

114