

RUNWAY/TAXIWAY/APRON PHYSICAL CHARACTERISTICS			
APRON / RWY / TWY	SURFACE	BEARING STRENGTH	ELEVATION
RWY 06/24	Grooved Asphalt	68/R/B/W/T	-
Main Apron	Concrete	72/R/C/W/T	97ft amsl
North Apron	Block Paving	31/F/C/X/T	103ft amsl
East Apron	Concrete	79/R/D/W/T	-
Southeast Apron	Concrete	72/R/C/W/T	-
Turnhouse Apron	Concrete	90/R/D/W/T	-
GA Apron	Concrete	90/R/D/W/T	-
Twy A (between A1 and A8 and A17 and D1)	Concrete	120/R/C/W/T	-
Twy A (between A8 and A17)	Asphalt	70/F/A/W/T	-
Twys E, F	Concrete	72/R/C/W/T	-
Twy G, H	Concrete	90/R/D/W/T	-
Twy L	Concrete	131/R/D/W/T	-
Twy M (Hold M1 to M2 and Hold M2 to M3)	Asphalt	58/F/B/X/T	-
Twy M (Hold M3 to Twy S), Twy Q	Asphalt	31/F/C/X/T	-
Twy P	Asphalt	82/R/D/W/T	-
Twy S	Concrete	79/R/D/W/T	-

COM		
ATIS	131.355	EDINBURGH TERMINAL INFO
TWR	121.980	EDINBURGH DELIVERY
	118.705	EDINBURGH TOWER
	121.755 (GMC)	EDINBURGH GROUND
	121.600	EDINBURGH FIRE
LIGHTING		
THR 06/24	HI green with HI green W bars.	
RWY 06	HI bi-d edge. HI colour coded C/L. End lights red. TDZ 870m.	
RWY 24	HI bi-d edge. HI colour coded C/L. End lights red. TDZ 900m.	
TWY	Green C/L with blue edge lights on sharp curves. RWY exits have alt green/yellow C/L lights to CAT II/III stop bars. Red stop bars at holding points. RWY guard lights on accesses to RWY.	

GUND (Geoid Undulation) = The height of the Geoid (MSL) above the Reference Ellipsoid (WGS 84) at the stated position.	
BEARINGS ARE MAGNETIC ELEVATIONS AND HEIGHTS ARE IN FEET	
ELEVATIONS IN FEET AMSL HEIGHTS IN FEET ABOVE AD	216 (80)

