

CS5489 - Machine Learning

Lecture 10a - Deep Learning

Prof. Antoni B. Chan


Dept. of Computer Science, City University of Hong Kong

Outline


- Going deeper
 - ReLU and Batchnorm
- Optimization methods
- Deep architectures and Image classification
- Transfer learning

Problems with Going Deeper

- **Vanishing Gradient Problem 1**
 - successive multiplications of small gradients gives smaller gradients, and converges to 0
 - the gradients backpropagated to the first few layers has small signal.
- Example: for 4-layers,



- **Vanishing Gradient Problem 2**
 - using backprop, the gradient at a node is the summation over $O(H^D)$ paths
 - D is the number of layers to the output layer.
 - H is the number of nodes in the layer.
 - the original loss signal gets "washed out".



- **Dataset Size**
 - a "small" network with just 40 inputs, 30 hidden nodes, and 1 output has ~1200 parameters.
 - if we don't have enough samples:
 - large variance in the parameter estimator (what you get may be far from the truth)
 - deeper networks are more complex, which are easier to overfit the training data.

- How many samples do we need?
 - Theorem (Bartlett, Maierov, Meir, 1998)


Suppose \mathcal{N} is a feed-forward network with W weights, L layers, and all non-output gates having a fixed piecewise-polynomial activation function with a fixed number of pieces (e.g., ReLU). Then $VCdim(\mathcal{N}) = O(WL \log W + WL^2)$.

- If the sample size is large compared to the VC dimension, then the learned classifier will generalize well.
 - for the same number of parameters, the deeper network requires more data (WL^2).
 - increasing the number of weights, requires a super-linear increase in sample size ($W \log W$).

ReLU activation function


- Rectified Linear Unit: $\text{ReLU}(z) = \max(0, z)$
 - easier to train with: gradient is either 0 or 1.
 - faster: don't need to calculate exponential
 - sparse representation: most nodes will output zero.

In [10]: `actfig`



Advantage of Sparsity


- if a hidden node $h = 0$, then $\frac{dL}{dh} = 0$.
 - This blocks some paths when computing the gradients.
 - Gradient signal is less washed out.
 - Reduces the vanishing gradient problem.



Better Network Parameterization

- There are equivalent parameterizations of the network by scaling up/down the weights in successive layers.
 - $f(\mathbf{x}) = \mathbf{A}^T r(\mathbf{B}^T \mathbf{x}) = \frac{1}{\epsilon} \mathbf{A}^T r(\epsilon \mathbf{B}^T \mathbf{x})$
 - $\epsilon > 0$ and $r(\cdot)$ is the ReLU activation.
- Problem:

- "internal covariate shift" - change in the distribution of activations during training, due to changes in the parameters.




Why is it bad?

- suppose, we have a linear network:
- $y = xw_1w_2w_3w_4$
- gradient of each layer is (g_1, \dots, g_4)
- update the parameters with GD:
 - $y = x(w_1 - \eta g_1)(w_2 - \eta g_2)(w_3 - \eta g_3)(w_4 - \eta g_4)$
 - there are many higher-order terms, e.g., $w_1w_2\eta^2g_3g_4$
 - although w_i are updated independently, they strongly affect each other.
 - hence, if the distribution of activations changes in 1 layer, then all layers are affected, and we need to adjust other layers.

Solution: Batch Normalization

- For each node in each layer, normalize the outputs to zero mean and unit variance, *over each mini-batch*.
 - this is analogous to the idea of normalizing the input feature vector to (0,1) Gaussian with standard ML models!
- Place batchnorm layer after linear transformation.



- Let $\{y_i\}_{i=1}^N$ be the output of the linear transform in one minibatch.
- For each node (dimension) in the layer:
 - normalize: $\hat{y}_i = \frac{y_i - \mu}{\sqrt{\sigma^2 + \epsilon}}$
 - μ, σ^2 are the mean and variance of $\{y_i\}$ in the mini-batch.
 - ϵ is a small constant for numerical stability.
 - scale-shift: $z_i = \gamma \hat{y}_i + \beta$
 - γ, β are learnable parameters
 - puts the output in the proper regime of the non-linear activation.
 - The final distribution has mean β and variance γ^2 .
- Notes:
 - batchnorm is applied to each node independently.
 - should put the batchnorm layer after the linear transformation layer.
 - the bias of the linear layer is not necessary since it is removed by batchnorm

- Training:
 - gradients can be computed through the batchnorm layer as usual.
- Training effects:
 - training is accelerated; can use higher learning rates
 - more stable gradients during training
 - increasing the scale of the activations decreases the gradient
 - self-correcting stabilization.
 - better generalization
 - no need for dropout or L2 regularization.

Example: MNIST

- for each Conv2D/Dense layer:
 - change activation to linear (default); remove bias term
 - append batch-norm and ReLU activation

```
In [11]: def build_nn():
    K.clear_session() # cleanup
    random.seed(4487); tf.random.set_seed(4487) # initialize random seed

    # build the network
    nn = Sequential()
    nn.add(Conv2D(10, (5,5), strides=(2,2), input_shape=(28,28,1),
                  padding='same', use_bias=False))
    nn.add(BatchNormalization(axis=3)) # apply batchnorm on channels
    nn.add(Activation("relu"))
    nn.add(Conv2D(40, (5,5), strides=(2,2), padding='same', use_bias=False))
    nn.add(BatchNormalization(axis=3))
    nn.add(Activation("relu"))
    nn.add(Conv2D(80, (5,5), strides=(1,1), padding='same', use_bias=False))
    nn.add(BatchNormalization(axis=3))
    nn.add(Activation("relu"))
    nn.add(Flatten())
    nn.add(Dense(units=50, use_bias=False))
    nn.add(BatchNormalization())
    nn.add(Activation("relu"))
    nn.add(Dense(units=10, activation='softmax'))

    return nn
```

```
In [12]: nn = build_nn()

# setup early stopping callback function
earlystop = keras.callbacks.EarlyStopping(
    monitor='val_loss',      # look at the validation loss
    min_delta=0.0001,       # threshold to consider as no change
    patience=5,             # stop if 5 epochs with no change
    verbose=1, mode='auto'
)
callbacks_list = [earlystop]

# compile and fit the network
nn.compile(loss=keras.losses.categorical_crossentropy,
           optimizer=keras.optimizers.SGD(learning_rate=0.02, momentum=0.9, nesterov=True),
           metrics=['accuracy'])
history = nn.fit(vtrainI, vtrainYb, epochs=100, batch_size=50,
                callbacks=callbacks_list,
                validation_data=validsetI, verbose=False)
```

Metal device set to: Apple M1 Max

2023-01-23 15:43:30.688074: I tensorflow/core/common_runtime/pluggable_device/pluggable_device_factory.cc:305] Could not identify NUMA node of platform GPU ID 0, defaulting to 0. Your kernel may not have been built with NUMA support.
 2023-01-23 15:43:30.688564: I tensorflow/core/common_runtime/pluggable_device/plug

```
gble_device_factory.cc:271] Created TensorFlow device (/job:localhost/replica:0/task:0/device:GPU:0 with 0 MB memory) -> physical PluggableDevice (device: 0, name: METAL, pci bus id: <undefined>)
2023-01-23 15:43:31.399733: W tensorflow/core/platform/profile_utils/cpu_utils.cc:128] Failed to get CPU frequency: 0 Hz
2023-01-23 15:43:31.593293: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
2023-01-23 15:43:36.994830: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```

Epoch 13: early stopping


- Test results
 - compared with L2-regularization (0.971), dropout (0.972), ensemble (0.982)

```
In [13]: plot_history(history)

predY = argmax(nn.predict(testI, verbose=False), axis=-1)
acc = metrics.accuracy_score(testY, predY)
print("test accuracy:", acc)
```

```
2023-01-23 15:44:02.983904: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```

test accuracy: 0.9817



Outline

- Going deeper
 - ReLU and Batchnorm
- **Optimization methods**
- Deep architectures and Image classification
- Transfer learning

Optimization with SGD

- Ideally, we would like to use all the samples to compute the gradient, but this is too time consuming.
- Use a *minibatch* (a few samples) at a time to estimate the gradient.
 - creates an unbiased estimator of the gradient.
 - the variance (expected squared error) depends on the number of samples.
 - i.e., the estimated gradient is *noisy*.


Learning rates

- **Problem:** For gradient descent, at the minimum we should have $\frac{dL}{d\mathbf{w}} = 0$.
- What about for SGD?
 - at the minimum $\frac{dL}{d\mathbf{w}} \neq 0$ because of noise in the gradient.
 - SGD still moves around.
- Solution: reduce the learning rate during the epochs.
 - Examples: for iteration/epoch k ,
 - **linear change:** $\eta_k = (1 - \alpha)\eta_0 + \alpha\eta_T$, where $\alpha = k/T$, and η_0, η_T given.
 - **decay:** $\eta_k = \frac{1}{1+\delta k}\eta_0$, where $0 < \delta < 1$.
 - we want a small learning rate when we are close to the minimum.
 - needs to be set empirically by examining the learning curves.

Example: Keras decay

- use the built-in `decay` parameter.
 - applied after each batch.

```
In [14]: plt.figure(figsize=(5,3))
its = arange(0,50*5400/50) # 50 epochs, 5400/50 iterations per epoch
lr = 0.02*(1./(1+its*1e-3))
plt.plot(its, lr)
plt.grid(); plt.xlabel('iteration (batch)'); plt.ylabel('learning rate');
```



```
In [15]: nn = build_nn()

# compile and fit the network
nn.compile(loss=keras.losses.categorical_crossentropy,
           optimizer=keras.optimizers.SGD(learning_rate=0.02,
                                           decay=1e-5, # decay LR each iteration (batch)
                                           momentum=0.9, nesterov=True),
           metrics=['accuracy'])
history = nn.fit(vtrainI, vtrainYb, epochs=50, batch_size=50,
                validation_data=validsetI, verbose=False)
```


```
2023-01-23 15:44:28.707974: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
2023-01-23 15:44:29.851928: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```

```
In [16]: plot_history(history)

predY = argmax(nn.predict(testI, verbose=False), axis=-1)
acc = metrics.accuracy_score(testY, predY)
print("test accuracy:", acc)
```

```
2023-01-23 15:45:15.109995: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```

```
test accuracy: 0.9806
```



Adaptive schedule

- reduce the learning rate when the validation loss no longer improves
 - similar to early stopping criteria
- implemented as a callback function

```
In [17]: # reduce LR by a factor of 0.1, if no change in 5 epochs
lrschedule = keras.callbacks.ReduceLROnPlateau(monitor='val_loss',
                                                factor=0.1, patience=5, verbose=1)
callbacks_list = [lrschedule]
```

```
In [18]: nn = build_nn()

# compile and fit the network
nn.compile(loss=keras.losses.categorical_crossentropy,
           optimizer=keras.optimizers.SGD(learning_rate=0.02, momentum=0.9, nesterov=True),
           metrics=['accuracy'])

history = nn.fit(vtrainI, vtrainYb, epochs=50, batch_size=50,
                callbacks=callbacks_list,
                validation_data=validsetI, verbose=False)
```

```
2023-01-23 15:45:25.304520: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
2023-01-23 15:45:26.355509: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```


```
Epoch 13: ReduceLROnPlateau reducing learning rate to 0.0019999999552965165.
Epoch 18: ReduceLROnPlateau reducing learning rate to 0.00019999999862164259.
Epoch 23: ReduceLROnPlateau reducing learning rate to 1.9999998039565982e-05.
Epoch 28: ReduceLROnPlateau reducing learning rate to 1.99999976757681e-06.
Epoch 33: ReduceLROnPlateau reducing learning rate to 1.99999976757681e-07.
Epoch 38: ReduceLROnPlateau reducing learning rate to 1.9999997391551008e-08.
Epoch 43: ReduceLROnPlateau reducing learning rate to 1.999999810209374e-09.
Epoch 48: ReduceLROnPlateau reducing learning rate to 1.9999997213915323e-10.
```

```
In [19]: plot_history(history)

predY = argmax(nn.predict(testI, verbose=False), axis=-1)
acc = metrics.accuracy_score(testY, predY)
print("test accuracy:", acc)
```

2023-01-23 15:46:10.480098: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.


test accuracy: 0.9816



Fixed schedule

- specify our own schedule using callback `LearningRateScheduler`
- pass a schedule function
- inputs are the epoch and current learning rate.
- outputs the learning rate for this epoch.

```
In [20]: def sc(epoch, curlr):  
        alpha = minimum(epoch/50, 1.)  
        return 0.02*(1-alpha)+0.0001*alpha  
epoch = arange(0,70)  
plt.figure(figsize=(5,2))  
plt.plot(epoch, sc(epoch,None))  
plt.grid(); plt.xlabel('epoch'); plt.ylabel('learning rate');
```



```
In [21]: nn = build_nn()  
  
# learning rate schedule  
lrschedule = keras.callbacks.LearningRateScheduler(sc, verbose=0)  
callbacks_list = [lrschedule]  
  
# compile and fit the network  
nn.compile(loss=keras.losses.categorical_crossentropy,  
           optimizer=keras.optimizers.SGD(learning_rate=0.02, momentum=0.9, nesterov=True),  
           metrics=['accuracy'])  
  
history = nn.fit(vtrainI, vtrainYb, epochs=50, batch_size=50,  
               callbacks=callbacks_list,  
               validation_data=validsetI, verbose=False)
```

2023-01-23 15:46:20.938007: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.


2023-01-23 15:46:22.006395: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.


```
In [22]: plot_history(history)

predY = argmax(nn.predict(testI, verbose=False), axis=-1)
acc = metrics.accuracy_score(testY, predY)
print("test accuracy:", acc)
```


2023-01-23 15:47:05.917733: I tensorflow/core/grappler/optimizers/custom_graph_optimizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.

test accuracy: 0.9819



Momentum

- **Problem:** The estimated gradient is noisy, can jump around.
- **Solution:** keep a running average of the gradients across mini-batches.
 - velocity: $\mathbf{v}^{(t)} = \alpha \mathbf{v}^{(t-1)} - \eta \left(\frac{dL}{d\mathbf{w}} \right)_{\mathbf{w}^{(t-1)}}$
 - accumulate the gradients
 - α is the momentum hyperparameter; how much it exponentially decays.
 - parameter update: $\mathbf{w}^{(t)} \leftarrow \mathbf{w}^{(t-1)} + \mathbf{v}^{(t)}$
- Example:
 - red path is using momentum
 - black arrows show the gradient directions at each step
 - without momentum, the path would oscillate wildly.



Nesterov Momentum


- Compute the gradient *after* the current velocity is applied.
 - interim update: $\tilde{\mathbf{w}} = \mathbf{w}^{(t-1)} + \alpha \mathbf{v}^{(t-1)}$
 - velocity: $\mathbf{v}^{(t)} = \alpha \mathbf{v}^{(t-1)} - \eta \left(\frac{dL}{d\mathbf{w}} \right)_{\tilde{\mathbf{w}}}$

$$\left\| \frac{dL}{d\mathbf{w}} \right\|_{\tilde{\mathbf{w}}}$$

- parameter update: $\mathbf{w}^{(t)} \leftarrow \mathbf{w}^{(t-1)} + \mathbf{v}^{(t)}$
- Adds a *correction factor* to improve convergence (for convex batch case)


Why does SGD work?

- The loss function has many local minima
- SGD adds "noise" to the true gradient.
 - the noise allows escaping/avoiding/jumping over small local minima.
- Example:
 - red arrow = true gradient
 - green arrow = added noise
 - black arrow = computed gradient




SGD smoothes the loss function

- the added gradient noise is equivalent to convolving the loss function with the noise density.
- higher learning rate \rightarrow larger noise \rightarrow smoother loss



- smoother loss removes the local minimum, making it easier to get near the global minimum.
 - but not exactly on it.



- need to reduce the learning rate in stages to converge to the global optimum.

Optimization with Adaptive Learning Rates

- Introduce a separate learning rate for each parameter, and automatically adapt the learning rates during optimization.
- **AdaGrad** (`keras.optimizers.Adagrad`)
 - adapt individual learning rates by dividing by the square-root of the gradient energy accumulated over the iterations.
 - $\mathbf{g} = \frac{dL}{d\mathbf{w}}$
 - $\mathbf{r}^{(t)} = \mathbf{r}^{(t-1)} + \mathbf{g}^2$
 - $\mathbf{w}^{(t)} = \mathbf{w}^{(t-1)} - \frac{\eta}{\delta + \sqrt{\mathbf{r}}} \mathbf{g}$
 - (operations are element-wise)
- **RMSProp** (`keras.optimizers.RMSprop`)
 - use exponential decay on the accumulated energy:
 - $\mathbf{r}^{(t)} = \rho \mathbf{r}^{(t-1)} + (1 - \rho) \mathbf{g}^2$
- **Adam** (`keras.optimizers.Adam`)
 - use momentum with exponential weighting to estimate the gradient and gradient energy.
 - $\mathbf{s}^{(t)} = \rho_1 \mathbf{s}^{(t-1)} + (1 - \rho_1) \mathbf{g}$
 - $\mathbf{r}^{(t)} = \rho_2 \mathbf{r}^{(t-1)} + (1 - \rho_2) \mathbf{g}^2$
 - adds a bias correction for these two estimates.
 - $\hat{\mathbf{s}}^{(t)} = \frac{1}{1 - \rho_1^t} \mathbf{s}^{(t)}$
 - $\hat{\mathbf{r}}^{(t)} = \frac{1}{1 - \rho_2^t} \mathbf{r}^{(t)}$
 - update:
 - $\mathbf{w}^{(t)} = \mathbf{w}^{(t-1)} - \frac{\eta}{\delta + \sqrt{\hat{\mathbf{r}}^{(t)}}} \hat{\mathbf{s}}^{(t)}$

Example

- change the optimizer when compiling the network.

```
In [23]: # compile and fit the network
nn.compile(loss=keras.losses.categorical_crossentropy,
           optimizer=keras.optimizers.Adam(learning_rate=0.01), # can set the initial lear
           metrics=['accuracy'])
history = nn.fit(vtrainI, vtrainYb, epochs=100, batch_size=50,
               callbacks=callbacks_list,
               validation_data=validsetI, verbose=False)
```


```
2023-01-23 15:50:04.389863: I tensorflow/core/grappler/optimizers/custom_graph_opt
imizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
2023-01-23 15:50:05.788572: I tensorflow/core/grappler/optimizers/custom_graph_opt
imizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```

```
In [24]: plot_history(history)

predY = argmax(nn.predict(testI, verbose=False), axis=-1)
acc = metrics.accuracy_score(testY, predY)
print("test accuracy:", acc)
```

```
2023-01-23 15:51:44.202787: I tensorflow/core/grappler/optimizers/custom_graph_opt
imizer_registry.cc:113] Plugin optimizer for device_type GPU is enabled.
```

```
test accuracy: 0.9842
```



Which optimizer is best?

- there's no best optimizer...
- based on the problem and own familiarity with tuning the hyperparameters.