

Lecture 1: Basic R

Zhentao Shi

Feb 18, 2017

Prerequisite

- Install [R](#)
- Install an IDE. [RStudio](#) is recommended.

Basic

- help system: `?`, `??`. eg. `?seq`, `??sequence`
- `c()`
- arithmetic
- logical vector & `|` `!=`, `any`, `all`
- factor
- character
- missing values `NA`, `NaN`
- index vector for selection `a[]`. Either positive integer or logical vector.

example

```
# logical vectors
```

```
logi_1 = c(T,T,F)
```

```
logi_2 = c(F,T,T)
```

```
logi_12 = logi_1 & logi_2
```

```
print(logi_12)
```

```
## [1] FALSE TRUE FALSE
```

Arrays

An array is a table of numbers. A matrix is a 2-dimensional array.

- array arithmetic: element-by-element. Particular attention must be exercised in binary operations involving two objects of different length. This is error-prone.
- `%*%`, `solve`, `eigen`

example: simple regression—OLS estimation with one x regressor and a constant.

- literally translate $\hat{\beta} = (X'X)^{-1}X'y$ into code.

```
# check the OLS fitting
```

```
rm(list = ls( ))
```

```
set.seed(111) # can be removed to allow the result to change
```

```
# set the parameters
```

```
n = 100
```

```
b0 = matrix(1, nrow = 2 )
```

```
# generate the data
```

```
e = rnorm(n)
```


```

X = cbind( 1, rnorm(n) )
Y = X %*% b0 + e

# OLS estimation
bhat = solve( t(X) %*% X, t(X)%*% Y )

# plot
plot( y = Y, x = X[,2], xlab = "X", ylab = "Y", main = "regression")
abline( a= bhat[1], b = bhat[2])
abline( a = b0[1], b = b0[2], col = "red")
abline( h = 0, lty = 2)
abline( v = 0, lty = 2)

```



- t -statistic:

$$t = \frac{\hat{\beta}_2 - \beta_{02}}{\hat{\sigma}_{\hat{\beta}_2}} = \frac{\hat{\beta}_2 - \beta_{02}}{\sqrt{[(X'X)^{-1}\hat{\sigma}^2]_{22}}}.$$

where $[\cdot]_{22}$ is the (2,2)-element of a matrix.

```

# calculate the t-value
bhat2 = bhat[2] # parameter we want to test
e_hat = Y - X %*% bhat
sigma_hat_square = sum(e_hat^2) / (n-2)
sig_B = solve( t(X) %*% X ) * sigma_hat_square
t_value_2 = ( bhat2 - b0[2] ) / sqrt( sig_B[2,2] )
print(t_value_2)

```

```
## [1] -0.5615293
```

Packages

An initial installation of R is small, but R has an extensive system of add-on packages. A package can be installed and invoked by

```
install.packages("package_name")
library(package_name)
```

eg: The following packages are useful for econometrics.

```
library(AER)
```

```
## Loading required package: car
## Loading required package: lmtest
## Loading required package: zoo
##
## Attaching package: 'zoo'
##
## The following objects are masked from 'package:base':
##
##      as.Date, as.Date.numeric
## Loading required package: sandwich
## Loading required package: survival
```

Mixed data types

- list
- data.frame

```
data("CreditCard")
head(CreditCard)
```

```
##   card reports      age income      share expenditure owner selfemp
## 1  yes         0 37.66667 4.5200 0.033269910 124.983300  yes     no
## 2  yes         0 33.25000 2.4200 0.005216942   9.854167   no     no
## 3  yes         0 33.66667 4.5000 0.004155556  15.000000  yes     no
## 4  yes         0 30.50000 2.5400 0.065213780 137.869200   no     no
## 5  yes         0 32.16667 9.7867 0.067050590 546.503300  yes     no
## 6  yes         0 23.25000 2.5000 0.044438400  91.996670   no     no
##   dependents months majorcards active
## 1           3     54           1    12
## 2           3     34           1    13
## 3           4     58           1     5
## 4           0     25           1     7
## 5           2     64           1     5
## 6           0     54           1     1
```

Input and output

- read.table()

- `write.table()`

example

```
HEX = read.csv("http://ichart.finance.yahoo.com/table.csv?s=0388.HK")
print(head(HEX))
write.csv(HEX, file = "HEX.csv")
```

Statistics


- `p`, `d`, `q`, `r`

example:

1. plot the density of $\chi^2(3)$ over `x_axis = seq(0.01, 15, by = 0.01)`
2. generate 1000 observations for the above distribution. plot the kernel density.
3. calculate the 95-th quantile and the empirical probability of observing a value greater than the 95-th quantile.

```
set.seed(888)
x_axis = seq(0.01, 15, by = 0.01)

y = dchisq(x_axis, df = 3)
plot(y = y, x=x_axis, type = "l")
z = rchisq(1000, df = 3)
lines( density(z), col = "red")
```



```
crit = qchisq(.95, df = 3)
```

```
mean( z > crit )
```

```
## [1] 0.047
```

User-defined function

- fun_name = function(args) {expressions}
- variables defined in a functions are local.

example: given a sample, calculate the 95% two-sided asymptotic confidence interval according to a central limit theorem.

```
# construct confidence interval
```

```
CI = function(x){  
  # x is a vector of random variables  
  
  n = length(x)  
  mu = mean(x)  
  sig = sd(x)  
  upper = mu + 1.96/sqrt(n) * sig  
  lower = mu - 1.96/sqrt(n) * sig  
  return( list( lower = lower, upper = upper) )  
}
```

Flow control

- if
- for, while

example: calculate the empirical coverage probability of a poisson distribution of degree of freedom 2.

```
Rep = 1000
```

```
sample_size = 100
```

```
capture = rep(0, Rep)
```

```
pts0 = Sys.time() # check time
```

```
for (i in 1:Rep){
```

```
  mu = 2
```

```
  x = rpois(sample_size, mu)
```

```
  bounds = CI(x)
```

```
  capture[i] = ( ( bounds$lower <= mu ) & (mu <= bounds$upper) )
```

```
}
```

```
mean(capture) # empirical size
```

```
## [1] 0.938
```

```
pts1 = Sys.time() - pts0 # check time elapse
```

```
print(pts1)
```

```
## Time difference of 0.203963 secs
```

Statistical models

- `lm(y~x, data =)`

Homework

One cannot acquire a new programming language without investing many hours after the lecture. [R-Introduction](#) is the best starting point. Please carefully go over this manual.