

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

// ===== src/app/(auth)/forgot-password/page.tsx ====='use client'; import React, { useState } from 'react';import Link from 'next/link';import {

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

</div>

<h1 className="text-2xl font-bold text-gray-900">€LvÈ[fmw</h1><h2 className="text-lg text-gray-700 mt-1 font-medium">b~Vb[Ex</h2>

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

value={email}

onChange={(e) => setEmail(e.target.value)}

placeholder="↵•"QelèQCEedQuirç{±"

className=

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

€LvÈ[fmw<div className="flex items-center gap-4">

<Link href="/login" className=

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

{ icon: CheckCircle2, title: 'eàR QİÖ desc.: ĩk8_ŦCēS2NăyQ7R6_ıapŸ((ŦŦW)eQz(ŦN -PkŦdWOShÀw [ŦQy-ŦŦıtitle) classN

€LvÈ[fmwu5UF[¢g {jt |û~ßV1.0 n•z ^•Năx

key={item.pain}

className="bg-white/5 border border-white/10 rounded-2xl p-5 flex gap-4 items-start hover:border-cyan-400/30 transition

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

{/* % % { \G6jçRÿççNâme%max)w-4xl mx-auto px-6 pb-20"> <h2 className="text-2xl font-bold text-center mb-10">99 vs 980 RŸć[ùkÔ<h1>

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

{/* % % {,N"Oy)OánA6W5hC"Pa%w/4xl mx-auto px-6 pb-20"> <div className="bg-white/5 border border-white/10 border-dashed rounded-2

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

// Detect password reset callback from Supabase useEffect() => { if (typeof window !== 'undefined') { const hash = window.location.hash; if (hash

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

const handleLogin = async (e: React.FormEvent) => { e.preventDefault(); setError(""); // Frontend validation const emailCheck = validateEmail(em

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

await new Promise(r => setTimeout(r, 300)); // Check account expiration try { const sb = await getSupabaseBrowser(); const { data: { us

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

<p className="text-gray-700 mt-1 text-sm font-medium">[çg {it fzeç/458</p> {/* Login Card */} <div className="bg-white rounded-2xl shadow

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

{error}

</div>

))

<form onSubmit={handleLogin} className="space-y-6 animate-fade-in-up">

<div>

<label class

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

</div> {/* u(b7SO<®/-y&A&B&C&D&E&F&G&H&I&J&K&L&M&N&O&P&Q&R&S&T&U&V&W&X&Y&Z&[&\&]&^&_&`&a&b&c&d&e&f&g&h&i&j&k&l&m&n&o&p&q&r&s&t&u&v&w&x&y&z&{&|&~&ß&V&1.0 n•z ^•Năx

<input type="che

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

// ===== src/app/(auth)/privacy/page.tsx =====import Link from 'next/link';import { ArrowLeft } from 'lucide-react'; export default function Priva

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

</div>

</section>

{/* {,N zà */}<section>

<h2 className="text-lg font-bold text-gray-900 mb-3">N 0 Oá`oO•u(çdwô</h2>

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

</section> {/* {,Qmzà - fôesççmQúX/T %4201as}Name="text-lg font-bold text-gray-900 mb-3">Qm0 epcnQúxçiv MăssName="space-y-3">

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

</div> </section> {/* {,N]zà */}<section> <h2 className="text-lg font-bold text-gray-900 mb-3">N]0 g*b ^tN°Cđrčh2> </h2>

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

import { getSupabaseBrowser } from '@lib/supabase-browser';import { useRouter, useSearchParams } from 'next/navigation';import Link from 'next/link';im

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

```
}    } catch { /* ignore */ }    })(); }, [router]); // Validate invitation token  useEffect() => {    if (!inviteToken) { setInviteChecked(true); return; }    (async
```

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

setError(""); setLoading(true); try { // 1. Register via our API (creates user record with selected role) const res = await fetch('/api/auth/register',

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

return (<div className="min-h-screen flex items-center justify-center bg-gradient-to-br from-blue-50 via-white to-slate-50 px-4 py-8"> <div classNa

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

<div className="relative">

<input

type={showPassword ? 'text' : 'password'}

value={password}

on

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

<p className="text-sm text-gray-600">O`]ò^« {inviteInfo.inviterName} •£<

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

value={redemptionCode}

onChange={(e) => setRedemptionCode(e.target.value.toUpperCase())}

placeholder="<÷•“Qe

€LvÈ[fmwu5UF[¢g {jt |û~ßV1.0 n•z ^•Nãx
<Captcha onValidate={setCaptchaValid} /> </div> <div className="flex gap-3"> <button type="button"

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

return (<div className="min-h-screen bg-gray-50"> <div className="max-w-3xl mx-auto px-4 py-8"> <Link href="/" className="ir

3.2 g R_iN-e⁻eP•

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

<p>7.3 y•kbY R60 •ûsp_7.4E•kubV(•s•Dg•Să•Lp•Că•z•Cw•W•y•m•j•W•s•j•Q•v•R•o•p•p•n•ö•(170

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

throw new Error(`•“QeQ...[!•...•Çg Y)••^•ePR6(\$mod,engh)PV%);Validation EMAIL_RE = /^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}\$/;const PHO

€LvÈ[fmwu5UF[çg {;t |û~ßV1.0 n•z ^•Năx

`*/export function validateCode(code: unknown): ValidationResult { if (typeof code !== 'string' || !code.trim()) { return { valid: false, error: '↵÷•"DeQQttrm`

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

let page = DEFAULT_PAGE; let pageSize = DEFAULT_PAGE_SIZE; if (params.page !== undefined && params.page !== null) { const p = Number(para

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

return { valid: true };} /** * Batch validate multiple fields, returns first error or all-valid */export function validateAll(checks: Array<{ name: string; result: Vali

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

const serverRecord = Array.isArray(data?.data) ? data.data[0] : data?.data; if (!serverRecord?.updated_at) return false; const serverTime = new Dat

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

}}, 5 * 60 * 1000); // % % % Rate limit in config file
RateLimitRule { windowMs: number; // time window in milliseconds maxRequests: number; // max requests per windowMs

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

if (pathname === '/api/auth/register') { const ip = getClientIP(request); const result = checkRateLimit(ipStore, `register:\${ip}`, REGISTER_LIMIT.window

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

},); } // Add rate limit headers to successful responses const response = NextResponse.next(); response.headers.set('X-RateLimit-Remainin

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

"style-src 'self' 'unsafe-inline' https://fonts.googleapis.cn", "font-src 'self' https://fonts.gstatic.cn", "img-src 'self' data: blob: https:", `connect-src 'self' https://`

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Nãx

```
}); server.once('error', err => { console.error(err); process.exit(1); }); server.listen(port, () => { console.log('`> Server listening at http://${hostname}
```


€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

returnPolicy: text('return_policy'), profileCompleted: boolean('profile_completed').default(false), seatLimit: integer('seat_limit').default(1), seatUsed: integ

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

id: varchar('id', { length: 36 }).primaryKey().\$defaultFn() => crypto.randomUUID()), companyId: varchar('company_id', { length: 36 }).notNull(), name: text

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

id: varchar('id', { length: 36 }).primaryKey().\$defaultFn() => crypto.randomUUID()), companyId: varchar('company_id', { length: 36 }).notNull(), schemeld:

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

companyId: varchar('company_id', { length: 36 }), category: text('category').notNull(), name: text('name').notNull(), scenario: text('scenario'), stepsJson: t

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

feishuDocUrl: text('feishu_doc_url'),)); export const courseLessons = pgTable('course_lessons', { id: varchar('id', { length: 36 }),primaryKey().\$defaultFn()

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

category: varchar('category', { length: 100 }), specifications: jsonb('specifications'), features: jsonb('features'), manualUrl: text('manual_url'), videoUrl: tex

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

feedback: text('feedback'), createdAt: timestamp('created_at', { withTimezone: true }).notNull().defaultNow(),); export const qualityInspections = pgTable('

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

reviewedBy: varchar('reviewed_by', { length: 36 }).notNull(), status: varchar('status', { length: 50 }).default('pending'), note: text('note'), createdAt: timestar

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

description: text('description'), recordedAt: timestamp('recorded_at', { withTimezone: true }), createdAt: timestamp('created_at', { withTimezone: true }).no

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

// ===== QeēL`h ===== export const onboardingTasks = pgTable('onboarding_tasks', { id: varchar('id', { length: 36 }).pr

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

createdAt: timestamp("created_at", { withTimezone: true }).notNull().defaultNow(),); // ===== QQcbx ^h ===== export con

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

title: text('title').notNull(), content: text('content').notNull(), category: varchar('category', { length: 100 }), tags: text('tags'), createdAt: timestamp('created_at')

€LvÈ[fmwu5UF[çg {it |û~ßV1.0 n•z ^•Năx

// ===== m;R`ea_x^h ===== export const activityLogs = pgTable('activity_logs', { id: varchar('id', { length: 36 }).primaryKey()

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

export const dailyReports = pgTable('daily_reports', { id: varchar('id', { length: 36 }).primaryKey().\$defaultFn(() => crypto.randomUUID()), companyId: varcl

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

id: varchar("id", { length: 36 }).primaryKey().\$defaultFn() => crypto.randomUUID()), userId: varchar("user_id", { length: 36 }).notNull(), questionId: varchar(

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

financeRecords, teams, invitations, onboardingTasks, onboardingRecords, notifications, schedules, redemptionCodes, customerRecords, dailyPract

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

```
if (process.env.COZE_SUPABASE_URL && process.env.COZE_SUPABASE_ANON_KEY) {      envLoaded = true;      return;    }  } catch {    // do
```

€LvÈ[fmwu5UF[¢g {it |û~ßV1.0 n•z ^•Năx

/** * Check if we are in a build phase where env vars may not be available. * During `next build`, routes are imported for page data collection, * but Supaba

€LvÈ[fmwu5UF[¢g {;t |û~ßV1.0 n•z ^•Năx

// Token-based clients are per-request and should not be cached. if (!token) { const cached = clientCache.get('no-token'); if (cached) return cached; }

€LvÈ[fmwu5UF[¢g {it |û~BV1.0 n•z ^•Nãx
{, 60 ~u