



ORNL is managed by UT-Battelle, LLC for the US Department of Energy




AI/ML in Comms





Competition
Fantasy
Adding
intelligence to
the AD9361 chip.



/S.



Competition
Reality
Lots and LOTS
of arguments
about
compliance.

Age Old Problem: Accessing Congested Spectrum

20th Century Wireless



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Lower your power.

21st Century Wireless?



FCC ID: DC9-OVS01

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device must demonstrate intelligent RF access, and (2) this device must respond to intelligent RF access, including from greater intelligences that may cause undesired operation.


Increase your intelligence?

But what is radio intelligence?




Increasing Radio Intelligence

"Learning is the search of a parameter space in order to optimize performance."



How to Transmit?



What to Transmit?



Make smart decisions on:

- Frequency
- Time
- Power

Make smart decisions on:


- Waveform
- Spreading / Hopping
- Anti-jamming

Make smart decisions on:

- Error-correction
- Encryption
- Cyber Security




Radio Intelligence with Comm's Demon





- 1. Hot and cold molecules exist inside a box
- 2. A "demon" manipulates a door to trap same type molecules on each side
- 3. Thermodynamics is violated
- 4. Physicists freak out




Comm's Demon

- A device with universal hardware is placed in an environment
- 2. Objectives are given to the "demon"
- 3. The demon rederives all formerly human-invented processing for that environment
- 4. Comm's people disbelieve




Deepmod: Summoning the Demon






2018 Deepmod: Acoustic Channel



Software

Hardware




<u>Demo "Machine Speak"</u>

- Deep convolutional neural network autoencoder
- Single transducer rig (soundcard, microphone, speaker)
- GNU Radio, TensorFlow, Natural Language Toolkit
- Classes are English phonemes (e.g. sss, vvv)
- Listen as computers discover communication



2018 Deepmod: Powerline Communications (PLC) Channel



PLC channel: Use existing (and unintended) infrastructure to transmit information. Can be used in home networks or disaster scenarios.

<u>PLC Deepmod</u>: Swap out speaker/microphone for powerline couplers. Same machine.



2018 Deepmod: RF (Wireless) Channel

Radio Frequency (RF) channel: Is the de facto channel for "last mile" communications. Transducers in this case are antennas.



RF Deepmod

- Sample rate = 1 Msps
- Center frequency = 900 MHz
- SNR adjusted to match simulation
- 256 classes, 16 (real) samples, 1 bit per sample
- 0 signal processing blocks
- High rate communications

Deepmod learns to communicate.



Don't Ask:

Q1: What does the deepmod constellation look like?

A1: There's no constellation.

Q2: What equalizer does deepmod use?

A2: There's no equalizer.

Q3: How does deepmod handle CFO correction?

A3: It just does. Deal with it.

Q4: How does it perform against the equivalent human system?

A4: I can't win this argument...

- If deepmod does worse in simulation people will say "Ha! BPSK in AWGN is 1 dB better!"
- If deepmod is better over-the-air people will say: "Ha! You just need to extend your equalizer! Lower beta! Change modulation! Use an FEC! Etc.! Etc.!"

Do Ask:

But is deepmod intelligent?



The Turing Test

"...a test of a machine's ability to exhibit intelligent behavior equivalent to, or indistinguishable from, that of a human"



The Imitation Game

Toon A wants to find out if Toon B is a bot.

Toon A: "Hey you want to team up?"
Toon B: "Sure just come out of that
house and we'll own some stuff!"

Is Toon B a bot or human?

- 1. The primary difficulty of the Turing Test is knowing what questions to ask.
- 2. The secondary difficulty is knowing how to interpret the answers given.



The CAPTCHA Test

Completely Automated Public Turing test to tell Computers and Humans Apart



A counterpart to the Turing Test. Now a computer is determining if YOU are intelligent.




The Dr. Anderson Test


Common Student Question:


"Dr. Anderson, do you think I could code this up to automatically classify [whatever]?"

Common Teacher Response:

"Well, can you classify it?"







Any cognitive ability achievable by humans can ultimately be achieved by a machine



Radio Intelligence Test

<u>Turing:</u> A human guessing if a computer is a human or not
 <u>CAPTCHA:</u> A computer guessing if a human is a computer or not
 <u>Anderson:</u> If a human can guess it then so can a computer

An observation: Artificial radio intelligence may be easier to test than artificial human intelligence. We don't care how the machine answers the question; we just care if the answer is correct.

For now, let's just say: A radio system designed artificially by a computer is deemed intelligent if a human - given an unlimited amount of time - would derive a system with similar behavior for: hardware, environment, and objectives given.

Man vs. Demon



Man vs. Demon


- This is a noisy symbol representing four bits (e.g. 1101)
- We want to place 16 of these on a fenced, flat space so that no two clusters overlap (overlap means bit errors!)
- Minimize the bit-error rate



Man vs. Demon

- This is a noisy symbol representing four bits (e.g. 1101)
- We want to place 16 of these on a fenced, flat space so that no two clusters overlap (overlap means bit errors!)
- Minimize the bit-error rate

- This is a noisy symbol representing four bits (e.g. 1101)
- Give a machine a convolutional neural network with two dimensional fully-connected inner layer






Man vs. Demon


- This is a noisy symbol representing four bits (e.g. 1101)
- We want to place 16 of these on a fenced, flat space so that no two clusters overlap (overlap means bit errors!)
- Minimize the bit-error rate

- This is a noisy symbol representing four bits (e.g. 1101)
- Give a machine a convolutional neural network with two dimensional fully-connected inner layer

Human Invented 16-QAM




Machine Invented 16-QAM



Man vs. Demon: A New Environment

- Most channels don't have "nice" noise...
- This is now a noisy symbol representing four bits (e.g. 1101)
- The human-invented 16-QAM is terrible with massive cluster overlaps (bit errors)
- What can we do?





Man vs. Demon: A New Environment

- Most channels don't have "nice" noise...
- This is now a noisy symbol representing four bits (e.g. 1101)
- The human-invented 16-QAM is terrible with massive cluster overlaps (bit errors)
- What can we do?


• Same machine. New discovery.


IMPORTANT If the human radio could change modulation from 16-QAM to BPSK then that's **adaptation**. Inventing 8x2-QAM in situ is **intelligence**.





Test 1: Contested Channel





Test 1: Place the radio into an environment with narrowband interference

What A Human Might Do

- Notch filter on frontend would remove interference but may also harm narrowband signals.
- With OFDM you could suppress the affected subcarrier.
- Specific equalizer maybe?

- First learns to communicate without interference present
- Goes dumb with jammer turned on
- Continued learning; reestablishes a comms link in the presence of the interference.
- CNN helped maybe?



Test 2: Relay Channel



Test 2: Place the radios into an environment with a single-hop amplify-and-forward relay channel

What A Human Might Do

- Relay channel may result in heterogenous links
- Adapt power and/or coding depending on direction and channel quality
- Additional filtering for CFO / phase effects

- A third node used as relay (just a dumb AFR node)
- No direct communications between deepmod nodes
- Deepmod learns to communication at the effective SNR level



Test 3: Lone Survivor Channel

Test 3: Place multiple single antenna radios into the same environment with the same objective



What A Human Might Do

- Cooperative MIMO channel
- Share channel state information between all transmitting nodes and receiver
- Fine-grained synchronization
- Have signals combine constructively OTA

Deepmod0



Deepmod0





Deepmod1



- Two deepmod nodes are assigned "deepmod0" the other node is "deepmod1"
- Not aware of other deepmod0
- The two node zeros initially treat each the node as environment noise
- Eventually cooperated for "3 dB" gain

Test 4: Mobile Channel





Test 4: Allow one radio to move

What A Human Might Do


- Mobility affects channel coherence time and fading
- Train during preamble and equalize at receiver?
- Space-time block coding
- Estimate Doppler spreading and then compensate

- Deepmod0 placed in hotel room; deepmod1 placed in back of vehicle
- Nodes learn to communicate while stationary
- Similar behavior to NB jammer during movement
- Training epochs affected by velocity




Test 5: Narrowband

Google image search: "narrowband spectral envelope"...



... and then tell deepmod to try and look like it.



Test 5: Require spectrum to be narrowband.

What A Human Might Do

- Results naturally from whatever modulation is being used
- If artificial, pulse shape the entire packet to match envelope
- Add artificial noise to missing bands

- Keep objective of "try and minimize bit (class) error rate"
- Also give objective of "look like these points in the spectrum"
- Deepmod converges to communications while evolving to narrowband spectrum




Test 6: Spectral Efficiency

Test 6: Give radios r less spectral efficiency (or 1/r more samples per class).

What A Human Might Do

- Higher energy per bit
- Repetition code
- Block code
- Turbo code
- ACK / Retransmission



- I don't know...
- Rate less than one means more samples per class?
- Increase innermost "hidden layer"
- Was able to lower the effective BER for the same power per class (bit)
- Shannon and Turing walk into a bar...



Conclusion

- Future bands of spectrum will require some degree of intelligence from wireless devices at all layers of the protocol stack before transmission is allowed
- A "Turing Test" for radios is needed to determine sufficient intelligence
- It's the communities' (our) responsibility to 1) Determine which intelligence the PHY layer is responsible for
- And 2) Define a set of "questions" to "ask" the radio to determine intelligence:
 - How do you react to a relay channel?
 - How do you react to multiple objectives?
 - How do you react to mobility?
 - How do you react to cooperation?
 - How do you react to statistical channel changes?
 - How do you react to spectral efficiency?
 - How do you react to nonideal environments?
 - Etc.
- And 3) Determine the appropriate radio "responses" that imply intelligence:
 - I mitigated the jammer.
 - I decreased my error floor.
 - I narrowed my spectral use.
 - Etc.
- Intelligent? Yes/No!



Questions?

