REPORT



과 목: 네트워크프로그래밍

제출일자: 2021.09.08

담당교수: 황성호

학 과: 컴퓨터공학과

학 번: 201720970

이 름: 권대한

1. 예제2-2 소스코드

```
#define _WINSOCK_DEPRECATED_NO_WARNINGS
#pragma comment(lib, "ws2_32")
#include <stdio.h>
#include <stdlib.h>
#include <WinSock2.h>
void err_quit(char* msg)
        //"far" + pointer + void
        LPVOID lpMsgBuf;
        FormatMessage
                //flag
                FORMAT_MESSAGE_ALLOCATE_BUFFER | FORMAT_MESSAGE_FROM_SYSTEM,
                //source
                NULL,
                //message id
                WSAGetLastError(),
                //language id
                MAKELANGID(LANG_NEUTRAL, SUBLANG_DEFAULT),
                //Long Pointer t_string, buffer location
                (LPTSTR)&lpMsgBuf,
                //size
                0,
                //arguments
                NULL
        );
        MessageBox
                //handle
                NULL,
                //text
                (LPCTSTR)lpMsgBuf,
                //caption
                msg,
                //type
```

```
MB_ICONERROR
        );
        //pointer memory free Func
        LocalFree(lpMsgBuf);
        //error code
        exit(1);
}
int main(int argc, char* argv[])
{
        WSADATA wsa;
        if (WSAStartup(MAKEWORD(2, 2), &wsa) != 0)
        {
                return 1;
        MessageBox(NULL, "WinSock 초기화 성공!", "알림", MB_OK);
        //Socket()
        SOCKET tcp_sock = socket(AF_INET, SOCK_STREAM, 0);
        if (tcp_sock == INVALID_SOCKET)
        {
                err_quit("socket()");
        }
        MessageBox(NULL, "TCP 소켓 생성 성공!", "알림", MB_OK);
        //Closesocket()
        closesocket(tcp_sock);
        WSACleanup();
        return 0;
}
```

→출력 결과



